



ELTE

FACULTY OF
INFORMATICS

LOGISTIC REGRESSION

Machine Learning Course
Balázs Nagy, PhD




ELTE | IK

DEPARTMENT OF
ARTIFICIAL
INTELLIGENCE


Classification problem

- **Example problem:**
Classify tumors by their size into two class (malignant, non-malignant)




Classification problem

- **Example problem:**
Classify tumors by their size into two class (malignant, non-malignant)
- Linea regression is not sufficient here



Classification problem

- **Example problem:**
Classify tumors by their size into two class (malignant, non-malignant)
- Linear regression is not sufficient here



Vertical line as a threshold would be okay, but previous model not designed for that


Classification

- Need a function with two outputs ($y = 0$ or 1)
- Sigmoid function (also called Logistic Function)

$$h_{\theta}(x) = g(\theta^T x)$$

$$z = \theta^T x$$


$$g(z) = \frac{1}{1 + e^{-z}}$$



- $h(x)$ is a probability that the output is 1

$$h_{\theta}(x) = P(y = 1|x; \theta) = 1 - P(y = 0|x; \theta)$$
$$P(y = 0|x; \theta) + P(y = 1|x; \theta) = 1$$


Decision Boundary - Linear



$$h_{\theta}(x) = g(\theta_0 + \theta_1 x_1 + \theta_2 x_2)$$


Predict " $y = 1$ " if $-3 + x_1 + x_2 \geq 0$

Decision Boundary – Non-Linear





$$h_{\theta}(x) = g(\theta_0 + \theta_1 x_1 + \theta_2 x_2 + \theta_3 x_1^2 + \theta_4 x_2^2)$$

Predict “ $y = 1$ ” if $-1 + x_1^2 + x_2^2 \geq 0$



$$h_{\theta}(x) = g(\theta_0 + \theta_1 x_1 + \theta_2 x_2 + \theta_3 x_1^2 + \theta_4 x_1^2 x_2 + \theta_5 x_1^2 x_2^2 + \theta_6 x_1^3 x_2 + \dots)$$

Example





Cost function – Logistic Regression

- We cannot use the same cost function that we use for linear regression because the Logistic Function will cause the output to be wavy, causing many local optima and it will not be a convex function

$$C = \frac{1}{2m} \sum_{i=1}^m (h_w(x^i) - y^i)^2$$

?




Cost function – Logistic Regression

$$J(\theta) = \frac{1}{m} \sum_{i=1}^m \text{Cost}(h_{\theta}(x^{(i)}), y^{(i)})$$

$$\text{Cost}(h_{\theta}(x), y) = -\log(h_{\theta}(x)) \quad \text{if } y = 1$$

$$\text{Cost}(h_{\theta}(x), y) = -\log(1 - h_{\theta}(x)) \quad \text{if } y = 0$$




Cost function – Logistic Regression

$$J(\theta) = \frac{1}{m} \sum_{i=1}^m [-y^{(i)} \log(h_{\theta}(x^{(i)})) - (1 - y^{(i)}) \log(1 - h_{\theta}(x^{(i)}))] ,$$

and the gradient of the cost is a vector of the same length as θ where the j^{th} element (for $j = 0, 1, \dots, n$) is defined as follows:

$$\frac{\partial J(\theta)}{\partial \theta_j} = \frac{1}{m} \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)}) x_j^{(i)}$$



Optimization

- Optimization algorithms:

- Gradient descent
- Conjugate gradient
- BFGS
- L-BFGS

- Advantages:


- No need to manually pick α
- Often faster than gradient descent

- Disadvantages:


- More complex

Multi Class Classification


Binary classification:



Multi-class classification:



Multi Class Classification



- Train a logistic regression classifier for each class i to predict the probability that $y = i$.
- On a new input x , to make a prediction, pick the class i that maximizes.

$$y \in \{0, 1, \dots, n\}$$

$$h_{\theta}^{(0)}(x) = P(y = 0|x; \theta)$$

$$h_{\theta}^{(1)}(x) = P(y = 1|x; \theta)$$

...

$$h_{\theta}^{(n)}(x) = P(y = n|x; \theta)$$

$$\text{prediction} = \max_i (h_{\theta}^{(i)}(x))$$



ELTE

FACULTY OF
INFORMATICS

Thank you for your attention!