DW_ram_rw_a_dff

Asynchronous Single-Port RAM (Flip-Flop-Based)

Version, STAR, and myDesignWare Subscriptions: IP Directory

Features and Benefits

Revision History

- Parameterized word depth
- Parameterized data width
- Asynchronous static memory
- Parameterized reset implementation
- High testability using DFT Compiler



Description

DW_ram_rw_a_dff implements a parameterized, asynchronous, single-port static RAM.

Table 1-1 Pin Description

Pin Name	Width	Direction	Function
rst_n	1 bit	Input	Reset, active low
cs_n	1 bit	Input	Chip select, active low
wr_n	1 bit	Input	Write enable, active low
test_mode	1 bit	Input	Enables `test_clk`
test_clk	1 bit	Input	Test clock to capture data during `test_mode`
rw_addr	ceil($\log_2$[*depth*]) bits	Input	Address bus
data_in	*data_width* bits	Input	Input data bus
data_out	*data_width* bits	Output	Output data bus

Table 1-2 Parameter Description

Parameter	Values	Description
data_width	1 to 256 Default: None	Width of `data_in` and `data_out` buses
depth	2 to 256 Default: None	Number of words in the memory array (address width)
rst_mode	0 or 1 Default: 1	Determines if the `rst_n` input is used. ■ 0: `rst_n` initializes the RAM ■ 1: `rst_n` is not connected

Table 1-3 Synthesis Implementations

Implementation Name	Function	License Feature Required
rtl[a]	Synthesis model	DesignWare

a. The implementation, “rtl,” replaces the obsolete implementation, “str.” Existing designs that specify the obsolete implementation (“str”) will automatically have that implementation replaced by the new superseding implementation (“rtl”) as will be noted by an information message (SYNDB-36) generated during DC compilation.

Table 1-4 Simulation Models

Model	Function
DW06.DW_RAM_RW_A_DFF_CFG_SIM	VHDL simulation configuration
dw/dw06/src/DW_ram_rw_a_dff_sim.vhd	VHDL simulation model source code
dw/sim_ver/DW_ram_rw_a_dff.v	Verilog simulation model source code

The write data enters the RAM through the `data_in` input port and is read out at the `data_out` port. The RAM is constantly reading regardless of the state of `cs_n`.

The `rw_addr` port is used to address the *depth* words in memory. For addresses beyond the maximum depth (for example, `rw_addr` = 7 and `depth` = 6), the `data_out` bus is driven low. No warnings are given during simulations when an address beyond the scope of *depth* is used.

Attention This component contains clock signals for internal flip-flops that are derived from the `wr_n` and `test_clk` ports. To keep hold times and internal clock skews to a minimum, you should consider instances of this component to be individual floorplanning elements.

Chip Selection, Reading and Writing

The `cs_n` input is the chip select, active low signal that enables data to be written to the RAM. When `cs_n` is low, the RAM is enabled to be read, and data is written to the RAM when there is a low-to-high transition of `wr_n`, write enable.

When `cs_n` is high, the RAM is disabled, and the `data_out` bus is driven low.

Reset

rst_n
This signal is an active-low input that initializes the RAM to zeros if the `rst_mode` parameter is set to 0, independent of the value of `cs_n`. If the `rst_mode` parameter is set to 1, `rst_n` does not affect the RAM and should be tied high or low. In this case, synthesis optimizes the design, and does not use the `rst_n` signal.

Making the RAM Scannable

DW_ram_rw_a_dff may be made scannable using DFT Compiler. Use the `set_test_hold 1 test_mode` command before `insert_scan`.

The `test_mode` signal, when active (high), selects the `test_clk` port to control the capture of data into the RAM. The `test_mode` signal may be tied low if a scannable design is not required. When `test_mode` is tied low, synthesis optimizes the design, and does not connect the `test_mode` and `test_clk` signals.

Attention

For scannable designs, the `test_mode` signal should only be active during scan shifting (i.e., when scan enable is active). When `test_mode` is active, all RAM addresses are written with the `data_in` value at the rising edge of `test_clk`. When `test_mode` and scan enable are both active, the data currently in the RAM is shifted out for viewing the state of the RAM.

Application Notes

DW_ram_rw_a_dff is intended to be used as a small scratch-pad memory or register file. Because DW_ram_rw_a_dff is built from the cells within the ASIC cell library, it should be kept small to obtain an efficient implementation. If a larger memory is required, you should consider using a hard macro RAM from the ASIC library in use.

Suppressing Warning Messages During Verilog Simulation

The Verilog simulation model includes macros that allow you to suppress warning messages during simulation.

To suppress all warning messages for all DWBB components, define the DW_SUPPRESS_WARN macro in either of the following ways:

- Specify the Verilog preprocessing macro in Verilog code:

  ```
  `define DW_SUPPRESS_WARN
  ```

- Or, include a command line option to the simulator, such as:

  `+define+DW_SUPPRESS_WARN` (which is used for the Synopsys VCS simulator)

The warning messages for this model include the following:

- If values other than 1 or 0 are present on a clock port, the following message is displayed:

  ```
  WARNING: <instance_path>.<clock_name>_monitor:
      at time = <timestamp>, Detected unknown value, x, on <clock_name> input.
  ```

  To suppress only this warning message for all DWBB components, use the following macro:

  - Define the DW_DISABLE_CLK_MONITOR macro. You can define this macro in the following ways:
    - Specify the Verilog preprocessing macro in Verilog code:

      ```
      `define DW_DISABLE_CLK_MONITOR
      ```

    - Or, include a command line option to the simulator, such as:

      `+define+DW_DISABLE_CLK_MONITOR` (which is used for the Synopsys VCS simulator)

  This message is also suppressed using the DW_SUPPRESS_WARN macro explained earlier.

Timing Waveforms

The figures in this section show timing diagrams for various conditions of DW_ram_rw_a_dff.

Figure 1-1 Instantiated RAM Timing Waveforms



Figure 1-2 RAM Reset Timing Waveforms



[1] Internal RAM Data is the array of memory bits; the memory is not available to users.

Related Topics

- Memory – Synchronous RAMs Listing
- DesignWare Building Block IP User Guide

HDL Usage Through Component Instantiation - VHDL

```
library IEEE,DWARE;
use IEEE.std_logic_1164.all;
use DWARE.DWpackages.all;
use DWARE.DW_foundation_comp.all;

entity DW_ram_rw_a_dff_inst is
  generic (inst_data_width : INTEGER := 8;
           inst_depth      : INTEGER := 8;
           inst_rst_mode   : INTEGER := 0 );
  port (inst_rst_n     : in std_logic;   inst_cs_n      : in std_logic;
        inst_wr_n      : in std_logic;   inst_test_mode : in std_logic;
        inst_test_clk  : in std_logic;
        inst_rw_addr : in std_logic_vector(bit_width(inst_depth)-1 downto 0);
        inst_data_in : in std_logic_vector(inst_data_width-1 downto 0);
        data_out_inst: out std_logic_vector(inst_data_width-1 downto 0)  );
end DW_ram_rw_a_dff_inst;

architecture inst of DW_ram_rw_a_dff_inst is
begin

  -- Instance of DW_ram_rw_a_dff
  U1 : DW_ram_rw_a_dff
    generic map (data_width => inst_data_width,   depth => inst_depth,
                 rst_mode => inst_rst_mode )
    port map (rst_n => inst_rst_n,   cs_n => inst_cs_n,   wr_n => inst_wr_n,
              test_mode => inst_test_mode,   test_clk => inst_test_clk,
              rw_addr =>   inst_rw_addr,   data_in => inst_data_in,
              data_out => data_out_inst );
end inst;

-- pragma translate_off
configuration DW_ram_rw_a_dff_inst_cfg_inst of DW_ram_rw_a_dff_inst is
  for inst
  end for; -- inst
end DW_ram_rw_a_dff_inst_cfg_inst;
-- pragma translate_on
```

HDL Usage Through Component Instantiation - Verilog

```
module DW_ram_rw_a_dff_inst( inst_rst_n, inst_cs_n, inst_wr_n,
        inst_test_mode, inst_test_clk, inst_rw_addr, inst_data_in,
        data_out_inst );

  parameter data_width = 8;
  parameter depth = 8;
  parameter rst_mode = 0;
  `define bit_width_depth 3 // ceil(log2(depth))

  input inst_rst_n;
  input inst_cs_n;
  input inst_wr_n;
  input inst_test_mode;
  input inst_test_clk;
  input [`bit_width_depth-1 : 0] inst_rw_addr;
  input [data_width-1 : 0] inst_data_in;
  output [data_width-1 : 0] data_out_inst;

  // Instance of DW_ram_rw_a_dff
  DW_ram_rw_a_dff #(data_width, depth, rst_mode)
    U1 (.rst_n(inst_rst_n),   .cs_n(inst_cs_n),   .wr_n(inst_wr_n),
        .test_mode(inst_test_mode),   .test_clk(inst_test_clk),
        .rw_addr(inst_rw_addr),   .data_in(inst_data_in),
         .data_out(data_out_inst) );
endmodule
```

Revision History

For notes about this release, see the *DesignWare Building Block IP Release Notes*.

For lists of both known and fixed issues for this component, refer to the STAR report.

For a version of this datasheet with visible change bars, click here.

Date	Release	Updates
July 2020	DWBB_201912.5	■ Adjusted content and title of "Suppressing Warning Messages During Verilog Simulation" on page 4 and added the DW_SUPPRESS_WARN macro
October 2019	DWBB_201903.5	■ Added the "Disabling Clock Monitor Messages" section
January 2019	DWBB_201806.5	■ Updated example in "HDL Usage Through Component Instantiation - VHDL" on page 6 ■ Added this Revision History table and the document links on this page

Copyright Notice and Proprietary Information

© 2022 Synopsys, Inc. All rights reserved. This Synopsys software and all associated documentation are proprietary to Synopsys, Inc. and may only be used pursuant to the terms and conditions of a written license agreement with Synopsys, Inc. All other use, reproduction, modification, or distribution of the Synopsys software or the associated documentation is strictly prohibited.

Destination Control Statement

All technical data contained in this publication is subject to the export control laws of the United States of America. Disclosure to nationals of other countries contrary to United States law is prohibited. It is the reader's responsibility to determine the applicable regulations and to comply with them.

Disclaimer

SYNOPSYS, INC., AND ITS LICENSORS MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Trademarks

Synopsys and certain Synopsys product names are trademarks of Synopsys, as set forth at https://www.synopsys.com/company/legal/trademarks-brands.html.

All other product or company names may be trademarks of their respective owners.

Free and Open-Source Software Licensing Notices

If applicable, Free and Open-Source Software (FOSS) licensing notices are available in the product installation.

Third-Party Links

Any links to third-party websites included in this document are for your convenience only. Synopsys does not endorse and is not responsible for such websites and their practices, including privacy practices, availability, and content.

Synopsys, Inc.
www.synopsys.com