



SW

```

Ena
Conf t
Int ran f0/1 - 9 , f0/12 - 24
Sw m acc
Sw acc vl 44
Sh
Exit
Int f0/11
Sw m acc
Sw acc vl 10
No sh
Exit
Int f0/10
Sw m tr
No sh
Exit
Int vlan 10
Ip add 10.67.10.10 255.255.255.128
Ip default-gateway 10.67.10.1
Username admin password Technikus
Ip domain name vh.lan
Cry k g rsa
1024
Line vty 0 4
Login local
Transport input ssh
Exit
Vlan 10
Name VH10
Vlan 20
Name VH20
Exit
Int ran f0/11 -13
Sw mode acc
Sw acc vl 10

```

```
No sh
Int ran f0/14 - 16
Sw m acc
Sw acc vl 20
No sh
Exit
```

-----

Router

```
Ena
Conf t
Hostname TR67
Enable password TechnikusEna
Int g0/0/1
Ip add 192.168.19.27 255.255.255.0
Ipv6 add fe80::1 link-local
Ipv6 add fc00::1/64
No sh
Int g0/0/0.10
Encap dot 10
Ip add 10.67.10.1 255.255.255.128
Ipv6 add fe80::1 link-local
Ipv6 add fc10::1/64
Ip nat inside
Int g0/0/0.20
Encap dot 20
Ip add 10.67.20.1 255.255.255.128
Ipv6 add fe80::1 link-local
Ipv6 add fc20::1/64
Ip nat inside
No sh
Exit
Int g0/0/1
Ip nat outside
Exit
Access-list 1 permit any
Ip nat inside source list 1 interface g0/0/1 overload
Ipv6 unicast-routing
Ip dhcp pool cimek
Network 10.67.10.1 255.255.255.128
Default-router 10.67.10.1
Dns 192.168.100.120
```

Ethernet adapter Ethernet:

```
Connection-specific DNS Suffix  . :  
Link-local IPv6 Address . . . . . : fe80::19fc:3723:b5fb:58b2%2  
IPv4 Address. . . . . : 10.67.10.2  
Subnet Mask . . . . . : 255.255.255.128  
Default Gateway . . . . . : 10.67.10.1
```

Ip route 0.0.0.0 0.0.0.0 192.168.19.1