

Keep tabs alive, and reload only when an action changes the data

FixUp Moto · Flutter app · implementation plan · documentation copy

Why it happens

The five tabs sit in a plain `ShellRoute` (`lib/core/router/app_router.dart`). Switching tabs *replaces* the page: the old one — and its page-scoped `HomeBloc` — is destroyed, and coming back builds a new one whose `create:` fires `HomeStatsRequested` again. That is the spinner and the API call.

Now (`ShellRoute`)
Member → Booking → Member
build – fetch – X destroyed
build again – fetch ☒

After (`StatefulShellRoute`)
Member → Booking → Member
build – fetch – hidden – shown (instant)
bloc + data + scroll kept alive

Part 1 — keep the tabs alive

Replace `ShellRoute` with `go_router`'s `StatefulShellRoute.indexedStack` (`go_router ^18` is installed): each tab is a branch built on first visit, then only hidden/shown, so data and scroll position survive and the API is hit once per tab.

- `app_router.dart` — five `StatefulShellBranch` es (home, feeds, membership, bookings with its nested `services/detail/:id` , profile); same routes and builders; the shell builder passes `navigationShell` to `MainShell` .
- `main_shell.dart` — take a `StatefulNavigationShell` ; `selectedIndex` is `navigationShell.currentIndex` ; a tap calls `goBranch(index)` ; back from a non-Home tab calls `goBranch(0)` . `context.go(RouteNames.bookings)` elsewhere keeps working.
- Logout is safe: leaving for `/login` removes the whole shell, so every kept-alive tab is destroyed.

Part 2 — stay fresh with “action succeeded → reload”

Kept-alive tabs only change when told to. The trigger already half-exists: `BookingsBloc` reloads the list after a create — but on the *create page's own* bloc, which never loaded a list, so it does nothing, and the Bookings tab's separate bloc is never told. A tiny app-scoped `DataRefreshCubit` (same pattern as `SelectedWorkshopCubit` : lazy singleton + `BlocProvider.value`) closes that gap: an action calls `invalidate(kind)` , and the tab that owns that data reloads straight away, even while hidden.

CreateBookingPage — BookingActionSuccess → invalidate(bookings)
| (BlocListener, tab is alive but hidden)
BookingsPage ←————→ BookingsListRequested (loaded by the time you're back)

Action succeeds	Calls	Who reloads
Create booking (<code>create_booking_page.dart</code> success listener)	<code>invalidate(bookings)</code>	Bookings tab → <code>_loadBookings()</code>
Add bike (<code>add_bike_page.dart</code> <code>BikesAdded</code>)	<code>invalidate(stats)</code>	Home, Membership, Profile → <code>HomeStatsRequested</code>
Cancel booking	nothing new — same bloc as the list already reloads	
Add bike → My Bikes list	nothing new — existing <code>pop(true)</code> reload	

Files: new `lib/core/refresh/data_refresh_cubit.dart` (state carries a counter so the same kind twice still fires); `injection_container.dart` + `app.dart` (register/provide it); a `BlocListener` in `bookings_page.dart`, `home_page.dart`, `membership_page.dart`, `profile_page.dart`.

Assumptions to confirm: adding a bike can change `stats` (`qty`), and creating a booking doesn't (it only touches the bookings list).

Verification

- `flutter analyze` clean.
- Cubit test: `invalidate` emits, and the same kind twice emits twice.
- Widget tests: `invalidate(bookings)` makes `BookingsPage` send a second `BookingsListRequested`; `invalidate(stats)` makes Home/Membership/Profile send a second `HomeStatsRequested`; a successful create calls `invalidate(bookings)`.
- Router test with two branches: switch away and back, the page is not rebuilt (one fetch, not two).
- Manual: Member → Booking → Member is instant; create a booking and the Bookings list already has it when you return; log out and in as someone else shows no old data.