

Linear Algebra for Machine Learning in Python

Dr. Moritz Wolter

August 10, 2022

High Performance Computing and Analytics Lab

Introcution

Essential operations

Linear curve fitting

Regularization using eigen- oder singular values

Introcution

TODO

$\mathbf{A} \in \mathbb{R}^{m,n}$ is a real-valued Matrix with m rows and n columns.

$$\mathbf{A} = \begin{pmatrix} a_{11} & a_{12} & \dots & a_{1n} \\ a_{21} & a_{22} & \dots & a_{2n} \\ \vdots & \vdots & & \vdots \\ a_{m1} & a_{m2} & \dots & a_{mn} \end{pmatrix}, a_{ij} \in \mathbb{R}. \quad (1)$$

Essential operations

Addition

To matrices $\mathbf{A} \in \mathbf{R}^{m,n}$ and $\mathbf{B} \in \mathbf{R}^{m,n}$ can be added by adding their elements.

$$\mathbf{A} + \mathbf{B} = \begin{pmatrix} a_{11} + b_{11} & a_{12} + b_{12} & \dots & a_{1n} + b_{1n} \\ a_{21} + b_{21} & a_{22} + b_{22} & \dots & a_{2n} + b_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ a_{m1} + b_{m1} & a_{m2} + b_{m2} & \dots & a_{mn} + b_{mn} \end{pmatrix} \quad (2)$$

Multiplication

Multiply $\mathbf{A} \in \mathbb{R}^{m,n}$ by $\mathbf{B} \in \mathbb{R}^{n,p}$ produces $\mathbf{C} \in \mathbb{R}^{m,p}$,

$$\mathbf{AB} = \mathbf{C}. \quad (3)$$

To compute \mathbf{C} the elements in the rows of \mathbf{A} are multiplied with the column elements of \mathbf{B} and the products added,

$$c_{ik} = \sum_{j=1}^m a_{ij} \cdot b_{jk}. \quad (4)$$

Linear Algebra for Machine Learning in Python

└ Essential operations

└ Multiplication

Multiply $\mathbf{A} \in \mathbb{R}^{m \times k}$ by $\mathbf{B} \in \mathbb{R}^{k \times p}$ produces $\mathbf{C} \in \mathbb{R}^{m \times p}$,

$$\mathbf{AB} = \mathbf{C}. \quad (3)$$

To compute \mathbf{C} the elements in the rows of \mathbf{A} are multiplied with the column elements of \mathbf{B} and the products added,

$$c_{ik} = \sum_{j=1}^m a_{ij} \cdot b_{jk}. \quad (4)$$

Define on the board:

- Dot product $\mathbf{a} \cdot \mathbf{b} = a_1 b_1 + a_2 b_2 + \dots + a_n b_n$ for two vectors $\mathbf{a}, \mathbf{b} \in \mathbb{R}^n$.
- Row times column view [Str+09]:

TODO

The Transpose

TODO: use an orthogonal matrix!

Motivation of the determinant

TODO

Computing determinants in two or three dimensions

The two dimensional case:

$$\begin{vmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{vmatrix} = a_{11} \cdot a_{22} - a_{12} \cdot a_{21} \quad (5)$$

(6)

Computing the determinant of a three dimensional matrix.

$$\begin{vmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{vmatrix} = a_{11} \cdot \begin{vmatrix} a_{21} & a_{23} \\ a_{32} & a_{33} \end{vmatrix} - a_{12} \cdot \begin{vmatrix} a_{21} & a_{13} \\ a_{32} & a_{33} \end{vmatrix} + a_{13} \cdot \begin{vmatrix} a_{21} & a_{23} \\ a_{22} & a_{23} \end{vmatrix} \quad (7)$$

Linear Algebra for Machine Learning in Python

└ Essential operations

└ Computing determinants in two or three dimensions

The two dimensional case:

$$\begin{vmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{vmatrix} = a_{11} \cdot a_{22} - a_{12} \cdot a_{21} \quad (5)$$

(6)

Computing the determinant of a three dimensional matrix:

$$\begin{vmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{vmatrix} = a_{11} \cdot \begin{vmatrix} a_{22} & a_{23} \\ a_{32} & a_{33} \end{vmatrix} - a_{12} \cdot \begin{vmatrix} a_{21} & a_{23} \\ a_{31} & a_{33} \end{vmatrix} + a_{13} \cdot \begin{vmatrix} a_{21} & a_{22} \\ a_{31} & a_{32} \end{vmatrix} \quad (7)$$

Draw the sign pattern on the board:

$$\begin{vmatrix} + & - & + & \dots \\ - & + & - & \dots \\ + & - & + & \dots \\ \vdots & \vdots & \vdots & \ddots \end{vmatrix} \quad (8)$$

The determinant can be expanded along any column as long as the sign pattern is respected.

Determinants in n-dimensions

$$\begin{vmatrix} a_{11} & a_{21} & \dots & a_{1n} \\ a_{21} & a_{22} & \dots & a_{2n} \\ \vdots & \vdots & & \vdots \\ a_{m1} & a_{m2} & \dots & a_{mn} \end{vmatrix} = a_{11} \begin{vmatrix} a_{22} & \dots & a_{2n} \\ \vdots & & \vdots \\ a_{m2} & \dots & a_{mn} \end{vmatrix} + a_{21} \begin{vmatrix} a_{21} & \dots & a_{2n} \\ \vdots & & \vdots \\ a_{m2} & \dots & a_{mn} \end{vmatrix} \\
 - a_{m1} \begin{vmatrix} a_{11} & \dots & a_{1n} \\ a_{21} & \dots & a_{2n} \\ \vdots & & \vdots \end{vmatrix}$$

Linear curve fitting

What is the best line connecting measurements?

$$\mathbf{A}^\dagger = (\mathbf{A}^T \mathbf{A})^{-1} \mathbf{A}^T \quad (9)$$

Linear Algebra for Machine Learning in Python

└ Linear curve fitting

└ The Pseudoinverse

$$\mathbf{A}^{\dagger} = (\mathbf{A}^T \mathbf{A})^{-1} \mathbf{A}^T$$

(9)

Sometimes solving $\mathbf{Ax} + \mathbf{b} = 0$ is impossible. One the board, derive:

$$\min_x \frac{1}{2} |\mathbf{Ax} - \mathbf{b}|^2 \quad (10)$$

$$(11)$$

At the optimum we expect,

$$0 = \nabla_x \frac{1}{2} |\mathbf{Ax} - \mathbf{b}|^2 \quad (12)$$

$$= \nabla_x \frac{1}{2} (\mathbf{Ax} - \mathbf{b})^T (\mathbf{Ax} - \mathbf{b}) \quad (13)$$

$$= (\mathbf{Ax} - \mathbf{b}) \mathbf{A}^T \quad (14)$$

$$= \mathbf{A}^T \mathbf{Ax} - \mathbf{A}^T \mathbf{b} \quad (15)$$

$$\mathbf{A}^T \mathbf{b} = \mathbf{A}^T \mathbf{Ax} \quad (16)$$

$$(\mathbf{A}^T \mathbf{A})^{-1} \mathbf{A}^T \mathbf{b} = \mathbf{x} \quad (17)$$

Regularization using eigen- oder singular values

TODO

TODO

References

- [Str+09] Gilbert Strang, Gilbert Strang, Gilbert Strang, and Gilbert Strang. *Introduction to linear algebra*. Vol. 4. Wellesley-Cambridge Press Wellesley, MA, 2009.