

### Homework 3<sup>1</sup>

**Submit on NYU Classes by Fri. Sept. 27 at 8:00 p.m.** You may work together with one other person on this homework. If you do that, hand in JUST ONE homework for the two of you, with both of your names on it. You may \*discuss\* this homework with other students but YOU MAY NOT SHARE WRITTEN ANSWERS OR CODE WITH ANYONE BUT YOUR PARTNER.

**IMPORTANT SUBMISSION INSTRUCTIONS:** Please submit your solutions in 3 separate files: one file for your written answers to Part I, one file for your written answers/output for the questions in Part II, and one file with your code (a zip file if your code requires more than one file).

## Part I: Written Exercises

1. A medical researcher wishes to evaluate a new diagnostic test for cancer. A clinical trial is conducted where the diagnostic measurement  $y$  of each patient is recorded along with attributes of a sample of cancerous tissue from the patient. Three possible models are considered for the diagnostic measurement:
  - Model 1: The diagnostic measurement  $y$  depends linearly only on the cancer volume.
  - Model 2: The diagnostic measurement  $y$  depends linearly on the cancer volume and the patient's age.
  - Model 3: The diagnostic measurement  $y$  depends linearly on the cancer volume and the patient's age, but the dependence (slope) on the cancer volume is different for two types of cancer – Type I and II. (Hint: Use a variable  $x_3$  which is assigned the value 1 if the cancer is Type I, and  $x_3$  has the value 0 if the cancer is of Type II.)
- (a) Define variables for the cancer volume, age and cancer type and write a linear model for the predicted value  $\hat{y}$  in terms of these variables for models 1 & 2 above.
- (b) Do the same for model 3. For Model 3, you will want to use one-hot coding as mentioned above.
- (c) What are the number of parameters in model 1 & 2? Which model is the most complex?
- (d) Since the models in part (a) are linear, given training data, we should have  $\hat{\mathbf{y}} = X\mathbf{w}$  where  $\hat{\mathbf{y}}$  is the vector of predicted values on the training data,  $X$  is a design matrix (feature matrix) and  $\mathbf{w}$  is the vector of parameters. To test the different models, data is collected from 100 patients. The records of the first three patients are shown below:

Patient ID	Measurement $y$	Cancer type	Cancer volume	Patient age
12	5	I	0.7	55
34	10	II	1.3	65
23	15	II	1.6	70
$\vdots$	$\vdots$	$\vdots$	$\vdots$	$\vdots$

For model 1 in part (a), based on this data, what are the first three rows of the matrix  $X$ ?

For model 2 in part (a), based on this data, what are the first three rows of the matrix  $X$ ?

For model 3 in part (a), based on this data, what are the first three rows of the matrix  $X$ ?

---

<sup>1</sup>Some of these are modified from Prof. Rangan's questions.

加常数!

- (e) To evaluate the models, 10-fold cross validation is used with the following results.

Model	training MSE	validation MSE
1	2.0	2.01
2	0.7	0.72
3	0.65	0.90

Which model should be selected?

2. Suppose you were interested in crop yields and you had collected data on the amount of rainfall, the amount of fertilizer, the average temperature, and the number of sunny days.

How could you formalize this as a regression problem?

3. This data for this problem is from [https://stats.libretexts.org/Homework\\_Exercises/General\\_Statistics/Exercises%3A\\_OpenStax/12.E%3A\\_Linear\\_Regression\\_and\\_Correlation\\_\(Exercises\)](https://stats.libretexts.org/Homework_Exercises/General_Statistics/Exercises%3A_OpenStax/12.E%3A_Linear_Regression_and_Correlation_(Exercises))

	Mid-Career Salary (in thousands)	Yearly Tuition
Princeton	137	28,540
Harvey Mudd	135	40,133
CalTech	127	39,900
US Naval Academy	122	0
West Point	120	0
MIT	118	42,050
Lehigh University	118	43,220
NYU-Poly	117	39,565
Babson College	117	40,400
Stanford	114	54,506

Suppose we want to predict the mid-career salary from a person based on the cost of the college they attended. To do this, apply linear regression to the above dataset, using the closed-form formula presented in class.<sup>2</sup> Then answer the following questions.

- The closed form formula uses a matrix  $X$ . What is the value of the matrix  $X$  in this problem?
  - Give the equation for the linear function (line) produced using linear regression, in the form  $g(x) = w_1x + w_0$ .
  - Create a scatter plot of the data, and plot the least squares line in your graph.
  - Compute the determination of correlation,  $R^2$ .
  - Using this linear function, what is the predicted the mid-career salary of a person whose yearly college tuition costs 40,000?
  - Repeat the above steps where the outliers are removed (the outliers are the two service academies whose tuition is \$0.00)
4. In this problem, each example has only one feature:  $\mathbf{x}^{(i)} = x_1^{(i)}$  for  $i = 1 \dots N$ .

Consider a linear model of the form,

$$y \approx \mathbf{w}x,$$

which is a linear model, but with the intercept forced to zero. This occurs in applications where we want to force the predicted value  $\hat{y} = 0$  when  $x = 0$ . For example, if we are modeling  $y =$  output power of a motor vs.  $x =$  the input power, we would expect  $x = 0 \Rightarrow y = 0$ .

---

<sup>2</sup>You may use a computer/calculator to perform the steps - just make sure you know how to do this by hand.

- (a) Given data  $(x^{(i)}, y^{(i)})$  for  $i \in 1 \dots N$ , write a cost function representing the residual sum of squares (RSS) between  $y_i$  and the predicted value  $\hat{y}_i$  as a function of  $\mathbf{w}$ .
  - (b) Taking the derivative with respect to  $\mathbf{w}$ , find the  $\mathbf{w}$  that minimizes the RSS.
5. (extra credit) Suppose when performing linear regression, we cared more about getting some examples correct than on getting other examples correct. To model this we could *weigh* the cost of some mistakes more than others.

Our goal is now to find:

$$\hat{\mathbf{w}}_{wLS} = \arg \min_{\mathbf{w} \in \mathbb{R}^d} \left( \sum_{i=1}^N w^{(i)} (y^{(i)} - \mathbf{x}^{(i)T} \mathbf{w})^2 \right)$$

Find a closed form solution to this problem. (Hint: You can create a matrix  $\Omega \in \mathbb{R}^{N \times N}$  which is a diagonal matrix where  $\Omega_{i,i} = w^{(i)}$ . Now  $\hat{\mathbf{w}}_{wLS} = \arg \min_{\mathbf{w} \in \mathbb{R}^d} (\mathbf{y} - X\mathbf{w})^T \Omega (\mathbf{y} - X\mathbf{w})$ .)

## Part II: Programming Exercise

In this programming experiment you will implement  $k$  nearest neighbors ( $k$ -NN) to classify an Iris as *Iris Setosa*, *Iris Versicolour*, or *Iris Virginica*.

The dataset can be found at <https://archive.ics.uci.edu/ml/datasets/iris>

Each line of the file consists of 4 measurements (*sepal length in cm*, *sepal width in cm*, *petal length in cm*, and *petal width in cm*) and the type of iris these measurements came from.

In your algorithm, you will only use two of these features: *sepal length* and *petal width*. (We are only using these two features since this is an assignment for you to experiment with different values of  $k$  and different distance measurements. With all 4 features, it is easy to classify the Iris perfectly; try this when you have completed your assignment)

Implement the  $k$ -Nearest Neighbor algorithm to classify the test examples, using an *euclidean-distance* function.

Run your algorithm with  $k = 1$ ,  $k = 3$  and with  $k = 5$ .

For  $k > 1$ , sort the training examples by distance from the test example, smallest to largest, to find the  $k$  nearest training examples.

Answer the following questions in a pdf file called `proganswers.pdf`:

1. For  $k = 1$ , which examples were not correctly classified?
2. Report the accuracy on the test set for  $k = 1$ .
3. For  $k = 3$ , which examples were not correctly classified?
4. Report the accuracy on the test set for  $k = 3$ .
5. For  $k = 5$ , which examples were not correctly classified?
6. Report the accuracy on the test set for  $k = 5$ .
7. Suppose we used the very simple Zero-R classifier on this dataset, rather than  $k$ -NN. That is, we classify all examples in the test set as belonging to the class that is most common in the training set. What is the resulting accuracy?
8. Choose a new distance function for your  $k$ -NN algorithm.

You can choose whatever distance function you like, but should choose something that you think might yield higher accuracy than the euclidean distance function.

Run  $k$ -NN with your distance function, using the same training and test sets, to classify the examples in the test set.

Did your distance function achieve higher accuracy (for  $k = 1$ ,  $k = 3$ , and  $k = 5$ ) than the first distance function? If it didn't, what is a possible reason that it didn't?<sup>3</sup>

9. (extra credit) Implement 5-fold cross-validation on the training set to determine which of the following values of  $k$  works better in  $k$ -NN: 3, 7, 99.

More particularly, to implement the 5-fold cross-validation, divide the training set into 5 sets of equal size. In practice you may want to randomly permute the data before dividing it into 5 sets, but for this assignment, just take the first 1/5 of the examples listed in the file, then the second 1/5, etc. (and DON'T PERMUTE) the examples first.

Then for each of the 3 values of  $k$ , do the following. (1) For each of the 5 sets, **train on the examples in the other four sets, and test on the examples in the 5th set.** The result is that a prediction has been made on each example in the training set. (2) Calculate the percentage of these predictions that were correct. This is the cross-validation accuracy (for this value of  $k$ ).

---

<sup>3</sup>If we use the “test” set to choose which distance function and value of  $k$  was best - we should be calling this set a “validation” set and not a “test” set.