Where the Error of the Factorised Cumulant Chain Lives, and What It Costs

WhestBench Phase 2, Algorithm track. Team Hack2Publish: mdhamidhosen, esfer_sami, foyshal_sk.

Submission #334870 (v56As_fs, A class): adjusted score **3.6521e-9**, raw final-layer MSE **1.950e-8**. **Nomination-safe submission #334869** (v56s_fs, B class, ≤ ∼18k warm-call operations, estimate): adjusted score **3.6723e-9**.

11 October 2026. This is the main write-up. The full technical report is attached as the Appendix (full technical report), and "App. §x" refers to its sections. Each number and claim is labelled by its source:

- *graded: an official grade, with its submission id;*
- *measured: a run of our own scripts, with the result file named in App. §8.3;*
- *derived: algebra or arithmetic, with the derivation in the Appendix;*
- *estimate or untested: not yet measured;*
- *conjecture: an interpretation we have not tested, marked as such.*

---

1. Summary

We started from 504aldo's public, MIT-licensed factorised third-cumulant chain ("V29"), which graded 5.418e-9 when submitted verbatim. Our changes take it to **3.6521e-9 (−32.6 %)**: raw MSE falls by 8.6 % (2.133e-8 → 1.950e-8) and util by 26 % (0.254 → 0.187) (derived).

Mechanistic contributions. These are what we consider our contribution to the understanding of white-box estimation:

1. **A spherical-input identity** (§3.1; derived, injection check measured, graded −1.1 % raw at zero cost).
2. **A parity theorem** (§3.2; derived, verified numerically): old κ_3 is odd in the later weights, so every closure built on even statistics loses it.
3. **An error map with channel oracles** (§4; measured on $6{\cdot}10^7$-sample Monte-Carlo teachers). The closures are accurate when given true inputs; the error is input error made at each ReLU and accumulated through depth; the teacher's κ_3 and κ_4 inputs together would take the raw MSE to ×0.272 on MLP #0; the κ_4 gain lives in the **per-neuron pattern** of the κ_4 diagonal, not its level.
4. **A Hermite cubic-star feature, V56** (§5.2; identity derived and verified numerically to ≤ 8.1e-16; graded −4.4 %), motivated by a measured ceiling ladder: second-order births cap the κ_4 pattern at 0.45–0.55, cubic births reach 0.80–0.85.
5. **An analysis of the κ_3-dressed C·T channel** (§4.5; oracle and component level, not graded): with the star it reaches the cubic-birth ceiling, and the chain's own legs reproduce it, but not yet at an affordable cost.
6. **A negative-result atlas** (§7): 24 of the more than 60 architecture and representation ideas we killed, each with its gate and measured number, and three working conclusions that we label as empirical, not proven.

Engineering and fitted components. We state these plainly. Most of the gain from 5.418e-9 to 4.0784e-9 is **cost engineering**: Strassen placement, a transport join, dead-neuron compaction, D21 trimming and an operation budget for the grader's hidden limits (§6). This is performance optimisation, not new understanding. The κ_4 gain from 4.0784e-9 to 3.6521e-9 (−10.5 %) passes through **V55, a linear map fitted offline** to our own Monte-Carlo teacher (§5.1); the V56 star enters as one more feature of that fitted map. FB 1.25, β 1.2, the s3sq coefficient ×1.25, AGE_OLD 5 and R_OLD 352 are **tuned constants**.

Leaderboard context. On the 10 Oct leaderboard the six highest entries are ahead of us on both factors (raw MSE 1.14–1.65e-8 at util 0.106–0.144). Our raw MSE is comparable to entries ranked 11–40. Their methods are not public, and we make no claim about what they are.

---

2. Starting point: the reference method (not claimed)

2.1 Task and score

For a bias-free ReLU MLP of width n = 1024 and depth 16, with He-initialised weights and input $x \sim N(0, I)$, the estimator returns $E[h^{(1)}]$ for every layer. The score is

score = MSE_final × max(0.1, FLOPs / 2^{41}),

with the final-layer MSE measured against a 10^9-sample Monte-Carlo reference. FLOPs are metered by flopscope. We use **1 u = 2^{31} FLOPs**, about one dense 1024^3 product; the budget is then 1024 u, "util" is FLOPs/budget, and the 0.1 floor is 102.4 u. The grader caps each MLP at 120 s of wall time, 0.4 s of residual Python time outside metered operations, and 8 GB of address space. A capped MLP scores about 0.35, so a single cap in a hundred MLPs ruins a submission.

2.2 504aldo's V29 (MIT)

Our estimator modifies **504aldo's public V29** (`whest-p2-cumulant-k3`, forum post #18218), which implements the factorised K = 3 "simple" cumulant propagation of Wu et al. (arXiv:2605.05179, §4.3). Per layer it carries the mean, the covariance C, and the third cumulant κ_3 as a **sum of sources**, one per ReLU. Each source is stored as a propagator leg P_s, a birth leg A_s = P_s a_b, and thin n×16 feedback legs. The next ReLU needs the slices D3_i = κ_iii and D21_ic = κ_iic, read per source from contractions of Hadamard products of the legs. Sources older than four layers live in a shared basis of rank 384 (the oldest in a nested rank-224 sub-basis). κ_4 is not carried: it is regenerated each layer as G_off = λ_l C_off, with a per-MLP adaptive λ. Products use pooled Strassen–Winograd.

The author prices V29 at 260 u and reports a tolerance law: extra final MSE ≈ 4.2e-6·ε^2, where ε is the relative RMS error of D21, so D21 must be right to about 2 %.

Graded baseline. V29, submitted verbatim, graded **5.418e-9** (raw 2.133e-8, util 0.254; **#331681**), matching the author's own submission.

Licence and scope of our claims. Every file we ship keeps 504aldo's MIT copyright notice and LICENSE, and carries a lineage header that names each change and its date. **Only the changes in §3–§6 are claimed as ours.** The sum-of-sources representation, the shared basis, the memoryless κ_4 law, the feedback legs and the pooled Strassen engine are the reference method.

---

3. Exact identities and derivations

3.1 Spherical-input identity (derived; V31)

Write the Gaussian input as $X = (R/\sqrt{n})\cdot Y$, with Y uniform on the sphere of radius $\sqrt{n}$ and $R \sim \chi_n$ independent of Y. A bias-free ReLU network is positively homogeneous of degree 1, so

$E[h(X)] = a_1 E[h(Y)]$, $a_1 = \sqrt{(2/n)}\,\Gamma((n+1)/2)/\Gamma(n/2) = 0.99975589$.

The sphere input has C = I and $\kappa_3 = 0$, and its κ_4 is an exact harmonic core, $g = -6/(n+2)$ in the chain's representation. The estimator injects that core at layer 0, runs the existing κ_4 machinery unchanged, and rescales the output by a_1.

- **Measured:** the injection reproduces the predicted scale shift to 0.3 %.
- **Graded:** −1.1 % raw at zero cost (#331787).

The idea came from a public Phase-2 repository, surfaced by an outside-AI consultation (App. §2.1). The derivation for this chain and its integration are ours.

3.2 Parity theorem: no mean-field part of the deep κ_3 (derived and verified; App. §2.2)

Take a source born at layer b. At any later layer l its legs are $P = W^{T(l)}\ D\ P'$ and $A = P\ a_b$, where P', a_b and the birth coefficients do not depend on $W^{(l)}$. Every quantity linear in the source's κ_3 (the slice products and D3) is therefore **odd** in $W^{(l)}$, while $C^{(l)}$, the leg Grams and the per-neuron variances are **even**. Because the weight ensemble is sign-symmetric,

$E[\ H_s^{(l)} \mid C^{(l)}$, Gram(A_s, P_s), all state before l] = 0, exactly.

Consequences:

- Any closure that replaces old sources by a function of even statistics (mean-field closures, scale mixtures, polynomials in C) discards their entire contribution. This is consistent with the public log's failures of such closures (9.1e-7 and 2.3e-6) and with our learned residual correctors, which recover only 0.3–0.7 % of the residual (§7).
- Replacing a source by its conditional expectation given one fresh weight row has a relative-error floor of $\sqrt{(6/(r+8))}$ in the retained dimension r: 12 % at r = 384, far above the 2 % tolerance.
- κ_4 terms built from two κ_3 factors are even, and $C \otimes C$ is the only even invariant available. We read this as the reason the regenerated law G_off = λ_l C_off works (conjecture beyond the derivation; not tested separately).

Status: derived, then verified (11 Oct; `experiments/probes/parity_check.py`). On the frozen V56 chain (width 128), flipping $W^{(l)}$ leaves every earlier layer and $C^{(l)}$, $var^{(l)}$ bit-identical and flips μ, d3 and D21 exactly (difference 0.0; tested at l = 5, 10). The floor's algebra holds by Monte Carlo, and the bound $\|\tau\|^2 \le (r+2)\|T\|^2/3$ is the exact operator norm (eigen-computation, r = 2–8); a written proof is in App. §2.2. The floor is a statement about the idealised fresh-row model. The mean $\mu^{(l)}$ is also odd, so closures that condition on μ are not covered. The argument originated in a Claude subagent consultation.

3.3 A half-carried feedback term (derived and measured; shipped as tuned FB 1.25)

Expanding the post-ReLU κ_3 to first order in C shows that the newborn source carries exactly **half** of two all-distinct K×C families (derived, App. §2.4). Regression on the slice residual gives coefficients of −0.55 to −0.9, against −1/2 predicted: consistent in sign and size, not exact.

Restoring the missing families in full makes the final mean worse: +3.4 % / +3.1 % on the teacher pair, and ×1.024 on 100 MLPs at FB 2.0. A quarter restoration (FB 1.25) with the adaptive-λ exponent β = 1.2 scored ×0.9946 ± 0.0007 on the 100-MLP harness and graded 5.1284e-9 (#332110), at zero FLOPs. The shipped scale is therefore a **tuned constant**, not the derived one. Why the full restoration hurts is open; one explanation is ruled out (App. §6.5 (b)): the quadratic feedback cross term that also grows with FB is inert.

---

4. The error map: where the chain's error lives

All results in this section are measured, using our Monte-Carlo teachers with $6 \cdot 10^7$ samples on public MLP #0 and a synthetic 1024×16 He network. They record the per-layer pre- and post-ReLU means, covariances, κ_3 slices and κ_4 diagonal. An **oracle** replaces one quantity inside the chain by the teacher's value and reruns the chain end to end. Two networks are a small sample; we state each result for the network it was measured on.

4.1 The closures are accurate; the error is accumulated input error

- **Mean closure.** Given the teacher's true marginals (μ, var, κ_{3iii}, κ_{4iiii}), the Edgeworth mean closure matches the teacher's ReLU mean to 5e-11–1.5e-10 at every layer.
- **Covariance closure.** Teacher-forced at one layer, the bivariate covariance closure falls to the teacher's noise.
- **Accumulation.** The chain's per-layer MSE grows smoothly, from 0.7e-9 at L1 to 2.29e-8 at L16.
- **Inherited share.** Forcing the true mean at every layer removes about 80 % of the final error.

We read these as: the error is **fresh input error** made at each ReLU and carried forward through depth.

4.2 Channel and joint oracles

The base is the plain chain at util 0.2476 (App. §4.8 gives the full table).

Teacher input injected (every layer)	MLP #0	Synthetic net
None (plain chain)	2.273e-8 (×1)	1.920e-8 (×1)
κ_3 slice + d3	×0.607	×0.716
κ_4 diagonal	×0.686	×0.885
κ_3 slice + d3 + κ_4 diagonal	**×0.272**	**×0.569**
κ_3 slice + d3 + κ_4 *pattern* at the chain's level	×0.294	×0.606

- **κ_3 is the larger single lever** on both networks.
- **The two inputs compound more than multiplicatively.** The product of the single-input ratios would be 0.416 and 0.634; jointly they give 0.272 and 0.569.
- **The remainder is consistent with the variance channel.** In the separate channel oracle of App. §4.2 (base 2.290e-8), the true variance, κ_3 diagonal and κ_4 diagonal together take MLP #0 to ×0.057, the truth's own noise floor. The two oracles inject different κ_3 quantities, so this is a consistency check, not a decomposition.

4.3 κ_3: where the error is real, and where the gain lives

We compared the chain's κ_3 with the teacher at every layer, and subtracted in quadrature a Gaussian estimate of the teacher's own sampling noise (derived; this assumes the two are independent):

Layer	D21 off-diagonal error	Teacher noise (est.)	Net D21 error	d3 norm ratio, chain/teacher
2	4.4 %	5.3 %	≈ 0	1.002
4	4.2 %	2.5 %	3.4 %	0.998
8	4.9 %	1.2 %	4.8 %	0.996
12	5.9 %	0.7 %	5.9 %	0.993
16	6.9 %	0.5 %	6.9 %	0.986

Under that noise estimate, the early "error" is mostly teacher noise, while the late slice error is real and grows with depth; the d3 level shrinks by 1.4 % at L16. Of the slice error, 91–96 % sits in the **all-distinct** post-ReLU entries $\kappa_3(h_i, h_j, h_k)$ (App. §4.5).

Localisation. Injecting the teacher's κ_3 only in a window of layers (MLP #0, base 2.2732e-8):

Window	Slice + d3	Slice only	d3 only
L1–4	×1.004	—	—
L5–8	×0.942	—	—
L9–12	×0.857	—	—
L13–16	×0.806	—	—
L1–8	—	×0.937	×1.012
L9–16	—	×0.834	×0.853

The gain lives at **L9–16**, where the slice and d3 matter about equally. Injecting the teacher's κ_3 into the feedback legs alone is worth ×1.001.

4.4 κ_4: the pattern, not the level

Injecting the teacher's κ_4 diagonal into the mean closure takes the raw MSE from 2.290e-8 to 1.609e-8. How that gain splits:

- **The teacher's pattern at the chain's own level** gives 1.551e-8, which is **108 %** of the gain.

- **The chain's pattern at the teacher's level** is *worse than no oracle* (+21.5 %).
- **In our oracles, κ_4 helps only through the mean closure's diagonal input.** True κ_4 everywhere except the mean closure gives ≈ ×1; the off-diagonal slices injected alone give ×1.03–1.22.
- **The chain's pattern is weak where it matters.** Over all neurons the chain's κ_4 diagonal correlates 0.78–0.83 with the truth; on the decisive neurons ($|\mu/\sigma| < 1.5$) that drive the mean closure, only 0.26–0.34.

A ceiling ladder for κ_4 carriers. We measured the ceiling of whole *families* of birth laws by restarting a Gaussian h layers back and expanding each ReLU to Hermite order K (App. §5.4, $N = 4 \cdot 10^6$):

- **Quadratic births are capped:** births that stop at second order reach pattern correlation 0.45–0.55. Every second-order carrier we and outside models proposed stalled at or below this band (0.03–0.56, §7), which is consistent with, though does not prove, the cap being the cause.
- **Cubic births suffice:** cubic births over six layers reach 0.80–0.85, and K = 4 adds ≤ 0.02.
- **Ages are complementary:** ages 1–6 are needed jointly. Ages 1–4 give 0.68–0.74, and ages 4–6 alone give only 0.37–0.41.

This ladder is why V56 uses a *cubic* feature.

4.5 The κ_3-dressed C·T channel (measured at oracle and component level; not graded)

The V56 star (§5.2) is the *Gaussian* cubic birth. A κ_3-dressed C·T readout, ct_i = 24 Σ_a g_a Ỹ_ai X_ai Q_ai, reads the chain's κ_3 through the quadratic and cubic Hermite vertices (design from a 9 Oct consultation; every number below is ours, App. §5.8):

- **Ceiling.** Sample-exact star + C·T reaches 0.82–0.85, matching the cubic-birth ceiling of §4.4. C·T alone sits at 0.42–0.44, where an earlier hub-pair carrier was killed; it is complementary to the star.
- **The chain's own legs reproduce it** at fidelity 0.993–0.996 on decisive neurons (component test).
- **End to end under an oracle map** (fitted to the teacher on the evaluation network, FLOPs not metered): ×0.773 with the sample-exact feature, ×0.819 with the chain's exact C·T on the available source subset.
- **Cost.** An exact age-collapse identity, Γ_a = G_a + Ystep_a Γ_{a+1}, plus grouping by dense anchor, reduces it to two dense products per source and target (derived; matches the per-age route to 2.6–3.2e-7). At r = 64 a sketch keeps ×0.865 at about 40 u (estimate), roughly score-neutral. A rank-32 sketch keeps ×0.874 at an estimated 18–20 u. It is untested on V56 and is our main open lead.

---

5. The κ_4-pattern programme (graded)

5.1 V55: a fitted, zero-FLOP κ_4-pattern map (fitted component)

Given §4.4, V55 corrects the pattern, not the level. At every layer ≥ 6 (≥ 4 from #334762 on), a **fitted linear map** turns seven per-neuron quantities the chain already holds into a predicted pattern of κ_4/v^2: s3sq = $(D3/v\text{^}1.5)^2$; the row and column energies of the standardised D21; the correlation-row energy of C_pre; $|\mu/\sigma|$; the chain's own κ_4/v^2; and a constant. The pattern is rescaled to the chain's layer-mean level and fed **only** to the mean closure. The map is fitted offline, on decisive neurons, against our own teacher for MLP #0; the synthetic net is held out. It costs 0 u and +310 operations.

- **Pattern correlation:** 0.41–0.55 on MLP #0 against 0.24–0.41 for the chain, and 0.41–0.52 held out on the synthetic net.
- **100-MLP harness:** ×0.9455 [90 % CI 0.9410, 0.9498], with 97/100 MLPs improved.
- **Graded:** −5.4 % in both classes. The harness projected 3.8764e-9 / 3.8562e-9; the grades were 3.8762e-9 (#334588) and 3.8582e-9 (#334591).

V55 is a regression on chain features, not a mechanism; its features saturate near pattern correlation 0.5 (App. §5.3).

5.2 V56: the Gaussian cubic-star feature

The cubic Hermite coefficient of the ReLU, $c = -\alpha\varphi(\alpha)/6$ in standardised units, together with the Wick identity $\kappa(u_a^3, u_b, u_c, u_d) = 6\rho_{ab}\rho_{ac}\rho_{ad}$, injects a **star**-shaped fourth cumulant downstream of every hub (derived; verified

numerically to ≤ 8.1e-16, App. §2.5). V56 reads this star from the chain's **own** young dense source legs (ages ≤ 6), with the per-source coefficient recorded at birth (App. §5.8 notation):

$\text{star}_i = 24\,\Sigma_a\, c_a\, \bar{Y}_{ai}\, X_{ai}^3$.

The star enters as an eighth feature of the V55 map, at zero added FLOPs: util 0.1857, against 0.1855 for the V55 reference. Alone its ceiling is 0.47–0.52, but it is complementary to the V55 features: with teacher μ and C, leave-one-layer-out fits rise from 0.48–0.56 to 0.65–0.74. The star idea came from an outside "Hermite Tree Quartic Bank" proposal that built on our own Hermite-family ceilings (App. §5.4–§5.5).

Graded. −4.4 % (#334805, B) and 3.6597e-9 (#334811, A). Refitting the map on the synthetic net gave a further −0.29 % / −0.21 %, reaching **3.6723e-9 (#334869) and 3.6521e-9 (#334870)**.

The κ_4 programme as a whole took the score from 4.0784e-9 to 3.6521e-9 (−10.5 %) at unchanged cost. Its tuning is closed: star ×0.75 / ×1.5 cost ×1.011, and star ages 4 cost ×1.0045.

---

6. Engineering components: cost under the meter and the grader's limits

These sections are performance engineering. We report them because they carry most of the cost reduction and because the grader's hidden limits shaped every later design, not as contributions to understanding.

6.1 Graded trajectory

Step	Our change	Score (id)	Raw MSE	Util
V29 verbatim (reference)	—	5.418e-9 (#331681)	2.133e-8	0.254
Strassen recursion floor 32 → 8	Two more Strassen levels on the basis families	5.220e-9 (#331686)	2.132e-8	0.244
+ first call at full depth	Strassen depth on each worker's first call	5.195e-9 (#331732)	2.132e-8	0.2436
+ V31 spherical-input identity	§3.1, 0 FLOPs	5.137e-9 (#331787)	2.108e-8	0.2437
+ FB 1.25, β 1.2	§3.3 (tuned), 0 FLOPs	5.1284e-9 (#332110)	2.1046e-8	—
Transport join	Shared basis rebuilt at a join by transport, with no range finder	4.9519e-9 (#332257)	2.1788e-8	0.2273
+ AGE_OLD 5, R_FB 4	One more dense young age; feedback rank 16 → 4	4.8066e-9 (#332324)	2.1371e-8	0.2249
v48 compaction	Dead neurons (Φ < 1e-2) dropped from the next transport	4.6294e-9 (#332391)	2.1462e-8	—
v49 basis-side Strassen + aliased Grams	§6.2	4.4157e-9 (#332401)	2.1463e-8	—
v50 D21 live columns	D21 columns of dead neurons never computed	4.2512e-9 (#332404)	2.1537e-8	—
v51 D21 rows	D21 rows of very dead neurons never computed	4.1081e-9 (#332418) / 4.0902e-9 (#332420)	2.1545e-8 / 2.1636e-8	0.191 / 0.189
v52 operation budget, B / A	§6.3: safe against the residual cap	4.1696e-9 (#332566) / 4.1228e-9 (#332567)	—	—
+ R_OLD 352, Tq from QR, R_FB 2	Exact or near-exact trims	B 4.0995e-9 (#332626); A, R_OLD 352 only, 4.0784e-9 (#332621)	2.197e-8 (B)	—
V55 κ_4-pattern map, B / A	§5.1 (fitted)	3.8762e-9 (#334588) / 3.8582e-9 (#334591)	—	—
+ s3sq coefficient ×1.25, B / A	Map coefficient (tuned)	3.8539e-9 (#334762) / 3.8331e-9 (#334763)	—	—
V56 cubic star, B / A	§5.2	3.6829e-9 (#334805) / 3.6597e-9 (#334811)	1.9706e-8 / 1.9539e-8	—
+ map fitted on the synthetic net, B		**3.6723e-9 (#334869)**	—	—
+ map fitted on the synthetic net, A		**3.6521e-9 (#334870)**	**1.950e-8**	0.187

Util is the grader's figure or adjusted ÷ raw. "—" means the value is not listed here. The B class keeps ≤ ~18k warm-call operations for a safety margin under the residual-time cap; the A class runs at about 20k.

6.2 Cost levers

- **Transport join.** V29 rebuilds the shared basis at each join with a randomized range finder; we **transport the previous basis** through the layer and append the joiner. Raw rises slightly (2.1046e-8 → 2.1788e-8), util falls from 0.2437 to 0.2273, and the score improves by 3.4 % (#332257; harness predicted ×0.959).
- **AGE_OLD 5, feedback rank 4.** One more young age kept dense, feedback rank 16 → 4: −2.9 % (#332324, derived). On V56, five nearby age/rank settings score ×1.026 to ×1.104 on 100 MLPs; the shipped setting is the best we tested.
- **Dead-neuron compaction (input side only).** A neuron with small Φ = P(z > 0) has a near-zero post-ReLU response. v48 drops neurons with Φ < 1e-2 from the next transport's inner dimension (−3.7 %, #332391); v50 skips their D21 columns (−3.7 %, #332404); v51 skips the D21 rows of very dead neurons (Φ < 3e-3 or 7e-3; −3.4 % / −3.8 %, #332418 / #332420). Compacting the *output* side failed in every form we tried (measured on the teacher pair):

removing dead neurons as hubs of the new source ×6.40 / ×6.74; zeroing their transported-covariance entries ×1.59 / ×1.46; treating always-on neurons as hubs ×10.0 / ×8.0.

- **Strassen placement and aliased Grams.** Lowering V29's recursion floor from 32 to 8 added two levels on the rank-384/224 families: −3.7 % (#331686; prediction drift 4.9e-13, peak 5.97 GB). v49 routes the basis-side products (join projections, factor rotations, Qc, the D21 lift) through Strassen and writes the joiner Grams as YY^T, which the meter bills at half: −4.6 % (#332401). Level 6 peaked at 8.13 GB, above the cap.

On 26 Sep alone, compaction, trimming and Strassen placement took the score from 4.8066e-9 to 4.1081e-9 (−14.5 %). Over the whole cost programme, the trims removed 22 % of the metered FLOPs (util 0.2437 → 0.189, #332110 → #332420) for +2.8 % raw.

6.3 The residual-time cap and the operation budget

Two variants that ran cleanly on our machines graded catastrophically: #332402 at 0.0434 (≈ 12 % of MLPs capped) and #332425 at 0.0204 (≈ 6 %). Memory was not the cause (local peak 5.51 GiB). We measured that the residual Python time tracks the **number of metered operations**, with no other dependence on the variant that we found: 0.053–0.059 ms per op on Kaggle for every variant, and about 0.02 ms per op inferred (not measured) for the grader. The failing variants issued 21.7k–22.3k operations; one at about 16.4k had passed.

The fix was an **operation budget**: Strassen only where it saves at least about 2 u per 1,000 operations, since each top-level Strassen call costs 110–240 operations. This defines our classes: **B** (nomination-safe), ≤ ~18k operations; **A**, about 20k. The budget cost +1.9 % / +0.8 % graded against v51, and neither class has had a capped MLP since (#332566, #332567).

A second hidden limit appeared with V56. Two 3-D broadcast forms of the cubic star passed in-process runs but failed the grader's smoke test four times (#334786, #334787, #334798, #334799). The first failed the address-space limit ("Unable to allocate 450 MiB"), which only `whest run --runner subprocess` reproduced; the in-place form failed although our subprocess repro passed. The per-slot 2-D form passed (#334805). `whest validate` catches neither limit, so our pre-submission check is an operation count plus a subprocess run.

---

7. Negative-result atlas

"Gate" is the pre-registered pass criterion. Kill types: C, a ceiling or oracle (an upper bound); P, a teacher-forced component test; E, an end-to-end prototype; K, a knob on the 100-MLP harness. Ratios are final-MSE or score ratios against the chain. Details are in App. §6.

Idea	Gate	Measured	Kill
Compensating closure with no old tier (8 models proposed variants)	≤ chain MSE	7.43e-7, 32× the chain; every knob 6.8–9.9e-7	C
Mean-field / even-statistic closures of old κ_3	—	Zero by the parity theorem: old κ_3 is odd in later weights (§3.2)	derived, verified
Low-rank Hadamard products of source legs	low rank	A∘P needs 681–778 of 1024 directions for 99 % energy	C
Query surrogates: trace, diagonal Hermite, TensorSketch	D21 ≤ 2 %	98.2 %, 95.4 %, 790 % at L14	C/P
Source-free dressed hypertree (DHMP)	next D21 ≤ 2.5 %	36–40 %	P
Hermite-tree κ_3 replacing the chain	closure ≤ chain	10–20× worse	P
Every second-order κ_4 carrier (8 designs)	pattern corr ≥ 0.70	0.03–0.56	C
Learned residual correctors (ridge, GBM; 102,400 neurons)	—	0.3–0.7 % of the residual recovered	E
Monte-Carlo control variates	—	Tangent-surrogate corr 0.15–0.29 at L16; variance reduction 1.0–2.2×	P
C·T channel via age-collapsed sketches (ACDS), r = 64	score gain at ≤ ∼30 u	Oracle E2E ×0.865 at ≈ 40 u (estimate): score about neutral. r = 32 (×0.874, est. 18–20 u) is open	E (parked)
Missing cubic-response C×κ_3 term (RLL)	ρ ≥ 0.1 with the residual at L ≥ 9	ρ ≈ 0; adding half the term worsens the slice residual by 15–42 %	P
γ-patch: FB 2.0 with the quadratic cross term held	ratio < 1	×1.0243, the same as unpatched FB 2.0 (×1.0244)	K
$\kappa_4 \to \kappa_3$ feed from the exact κ_4 ($N = 10^6$)	exact ≤ 0.80 pass, > 0.92 kill	×1.115	C/E
κ_3 level rescaling, d3 or D21 ×0.98–1.02	< 1 on both nets	×0.984 to ×1.074; the one gain does not transfer	K
Single shared pool for the whole κ_3	D21 ≤ 2 % at some r ≤ 512	3.4–6.3 % at r = 512; 0.2–1 % only at r = 768	C
Deferred exact join (youngest source exact)	D21 ≤ 2 %	2.5–8 % at r = 352–512	C
Age/rank re-split of V56 (5 settings)	score ratio < 1	×1.026 to ×1.104	K
Checkpointed birth archive (κ_3 skipped in a window, sources kept)	≈ ×1	×14.8 (L1–4) to ×125.6 (L1–12); no recovery after the window	E
Trace projection of old κ_3 (Wu et al.)	D21 ≤ 2 %	26–42 %	C
Cost-first κ_3 representation at 60 % of the cost	2 % channel accuracy	None found; slice-only states are not exact to first order (derived)	derived
Network-conditioned routing over 86 archived variants	≥ 3 % gain	Oracle ceiling 0.80 % before overhead	C
Learned pair-memory student PM364 (source-free, 364 parameters)	MSE to V56 ≤ 1e-9; D21, d3 ≤ 2 %	MSE −0.9 % after training; D21 58–70 %, d3 25–39 %	E
Exact old tier (no confinement)	score gain	−3.9 % MSE for +19 % cost	E
Strassen level 6	≤ 8 GB	8.13 GB	cap

7.1 Working conclusions (empirical; not proven)

1. Within the sum-of-sources family, cost and accuracy traded roughly one for one in every knob we swept. This is an empirical regularity over our sweeps, not a theorem. On the 100-MLP harness the shipped constants sit at the score optimum of the settings tested: β 1.2 (×0.9993), λ ×0.9 (×1.0026), the FB × β grid (within +0.12 %), R_OLD 448 (×1.0113), AGE_OLD 6 on V56 (×1.014), and the five-point age/rank grid on V56, where the best ceiling point gains 0.5 % raw for 3.2 % more util and saving 4.3 % util costs 10.3 % raw. The exceptions in our records are levers that are **exact or nearly exact** (transport join, compaction, Strassen placement, aliased Grams); these are where our cost gains came from. A 27

Sep audit of 74 earlier kills revived 8, all cost or knob levers killed on the wrong criterion; no architecture kill was revived.

2. Local corrections of one channel made the final mean worse in every case we tested: full FB restoration (+3.4 % / +3.1 %); the γ-patch (×1.0243); the RLL term (slice residual 15–42 % worse); scaling the chain's $\kappa_4 \to \kappa_3$ feed toward the larger exact feed (−5 % costs 0.45 %, +10 % costs 9.4 %); injecting the sampled exact feed (×1.115); raising d3 toward the teacher's level (×1.032 / ×1.015); single κ_4 slices (×1.03–1.22). Only **joint** input oracles give large gains (×0.272 against ×0.607 and ×0.686 alone). *Measured at one step (App. §7.5):* the chain's fresh closure-input errors cancel. Their norms sum to 1.9–2.6× their joint error, chiefly var against d3 (cosine down to −0.83). Correcting var alone (L2–L9) or d3 alone (L4–L10) makes the step worse by up to ×1.31 and ×1.13, while var and d3 together always help (×0.56–0.79). How this carries through depth to the final mean remains a conjecture, and for the feed, Monte-Carlo noise is a competing explanation. The practical rule we adopted: local tests are necessary gates, not sufficient ones; candidates are promoted only on the end-to-end mean.

3. Every source-free or pooled κ_3 state we built failed its accuracy gate. *Conjecture:* the common cause is that the all-distinct κ_3 entries, where 91–96 % of the slice error sits (§4.3), are information a cheap state does not hold. Evidence:

- **The slice-state argument (derived in an outside consultation; App. §6.6 (g)).** A perturbation H = ε Sym(e_a, e_b, e_c) with distinct a, b, c is invisible to the mean, the covariance and the slice, yet after one transport it produces a slice and a diagonal that are first order in ε. A recursion on the slice alone therefore cannot be exact to first order, and a linear state closed under every transport that returns every diagonal needs $C(n+2, 3) \approx 1.8 \cdot 10^8$ numbers. The argument does **not** exclude nonlinear, restricted-family or approximate encodings (the source chain itself is one).
- **Age memory (measured).** Keeping only sources of age ≤ h leaves D21 errors of 84 / 65 / 46 / 31 / 16 % at h = 2 / 4 / 6 / 8 / 10; six age modes still leave 8.5 %.
- **Pooling (measured).** Pooling only the old sources costs 1.2–1.3 % at r = 384, but pooling everything needs r = 768.
- **Skipping and learning (measured).** κ_3 could not be deferred to a checkpoint (×14.8 to ×125.6), and our per-neuron-feature student PM364 did not learn it: its D21 error at L2, the first transport, is 57.6 % and does not move under training (two seeds). This rules out that student design, not learned states in general.
- **Averaging (derived).** By the parity theorem (§3.2), closures built on even statistics lose old κ_3 entirely.

Where our cost goes. A V56 call-site ledger puts 193.8 u in one warm call: about 70 u in the D21 hub readout, 63 u in young-leg transport, 20 u in the old basis, and about 40 u elsewhere, which issues 11.3k of the 20.6k operations. The 133 u in the two per-source families grows with depth, and nothing we tested removes it without at least a comparable accuracy loss. For comparison, the reference algorithm of Wu et al. costs about 4,150 u at our size (derived from their cost table), about 21× V56.

Relation to the leaderboard. On the 10 Oct board the six highest entries have raw MSE 1.14–1.65e-8 at util 0.106–0.144; we show raw 1.97e-8 at util 0.187. One entry at rank 11 has V29-level raw MSE (2.10e-8) at util 0.102. At our raw MSE, util 0.10 would score about 2.0e-9 (derived). We do not know the leaders' mechanisms. Our measurements exclude only the specific κ_3 representations in the table above as cheaper drop-in replacements inside our chain.

---

8. Reproducibility

Versions. whestbench 0.16.1, flopscope 0.12.1, dataset revision v2-phase2. Every graded number carries its AIcrowd submission id.

Path	Contents
`submissions/<variant>/estimator.py`	Every shipped estimator, with a lineage header naming each change. #334870 is `submissions/v56As_fs/`, #334869 is `submissions/v56s_fs/`, the reference is `submissions/v29/`.
`experiments/variants/`	Research variants and oracles (`r20_joint_oracle.py`, `r20_cba.py`, `r20_feed_oracle.py`, `v55_k4c.py`, `v56_star.py`, `v56_fbg.py`)
`experiments/probes/`	Probes (`site_ledger.py`, `pool_ceiling.py`, `k3_error_profile.py`, `r17_hermite_family_ceiling.py`, `r20_onestep_channels.py`, `astra_rll_test.py`, `kaggle_pair_compare.py`)
`experiments/student/`	The PM364 student (PyTorch and flopscope versions, V56 label dump, trainer)
`kaggle/`, `kaggle/k4/`	Kaggle kernel wrappers, the 100-MLP harness runners, and the teacher scripts
`results/summaries/`	Result files, including `oct10/` and `student/`
`consultations/`, `docs/architecture_research/KILL_AUDIT.md`	Consultation notes and verdicts, and the kill register
`writeup/`	This document, the Appendix and the PDF builder

App. §8.3 maps every Appendix section to its script and result file; known gaps in our records are in App. §8.4.

The 100-MLP harness. It runs the public mini split with its 10^9-sample truth on five Kaggle CPU runners. `kaggle_pair_compare.py` reports the paired geometric-mean ratio, wins, a bootstrap 90 % interval, the score and the residual-time profile. The base is bit-identical across runners, and paired standard errors are 0.01–0.15 %. Against the grader, every predicted sign has matched the grade; for single changes worth more than about 1 % the predicted size was within 0.05–0.7 percentage points; for gains under 0.5 % the size was unreliable. The harness measures residual time but does not enforce the cap.

Building the PDFs. `python writeup/build_pdf.py` builds the Appendix; `python writeup/build_pdf.py writeup/WRITEUP_MAIN.md --out WRITEUP_MAIN` builds this document. All scripts will be released under MIT after the competition closes.

---

9. Disclosure of AI use

Code. Apart from 504aldo's reference code, essentially all code and probe scripts were written by AI coding assistants (Anthropic Claude models, mainly Claude Opus 5 and 5.5, via Claude Code) under the team's direction. This includes every estimator variant, oracle, probe, harness runner and the PM364 student. Claude subagents also carried out specific derivations and measurement tasks.

Ideas. Many architecture proposals came from consultations with outside AI systems (GPT-5.6, Astra 6, Gemini 3.1 Pro, Grok, DeepSeek, Copilot, SciMaster/Bohrium, and several unsigned answers) over more than 18 rounds (App. §6.4, §9). Of the shipped ideas:

- the spherical-input reparameterisation was pointed out in an outside consultation, which referred to a public repository;
- the cubic-star feature comes from an outside proposal built on our own ceilings;
- the parity argument and the FB-scale derivation came from Claude subagent work with us;
- the slice-state argument (§7.1) came from an outside consultation.

Most proposals were killed (§7); several outside documents reported passing measurements that no run supported (App. §6.4).

Write-up. The text of this write-up and of the Appendix was drafted by AI and checked by the team.

Validation. Apart from the cited figures of 504aldo, Wu et al. and the public leaderboard, and the numbers marked as estimates, every number here was produced by our own scripts (or derived from them) or by the official grader. Every outside claim was re-derived or re-measured before we used it. On 11 Oct 2026 an automated, AI-run fact-check compared

every number in this document with the result files, and the errors it found were corrected. No leaderboard feedback entered any fitted coefficient: the V55 map was fitted against our own teacher for MLP #0, and the shipped V56 maps against our own teacher for the synthetic network.

Understanding: what was verified numerically and what is only derived. The team directed the work and reviewed the results, but several derivations were produced with AI assistance.

- *Verified numerically:* the cubic-star and Wick identities (to ≤ 8.1e-16) and their readout factors (to ≤ 9.0e-15); the spherical identity's scale shift (to 0.3 %); the age-collapse and anchor-grouping identities (to 2.6–3.2e-7); the closure accuracy given true inputs (§4.1); the implementation parity checks (PM364's flopscope and PyTorch versions agree to 2.8e-7); the parity theorem's sign flip on the real chain (exact) and the $\sqrt{(6/(r+8))}$ floor (Monte Carlo plus exact operator norm, with a written proof).
- *Derived, consistent with measurements but not exactly confirmed:* the half-carried feedback term (regression −0.55 to −0.9 against −1/2).
- *Derived only:* the slice-state argument and the C(n+2, 3) count, and the Wu et al. cost comparison.
- *Conjectures:* the depth propagation of the (one-step measured) error cancellation of §7.1 (2), the common cause in §7.1 (3), and the link from parity to the G_off = λ_l C_off law (§3.2).

References

1. Wu et al., arXiv:2605.05179 (v2). The factorised K = 3 "simple" cumulant chain (§4.3), its cost table, and the reference implementations.
2. 504aldo, *whest-p2-cumulant-k3* (GitHub, MIT licence), and WhestBench Phase 2 forum post #18218. The V29 factorised third-cumulant chain used as our reference method.
3. WhestBench (whestbench 0.16.1) and flopscope (0.12.1), the ARC White-Box Estimation Challenge 2026 benchmark and FLOP meter (Alignment Research Center / AIcrowd). The organiser ruling of 11 Sep 2026 states that Strassen–Winograd is legal at any recursion depth.
4. Appendix (full technical report): *Where the Error of the Factorised Cumulant Chain Lives: Exact Identities, Cost Engineering, and a Cubic-Birth κ_4-Pattern Programme for Deep ReLU MLPs*, Hack2Publish, 11 Oct 2026 (`writeup/ALGORITHM_TRACK_PAPER.md`).