Practica Git

Integrantes:

- Francisco Jose Calle Pari
- Emilson Edson Flores Chambi

A) Crear el repositorio

```
PC-7@DESKTOP-RP7KGR4 UCRT64 ~
$ git config --global --list
user.name=Fran
user.email=franciscoparicalle@gmail.com

PC-7@DESKTOP-RP7KGR4 UCRT64 ~
$ mkdir PracticaGit

PC-7@DESKTOP-RP7KGR4 UCRT64 ~
$ cd PracticaGit

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit
$ git init -b master
Initialized empty Git repository in C:/Users/PC-7/PracticaGit/.git/

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git status
On branch master

No commits yet

nothing to commit (create/copy files and use "git add" to track)
```

B) Area de trabajo y primer commit

```
PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ code.
bash: $'\302\223code.': command not found

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git status
On branch master

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        index.html

nothing added to commit but untracked files present (use "git add" to track)

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git add index.html

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git status
On branch master

No commits yet

Changes to be committed:
  (use "git rm --cached <file>..." to unstage)
        new file:   index.html


PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git commit -m "Version inicial"
[master (root-commit) 881419d] Version inicial
 1 file changed, 12 insertions(+)
 create mode 100644 index.html

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git log
commit 881419d2f882f913d8c48c11918378fda0b9046f (HEAD -> master)
Author: Fran <franciscoparicalle@gmail.com>
Date:   Thu Oct 8 17:29:18 2026 -0400

    Version inicial

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git log --oneline
881419d (HEAD -> master) Version inicial
```

C) Modificar y guardar

```
PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git status
On branch master
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   index.html

no changes added to commit (use "git add" and/or "git commit -a")

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git add index.html

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git commit -m "Version agrega companero y materia"
[master f83c79f] Version agrega companero y materia
 1 file changed, 2 insertions(+)

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git log --oneline
f83c79f (HEAD -> master) Version agrega companero y materia
881419d Version inicial
```

D) Practicar restore

```
PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git status
On branch master
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   index.html

no changes added to commit (use "git add" and/or "git commit -a")

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git restore index.html

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ cat index.html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Mi perfil</title>
</head>
<body>
    <h1>Ingenieria de Sistemas</h1>
    <p>Estudiante: Francisco Jose Calle Pari</p>
    <p>Estudiante: Emilson Edson Flores Chambi</p>
    <p>Materia: Proyecto Integrador Intermedio II</p>
</body>
</html>
PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git status
On branch master
nothing to commit, working tree clean
```

E) Crear y utilizar rama

```
PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git branch
* master

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git branch diseño

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git checkout diseño
Switched to branch 'diseño'

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (diseño)
$ git branch
* diseño
  master

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (diseño)
$ git status
On branch diseño
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   index.html

no changes added to commit (use "git add" and/or "git commit -a")

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (diseño)
$ git add.
git: 'add.' is not a git command. See 'git --help'.

The most similar command is
        add

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (diseño)
$ git commit -m "Version agrega informacion academica"
On branch diseño
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   index.html

no changes added to commit (use "git add" and/or "git commit -a")

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (diseño)
$ git commit -m "Version agrega informacion academica"
On branch diseño
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   index.html
```

```
no changes added to commit (use "git add" and/or "git commit -a")

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (diseño)
$ git log --oneline
f83c79f (HEAD -> diseño, master) Version agrega companero y materia
881419d Version inicial

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (diseño)
$ git add index.html

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (diseño)
$ git commit -m "Version agrega informacion academica"
[diseño d5474d4] Version agrega informacion academica
 1 file changed, 1 insertion(+)

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (diseño)
$ git log --oneline
d5474d4 (HEAD -> diseño) Version agrega informacion academica
f83c79f (master) Version agrega companero y materia
881419d Version inicial

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (diseño)
$ git checkout master
Switched to branch 'master'

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git branch
  diseño
* master

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ cat index.html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Mi perfil</title>
</head>
<body>
    <h1>Ingenieria de Sistemas</h1>
    <p>Estudiante: Francisco Jose Calle Pari</p>
    <p>Estudiante: Emilson Edson Flores Chambi</p>
    <p>Materia: Proyecto Integrador Intermedio II</p>
</body>
```

F) Recuperar información de historial

```
PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git log --oneline
f83c79f (HEAD -> master) Version agrega companero y materia
881419d Version inicial

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git checkout 881419d--index.html
error: pathspec '881419d--index.html' did not match any file(s) known to git

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git checkout 881419d -- index.html

PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ git status
On branch master
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   index.html


PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$ cat index.html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Mi perfil</title>
</head>
<body>
    <h1>Ingenieria de Sistemas</h1>
    <p>Estudiante: Francisco Jose Calle Pari</p>
</body>
</html>
PC-7@DESKTOP-RP7KGR4 UCRT64 ~/PracticaGit (master)
$
```

¿Qué ocurrió con index.html?

R. el archivo fue recuperado desde el commit “Version inicial” y volvió a tener su contenido original, y se eliminaron los cambios añadidos posteriores al inicial, pero los commits anteriores permanecen guardados en el historial

Respuesta a las Preguntas

1. ¿Cuál es la diferencia entre área de trabajo y staging area?

El área de trabajo contiene los archivos que estamos creando o modificando. El staging area es donde preparamos los cambios seleccionados mediante git add antes de guardarlos definitivamente con git commit.

2. ¿Para qué sirve git log --oneline?

Sirve para visualizar el historial de commits de forma resumida, mostrando en una sola línea el identificador abreviado de cada commit y su mensaje.

3. ¿Qué diferencia existe entre git restore y git checkout?

git restore se utiliza principalmente para restaurar archivos o descartar modificaciones. git checkout permite cambiar de rama y también recuperar archivos de commits anteriores. Actualmente, para cambiar de rama también se puede utilizar git switch.

4. ¿Para qué sirve una rama (branch)?

Una rama permite desarrollar funcionalidades o realizar modificaciones de forma independiente, sin afectar directamente a la rama principal. Posteriormente, los cambios pueden integrarse mediante un merge