ITEC Rio Cuarto

Carrera: Técnico Superior en Desarrollo de Software

Espacio Curricular: **Inglés**

Docente: **Victoria Cormick**

Examen: Trabajo Práctico #2 –

Fecha: Junio 2024

1) Read the text and extract the following phrases:

-10 Noun phrases. Resaltadas en color AMARILLO

-10 Verb phrases. Resaltadas en color VERDE

-10 Adjective phrases. Resaltadas en color CELESTE

2) Extra point:

Read the following text and identify the following types of verbs:

- **2 present simple verbs.** Resaltadas en color ROSA
- **2 passive voice.**
- **2 modal verbs** Las palabras pintadas en rojo (Must, Can, Should)

MySQL Replication

Set up MySQL master-slave replication

- Last updated on: 2018-10-25

Master-slave data replication allows for replicated data to be copied to multiple computers for backup and analysis by multiple parties. Needed changes identified by a group member must to be submitted to the designated "master" of the node. This differs from **Master-Master replication**, in which data can be updated by any authorized contributor of the group.

This article provides steps for setting up MySQL master-slave database replication between two Cloud Servers. The operating system used for the examples in the article is CentOS 6, built from a Rackspace Cloud Servers base image.

Before you begin

The steps in this article use two Cloud Servers, db01 and db02. Cloud Servers have two IP addresses (one public, one private). The examples demonstrate configuring replication over the private IP interface so that no bandwidth charges are incurred. For the duration of the article, db01 is considered the *master* MySQL server (running in read-write mode), and db02 is considered the *slave* server (running in read-only mode).

ITEC Rio Cuarto

Carrera: Técnico Superior en Desarrollo de Software

Espacio Curricular: **Inglés**
Docente: **Victoria Cormick**
Examen: Trabajo Práctico #2 –
Fecha: Junio 2024

If you already have a MySQL database running on the master node, a dump and restore into the slave node is required before configuring replication between them. You use the **mysqldump** command to dump a database into a file, then transfer it and restore it to the slave. After the necessary configuration has been performed, replication is in effect. For more information, see the **Configure replication** section.

Create the Cloud Servers

Create two Linux cloud servers, using the Centos 6 base image. Use the following steps to create each server separately.

1. Log in to the **Cloud Control Panel**.
2. In the top navigation bar, click **Select a Product > Rackspace Cloud**.
3. Select **Servers > Cloud Servers**.
4. Click **Create Server**.
5. Name the servers so that you can easily identify them during the setup.
6. Select the Centos 6 base image.
7. Select the RAM configuration appropriate for your database requirements.
8. Click **Create Server**.

The commands outlined in the following sections need to be executed by a privileged (root, sudo group) user. Any strings or values specified in brackets should be replaced with data specific to your setup...