



Università degli Studi Roma Tre
Dipartimento di Informatica e Automazione
Computer Networks Research Group

netkit lab


walkthrough

Version	1.3
Author(s)	Massimo Rimondini
E-mail	contact@netkit.org
Web	http://www.netkit.org/
Description	a step-by-step example showing how to set up a complete netkit lab with a few technologies

copyright notice


- All the pages/slides in this presentation, including but not limited to, images, photos, animations, videos, sounds, music, and text (hereby referred to as “material”) are protected by copyright.
- This material, with the exception of some multimedia elements licensed by other organizations, is property of the authors and/or organizations appearing in the first slide.
- This material, or its parts, can be reproduced and used for didactical purposes within universities and schools, provided that this happens for non-profit purposes.
- Information contained in this material cannot be used within network design projects or other products of any kind.
- Any other use is prohibited, unless explicitly authorized by the authors on the basis of an explicit agreement.
- The authors assume no responsibility about this material and provide this material “as is”, with no implicit or explicit warranty about the correctness and completeness of its contents, which may be subject to changes.
- This copyright notice must always be redistributed together with the material, or its portions.

walk through what?




- the goal of this lab is to:
 - put together some technologies presented in other labs
 - step-by-step show how to set up a netkit lab from scratch
- prerequisites
 - it is advisable to take a look at the following netkit labs beforehand:
 - two hosts
 - static routing
 - web server
 - dns

the goal



the goal



vademecum

1. create an empty directory where to put the lab
2. set up physical topology
3. set up routing
4. set up additional technologies
 - in this lab:
 - web server
 - dns

vademecum


1. create an empty directory where to put the lab
2. set up physical topology
3. set up routing
4. set up additional technologies
 - in this lab:
 - web server
 - dns

vademecum

1. create an empty directory where to put the lab

host machine

```
user@localhost:~$ mkdir mylab  
user@localhost:~$ cd mylab  
user@localhost:~/mylab$ █
```



note: here we use terminal commands for any operations
if you feel more comfortable with a graphical file manager/editor, feel free to use it


vademecum

1. create an empty directory where to put the lab
2. set up physical topology
3. set up routing
4. set up additional technologies
 - in this lab:
 - web server
 - dns

2. physical topology

- first of all, we tell netkit which virtual machines (=network nodes) the network consists of

2. physical topology



2. physical topology

- in netkit, each virtual machine corresponds to a directory in the lab



▼ host machine


```
user@localhost:~/mylab$ mkdir client server r1 r2 \
ns-org ns-root ns-net
user@localhost:~/mylab$
```

2. physical topology

- now, we tell netkit about how virtual machines (=network nodes) are interconnected
- this information goes into file **lab.conf**



2. physical topology



2. physical topology

— lab.conf

client[0]=A

r1[0]=A

r1[1]=C

ns-org[0]=C

ns-root[0]=C

ns-net[0]=C

r2[0]=B

r2[1]=C

server[0]=B



2. physical topology

lab.conf

client[0]=A

r1[0]=A
r1[1]=C

ns-org[0]=C

ns-root[0]=C

ns-net[0]=C

r2[0]=B

r2[1]=C

server[0]=B

- **r1's interface eth0** is connected to collision domain **A**
- **r1's interface eth1** is connected to collision domain **C**



vademecum

1. create an empty directory where to put the lab
2. set up physical topology
3. **set up routing**
4. set up additional technologies
 - in this lab:
 - web server
 - dns


3. routing

- the configuration of ip routing consists of two parts:
 - assignment of ip addresses to network interfaces
 - achieved using the `ifconfig` command
 - configuration of static routing
 - achieved using the `route` command
- all these things are commands that virtual machines must run at startup
 - we put them inside `.startup` files



tip: these files are very similar to each other, so **copy&paste** is your friend ;-)

3. routing




3. routing

```
client.startup  
  
ifconfig eth0 192.168.0.111 netmask 255.255.255.128 up  
  
route add default gw 192.168.0.1 dev eth0
```

current lab contents

- client
- ns-net
- ns-org
- ns-root
- r1
- r2
- server
- client.startup
- lab.conf



3. routing

r1.startup

```
ifconfig eth0 192.168.0.1 netmask 255.255.255.128 up  
ifconfig eth1 10.0.0.1 netmask 255.255.255.0 up
```

```
route add -net 192.168.0.128/25 gw 10.0.0.2 dev eth1
```

each router must learn about
non-adjacent networks (only)

current lab
contents

- client
- ns-net
- ns-org
- ns-root
- r1
- r2
- server
- client.startup
- lab.conf
- r1.startup



3. routing

r2.startup


```
ifconfig eth0 192.168.0.129 netmask 255.255.255.128 up  
ifconfig eth1 10.0.0.2 netmask 255.255.255.0 up
```

```
route add -net 192.168.0.0/25 gw 10.0.0.1 dev eth1
```

each router must learn about
non-adjacent networks (only)

current lab
contents

- client
- ns-net
- ns-org
- ns-root
- r1
- r2
- server
- client.startup
- lab.conf
- r1.startup
- r2.startup



3. routing

ns-org.startup


```
ifconfig eth0 10.0.0.3 netmask 255.255.255.0 up
```

```
route add -net 192.168.0.0/25 gw 10.0.0.1 dev eth0
```

```
route add -net 192.168.0.128/25 gw 10.0.0.2 dev eth0
```

current lab
contents

- client
- ns-net
- ns-org
- ns-root
- r1
- r2
- server
- client.startup
- lab.conf
- ns-org.startup
- r1.startup
- r2.startup



3. routing

ns-root.startup


```
ifconfig eth0 10.0.0.4 netmask 255.255.255.0 up
```

```
route add -net 192.168.0.0/25 gw 10.0.0.1 dev eth0
```

```
route add -net 192.168.0.128/25 gw 10.0.0.2 dev eth0
```

current lab
contents

- client
- ns-net
- ns-org
- ns-root
- r1
- r2
- server
- client.startup
- lab.conf
- ns-org.startup
- ns-root.startup
- r1.startup
- r2.startup



3. routing

ns-net.startup


```
ifconfig eth0 10.0.0.5 netmask 255.255.255.0 up
```

```
route add -net 192.168.0.0/25 gw 10.0.0.1 dev eth0
```

```
route add -net 192.168.0.128/25 gw 10.0.0.2 dev eth0
```


current lab contents

- client
- ns-net
- ns-org
- ns-root
- r1
- r2
- server
- client.startup
- lab.conf
- ns-net.startup
- ns-org.startup
- ns-root.startup
- r1.startup
- r2.startup



3. routing

```
server.startup  
ifconfig eth0 192.168.0.222 netmask 255.255.255.128 up  
route add default gw 192.168.0.129 dev eth0
```



current lab contents

- client
- ns-net
- ns-org
- ns-root
- r1
- r2
- server
- client.startup
- lab.conf
- ns-net.startup
- ns-org.startup
- ns-root.startup
- r1.startup
- r2.startup
- server.startup

3. routing

- at this point it is strongly advised to start the lab and check that the routing works

▼ **host machine**

```
user@localhost:~/mylab$ 1start
```




▼ **client**

```
client:~# ping 192.168.0.222
```



current lab
contents



3. routing

- at this point it is strongly advised to start the lab and check that the routing works

- if it doesn't...



- ...check physical topology (`lab.conf`)
- ...check boot-time virtual machine messages (errors printed in blue are relevant)
- ...check routing tables (`route -n`)
- ...

current lab contents

client
ns-net
ns-org
ns-root
r1
r2
server
client.startup
lab.conf
ns-net.startup
ns-org.startup
ns-root.startup
r1.startup
r2.startup
server.startup


vademecum

1. create an empty directory where to put the lab
2. set up physical topology
3. set up routing
4. set up additional technologies
 - in this lab:
 - web server
 - dns

4. web server

- first of all, we need to instruct **server** to start the web server (**apache**) at boot time
- since we must set up a user's web site, we also need to enable **apache's userdir** module
- this is achieved by adding lines to **server.startup**

current lab contents



4. web server

- the module must be enabled *before* **apache** is started

server.startup


```
ifconfig eth0 192.168.0.222 netmask 255.255.255.128 up
```

```
route add default gw 192.168.0.129 dev eth0
```

```
a2enmod userdir
```

```
/etc/init.d/apache2 start
```


current lab contents



4. web server

- now, we create a simple home page for user `guest` (the only non-root user that is available by default in netkit)
- according to the default configuration of module `userdir`, this page must be placed in `/home/guest/public_html/index.html`
- therefore, we put it in `server/home/guest/public_html/index.html`

current lab contents




4. web server

hosts
`http://server.net/~guest/`

`server/home/guest/public_html/index.html`

```
<html>
  <body>
    Hello!
  </body>
</html>
```

current lab contents



4. web server

- at this point we can start the lab and check that the web server works


▼ **host machine**

```
user@localhost:~/mylab$ 1start
```

▼ **client**

```
client:~# 1links http://server.net/~guest
```

current lab
contents



vademecum

1. create an empty directory where to put the lab
2. set up physical topology
3. set up routing
4. set up additional technologies
 - in this lab:
 - dns
 - web server

4. dns

- first of all, we need to instruct some virtual machines to start a name server software (**bind**) at boot time
- we need to add a line to **.startup** files




4. dns

ns-org.startup

```
ifconfig eth0 10.0.0.3 netmask 255.255.255.0 up  
  
route add -net 192.168.0.0/25 gw 10.0.0.1 dev eth0  
route add -net 192.168.0.128/25 gw 10.0.0.2 dev eth0  
/etc/init.d/bind start
```

current lab
contents

- client
- ns-net
- ns-org
- ns-root
- r1
- r2
- server
- client.startup
- lab.conf
- ns-net.startup
- ns-org.startup
- ns-root.startup
- r1.startup
- r2.startup
- server.startup



4. dns

ns-root.startup

```
ifconfig eth0 10.0.0.4 netmask 255.255.255.0 up
```


```
route add -net 192.168.0.0/25 gw 10.0.0.1 dev eth0
```

```
route add -net 192.168.0.128/25 gw 10.0.0.2 dev eth0
```

```
/etc/init.d/bind start
```

current lab contents

- client
- ns-net
- ns-org
- ns-root
- r1
- r2
- server
- client.startup
- lab.conf
- ns-net.startup
- ns-org.startup
- ns-root.startup
- r1.startup
- r2.startup
- server.startup




4. dns

ns-net.startup

```
ifconfig eth0 10.0.0.5 netmask 255.255.255.0 up  
  
route add -net 192.168.0.0/25 gw 10.0.0.1 dev eth0  
route add -net 192.168.0.128/25 gw 10.0.0.2 dev eth0  
/etc/init.d/bind start
```

current lab
contents

- client
- ns-net
- ns-org
- ns-root
- r1
- r2
- server
- client.startup
- lab.conf
- ns-net.startup
- ns-org.startup
- ns-root.startup
- r1.startup
- r2.startup
- server.startup




4. dns

- now, we need to configure the dns service
- dns configuration consists of some files inside `/etc/bind/`
 - we create these files inside each virtual machine's subdirectory
 - `ns-org/etc/bind`
 - `ns-root/etc/bind`
 - `ns-net/etc/bind`



4. dns

- but, hey... dns configuration is rather tricky!



tip: copy files from the dns netkit lab and adjust them as needed


current lab contents

client
ns-net
ns-org
ns-root
r1
r2
server
client.startup
lab.conf
ns-net.startup
ns-org.startup
ns-root.startup
r1.startup
r2.startup
server.startup

4. dns

- download the dns lab from the netkit web site
- copy files from the dns lab to our lab as follows:

from (dns lab)	to (our lab)
dnsroot/etc/bind/db.root dnsroot/etc/bind/named.conf	ns-root/etc/bind
dnsorg/etc/bind/db.org dnsorg/etc/bind/db.root dnsorg/etc/bind/named.conf	ns-org/etc/bind
dnsnet/etc/bind/db.net dnsnet/etc/bind/db.root dnsnet/etc/bind/named.conf	ns-net/etc/bind






4. dns

- trim `named.conf` contents to the essential

```
ns-root/etc/bind/named.conf
```

```
zone "." {  
    type master;  
    file "/etc/bind/db.root";  
};
```

current lab contents





4. dns

- trim `named.conf` contents to the essential and add the requested `allow-recursion` statement


— `ns-org/etc/bind/named.conf`

```
options {  
    allow-recursion {0/0; };  
};  
  
zone "." {  
    type hint;  
    file "/etc/bind/db.root";  
};  
  
zone "org" {  
    type master;  
    file "/etc/bind/db.org";  
};
```

insert this additional statement
in the configuration of `ns-org`
and `ns-net`:

```
options {  
    allow-recursion {0/0; };  
};
```

current lab contents





4. dns

- trim `named.conf` contents to the essential and add the requested `allow-recursion` statement


— `ns-net/etc/bind/named.conf`


```
options {  
    allow-recursion {0/0; };  
};  
  
zone "." {  
    type hint;  
    file "/etc/bind/db.root";  
};  
  
zone "net" {  
    type master;  
    file "/etc/bind/db.net";  
};
```

insert this additional statement
in the configuration of `ns-org`
and `ns-net`:

```
options {  
    allow-recursion {0/0; };  
};
```

current lab contents






4. dns

- configure authoritative information
 - on **ns-root** we just need to update:
 - the address of the root name server
 - the address of the delegated name servers

ns-root/etc/bind/db.root

```
$TTL      60000
@          IN SOA      ROOT-SERVER.  root.ROOT-SERVER. (
                                2006031201 ; serial
                                28800 ; refresh
                                14400 ; retry
                                3600000 ; expire
                                0 ; negative cache ttl
                                )
@          IN NS       ROOT-SERVER.
ROOT-SERVER.  IN A      10.0.0.4
org.         IN NS      dnsorg.org.
dnsorg.org.  IN A       10.0.0.3
net.         IN NS      dnsnet.net.
dnsnet.net.  IN A       10.0.0.5
```

current lab contents



authority
for org

ns-org



4. dns


- configure authoritative information
 - on **ns-org** we need to:
 - update the address of the authority for **org**
 - add a record for the **client** machine
 - discard all the rest (we have no further delegations in this lab)


ns-org/etc/bind/db.org

```
$TTL      60000
@          IN SOA  dnsorg.org.  root.dnsorg.org. (
                        2006031201 ; serial
                        28800 ; refresh
                        14400 ; retry
                        3600000 ; expire
                        0 ; negative cache ttl
                        )
@          IN NS   dnsorg.org.
dnsorg     IN A    10.0.0.3
client     IN A    192.168.0.111
```

has **client.org**
as DNS name

current lab
contents






4. dns

- configure authoritative information
 - on ns-net we need to:
 - update the address of the authority for net
 - add a record for the server machine
 - discard all the rest (we have no further delegations in this lab)

ns-net/etc/bind/db.net

```
$TTL      60000
@          IN SOA  dnsnet.net.  root.dnsnet.net. (
                        2006031201 ; serial
                        28800 ; refresh
                        14400 ; retry
                        3600000 ; expire
                        0 ; negative cache ttl
                        )
@          IN NS   dnsnet.net.
dnsnet     IN  A    10.0.0.5
server     IN  A    192.168.0.222
```

current lab contents




4. dns

- configure hints
 - on all the (non-root) name servers we need to update the address of the root name server

ns-org/etc/bind/db.root

.	IN	NS	ROOT-SERVER.
ROOT-SERVER.	IN	A	10.0.0.4

current lab contents




4. dns

- configure hints
 - on all the (non-root) name servers we need to update the address of the root name server

ns-net/etc/bind/db.root

.	IN	NS	ROOT-SERVER.
ROOT-SERVER.	IN	A	10.0.0.4

current lab contents



uses `ns-org` as
local name server;


4. dns

- last, but not least
 - configure a resolver for `client`!
 - in Linux, this goes to
`/etc/resolv.conf`, therefore we put it
in `client/etc/resolv.conf`

`client/etc/resolv.conf`

```
nameserver 10.0.0.3
```

current lab contents



4. dns

- at this point it is a good idea to start the lab and check that the dns works


▼ **host machine**

```
user@localhost:~/mylab$ 1start
```

▼ **client**

```
client:~# dig server.net
```

current lab
contents




4. dns

- at this point it is a good idea to start the lab and check that the dns works
 - if it doesn't...
 - ...check boot-time virtual machine messages (errors printed in blue are relevant) to see if `bind` has failed starting
 - ...check `/var/log/syslog` (that's where `bind` logs its errors)
 - ... query for intermediate information (e.g., from `client` perform an iterative query to get the address of the root name server)
 - ...



current lab contents



done

- that's it!



```
host machine
user@localhost:~/mylab$ 1crash
█
```

- after stopping it, the lab can be packed in a tar.gz file for redistribution

