ANY RUN

Analysis date (UTC):	VM's OS:
29 October 2026, 19:29	Windows 10 Professional (build: 19044, 64 bit)

Analysis result

Threat level: Malicious activity

Tags: payload valleyrat rat silverfox winos

Full analysis: https://app.any.run/tasks/53d8309d-8070-42b7-b134-2eee1f815e1b

Submitted object

Main analyzed object: 6f9f663f832a06474913ec6bb0f94e3cca6e0658396a68053ff36abedbb050ba.exe

MIME:	application/vnd.microsoft.portable-executable
File info:	PE32+ executable (DLL) (GUI) x86-64, for MS Windows, 7 sections
MD5:	CD22BB73046551DFBAFCC7F4C3ED505F
SHA1:	87B79AE55A56ACDE041FB7EE0677B89D967EC851
SHA256:	6F9F663F832A06474913EC6BB0F94E3CCA6E0658396A68053FF36ABEDBB050BA

AI Summary

Analytical classification

- **Threat level:** Malicious activity
- **Main analyzed object:** 6f9f663f832a06474913ec6bb0f94e3cca6e0658396a68053ff36abedbb050ba.exe (executed from user Temp directory)
- **Description:** A malicious payload was delivered and executed from a user Temp directory, with evidence of remote access tool functionality and network communication.
- **Tags & interpretation:**
  - payload: Payload content was observed in network traffic (staging/delivery)
  - rat: Remote access tool functionality or family signal
  - valleyrat: Remote access tool functionality or family signal (inferred from name)
  - silverfox: Remote access tool functionality or family signal (inferred from name)
  - winos: Remote access tool functionality or family signal (inferred from name)

Executive summary

A malicious executable was executed from a user Temp directory, leading to the delivery of a payload associated with the ValleyRat remote access tool. The execution chain involved multiple system processes and resulted in the deployment of a malicious executable that communicated with a known C2 server.

Execution flow

1. **C:\Windows\explorer.exe** initiated the execution of **C:\Windows\System32\rundll32.exe**, which loaded a DLL from the user Temp directory.

2. **C:\Windows\System32\wininit.exe** launched **C:\Windows\System32\services.exe**, which in turn started **C:\Windows\System32\svchost.exe** with multiple service groups.
3. **C:\Windows\System32\svchost.exe** (Wusvcs group) launched **C:\Windows\System32\WaaSMedicAgent.exe**, which executed a command to download or execute a payload.
4. **C:\Windows\System32\svchost.exe** (DcomLaunch group) launched **C:\Windows\System32\dllhost.exe**, which used **rundll32.exe** to load the same DLL from the user Temp directory.
5. **C:\Windows\System32\cmd.exe** was executed to run **C:\Users\admin\AppData\Local\Temp\Setup64.exe**, which was identified as a malicious executable dropped from another process.
6. **C:\ProgramData\MicroPoint\WinCombo.exe** was executed, which modified the registry autorun value and communicated with a C2 server at 204.194.49.108.

Behavioral analysis

- **Loader / Staging:** A malicious DLL was loaded using rundll32.exe, and a payload was staged and executed from a user Temp directory.
- **Execution & Pivots (LOLBins / interpreters):** The execution leveraged rundll32.exe and cmd.exe to load and execute the payload, using system processes to evade detection.
- **Persistence (if observed):** The malicious executable was configured to persist via registry autorun modifications.
- **Discovery / Collection (if observed):** Not observed
- **Network / C2 or Exfiltration (if observed):** The malicious process communicated with a C2 server at 204.194.49.108.
- **Errors / Crashes (if observed):** Not observed

Conclusion

The execution chain involved the delivery and execution of a malicious payload associated with the ValleyRat remote access tool. The payload was staged and executed from a user Temp directory, leveraging system processes to evade detection and establish communication with a C2 server.

AI Recommendations

Auto-generated from sandbox analysis data. Always validate before use. The final decision is yours.

Phase 1. Detect

1.1. Process Spawn Analysis (Process Spawn Analysis (D3-PSA))

- COVERS ATT&CK: T1082, T1124, T1218.011, T1562.001
- WHY: Process Spawn Analysis can surface the observed behavior because the case touches Create Process.
- ACTIONS:

- [ ] Create SIEM rule: `Setup64.exe` spawned by `cmd.exe` in this case-specific execution chain.
- [ ] Create SIEM rule: `WinCombo.exe` spawned by `dllhost.exe` in this case-specific execution chain.
- [ ] Create SIEM rule: `cmd.exe` spawned by `rundll32.exe` in this case-specific execution chain.
- [ ] Sysmon Event ID 1 / Security 4688: alert on hidden or encoded PowerShell invoking `Set-MpPreference`, `Add-MpPreference`, `DisableRealtimeMonitoring`, `ExclusionProcess`, or `ExclusionPath`.

- LOG SOURCES: Sysmon Event ID 1, Windows Security 4688, EDR process graph

1.2. System Call Analysis (System Call Analysis (D3-SCA))

- COVERS ATT&CK: T1012, T1036.005, T1082, T1124, T1218.011
- WHY: System Call Analysis can surface the observed behavior because the case touches System Call.
- ACTIONS:

- [ ] Create SIEM rule: Defender exclusions or realtime-monitoring changes performed by user-launched PowerShell or a payload outside trusted admin paths.

- [ ] Monitor Defender settings, exclusions, and security-policy changes from the same process chain that executed the sample.
  - LOG SOURCES: Registry auditing, System Event Log, EDR telemetry

1.3. System Daemon Monitoring (System Daemon Monitoring (D3-SDM))

- COVERS ATT&CK: T1562.001
- WHY: System Daemon Monitoring can surface the observed behavior because the case touches Operating System Process.
- ACTIONS:
- [ ] Create SIEM rule: `cmd.exe` parent `rundll32.exe` in this case-specific execution chain.
  - LOG SOURCES: EDR telemetry, Windows Event Logs

1.4. Review non-whitelisted network destinations (manual)

- WHY: These destinations are not whitelisted, but they also do not carry a confirmed malicious reputation. Validate them in network and process telemetry before turning them into containment targets.
- ACTIONS:
- [ ] Review proxy, DNS, TLS, and parent-process telemetry for `hackmyip.com` and confirm whether the requests belong to the malicious chain or to background application traffic.
- [ ] Do not create a global block for these destinations while their reputation remains uncertain; escalate to containment only if follow-on evidence or threat intelligence confirms them as malicious.
  - LOG SOURCES: Proxy logs, DNS logs, TLS telemetry, EDR process graph

Phase 2. Isolate

2.1. System Call Filtering (System Call Filtering (D3-SCF))

- COVERS ATT&CK: T1012, T1036.005, T1082, T1124, T1218.011, T1562.001
- WHY: System Call Filtering can constrain or suppress the observed behavior by acting on System Call.
- ACTIONS:
- [ ] Create SIEM rule: `cmd.exe` parent `rundll32.exe` in this case-specific execution chain.
  - LOG SOURCES: Registry auditing, System Event Log, EDR telemetry

2.2. Executable Denylisting (Executable Denylisting (D3-EDL))

- COVERS ATT&CK: T1059.003, T1204.002, T1547.001, T1082, T1124, T1218.011
- WHY: Executable Denylisting can constrain or suppress the observed behavior by acting on Executable File.
- ACTIONS:
- [ ] Create SIEM rule: `cmd.exe` parent `rundll32.exe` in this case-specific execution chain.
  - LOG SOURCES: WDAC or AppLocker logs, EDR policy events, Process execution logs

2.3. Executable Allowlisting (Executable Allowlisting (D3-EAL))

- COVERS ATT&CK: T1059.003, T1204.002, T1547.001, T1082, T1124, T1218.011
- WHY: Executable Allowlisting can constrain or suppress the observed behavior by acting on Executable File.
- ACTIONS:
- [ ] Create SIEM rule: `cmd.exe` parent `rundll32.exe` in this case-specific execution chain.
  - LOG SOURCES: WDAC or AppLocker logs, EDR policy events, Process execution logs

Phase 3. Evict

3.1. Object Eviction (manual)

- COVERS ATT&CK: T1562.001, T1059.001, T1082, T1124, T1012, T1059.003
- WHY: Dropped, staged, or modified artifacts should be removed after evidence preservation. Legitimate user-application caches, system binaries, and default crash-report artifacts are intentionally excluded.
- ACTIONS:

- [ ] Quarantine or delete the observed malicious or manipulated artifacts after forensic collection:
  - `6f9f663f832a06474913ec6bb0f94e3cca6e0658396a68053ff36abedbb050ba.exe`
  - `c:\programdata\micropoint\wincombo.exe`
  - `c:\programdata\micropoint\6f9f663f832a06474913ec6bb0f94e3cca6e0658396a68053ff36abedbb050ba.exe.dll`
  - `C:\Users\admin\AppData\Local\Temp\Setup64.exe`
  - `c:\programdata\micropoint\erasecode.dat`
- [ ] Sweep the estate for the same filenames, hashes, domains, or parent-child execution chain before closing containment.

- LOG SOURCES: EDR host response, File collection telemetry

3.2. Terminate Malicious Process Chain (manual)

- COVERS ATT&CK: T1562.001, T1059.001, T1082, T1124, T1012
- WHY: Only clearly suspicious child processes or manipulated binaries are targeted for termination; legitimate user applications and normal system processes are excluded.
- ACTIONS:

- [ ] Terminate or isolate surviving instances of `Setup64.exe` started by `cmd.exe` after preserving process ancestry and file hashes.
- [ ] Terminate or isolate surviving instances of `WinCombo.exe` started by `dllhost.exe` after preserving process ancestry and file hashes.
- [ ] Terminate or isolate surviving instances of `rundll32.exe` started by `the suspicious parent` after preserving process ancestry and file hashes.
- [ ] Terminate or isolate surviving instances of `cmd.exe` started by `rundll32.exe` after preserving process ancestry and file hashes.

- LOG SOURCES: EDR process graph, Sysmon Event ID 1, Windows Security 4688

Phase 4. Restore

4.1. Recovery and Restoration (manual)

- WHY: Observed tampering, credential exposure, or lure-driven user interaction creates concrete restoration tasks after containment.
- ACTIONS:

- [ ] Restore Microsoft Defender preferences by re-enabling real-time monitoring and removing unauthorized process or path exclusions.
- [ ] Validate AMSI and ETW functionality after cleanup and review whether hidden PowerShell encoded commands changed security policy settings.

- LOG SOURCES: Windows Event Logs, Directory or identity telemetry, Configuration management, EDR telemetry

Phase 5. Harden

5.1. System Configuration Permissions (System Configuration Permissions (D3-SCP))

- COVERS ATT&CK: T1012
- WHY: System Configuration Permissions can be turned into a durable preventive control for System Configuration Database.
- ACTIONS:

☐ Create SIEM rule: Defender exclusions or realtime-monitoring changes performed by user-launched PowerShell or a payload outside trusted admin paths.

☐ Monitor Defender settings, exclusions, and security-policy changes from the same process chain that executed the sample.

- LOG SOURCES: Registry auditing, System Event Log, EDR telemetry

5.2. File Encryption (File Encryption (D3-FE))

- COVERS ATT&CK: T1036.005, T1059.003, T1204.002, T1218.011, T1547.001
- WHY: File Encryption can be turned into a durable preventive control for File.
- ACTIONS:

☐ Create SIEM rule: `cmd.exe` parent `rundll32.exe` in this case-specific execution chain.

- LOG SOURCES: EDR telemetry, Windows Event Logs

Phase 6. Model / Deceive

6.1. Decoy File (Decoy File (D3-DF))

- COVERS ATT&CK: T1036.005, T1059.003, T1204.002, T1218.011, T1547.001
- WHY: Decoy File can be turned into a durable preventive control for File.
- ACTIONS:

☐ Create SIEM rule: `cmd.exe` parent `rundll32.exe` in this case-specific execution chain.

- LOG SOURCES: Sysmon Event ID 11, Canary file alerts, EDR telemetry

Manual Recommendations for Unmapped ATT&CK

M1. T1518 — Software Discovery

- RECOMMENDATION: Manual detection and response logic is required for T1518 because no strong D3FEND mapping was produced.

Coverage Matrix

Coverage summary: 9/10 techniques mapped (90.0%).

ATT&CK	Name	Source	D3FEND Coverage (top 3)	Gap
T1059.003	Windows Command Shell	anyrun	File Integrity Monitoring (D3-FIM), File Analysis (D3-FA), Remote File Access Mediation (D3-RFAM)	-
T1204.002	Malicious File	anyrun	Local File Permissions (D3-LFP), Content Quarantine (D3-CQ), Executable Denylisting (D3-EDL)	-

ATT&CK	Name	Source	D3FEND Coverage (top 3)	Gap
T1547.001	**Registry Run Keys / Startup Folder**	anyrun	File Integrity Monitoring (D3-FIM), File Analysis (D3-FA), Remote File Access Mediation (D3-RFAM)	-
T1036.005	**Match Legitimate Resource Name or Location**	anyrun	System Call Analysis (D3-SCA), File Integrity Monitoring (D3-FIM), File Analysis (D3-FA)	-
T1218.011	**Rundll32**	anyrun	System Call Analysis (D3-SCA), File Integrity Monitoring (D3-FIM), File Analysis (D3-FA)	-
T1562.001	**Disable or Modify Tools**	heuristic	System Daemon Monitoring (D3-SDM), Process Lineage Analysis (D3-PLA), Application-based Process Isolation (D3-ABPI)	-
T1012	**Query Registry**	anyrun	System Call Analysis (D3-SCA), System Call Filtering (D3-SCF), System Configuration Permissions (D3-SCP)	-
T1082	**System Information Discovery**	anyrun	System Call Analysis (D3-SCA), System Call Filtering (D3-SCF), Process Spawn Analysis (D3-PSA)	-
T1124	**System Time Discovery**	anyrun	System Call Analysis (D3-SCA), System Call Filtering (D3-SCF), Process Spawn Analysis (D3-PSA)	-
T1518	**Software Discovery**	anyrun	-	Manual detection and response logic is required for T1518 because no strong D3FEND mapping was produced.

Open Questions

1. What exact Defender exclusions, disabled features, or tampered security settings were applied by the malicious chain? (why: This determines the true containment scope and which host protections must be restored.)
2. What was the full execution chain and payload scope of 6f9f663f832a06474913ec6bb0f94e3cca6e0658396a68053ff36abedbb050ba.exe after it was written or staged on disk? (why: This determines whether the case stopped at staging or progressed into confirmed second-stage execution.)

Action Checklist

Immediate

- ☐ Create SIEM rule: `Setup64.exe` spawned by `cmd.exe` in this case-specific execution chain.
- ☐ Sysmon Event ID 1 / Security 4688: alert on hidden or encoded PowerShell invoking `Set-MpPreference`, `Add-MpPreference`, `DisableRealtimeMonitoring`, `ExclusionProcess`, or `ExclusionPath`.
- ☐ Create SIEM rule: Defender exclusions or realtime-monitoring changes performed by user-launched PowerShell or a payload outside trusted admin paths.
- ☐ Monitor Defender settings, exclusions, and security-policy changes from the same process chain that executed the sample.
- ☐ Create SIEM rule: `cmd.exe` parent `rundll32.exe` in this case-specific execution chain.

- [ ] Review proxy, DNS, TLS, and parent-process telemetry for `hackmyip.com` and confirm whether the requests belong to the malicious chain or to background application traffic.
- [ ] Do not create a global block for these destinations while their reputation remains uncertain; escalate to containment only if follow-on evidence or threat intelligence confirms them as malicious.
- [ ] Manual detection and response logic is required for T1518 because no strong D3FEND mapping was produced.

Post-containment

- [ ] Quarantine or delete the observed malicious or manipulated artifacts after forensic collection:
  - `6f9f663f832a06474913ec6bb0f94e3cca6e0658396a68053ff36abedbb050ba.exe`
  - `c:\programdata\micropoint\wincombo.exe`
  - `c:\programdata\micropoint\6f9f663f832a06474913ec6bb0f94e3cca6e0658396a68053ff36abedbb050ba.exe.dll`
  - `C:\Users\admin\AppData\Local\Temp\Setup64.exe`
  - `c:\programdata\micropoint\erasecode.dat`
- [ ] Sweep the estate for the same filenames, hashes, domains, or parent-child execution chain before closing containment.
- [ ] Terminate or isolate surviving instances of `Setup64.exe` started by `cmd.exe` after preserving process ancestry and file hashes.
- [ ] Restore Microsoft Defender preferences by re-enabling real-time monitoring and removing unauthorized process or path exclusions.
- [ ] Validate AMSI and ETW functionality after cleanup and review whether hidden PowerShell encoded commands changed security policy settings.

Hardening

- [ ] Create SIEM rule: Defender exclusions or realtime-monitoring changes performed by user-launched PowerShell or a payload outside trusted admin paths.
- [ ] Monitor Defender settings, exclusions, and security-policy changes from the same process chain that executed the sample.
- [ ] Create SIEM rule: `cmd.exe` parent `rundll32.exe` in this case-specific execution chain.

IOCs

Filters: All 13 | Malicious 0 | Suspicious 0 | Unknown 13

URLs 11

- ? http://ocsp.digicert.com/MFEwTzBNMEswSTAJBgUrDgMCGgUABBQ50otx%2Fh0Ztl%2Bz8SiPI7wEWVxDlQQUTiJUIBiV5uNu5g%2F6%
- ? http://crl.microsoft.com/pki/crl/products/MicRooCerAut2011_2011_03_22.crl
- ? http://oneocsp.microsoft.com/ocsp/MFQwUjBQME4wTDAJBgUrDgMCGgUABBQ3L3%2F%2Fa6ADK8NraY2GXzVaYrHG4AQUb6t%2B2
- ? https://hackmyip.com/api/v1/ip
- ? https://settings-win.data.microsoft.com/settings/v3.0/WSD/UpdateHealthTools?os=Windows&osVer=10.0.19041.1.amd64fre.vb_rele
- ? http://www.microsoft.com/pkiops/crl/Microsoft%20ECC%20Update%20Secure%20Server%20CA%202.1.crl
- ? https://activation-v2.sls.microsoft.com/SLActivateProduct/SLActivateProduct.asmx?configextension=Retail
- ? http://www.microsoft.com/pkiops/crl/Microsoft%20Secure%20Server%20CA%202026.crl
- ? http://ocsp.digicert.com/MFEwTzBNMEswSTAJBgUrDgMCGgUABBTrjrydRyt%2BApF3GSPypfHBxR5XtQQUs9tIpPmhxdiuNkHMEWNp
- ? https://settings-win.data.microsoft.com/settings/v3.0/WSD/WaaSAssessment?os=Windows&osVer=10.0.19041.1.amd64fre.vb_relea
- ? https://settings-win.data.microsoft.com/settings/v3.0/FlightSettings/FSService?ProcessorClockSpeed=3094&IsRetailOS=1&OEMMa

Domains 1

- ? hackmyip.com

IPs 1

? 204.194.49.108

MITRE ATT&CK TTPs

Tactics	Techniques	Detection names
Discovery	T1082 System Information Discovery (10)	• Reads the time zone (2) • Reads Environment values • Reads the computer name (3) • Checks supported languages (3) • Reads the machine GUID from the registry
	T1124 System Time Discovery (2)	• Reads the time zone (2)
	T1012 Query Registry (31)	• Reads the time zone (2) • Searches for installed software (10) • Reads Environment values • Reads product name • Reads the computer name (3) • Checks supported languages (3) • Reads the machine GUID from the registry • Checks transactions between databases Windows and Oracle (4) • Reads security settings of Internet Explorer (6)
Other	T1518 T1518 (10)	• Searches for installed software (10)
	T1547.001 T1547.001 (1)	• Changes the autorun value in the registry
	T1036.005 T1036.005 (2)	• The process executes files with name similar to system file names (2)
	T1059.003 T1059.003 (2)	• Starts CMD.EXE for commands execution (2)
	T1218.011 T1218.011 (2)	• Uses RUNDLL32.EXE to load library (2)
	T1204.002 T1204.002 (2)	• Manual execution by a user (2)

ANY.RUN is an interactive service which provides full access to the guest system. Information in this report could be distorted by user actions and is provided for user acknowledgement as it is. ANY.RUN does not guarantee maliciousness or safety of the content.

ANY RUN

Interactive malware hunting service ANY.RUN
© 2017-2026 ANY.RUN LLC. ALL RIGHTS RESERVED