

Languages

U.D. Computación

DSIC - UPV

September 5, 2018

Definitions: Alphabet

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

- *Alphabet*: Finite set of symbols
 - $\Sigma = \{a, b, c\}$
 - $\Gamma = \{0, 1\}$
 - $\Delta_1 = \{\triangle, \square, \bigcirc\}$
 - $\Delta_2 = \{N, S, E, W\}$
- Example of sets that are not alphabets:
 - \emptyset
 - \mathbb{N}

Definitions: Word

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

- (Also known as *string* o *phrase*) finite and ordered sequence of symbols from a given alphabet
 - words over $\{a, b\}$: $x = aaba$, $y = aa$
 - words over $\{0, 1, 2\}$: $x = 2110$, $y = 0101$
- *empty word*: λ .

Definitions: Length

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

- *Length* of a word: number of symbols of the word
Let x and y be words over Σ , and let a be a symbol in Σ :

$$|x| = \begin{cases} 0 & \text{if } x = \lambda \\ 1 + |y| & \text{if } x = ay \end{cases}$$

- $|x|_a$ number of symbols a in the word x

Definitions: Words over Σ

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

- Σ^n set of words of length n over the alphabet
- $\Sigma^* = \bigcup_{i \geq 0} \Sigma^i$
- $\Sigma^+ = \bigcup_{i > 0} \Sigma^i$

Definitions: Canonic order

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

- The alphabetic order ($<_{\Sigma}$) does not allow an effective enumeration of the words over Σ
- Given two words x and y over Σ , the *canonic order* is defined as follows:

$$x < y \text{ if } \begin{cases} |x| < |y| \\ (|x| = |y|) \wedge (x = uav, y = ubw, a <_{\Sigma} b) \end{cases}$$

Operations on words: Concatenation

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Given $x = a_1 a_2 \cdots a_m$ and $y = b_1 b_2 \cdots b_n$, $a_i, b_j \in \Sigma$, the *concatenación* of x and y is defined as:

$$x \cdot y = xy = a_1 a_2 \cdots a_m b_1 b_2 \cdots b_n$$

The *power of a word* is defined taking into account the concatenation:

$$x^n = \begin{cases} \lambda & \text{if } n = 0 \\ x \cdot x^{n-1} = x^{n-1} \cdot x & \text{if } n > 0 \end{cases}$$

Operations on words: Concatenation

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Properties of the concatenation

Let x, y, z be words in Σ^* and $a \in \Sigma$

- 1 Asociative: $(x \cdot y) \cdot z = x \cdot (y \cdot z)$.
- 2 *Neutral element* (λ): $x\lambda = \lambda x = x$.
- 3 $|xy| = |x| + |y|$

Operations on words: Segment, prefix, suffix

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Given x and t , words over Σ^*

- t is a *segment* of x if there exist u and v such that $x = u \cdot t \cdot v$.
- If $u = \lambda$, then t is a *prefix* of x .
- If $v = \lambda$, then t is a *suffix* of x .

Operations on words: Reverse

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Given $x, y \in \Sigma^*$ and a symbol a of the alphabet, the *reverse* of a word is defined as:

$$\begin{cases} \lambda^r = \lambda \\ a^r = a \\ (ax)^r = x^r a \\ (xa)^r = ax^r \end{cases}$$

Operations on words: Reverse

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Properties of the reverse

Let x and y be two words in Σ^*

- 1 $(x^r)^r = x$
- 2 $(xy)^r = y^r x^r$
- 3 $(x^n)^r = (x^r)^n$ for any integer $n \geq 0$

Languages: Definitions

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

A *language* L is a subset of Σ^*

and therefore, these sets are also languages:

- \emptyset (empty language, it does not contain any word)
- Σ^* (all the possible words over Σ)

- A language is *finite* if it contains a finite set of words
- Otherwise, the language is infinite enumerable

Languages: Boolean operations

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

- Union: $L_1 \cup L_2 = \{x \in \Sigma^* : x \in L_1 \vee x \in L_2\}$
- Intersection: $L_1 \cap L_2 = \{x \in \Sigma^* : x \in L_1 \wedge x \in L_2\}$
- Complementation: $\overline{L} = \{x \in \Sigma^* : x \notin L\}$

Languages: Boolean operations

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

Properties of the union and intersection

- Associative
- Commutative
- Neutral element (\emptyset, Σ^*)
 - Union: \emptyset
 - Intersection: Σ^*
- Distributive:
 - $L_1 \cup (L_2 \cap L_3) = (L_1 \cup L_2) \cap (L_1 \cup L_3)$
 - $L_1 \cap (L_2 \cup L_3) = (L_1 \cap L_2) \cup (L_1 \cap L_3)$

Languages: Boolean operations

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Properties of the complementation

- $\overline{\Sigma^*} = \emptyset$

- $\overline{\emptyset} = \Sigma^*$

- $\overline{\overline{L}} = L$

Languages: Boolean operations

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Other operations

- Difference: $L_1 - L_2 = L_1 \cap \bar{L}_2$.
- Symmetric difference: $L_1 \oplus L_2 = (L_1 \cap \bar{L}_2) \cup (\bar{L}_1 \cap L_2)$.

Languages: Rational operations. Product

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

$$L_1 \cdot L_2 = \{xy \in \Sigma^* : x \in L_1 \wedge y \in L_2\}$$

Properties

- (Non-commutative). $L_1 \cdot L_2$ is not, necessarily, equal to $L_2 \cdot L_1$
- (Associative) $(L_1 \cdot L_2) \cdot L_3 = L_1 \cdot (L_2 \cdot L_3)$
- (Neutral element) $L \cdot \{\lambda\} = \{\lambda\} \cdot L = L$
- (Zero) $L \cdot \emptyset = \emptyset \cdot L = \emptyset$
- $\lambda \in L_1 \cdot L_2 \Leftrightarrow \lambda \in L_1 \wedge \lambda \in L_2$
- $L_1 \cdot (L_2 \cup L_3) = L_1 \cdot L_2 \cup L_1 \cdot L_3$
- $L_1 \cdot (L_2 \cap L_3) \subseteq L_1 \cdot L_2 \cap L_1 \cdot L_3$
 - Example: $L_1 = \{a, ab\}$, $L_2 = \{a\}$, $L_3 = \{ba\}$.

Languages: Rational operations. Power

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

$$L^n = \begin{cases} \{\lambda\} & \text{si } n = 0 \\ LL^{n-1} = L^{n-1}L & \text{si } n > 0 \end{cases}$$

Examples

- $\{aa, b\}^2 = \{bb, aab, baa, aaaa\}$
- $\emptyset^0 = (\Sigma^*)^0 = \{\lambda\}^0 = \{\lambda\}$

Languages: Rational operations. Closure

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Star closure

$$L^* = \bigcup_{i \geq 0} L^i$$

Positive closure

$$L^+ = \bigcup_{i > 0} L^i$$

Languages: Rational operations. Closure

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Relationship between star and positive closures

$$L^+ = \begin{cases} L^* & \text{si } \lambda \in L \\ L^* - \{\lambda\} & \text{si } \lambda \notin L \end{cases}$$

Languages: Rational operations. Closure

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

Properties:

- 1 $L \subseteq L^+ \subseteq L^*$ (because $L = L^1$).
- 2 $L_1 \subseteq L_2 \Rightarrow L_1^n \subseteq L_2^n$ ($\forall n \in \mathbb{N}$).
- 3 $L_1 \subseteq L_2 \Rightarrow L_1^* \subseteq L_2^*$ ($L_1^+ \subseteq L_2^+$)
- 4 $(L^*)^* = L^*$
- 5 $(L^+)^+ = L^+$
- 6 $L^+ = L^*L = LL^*$
- 7 $(L^+)^* = L^*$
- 8 $(L^*)^+ = L^*$

Languages: Quotient

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Right quotient

$$u^{-1}L = \{v \in \Sigma^* : uv \in L\}$$

Left quotient

$$Lu^{-1} = \{v \in \Sigma^* : vu \in L\}$$

Languages: Quotient

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

The quotient with respect to a word is usually referred to as *derivative*

Properties ($u, v \in \Sigma^*, a \in \Sigma$)

$$\blacksquare L_1 \subseteq L_2 \Rightarrow u^{-1}L_1 \subseteq u^{-1}L_2$$

$$\blacksquare u^{-1}(L_1 \cup L_2) = u^{-1}L_1 \cup u^{-1}L_2$$

$$\blacksquare u^{-1}(L_1 \cap L_2) = u^{-1}L_1 \cap u^{-1}L_2$$

■

$$a^{-1}(L_1 L_2) = \begin{cases} (a^{-1}L_1) L_2 & \text{si } \lambda \notin L_1 \\ (a^{-1}L_1) L_2 \cup a^{-1}L_2 & \text{si } \lambda \in L_1 \end{cases}$$

$$\blacksquare a^{-1}L^* = (a^{-1}L) L^*$$

$$\blacksquare (uv)^{-1}L = v^{-1}(u^{-1}L)$$

Languages: Homomorphisms

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

Given two alphabets Σ and Γ , an *homomorphism* is a mapping:

$$h : \Sigma \rightarrow \Gamma^*$$

This definition can be extended to words:

$$h : \Sigma^* \rightarrow \Gamma^*$$

$$\begin{cases} h(\lambda) = \lambda \\ h(xa) = h(x)h(a) \end{cases}$$

as well as to languages:

$$h(L) = \{h(x) : x \in L\}$$

Languages: Homomorphism

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Examples:

$$L_1 = \{\lambda, aa, bab, bbba\}$$

$$L_2 = \{x \in \{a, b\}^* : aa \notin \text{Seg}(x)\}$$

$$\begin{cases} h(a) = \lambda \\ h(b) = 1 \end{cases} \quad \begin{cases} g(a) = 01 \\ g(b) = 1 \end{cases}$$

1 $h(L_1) = \{\lambda, 11, 111\}$

2 $h(L_2) = \{1\}^*$

3 $g(\{a, b\}^*) = \{x \in \{0, 1\}^* : 00 \notin \text{Seg}(x) \wedge 0 \notin \text{Suf}(x)\}$

Languages: Inverse homomorphism

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Given an homomorphism $h : \Sigma^* \rightarrow \Gamma^*$, the *inverse homomorphism* is defined as:

$$h^{-1}(y) = \{x \in \Sigma^* : h(x) = y\}$$

This operation can be extended to languages:

$$h^{-1}(L) = \{x \in \Sigma^* : h(x) \in L\}$$

Languages: Inverse homomorphism

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

Examples:

$$L_1 = \{\lambda, aa, abab, bbba\}$$

$$L_2 = \{x \in \{a, b\}^* : aa \notin \text{Seg}(x)\}$$

$$\begin{cases} h(0) = ab \\ h(1) = ba \end{cases} \quad \begin{cases} g(0) = aa \\ g(1) = bab \end{cases}$$

1 $h^{-1}(L_1) = \{\lambda, 00\}$

2 $g^{-1}(L_2) = \{x \in \{0, 1\}^* : |x|_0 = 0\} = \{1\}^*$

3 $h^{-1}(L_2) = \{x \in \{0, 1\}^* : 10 \notin \text{Seg}(x)\}^*$

Languages: Other operations. Reverse

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions
Operations on words

Languages
Boolean operations
Rational operations
Other operations

Classes of
languages

It is possible to extend an operation defined on words to operate on languages. Reverse is an example of the first approach:

$$L^r = \{x^r : x \in L\}$$

Languages: Other operations. Reverse

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

Properties

1 Si $\Sigma = \{a\}$, $L^r = L$.

2 $(L_1 L_2)^r = L_2^r L_1^r$

3 $(L^n)^r = (L^r)^n$

4 $(L^*)^r = (L^r)^*$

5 $(L^r)^r = L$

Languages: Other operations. Segment, prefix, suffix

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

First approach is not valid if the operation on words return a set (language). A second approach is needed:

$$Seg(L) = \bigcup_{x \in L} Seg(x)$$

$$Pref(L) = \bigcup_{x \in L} Pref(x)$$

$$Suf(L) = \bigcup_{x \in L} Suf(x)$$

Classes of languages

Generalidades
sobre
lenguajes

U.D.
Computación

Definitions

Operations on words

Languages

Boolean operations

Rational operations

Other operations

Classes of
languages

A class of languages is a collection or non-empty set of languages.

Examples

- 1 \mathcal{L}_{FIN} Class of finite languages
- 2 $\mathcal{L}_{PAL} = \{L \subseteq \Sigma^* : x \in L \rightarrow x = x^r\}$
(class of palindromic languages)
- 3 $\mathcal{L}_{EVE} = \{L \subseteq \Sigma^* : x \in L \rightarrow |x| \bmod 2 = 0\}$
(class of even languages)
- 4 $\mathcal{L}_{no\lambda} = \{L \subseteq \Sigma^* : \lambda \notin L\}$
(class of languages that do not contain λ)