

Team notebook

March 8, 2023

Contents

1 DP	1
1.1 1D1D	1
1.2 1D2DMaxSum-Multiplication	1
1.3 CoinProblem	3
1.4 ConvexHullTrick	3
1.5 Digit _{dp}	3
1.6 DivideConquerDP	4
1.7 Knapsack	4
1.8 KnuthOptimization	6
1.9 LongestIncreasingSubsequence	6
1.10 connected _{component} _{dp}	7
2 Geometry	7
2.1 2DAlgorithms	7
2.2 3DAlgorithms	10
2.3 Polygons	11
2.4 SegmentIntersection	15
2.5 TrianglesCircles	16
3 Graphs	19
3.1 BellmanFord	19
3.2 BiconnectedComponents	20
3.3 CentroidDecomposition	22
3.4 Dijkstra	22
3.5 D'Esopo-Pape	23
3.6 EulerTour	23
3.7 FloydWarshall	24
3.8 HeavyLightDecomposition	24
3.9 Hungarian	26

3.10 LCA-SP	27
3.11 LaplacianMatrix	29
3.12 MaxBipartiteMatching	30
3.13 MaxFlowDinic	31
3.14 MaxFlowFordFulkerson	31
3.15 MinCostMaxFlow	33
3.16 MinCostMaxFlow2	35
3.17 SCC	35
3.18 StableMatching	36
3.19 ToposortDFS	37
3.20 ToposortKhan	38
4 Header	39
5 Math	39
5.1 ArithmeticEval	39
5.2 CRT	40
5.3 Combinatory	42
5.4 ErathostenesSieve	43
5.5 FFT	43
5.6 Functions	44
5.7 GaussianElimination	46
5.8 MathFuncions	47
5.9 Matrices	49
5.10 PrimeFactorization	49
5.11 Simplex	50
5.12 Simpson	51
6 Misc	52
6.1 AdHoc	52
6.2 Line input	53

6.3	NextGreaterLower	53
7	Strings	54
7.1	AhoCorasick	54
7.2	Hashing	54
7.3	KMP	55
7.4	LongestCommonSubstring	56
7.5	Manacher	56
7.6	PalindromicTree	57
7.7	SuffixArray	59
7.8	Trie	60
8	Structures	61
8.1	BinarySearch-Ternary	61
8.2	CDQDivideConquer	62
8.3	DinamicConnectivity	63
8.4	DisjointIntervals	64
8.5	FenwickTree	64
8.6	FenwickTree2D	64
8.7	Mo	65
8.8	Partially <p><i>persistent</i></p> <i>DSU</i>	66
8.9	PolicyBasedEDD	67
8.10	SegmentTree	67
8.11	SegmentTree2D	68
8.12	SegmentTreeBeats	69
8.13	SegmentTreeBeats2	73
8.14	SegmentTreeIterative	77
8.15	SegmentTreeLazy	77
8.16	SegmentTreePersistent	78
8.17	SegmentTreeSubarraySum	79
8.18	SparseTable	80
8.19	Treap	81
8.20	TreapImplicit	82
8.21	TreapImplicitFather	83
8.22	UnionFind	84
8.23	WaveletTree	85

1 DP

1.1 1D1D

```

#include <bits/stdc++.h>
using namespace std;

#define ll long long
#define ar array
#define rep(i, n) for(int i = 0; i<(int)n; ++i)
#define repr(i, a, b) for(int i = (int)a; i<(int)b; ++i)

const int mxN = 2e5+5, M = 1e9+7;
int n, s, dp[mxN], t[mxN], f[mxN];

int w(int j, int i){ //
    if(j >= i) return 1e9; // here is the cost function from (j, i)
    return s*(f[n]-f[j]) + t[i]*(f[i]-f[j]);
}

struct DD{ // index 0 is used as neutral state
    vector<pair<int, int>> v; // (start pos, best k)
    DD() { v.push_back(make_pair(0, 0)); }
    int qry(int i){
        return (--lower_bound(v.begin(), v.end(), make_pair(i+1,
            0)))>->second;
    }
    void upd(int x){
        for(int i = (int)v.size()-1; i>=0; --i){
            int y = v[i].first, oldk = v[i].second;
            if(y > x && dp[x] + w(x, y) < dp[oldk] + w(oldk, y))
                v.pop_back();
            else{
                int l = y+1, r = n+1;
                while(l < r){
                    int mid = (l+r)/2;
                    if(dp[x] + w(x, mid) < dp[oldk] + w(oldk, mid)) r = mid;
                    else l = mid+1;
                }
                if(r != n+1) v.push_back(make_pair(r, x)); break;
            }
        }
        if(v.size() == 0) v.push_back(make_pair(0, x));
    }
};

cin >> n >> s;
DD dd;
t[0] = f[0] = dp[0] = 0;

```

```

for(int i = 1; i<=n; ++i){
    cin >> t[i] >> f[i]; t[i] += t[i-1]; f[i] += f[i-1];
}
for(int i = 1; i<=n; ++i){
    int k = dd.qry(i); dp[i] = dp[k] + w(k, i);dd.upd(i);
}
cout << dp[n] << '\n';
// https://vjudge.net/problem/OpenJ_Bailian-1180

```

1.2 1D2DMaxSum-Multiplication

```

#include "../Header.cpp"

int main()
{
    // 1D Max Array Sum
    int n = 9, A[] = { 4, -5, 4, -3, 4, 4, -4, 4, -5 }; //Allow all
        negative numbers
    int sum = A[0], ans = A[0];
    for (int i = 1; i < n; i++)
    {
        sum = max(A[i] + sum, A[i]); // Ignores sum if prev sum is worse
            than A[i]
        ans = max(ans, sum);
    }
    cout << ans << "\n";

    // 2D Max Array Sum
    int B [100][100];
    ans = -INF;
    cin>>n;
    for (int i = 0; i < n; i++) for (int j = 0; j < n; j++)
    {
        cin >> B[i][j];
        if (j > 0) B[i][j] += B[i][j-1]; // Acum sum per Row
    }
    for (int l = 0; l < n; l++) for (int r = l; r < n; r++)
    {
        sum = B[0][r];
        int SubAns = B[0][r];
        if (l > 0){ sum -= B[0][l-1]; SubAns -= B[0][l-1]; }
        for (int row = 1; row < n; row++)
        {

```

```

            int aux = B[row][r];
            if(l > 0) aux -= B[row][l-1];
            sum = max(sum + aux, aux);
            SubAns = max (SubAns, sum);
        }
        ans = max(ans, SubAns);
    }
    cout << ans << "\n";

    // Max Array Multiplication
    vl c;
    bool o = 0;
    ans = 1;
    ll miniend = 1, maxiend = 1;
    for (int i = 0; i < c.size(); i++)
    {
        if(c[i] > 0)
        {
            o = 1;
            if(miniend < 0)miniend *= c[i];
            maxiend *= c[i];
        }
        else if(c[i] == 0)
        {
            miniend = 1;
            maxiend = 1;
        }
        else
        {
            int aux = maxiend;
            maxiend = max(1LL, miniend * c[i]);
            miniend = aux*c[i];
        }
        ans = max(ans, maxiend);
    }
    if(ans == 1 && !o) cout << "0\n";
    else
    {
        cout << ans << "\n";
    }

    // n dimension accumulative sum
    for dim = 0 to 4
        for a = 0 to na-1

```

```

    for b = 0 to nb-1
        for c = 0 to nc - 1
            for d = 0 to nd - 1
                pa = a - (dim==0); pb = b - (dim==1); pc = c -
                    (dim==2);
                pd = d - (dim==3);
                if (pa >= 0 && pb >= 0 && pc >= 0 && pd >= 0)
                    dp(a, b, c, d) += dp (pa, pb, pc, pd)

// o por cada celda
for x in S //(celda de menor a mayor tal que todas las anteriores
    estan procesadas)
}

```

1.3 CoinProblem

```

#include "../Header.cpp"

// Number of ways of reaching a quantity n from a set of coins c

int main()
{
    int c[5] = {1, 5, 10, 25, 50};
    int n;
    while(cin >> n)
    {
        int m[n+1];
        m[0] = 1;
        for(int i = 1; i <= n+1; i++) m[i] = 0;
        for(int j = 0; j < 5; j++)
        {
            for(int i = 1; i <= n+1; i++)
            {
                if(i - c[j] >= 0)
                {
                    m[i] += m[i - c[j]];
                    //m[i]=min(m[i],m[i-c[j]]+1); for
                    minimum coins
                }
            }
        }
    }
}

```

```

        cout << m[n] << "\n";
    }

    return 0;
}

```

1.4 ConvexHullTrick

```

#include "../Header.cpp"

struct Line {
    ll m, c, id;
    ll calc(ll x) {

        return m * x + c;
    }
};

bool obsolete(Line a, Line b, Line c){
    return (c.c - a.c) * (a.m - b.m) < (a.m - c.m) * (b.c - a.c);
}

vector<Line>lines;
void insert(Line l) {
    while(lines.size() > 1) {
        ll sz = lines.size();
        if(obsolete(lines[sz-2], lines[sz-1], l)){
            lines.pop_back();
        } else break;
    }
    lines.push_back(l);
}

```

1.5 Digit_{dp}

```

int dp[12][12][2]; // dp[i][s][f] {i: posicion, s: estado del problema,
    f: act < s}
int k, d;

// solve(r) - solve(l-1)
int call(int pos, int cnt, int f){
    if(cnt > k) return 0;
}

```

```

if(pos == num.size()){
    if(cnt == k) return 1;
    return 0;
}
if(dp[pos][cnt][f] != -1) return dp[pos][cnt][f];
int res = 0, LMT;
if(f == 0) LMT = num[pos];
else LMT = 9;
/// Try to place all the valid digits such that the number doesn't
/// exceed b
for(int dgt = 0; dgt <= LMT; dgt++){
    int nf = f, ncnt = cnt;
    if(f == 0 && dgt < LMT) nf = 1; /// The number is getting smaller
    at this position
    if(dgt == d) ncnt++;
    if(ncnt <= k) res += call(pos+1, ncnt, nf);
}
return dp[pos][cnt][f] = res;
}
int solve(string s){
    num.clear();
    while(s.size()){
        num.push_back((s.back()-'0')%10);
        s.pop_back();
    }
    reverse(num.begin(), num.end());
    memset(dp, -1, sizeof(dp));
    return call(0, 0, 0);
}

```

1.6 DivideConquerDP

```
#include "../Header.cpp"
```

```
/// dp(i, j) = min dp(i-1, k-1) + C(k, j) for all k in [0, j]
```

```
/// C(a, c) + C(b, d) <= C(a, d) + C(b, c) for all a <= b <= c <= d
```

```

vp c;
v1 acum1, acum2;

ll cost(ll i, ll j)
{

```

```

    return c[j].first * (acum1[j+1] - acum1[i]) - (acum2[j+1] - acum2[i]);
}

```

```
vector<ll> last, now;
```

```

void compute(int l, int r, int optl, int optr)
{

```

```
    if (l > r) return;
```

```

    int mid = (l + r) / 2;
    pair<ll, int> best = {cost(0, mid), -1};

```

```

    for(int k = max(1, optl); k < min(mid, optr) + 1; k++)
        best = min(best, {last[k - 1] + cost(k, mid), k});

```

```
    now[mid] = best.first;
```

```

    compute(l, mid - 1, optl, best.second);
    compute(mid + 1, r, best.second, optr);
}

```

```

int main(){
    ios_base::sync_with_stdio(0);
    cin.tie(0);

```

```

    ll n, k, x, w;
    while(cin >> n >> k){

```

```

        c.clear();
        for(int i = 0; i < n; i++){

```

```

            cin >> x >> w;
            c.push_back({x, w});
        }

```

```

        acum1.clear();
        acum2.clear();
        acum1.push_back(0);
        acum2.push_back(0);

```

```

        for(int i = 0; i < n; i++){
            acum1.push_back(c[i].second);
            acum2.push_back(c[i].first * c[i].second);
            acum1.back() += acum1[i];

```

```

    acum2.back() += acum2[i];
}

last.assign(n, INF);
now.resize(n);

for(int i = 0; i < k; i++) { compute(0, n - 1, 0, n - 1); swap(last,
    now); }

cout<< last[n-1]<<"\n";

}

```

1.7 Knapsack

```

#include "../Header.cpp"

int V[10000], W[10000], M[102][10202];

// index, capacity
int DP(int i, int c)
{
    if(i== -1)
    {
        return 0;
    }
    if(c==0) return 0;
    if(M[i][c] != -1) return M[i][c];

    M[i][c] = DP(i-1, c);
    if(W[i] <= c){
        M[i][c] = max(M[i][c], DP(i-1, c - W[i]) + V[i]);
    }
    return M[i][c];
}

// Variation

int usados=0,espacio_usado;
int knapSack(int W, int wt[], int val[], int n)
{
    int i, w;
    int K[n+1][W+1][3];

```

```

for (i = 0; i <= n; i++)
{
    for (w = 0; w <= W; w++)
    {
        if (i==0 || w==0){
            K[i][w][0]= 0;
            K[i][w][1]= 0;
            K[i][w][2]= 0;
        }
        else if (wt[i-1] <= w){
            K[i][w][0] = max(val[i-1] +
                K[i-1][w-wt[i-1]][0], K[i-1][w][0]);
            if(K[i-1][w][0]>val[i-1] + K[i-1][w-wt[i-1]][0])
            {
                K[i][w][1]=K[i-1][w][1];
                K[i][w][2]=K[i-1][w][2];
            }
            else{
                K[i][w][1]=K[i-1][w-wt[i-1]][1]+wt[i-1];
                K[i][w][2]=K[i-1][w-wt[i-1]][2]+1;
            }
        }
        else
        {
            K[i][w][0] = K[i-1][w][0];
            K[i][w][1] = K[i-1][w][1];
            K[i][w][2] = K[i-1][w][2];
        }
    }
}

usados=K[n][W][2];
espacio_usado=K[n][W][1];
return K[n][W][0];
}

int main()
{
    int v,W,t;
    cin>>t;
    for(int o=0;o<t;o++)
    {
        W=50;
        usados=0;

```

```

cin>>v;
int val[v];
int wt[v];
for(int i=0;i<v;i++)
{
    cin>>val[i];
    cin>>wt[i];
}
int n = sizeof(val)/sizeof(val[0]);
cout<<knapSack(W, wt, val, n)<<" brinquedos"<<endl;
cout<<"Peso: "<<espacio_usado<<" kg"<<endl;
cout<<"sobra(m) "<<v-usados<<" pacote(s)"<<endl<<endl;
}
return 0;
}

```

1.8 KnuthOptimization

```

int N; vector<int> A;
vector<vector<int>> DP, OPT;

int main()
{
    DP.assign(N + 1, vi(N + 1));
    OPT.assign(N + 1, vi(N + 1));

    rep(i, N) DP[i][i + 1] = A[i + 1] - A[i], OPT[i][i + 1] = i;

    repx(d, 2, N + 1) rep(l, N + 1 - d)
    {
        int r = l + d, l_ = OPT[l][r - 1], r_ = OPT[l + 1][r];
        DP[l][r] = 1e9;
        repx(i, l_, r_ + 1)
        {
            int aux = DP[l][i] + DP[i][r] + A[r] - A[l];
            if (aux < DP[l][r]) DP[l][r] = aux, OPT[l][r] = i;
        }
    }
}

```

1.9 LongestIncreasingSubsequence

```
#include "../Header.cpp"
```

```

vl A, p;
void print_LIS(int i) {
    if (p[i] == -1) { printf("%d", A[i]); return; } // backtracking routine
    print_LIS(p[i]); // backtrack
    printf(" %d", A[i]);
}

```

```

//O(nlogn)
int lis(vector<int> const& a) {
    int n = a.size();
    const int INF = 1e9;
    vector<int> d(n+1, INF);
    d[0] = -INF;

    for (int i = 0; i < n; i++) {
        int j = upper_bound(d.begin(), d.end(), a[i]) - d.begin();
        if (d[j-1] < a[i] && a[i] < d[j])
            d[j] = a[i];
    }

    int ans = 0;
    for (int i = 0; i <= n; i++) {
        if (d[i] < INF)
            ans = i;
    }
    return ans;
}

```

```

int main()
{
    ll t,n;
    cin>>t;
    while(t--)
    {
        int x;
        cin>>n;
        for(int i=0;i<n;i++)
        {
            cin>>x;
            A.push_back(x);
        }
    }
}

```

```

11 LIS[100][100] // LIS for any (i, j)
for(int z = 0; z < n; z++){
    int k = z, lis_end = z;
    vl L(n, 0), L_id(n, 0);
    p.assign (n, -1)

    for (int i = z; i < n; ++i) {
        int pos = lower_bound(L.begin() + z, L.begin()+k, c[i]) -
            L.begin();
        if(A[i]==L[pos])pos++;//For non strickly increasing
            subsequence
        L[pos] = c[i];
        L_id[pos] = i;
        p[i] = pos ? L_id[pos-1] : -1;
        if (pos == k) {
            k = pos+1;
            lis_end = i;
        }
    }
    for(int i = z; i < n; i++)
    {
        if(p[i] == -1) LIS[z][i] = 1;
        else LIS[z][i] = 1 + LIS[z][p[i]];
    }
}
cout<<"Final LIS is of length: "<< k<<"\n";
print_LIS(lis_end);cout<<"\n";

//DP
vl LI(n, 0), LD(n,0);
ll in=0,dec=0;
for(int i=0;i<n;i++)
{
    LI[i]=1;
    LD[i]=1;
    for(int j=0;j<i;j++)
    {
        if(A[j]<A[i])
        {
            LI[i]=max(LI[i],LI[j]+1);
        }
        if(A[j]>A[i])

```

```

        {
            LD[i]=max(LD[i],LD[j]+1);
        }
    }
    in=max(in,LI[i]);
    dec=max(dec,LD[i]);
}

return 0;
}

```

1.10 connected_{component}_{dp}

```

int n, k, dp[mxN][mxN][1005][3];
int a[mxN];

int ff(ll i, ll c, ll sum, ll b){ // {i, components, sum, borders} 1
    indexed
    if(b > 2 || sum > k) return 0; // k = limit sum
    if(c == 0 && i > 1) return 0;
    if(i == n+1) return b == 2 && c == 1; // array completely filled
    int &ret = dp[i][c][sum][b];
    if(ret != -1) return ret; // this behind changes between
        problems
    int nsum = sum + (a[i]-a[i-1])*(2*c-b); // all unknown positions
        equals to a[i]
    ll ans = 0;
    if(c >= 2) ans += (c-1)*ff(i+1, c-1, nsum, b); // merge two cc
    if(c >= 1) ans += (2LL*c-b)*ff(i+1, c, nsum, b); // add to a
        component end
    ans += (c+1-b)*(i+1, c+1, nsum, b); // create new component
    if(b < 2) ans += (2LL-b)*ff(i+1, c+1, nsum, b+1); // create new end
    if(b < 1) ans += (2LL-b)*ff(i+1, c, nsum, b+1); // extend cc to a
        border
    ans %= M; return ret = ans;
}

```


2 Geometry

2.1 2D Algorithms

```
#include "../Header.cpp"
```

```
double DEG_to_RAD(double d) { return d*PI / 180.0; }
double RAD_to_DEG(double r) { return r*180.0 / PI; }
```

```
//#define db long long
```

```
struct point { db x, y;
    point() { x = y = 0.0; }
    point(db _x, db _y) : x(_x), y(_y) {}
    bool operator <(const point& p) const { return (x < p.x ? true : (x
        == p.x && y < p.y)); }
    bool operator == (const point& p) const { return abs(p.x - x) < EPS
        && abs(p.y - y) < EPS; }
    point operator + (const point& p) const { return point(x + p.x, y +
        p.y); }
    point operator - (const point& p) const { return point(x - p.x, y -
        p.y); }
    point operator * (db p) const { return point(x * p, y * p); }
    point operator / (db p) const { return point(x / p, y / p); }
    db operator^(const point &p) const {return x * p.y - y * p.x; }
    db operator*(const point &p) const {return x * p.x + y * p.y; }
    db norm_sq() const { return x*x + y*y; }
    point rot(){ return point(-y, x); }
    point rot45(){ return point(x + y, y - x); }
```

```
// by angles but with cross
```

```
bool half() const { return y > 0 || (y == 0 && x > 0); }
bool operator<(const point &p) const
{
    int h1 = half(), h2 = p.half();
    return h1 != h2 ? h1 > h2 : ((*this) ^ p) > 0;
}
```

```
db ang()
{
    double a = atan2(y, x);
    if (a < 0) a += 2.0 * PI;
    return a;
}
```

```
};
```

```
db dist(const point& p1, const point& p2) {
    return sqrt((p1.x-p2.x)*(p1.x-p2.x)+ (p1.y-p2.y)*(p1.y-p2.y)); }
db dist_sq(point p1, point p2) {
    return (p1.x - p2.x)*(p1.x - p2.x)+(p1.y - p2.y)*(p1.y - p2.y); }
```

```
point rotate(point p, db rad) {
    return point(p.x * cos(rad) - p.y*sin(rad),
        p.x * sin(rad) + p.y*cos(rad)); }
```

```
struct line { db a, b, c; };
```

```
void pointsToLine(point p1, point p2, line &l) {
    if (fabs(p1.x-p2.x) < EPS) // vertical line is fine
        l = {1.0, 0.0, -p1.x}; // default values
    else {
        db a = -(db)(p1.y-p2.y) / (p1.x-p2.x);
        l = {a,
            1.0, // IMPORTANT: we fix the value of b to 1.0
            -(db)(a*p1.x) - p1.y}; }
}
```

```
// for integers, normalized
```

```
void pointsToLine(point& p1, point p2, line &l) {
    l.a = p1.y - p2.y;
    l.b = p2.x - p1.x;
    l.c = p1.x * (p2.y - p1.y) - p1.y * (p2.x - p1.x);
    ll g = __gcd(abs(l.a), __gcd(abs(l.b), abs(l.c)));
    ll sgn = 1;
    if(l.a < 0 || (l.a == 0 && l.b < 0))sgn = -1;
    l.a /= g * sgn; l.b /= g * sgn; l.c /= g * sgn;
}
```

```
// not needed since we will use the more robust form: ax + by + c = 0
struct line2 { db m, c; }; // another way to represent a line
```

```
int pointsToLine2(point p1, point p2, line2 &l) {
    if (abs(p1.x-p2.x) < EPS) { // special case: vertical line
        l.m = INF; // l contains m = INF and c = x_value
        l.c = p1.x; // to denote vertical line x = x_value
        return 0; // we need this return variable to differentiate result
```

```

}
else {
    l.m = (db)(p1.y-p2.y) / (p1.x-p2.x);
    l.c = p1.y - l.m*p1.x;
    return 1;    // l contains m and c of the line equation y = mx + c
} }

bool areParallel(line l1, line l2) {    // check coefficients a & b
    return (fabs(l1.a-l2.a) < EPS) && (fabs(l1.b-l2.b) < EPS); }

bool areSame(line l1, line l2) {        // also check coefficient c
    return areParallel(l1 ,l2) && (fabs(l1.c-l2.c) < EPS); }

// returns true (+ intersection point) if two lines are intersect
bool areIntersect(line l1, line l2, point &p) {
    if (areParallel(l1, l2)) return false;    // no intersection
    // solve system of 2 linear algebraic equations with 2 unknowns
    p.x = (l2.b*l1.c - l1.b*l2.c) / (l2.a*l1.b - l1.a*l2.b);
    // special case: test for vertical line to avoid division by zero
    if (fabs(l1.b) > EPS) p.y = -(l1.a*p.x + l1.c);
    else p.y = -(l2.a*p.x + l2.c);
    return true; }

// Or use pointsToSlope, Revisar, mejor con 2 puntos
void perpendicular_line(point a, line l, line& ans)
{
    point b((-l.b*a.y-l.c)/l.a,a.y+1);
    b.x-=a.x;
    b.y-=a.y;
    b = rotate(b,90);
    b.x+=a.x;
    b.y+=a.y;
    pointsToLine(a,b, ans);
}

//Scalar projection of vector a onto vector b
// if s < -EPS or s > |b| + EPS then the projection is not on the segment
db sproject(point a, point b)
{
    return a*b/sqrt(b.norm_sq());
}

bool onSegment(const point& p, const point& p1, const point& p2)
{

```

```

    bool x = (abs(p1.x - p2.x) < EPS && abs(p.x - p2.x) < EPS) || (p.x <=
        max(p1.x, p2.x) && p.x >= min(p1.x, p2.x));
    bool y = (abs(p1.y - p2.y) < EPS && abs(p.y - p2.y) < EPS) || (p.y <=
        max(p1.y, p2.y) && p.y >= min(p1.y, p2.y));
    return x && y;
}

// convert point and gradient/slope to line, A PARTIR DE UNA DIRECCION M
// usar 1/l.a para calcular perpendicular
void pointSlopeToLine(point p, db m, line &l) {
    l.a = -m;    // always -m
    l.b = 1;    // always 1
    l.c = -((l.a*p.x) + (l.b*p.y));    // compute this
}

void closestPoint(line l, point p, point &ans) {
    line perpendicular;    // perpendicular to l and pass through p
    if (fabs(l.b) < EPS) {    // special case 1: vertical line
        ans.x = -(l.c); ans.y = p.y;    return; }

    if (fabs(l.a) < EPS) {    // special case 2: horizontal line
        ans.x = p.x;    ans.y = -(l.c); return; }

    pointSlopeToLine(p, 1/l.a, perpendicular);    // normal line
    // intersect line l with this perpendicular line
    // the intersection point is the closest point
    areIntersect(l, perpendicular, ans); }

// returns the reflection of point on a line
void reflectionPoint(line l, point p, point &ans) {
    point b;
    closestPoint(l, p, b);    // similar to distToLine
    point v = (b - p);    // create a vector
    ans = p + v + v;    // translate p twice

// returns the distance from p to the line defined by
// two points a and b (a and b must be different)
// the closest point is stored in the 4th parameter (byref)
db distToLine(point p, point a, point b, point &c) {
    // formula: c = a + u*ab
    point ap = (p - a), ab = (b - a);
    db u = ap * ab / ab.norm_sq();
    c = a + ab * u;    // translate a to c
    return dist(p, c);    // Euclidean distance between p and c

// returns the distance from p to the line segment ab defined by

```

```

// two points a and b (still OK if a == b)
// the closest point is stored in the 4th parameter (byref)
db distToLineSegment(point p, point a, point b, point &c) {
    point ap = (p - a), ab = (b - a);
    db u = ap * ab / ab.norm_sq();
    if (u < 0.0) { c = point(a.x, a.y); // closer to a
        return dist(p, a); } // Euclidean distance between p and a
    if (u > 1.0) { c = point(b.x, b.y); // closer to b
        return dist(p, b); } // Euclidean distance between p and b
    return distToLine(p, a, b, c); } // run distToLine as above

bool ccw(point p, point q, point r) {
    return ((q - p)^(r - p)) > -EPS; }

// returns true if point r is on the same line as the line pq
bool collinear(point p, point q, point r) {
    return fabs(((q - p)^(r - p))) < EPS; }

// angle from 0 to 2*PI
db anglet(point a, point o, point b) { // returns angle aob in rad
    point oa = (a - o), ob = (b - o);
    db ang = acos(oa * ob / sqrt(oa.norm_sq()*ob.norm_sq()));
    if(ang!=0&&!collinear(a,o,b)&&ccw(a,o,b))ang = 2*PI - ang;
    return ang; } // better

db angle(point a, point o, point b) { // returns angle aob in rad
    point oa = (a - o), ob = (b - o);
    return acos(oa * ob / sqrt(oa.norm_sq()*ob.norm_sq())); }

point min(point a,point b)
{
    if(a<b)return a;
    return b;
}
point max(point a, point b)
{
    if(!(a<b))return a;
    return b;
}

// 0 -> No intersection, 1 -> Point intersection, 2 -> segment
intersection
int SegmentIntersection(point a1, point a2, point b1, point b2, point&
ans, point& ans2)

```

```

{
    line A,B;
    point I;
    pointsToLine(a1,a2,A);
    pointsToLine(b1,b2,B);
    if(areSame(A,B)&&!(a1==a2)&&!(b1==b2))
    {
        ans=max(min(a1,a2),min(b1,b2));
        ans2=min(max(a1,a2),max(b1,b2));
        if(ans2<ans)return 0;
        else if(ans == ans2)return 1;
        return 2;
    }
    if (a1==a2&&b1==b2)
    {
        if(a1==b1)
        {
            ans=a1;
            return 1;
        }
        return 0;
    }
    if(a1==a2)
    {
        if(fabs(distToLineSegment(a1, b1, b2, ans)-0.0) < EPS)
        {
            ans=a1;
            return 1;
        }
        return 0;
    }
    if(b1==b2)
    {
        if(fabs(distToLineSegment(b1, a1, a2, ans)-0.0) < EPS)
        {
            ans=b1;
            return 1;
        }
        return 0;
    }
    if (areIntersect(A,B,I) && fabs(distToLineSegment(I, a1, a2,
ans)-0.0) < EPS && fabs(distToLineSegment(I, b1, b2, ans)-0 <
EPS))
    {
        return 1;
    }
}

```

```

    }
    return 0;
}

int32_t main() {
    vec a(1,3);
    cout<<30*PI/180<<endl;
    a = rotate(a, 30*PI/180);
    cout<<a.x<<" "<<a.y<<endl;

    cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC << "ms\n";
    return 0;
}

```

2.2 3DAlgorithms

```
#include "../Header.cpp"
```

```

struct point { db x, y, z;
    point() { x = y = z = 0.0; }
    //point(db r, db u, db v) : x(r*cos(u)*cos(v)), y(r*cos(u)*sin(v)),
    //    z(r*sin(u)) {}
    point(db _x, db _y, db _z) : x(_x), y(_y), z(_z) {}
    point operator^(const point &p) const {
        return { y*p.z - z*p.y, z*p.x - x*p.z, x*p.y - y * p.x};
    }
    db dot(point& p) { return x*p.x + y*p.y + z*p.z; }
    db norm() { return sqrt(x*x + y*y + z*z); }

    bool operator == (const point& p) const
    {
        return abs(p.x - x) < EPS && abs(p.y - y) < EPS && abs(p.z - z) <
            EPS;
    }
    point operator + (const point& p) const
    {
        return point(x + p.x, y + p.y, z + p.z);
    }
    point operator - (const point& p) const
    {
        return point(x - p.x, y - p.y, z - p.z);
    }
}

```

```

    }
    point operator * (db a) const
    {
        return point(x * a, y * a, z * a);
    }
    point operator / (db a) const
    {
        return point(x / a, y / a, z / a);
    }
    point unit() {
        db d = norm();
        return {x/d,y/d,z/d};
    }
};

db angle2(point& x, point& y)
{
    return acos(x.dot(y) / (R*R));
}

bool in_arc(point& p1, point& p2, point& n, point& inter)
{
    db ab = angle2(p1, p2);
    db ap = angle2(p1, inter);
    point d = (p1 * cos(ap) + (n ^ p1) * sin(ap));
    return ab > ap && inter == d;
}

bool do_intersect_circles()
{
    point a1 = g[j][z], a2 = g[j][0];
    if(z < g[j].size() - 1)
        a2 = g[j][z+1];
    point p1 = route[i], p2 = route[i+1];
    point n1 = (p1^p2).unit(), n2 = (a1^a2).unit();
    point inter = n1^n2;
    if(inter.norm() < EPS)continue;
    inter = inter.unit() * R;

    if(in_arc(p1, p2, n1, inter) && in_arc(a1, a2, n2, inter))
    {
        ag.push_back(angle2(p1, inter));
        continue;
    }
    inter = inter * -1.0;
    if(in_arc(p1, p2, n1, inter) && in_arc(a1, a2, n2, inter))

```

```

{
    ag.push_back(angle2(p1, inter));
    continue;
}
}

```

2.3 Polygons

```
#include "../Header.cpp"
```

```
db DEG_to_RAD(db d) { return d*PI / 180.0; }
```

```
db RAD_to_DEG(db r) { return r*180.0 / PI; }
```

```

struct point { db x, y;
    point() { x = y = 0.0; }
    point(db _x, db _y) : x(_x), y(_y) {}
    bool operator <(const point& p) const { return (x < p.x ? true : (x
        == p.x && y < p.y)); }
    bool operator == (const point& p) const { return abs(p.x - x) < EPS
        && abs(p.y - y) < EPS; }
    point operator + (const point& p) const { return point(x + p.x, y +
        p.y); }
    point operator - (const point& p) const { return point(x - p.x, y -
        p.y); }
    point operator * (db p) const { return point(x * p, y * p); }
    point operator / (db p) const { return point(x / p, y / p); }
    db operator^(const point &p) const {return x * p.y - y * p.x; }
    db operator*(const point &p) const {return x * p.x + y * p.y; }
    db norm_sq() const { return x*x + y*y; }
    point rot(){ return point(-y, x); }
}

```

```
// by angles but with cross
```

```
bool half() const { return y > 0 || (y == 0 && x > 0); }
```

```
bool operator<(const point &p) const
```

```

{
    int h1 = half(), h2 = p.half();
    return h1 != h2 ? h1 > h2 : ((*this) ^ p) > 0;
}

```

```
db ang()
```

```

{
    double a = atan2(y, x);
}

```

```

    if (a < 0) a += 2.0 * PI;
    return a;
}

```

```
};
```

```

db dist(point& p1, point& p2) {
    return sqrt((p1.x-p2.x)*(p1.x-p2.x)+ (p1.y-p2.y)*(p1.y-p2.y)); }
db dist_sq(point p1, point p2) {
    return (p1.x - p2.x)*(p1.x - p2.x)+(p1.y - p2.y)*(p1.y - p2.y); }

```

```

// returns the perimeter, which is the sum of Euclidian distances
// of consecutive line segments (polygon edges)

```

```

db perimeter(vector<point> &P) {
    db result = 0.0;
    for (ll i = 0; i < (ll)P.size()-1; i++) // remember that P[0] = P[n-1]
        result += dist(P[i], P[i+1]);
    return result; }

```

```
// returns the area
```

```

db area(const vector<point> &P) {
    db result = 0.0;
    for (ll i = 0; i < (ll)P.size()-1; i++) // Shoelace formula
        result += P[i]^P[i+1]; // if all points are ll
    return fabs(result)/2.0; } // result can be ll(eger) until last step

```

```

db seg_integrate(point& a, point& b, db t1, db t2)
{

```

```
    // area
```

```
    point p1 = a + (b-a) * t1;
```

```
    point p2 = a + (b-a) * t2;
```

```
    return (p1^p2) / 2.0;
```

```
}
```

```
db param(point p1, point p2, point a)
```

```
{
```

```
    if(p1.x != p2.x)
```

```
    {
```

```
        db sgn = 1;
```

```
        if(p1.x > p2.x)sgn = -1;
```

```
        return (a.x - p1.x) / abs(p2.x - p1.x) * sgn;
```

```
    }
```

```
    db sgn = 1;
```

```

    if(p1.y > p2.y)sgn = -1;
    return (a.y - p1.y) / abs(p2.y - p1.y) * sgn;
}

// note: to accept collinear points, we have to change the '> 0'
// returns true if point r is on the left side of line pq
bool ccw(point p, point q, point r) {
    return ((q - p)^(r - p)) > 0; }

int orientation(point p, point q, point r) {
    ll tmp = ((q - p)^(r - p));
    return tmp < 0 ? -1 : tmp == 0 ? 0 : 1; // sign
}

/*bool do_rectangles_intersect(point dl1, point ur1, point dl2, point
    ur2) {
    return max(dl1.x, dl2.x) <= min(ur1.x, ur2.x) && max(dl1.y, dl2.y) <=
        min(ur1.y, ur2.y);
}*/

bool do_segments_intersect(point p1, point q1, point p2, point q2) {
    int o11 = orientation(p1, q1, p2);
    int o12 = orientation(p1, q1, q2);
    int o21 = orientation(p2, q2, p1);
    int o22 = orientation(p2, q2, q1);
    // oxx != 0 means cross intersection, no T intersection
    if (o11 != o12 && o21 != o22 && o11 != 0 && o12 != 0 && o21 != 0 &&
        o22 != 0) // general case -> non-collinear intersection
        return true;
    return false;
}

// returns true if point r is on the same line as the line pq
bool collinear(point p, point q, point r) {
    return fabs(((q - p)^(r - p))) < EPS; }

// angle from 0 to 2*PI
db anglet(point a, point o, point b) { // returns angle aob in rad
    point oa = (a - o), ob = (b - o);
    db ang = acos(oa * ob / sqrt(oa.norm_sq()*ob.norm_sq()));
    if(ang!=0&&!collinear(a,o,b)&&ccw(a,o,b))ang = 2*PI - ang;
    return ang; } // better

db angle(point a, point o, point b) { // returns angle aob in rad
    point oa = (a - o), ob = (b - o);
    return acos(oa * ob / sqrt(oa.norm_sq()*ob.norm_sq())); }

```

```

// returns true if we always make the same turn while examining
// all the edges of the polygon one by one
bool isConvex(const vector<point> &P) {
    ll sz = (ll)P.size();
    if (sz <= 3) return false; // a point/sz=2 or a line/sz=3 is not convex
    bool firstTurn = ccw(P[0], P[1], P[2]); // remember one result
    for (ll i = 1; i < sz-1; i++) // then compare with the others
        if (ccw(P[i], P[i+1], P[(i+2) == sz ? 1 : i+2]) != firstTurn)
            return false; // different sign -> this polygon is concave
    return true; // this polygon is convex

// returns true if point p is in either convex/concave polygon P
bool inPolygon(point pt, const vector<point> &P) {
    if ((ll)P.size() < 3) return false; // avoid point or line
    db sum = 0; // assume the first vertex is equal to the last vertex
    for (ll i = 0; i < (ll)P.size()-1; i++) {
        if (((P[i] - pt)^(P[i+1] - pt)) > 0) //CCW check collinear
            sum += angle(P[i], pt, P[i+1]); // left turn/ccw
        else sum -= angle(P[i], pt, P[i+1]); // right turn/cw
    }
    return fabs(sum) > PI; } // 360d -> in, 0d -> out, we have large margin

// line segment p-q intersect with line A-B.
point lineIntersectSeg(point p, point q, point A, point B) {
    db a = B.y - A.y;
    db b = A.x - B.x;
    db c = B.x * A.y - A.x * B.y;
    db u = fabs(a * p.x + b * p.y + c);
    db v = fabs(a * q.x + b * q.y + c);
    return point((p.x * v + q.x * u) / (u+v), (p.y * v + q.y * u) / (u+v));
}

// cuts polygon Q along the line formed by point a -> point b
// (note: the last point must be the same as the first point)
// to cut the other side, swap (a,b)
vector<point> cutPolygon(point a, point b, const vector<point> &Q) {
    vector<point> P;
    for (ll i = 0; i < (ll)Q.size(); i++) {
        db left1 = (b - a)^(Q[i] - a), left2 = 0;
        if (i != (ll)Q.size()-1) left2 = (b - a)^(Q[i+1] - a);
        if (left1 > -EPS) P.push_back(Q[i]); // Q[i] is on the left of ab
        if (left1 * left2 < -EPS) // edge (Q[i], Q[i+1]) crosses line ab
            P.push_back(lineIntersectSeg(Q[i], Q[i+1], a, b));
    }
    if (!P.empty() && !(P.back() == P.front()))
        P.push_back(P.front()); // make P's first point = P's last point
}

```

```

return P; }

vector<point> CH_Andrew(vector<point> &Pts) {
    ll n = Pts.size(), k = 0;
    vector<point> H(2*n);
    sort(Pts.begin(), Pts.end());    // sort the points lexicographically
    for (ll i = 0; i < n; i++) {    // build lower hull
        while (k >= 2 && ccw(H[k-2], H[k-1], Pts[i]) <= 0) k--;
        H[k++] = Pts[i];
    }
    for (ll i = n-2, t = k+1; i >= 0; i--) {    // build upper hull
        while (k >= t && ccw(H[k-2], H[k-1], Pts[i]) <= 0) k--;
        H[k++] = Pts[i];
    }
    H.resize(k);
    return H;
}

point pivot(0, 0);
vector<point> CH_Graham(vector<point> &Pts) {
    vector<point> P(Pts);    // copy all points so that Pts is not affected
    ll i, j, n = (ll)P.size();
    if (n <= 3) {    // corner cases: n=1=point, n=2=line, n=3=triangle
        if (!(P[0] == P[n-1])) P.push_back(P[0]);    // safeguard from corner
        case
        return P; }    // the CH is P itself

    // first, find P0 = point with lowest Y and if tie: rightmost X
    ll P0 = 0;
    for (i = 1; i < n; i++)    // O(n)
        if (P[i].y < P[P0].y || (P[i].y == P[P0].y && P[i].x > P[P0].x))
            P0 = i;
    swap(P[0], P[P0]);    // swap P[P0] with P[0]

    // second, sort points by angle w.r.t. pivot P0, O(n log n) for this
    sort
    pivot = P[0];    // use this global variable as reference
    sort(++P.begin(), P.end(), [](point a, point b) { // we do not sort P[0]
        if (collinear(pivot, a, b))    // special case
            return dist(pivot, a) < dist(pivot, b); // check which one is closer
        db d1x = a.x-pivot.x, d1y = a.y-pivot.y;
        db d2x = b.x-pivot.x, d2y = b.y-pivot.y;
        return (atan2(d1y, d1x) - atan2(d2y, d2x)) < 0; }); // compare 2
        angles

```

```

// third, the ccw tests, although complex, it is just O(n)
vector<point> S;
S.push_back(P[n-1]); S.push_back(P[0]); S.push_back(P[1]); // initial S
i = 2;    // then, we check the rest
while (i < n) {    // note: n must be >= 3 for this method to work, O(n)
    j = (ll)S.size()-1;
    if (ccw(S[j-1], S[j], P[i])) S.push_back(P[i++]); // left turn, accept
    else S.pop_back(); } // or pop the top of S until we have a left turn
return S; } // return the result, overall O(n log n) due to angle
        sorting

point center_of_mass(vector<point>& Q)
{
    point ctr(0,0);
    for (ll i=0;i<Q.size()-1;i++)
    {
        ctr = ctr + Q[i];
    }
    ctr.x/=Q.size()-1;
    ctr.y/=Q.size()-1;
    return ctr;
}

// Pick's theorem
// A = i + b/2 - 1
// A: Area polygon with integer coords
// i: Interior points, b: points in the segments

// with vector form of integer segment
// (x0,y0) + t(dx,dy)
ll points_in_segment(point a, point b)
{
    ll absx=abs(a.x-b.x),absy=abs(a.y-b.y);
    return __gcd(absx,absy) + 1;
}

ll memo[101][101][101];

// Dp that pass all possible convex polygons
// from the shortest in(in.y < p.y)
// p si counter cw from in, p
ll all_convex(ll in, ll p, ll q, vector<point>& Q)
{
    if(memo[in][p][q] != -1) return memo[in][p][q];
    ll ans = 0;

```

```

for(int i = in + 1; i < Q.size(); i++)
{
    if(i != p && i != q && ccw(Q[in], Q[q], Q[i]) && ccw(Q[p], Q[q],
        Q[i]))
    {
        ans += (all_convex(in, q, i, Q) + 1);
    }
}
return memo[in][p][q] = ans;
}
bool comp(point& a, point& b)
{
    return a.y < b.y;
}
//...
vector<point>Q;
sort(ALL(Q), comp);
ll ans = 0;
for(int i = 0; i < n; i++)
{
    for(int p = i + 1; p < n; p++) for(int q = p + 1; q < n; q++)
    {
        if(ccw(Q[i], Q[p], Q[q]))
            ans += all_convex(i, p, q, Q) + 1;
        else
            ans += all_convex(i, q, p, Q) + 1;
        ans %= m;
    }
}

int main() {
    point a;
    ll n;
    vector<point>Q;
    cin>>n;
    for(ll i=0;i<n;i++)
    {
        cin>>a.x>>a.y;
        Q.push_back(a);
    }
    Q.push_back(Q[0]);
    cout<<area(Q);

```

```

cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC << "ms\n";
return 0;
}

```

2.4 SegmentIntersection

```

#include "../Header.cpp"

struct point { db x, y;
    point() { x = y = 0.0; }
    point(db _x, db _y) : x(_x), y(_y) {}
    bool operator <(const point& p) const { return (x < p.x ? true : (x
        == p.x && y < p.y)); }
    bool operator == (const point& p) const { return abs(p.x - x) < EPS
        && abs(p.y - y) < EPS; }
    point operator + (const point& p) const { return point(x + p.x, y +
        p.y); }
    point operator - (const point& p) const { return point(x - p.x, y -
        p.y); }
    point operator * (db p) const { return point(x * p, y * p); }
    point operator / (db p) const { return point(x / p, y / p); }
    db operator^(const point &p) const {return x * p.y - y * p.x; }
    db operator*(const point &p) const {return x * p.x + y * p.y; }
    db norm_sq() const{ return x*x + y*y; }
    point rot(){ return point(-y, x); }
    db ang()
    {
        double a = atan2(y, x);
        if (a < 0) a += 2.0 * PI;
        return a;
    }
};

db dist(const point& p1,const point& p2) {
    return sqrt((p1.x-p2.x)*(p1.x-p2.x)+ (p1.y-p2.y)*(p1.y-p2.y)); }

//Constant values to be returned
constexpr int Colinear = -1, NoIntersect = 0, Intersect = 1;
constexpr int CW = 2, CCW = 3;

int orientation(point& p, point& q, point& r) {

```



```

    ll tmp = (q - p)^(r - p);
    return tmp < 0 ? CW : tmp == 0 ? Colinear : CCW; // sign
}

struct segment { point p1, p2;
    segment(point _p1, point _p2) : p1(_p1), p2(_p2) {}
};

//Returns of list of intersection points between segments s1, and s2
//If they do not intersect, the result is an empty vector
//If they intersect at exactly 1 point, the result contains that point
//If they overlap for non-0 distance, the left and right points of that
// intersection
// are returned
bool onSegment(const point& p, const segment& s)
{
    bool x = (abs(s.p1.x - s.p2.x) < EPS && abs(p.x - s.p2.x) < EPS) ||
        (p.x <= max(s.p1.x, s.p2.x) && p.x >= min(s.p1.x, s.p2.x));
    bool y = (abs(s.p1.y - s.p2.y) < EPS && abs(p.y - s.p2.y) < EPS) ||
        (p.y <= max(s.p1.y, s.p2.y) && p.y >= min(s.p1.y, s.p2.y));
    return x && y;
}

vector<point> intersect(const segment& s1, const segment& s2)
{
    point a = s1.p1, b = s1.p2, c = s2.p1, d = s2.p2;

    if(orientation(a, b, c) == Colinear && orientation(a, b, d) ==
        Colinear &&
        orientation(c, d, a) == Colinear && orientation(c, d, b) ==
            Colinear)
    {
        point min_s1 = min(a, b), max_s1 = max(a, b);
        point min_s2 = min(c, d), max_s2 = max(c, d);

        if(max_s1 < min_s2 || max_s2 < min_s1) return {};

        point start = max(min_s1, min_s2), end = min(max_s1, max_s2);
        if(start == end)
            return {start};
        else
            return {min(start, end), max(start, end)};
    }
}

```

```

db a1 = b.y - a.y, a2 = d.y - c.y;
db b1 = a.x - b.x, b2 = c.x - d.x;
db c1 = a1*a.x + b1*a.y, c2 = a2*c.x + b2*c.y;
db det = a1*b2 - a2*b1;
if(abs(det) > EPS)
{
    point inter((b2*c1 - b1*c2)/det, (a1*c2 - a2*c1)/det), aux;
    //if(distToLineSegment(inter, s1.p1, s1.p2, aux) <= EPS &&
        distToLineSegment(inter, s2.p1, s2.p2, aux) <= EPS)
    if(onSegment(inter, s1) && onSegment(inter, s2))
        return {inter};
}
return {};
}

```

2.5 TrianglesCircles

```

#include "../Header.cpp"

//define double long long //Para usar enteros

db DEG_to_RAD(db d) { return d * PI / 180.0; }
db RAD_to_DEG(db r) { return r * 180.0 / PI; }

//sweepline rotating a circle around a point
// how many points are in circle radius r
// alpha = atan2(point - center) +- acos(dist/2r)

struct point { db x, y;
    point() { x = y = 0.0; }
    point(db _x, db _y) : x(_x), y(_y) {}
    bool operator <(const point& p) const { return (x < p.x ? true : (x
        == p.x && y < p.y)); }
    bool operator == (const point& p) const { return abs(p.x - x) < EPS
        && abs(p.y - y) < EPS; }
    point operator + (const point& p) const { return point(x + p.x, y +
        p.y); }
    point operator - (const point& p) const { return point(x - p.x, y -
        p.y); }
    point operator * (db p) const { return point(x * p, y * p); }
}

```

```

point operator / (db p) const { return point(x / p, y / p); }
db operator^(const point &p) const {return x * p.y - y * p.x; }
db operator*(const point &p) const {return x * p.x + y * p.y; }
db norm_sq() const{ return x*x + y*y; }
point rot(){ return point(-y, x); }

// by angles but with cross
bool half() const { return y > 0 || (y == 0 && x > 0); }
bool operator<(const point &p) const
{
    int h1 = half(), h2 = p.half();
    return h1 != h2 ? h1 > h2 : ((*this) ^ p) > 0;
}

db ang()
{
    double a = atan2(y, x);
    if (a < 0) a += 2.0 * PI;
    return a;
}

};

ll insideCircle(point p, point c, ll r) { // all integer version
    ll dx = p.x - c.x, dy = p.y - c.y;
    ll Euc = dx * dx + dy * dy, rSq = r * r; // all integer
    return Euc < rSq ? 0 : Euc == rSq ? 1 : 2; } //inside/border/outside

// P1 and P2 intersections of circles and radius r -> pos of centers of
// circles of intersection
bool circle2PtsRad(point p1, point p2, db r, point &c) {
    db d2 = (p1.x - p2.x) * (p1.x - p2.x) +
            (p1.y - p2.y) * (p1.y - p2.y);
    db det = r * r / d2 - 0.25;
    if (det < 0.0) return false;
    db h = sqrt(det);
    c.x = (p1.x + p2.x) * 0.5 + (p1.y - p2.y) * h;
    c.y = (p1.y + p2.y) * 0.5 + (p2.x - p1.x) * h;
    return true; } // to get the other center, reverse p1 and p2

db dist(point& p1, point& p2) { // Euclidean distance
    return sqrt((p1.x-p2.x)*(p1.x-p2.x)+ (p1.y-p2.y)*(p1.y-p2.y)); }
db dist_sq(point p1, point p2) {
    return (p1.x - p2.x)*(p1.x - p2.x)+(p1.y - p2.y)*(p1.y - p2.y); }

```

```

// a = max x, b = max y from the center, AREA
db A_ellipse(db a,db b)
{
    return a*b*PI;
}

// Length of segment with two points on the circumference
// separated by an angle
db chord(db r, db angle)
{
    return sqrt(2*r*r*(1-cos(angle)));
}

//Triangles
db perimeter(db ab, db bc, db ca) {
    return ab + bc + ca; }

db perimeter(point a, point b, point c) {
    return dist(a, b) + dist(b, c) + dist(c, a); }

db area(db ab, db bc, db ca) {
    // Heron's formula, split sqrt(a * b) into sqrt(a) * sqrt(b); in
    // implementation
    db s = 0.5 * perimeter(ab + bc + ca);
    return sqrt(s) * sqrt(s - ab) * sqrt(s - bc) * sqrt(s - ca); }

db area(point a, point b, point c) {
    return area(dist(a, b), dist(b, c), dist(c, a)); }

// Area of the circle enclosed by an arc and a chord defined by an angle
db segment(db r, db angle)
{
    return angle/2.0*r*r-area(chord(r,angle),r,r);
}

// And overlapping rectangle area > 0
bool rectangles_intersect(point a1,point a2,point b1,point b2,point&
    ans1, point& ans2)
{
    if(b1<a1)
    {
        swap(a1,b1);
        swap(a2,b2);
    }
}

```

```

}
if(b1.x>=a2.x||b1.y>=a2.y||b2.y<=a1.y)return 0;
ans1.x=b1.x;
ans1.y=max(b1.y,a1.y);
ans2.x=min(b2.x,a2.x);
ans2.y=min(b2.y,a2.y);
return 1;
}

struct line { db a, b, c; };

void pointsToLine(point p1, point p2, line &l) {
    if (fabs(p1.x - p2.x) < EPS) {          // vertical line is fine
        l.a = 1.0; l.b = 0.0; l.c = -p1.x;    // default values
    } else {
        l.a = -(db)(p1.y - p2.y) / (p1.x - p2.x);
        l.b = 1.0;          // IMPORTANT: we fix the value of b to 1.0
        l.c = -(db)(l.a * p1.x) - p1.y;
    } }

bool areParallel(line l1, line l2) {    // check coefficient a + b
    return (fabs(l1.a-l2.a) < EPS) && (fabs(l1.b-l2.b) < EPS); }

bool areSame(line l1, line l2) {        // also check coefficient c
    return areParallel(l1 ,l2) && (fabs(l1.c-l2.c) < EPS); }

// returns true (+ intersection point) if two lines are intersect
bool areIntersect(line l1, line l2, point &p) {
    if (areParallel(l1, l2)) return false;    // no intersection
    // solve system of 2 linear algebraic equations with 2 unknowns
    p.x = (l2.b * l1.c - l1.b * l2.c) / (l2.a * l1.b - l1.a * l2.b);
    // special case: test for vertical line to avoid division by zero
    if (fabs(l1.b) > EPS) p.y = -(l1.a * p.x + l1.c);
    else p.y = -(l2.a * p.x + l2.c);
    return true; }

db rInCircle(db ab, db bc, db ca) {
    return area(ab, bc, ca) / (0.5 * perimeter(ab, bc, ca)); }

db rInCircle(point a, point b, point c) {
    return rInCircle(dist(a, b), dist(b, c), dist(c, a)); }

// assumption: the required points/lines functions have been written
// returns 1 if there is an inCircle center, returns 0 otherwise

```

```

// if this function returns 1, ctr will be the inCircle center
// and r is the same as rInCircle
ll inCircle(point p1, point p2, point p3, point &ctr, db &r) {
    r = rInCircle(p1, p2, p3);
    if (fabs(r) < EPS) return 0;          // no inCircle center

    line l1, l2;          // compute these two angle bisectors
    db ratio = dist(p1, p2) / dist(p1, p3);
    point p = p2 + (p3 - p2) * (ratio / (1 + ratio));
    pointsToLine(p1, p, l1);

    ratio = dist(p2, p1) / dist(p2, p3);
    p = p1 + (p3 - p1) * (ratio / (1 + ratio));
    pointsToLine(p2, p, l2);

    areIntersect(l1, l2, ctr);          // get their intersection point
    return 1; }

db rCircumCircle(db ab, db bc, db ca) {
    return ab * bc * ca / (4.0 * area(ab, bc, ca)); }

db rCircumCircle(point a, point b, point c) {
    return rCircumCircle(dist(a, b), dist(b, c), dist(c, a)); }

// assumption: the required points/lines functions have been written
// returns 1 if there is a circumCenter center, returns 0 otherwise
// if this function returns 1, ctr will be the circumCircle center
// and r is the same as rCircumCircle
ll circumCircle(point p1, point p2, point p3, point &ctr, db &r){
    db a = p2.x - p1.x, b = p2.y - p1.y;
    db c = p3.x - p1.x, d = p3.y - p1.y;
    db e = a * (p1.x + p2.x) + b * (p1.y + p2.y);
    db f = c * (p1.x + p3.x) + d * (p1.y + p3.y);
    db g = 2.0 * (a * (p3.y - p2.y) - b * (p3.x - p2.x));
    if (fabs(g) < EPS) return 0;

    ctr.x = (d*e - b*f) / g;
    ctr.y = (a*f - c*e) / g;
    r = dist(p1, ctr); // r = distance from center to 1 of the 3 points
    return 1; }

//
// https://www.nayuki.io/res/smallest-enclosing-circle/computational-geometry-1
// O(N) expected time

```

```

void smallest_enclosing_circle(vector<point>& pts, point& center, db& r) {
    random_shuffle(pts.begin(), pts.end());
    center = pts[0]; r = 0;
    ll N = pts.size();
    for(ll i=1; i<N; i++) {
        if (dist(pts[i], center) > r + EPS) {
            center = pts[i];
            r = 0;
            for(ll j=0; j<i; j++) {
                if (dist(pts[j], center) > r + EPS) {
                    center = (pts[i] + pts[j]) * 0.5;
                    r = dist(pts[i], center);
                    for(ll k=0; k<j; k++) {
                        if (dist(pts[k], center) > r + EPS) {
                            db rr;
                            circumCircle(pts[i], pts[j], pts[k], center, rr);
                            r = dist(pts[k], center);
                        }
                    }
                }
            }
        }
    }
}

// returns true if point d is inside the circumCircle defined by a,b,c
ll inCircumCircle(point a, point b, point c, point d) {
    return (a.x - d.x) * (b.y - d.y) * ((c.x - d.x) * (c.x - d.x) + (c.y - d.y) * (c.y - d.y)) +
        (a.y - d.y) * ((b.x - d.x) * (b.x - d.x) + (b.y - d.y) * (b.y - d.y)) * (c.x - d.x) +
        ((a.x - d.x) * (a.x - d.x) + (a.y - d.y) * (a.y - d.y)) * (b.x - d.x) * (c.y - d.y) -
        ((a.x - d.x) * (a.x - d.x) + (a.y - d.y) * (a.y - d.y)) * (b.y - d.y) * (c.x - d.x) -
        (a.y - d.y) * (b.x - d.x) * ((c.x - d.x) * (c.x - d.x) + (c.y - d.y) * (c.y - d.y)) -
        (a.x - d.x) * ((b.x - d.x) * (b.x - d.x) + (b.y - d.y) * (b.y - d.y)) * (c.y - d.y) > 0 ? 1 : 0;
}

bool canFormTriangle(db a, db b, db c) {
    return (a + b > c) && (a + c > b) && (b + c > a); }

```

```

/*
Si un punto tiene un ngulo >= 60, el lado opuesto no es el menor del
triangulo
*/

// Function to find the circle on
// which the given three points lie
// better CIRCUMCENTER
tuple<db, db, db> findCircle(db x1, db y1, db x2, db y2, db x3, db y3)
{
    db x12 = x1 - x2;
    db x13 = x1 - x3;

    db y12 = y1 - y2;
    db y13 = y1 - y3;

    db y31 = y3 - y1;
    db y21 = y2 - y1;

    db x31 = x3 - x1;
    db x21 = x2 - x1;

    db sx13 = x1*x1 - x3*x3;
    db sy13 = y1*y1 - y3*y3;

    db sx21 = x2*x2 - x1*x1;
    db sy21 = y2*y2 - y1*y1;

    db f = ((sx13) * (x12)
            + (sy13) * (x12)
            + (sx21) * (x13)
            + (sy21) * (x13))
            / (2 * ((y31) * (x12) - (y21) * (x13)));
    db g = ((sx13) * (y12)
            + (sy13) * (y12)
            + (sx21) * (y13)
            + (sy21) * (y13))
            / (2 * ((x31) * (y12) - (x21) * (y13)));

    db c = -x1*x1 - y1*y1 - 2 * g * x1 - 2 * f * y1;

    // eqn of circle be x^2 + y^2 + 2*g*x + 2*f*y + c = 0
    // where centre is (h = -g, k = -f) and radius r
    // as r^2 = h^2 + k^2 - c
    db h = -g;

```

```

db k = -f;
db sqr_of_r = h * h + k * k - c;

// r is the radius
db r = sqrt(sqr_of_r);

//cout << "Centre = (" << h << ", " << k << ")" << endl;
//cout << "Radius = " << r;
return make_tuple(h, k, r);
}

```

3 Graphs

3.1 BellmanFord

```

#include "../Header.cpp"

int main()
{
    ios::sync_with_stdio(false);
    cin.tie(0);
    int v,e,x,y,w,r;
    cin >> v >> e >> r;
    pll h;
    vl d(v, INF);
    d[r] = 0;//nodo de inicio
    vector<vector<pll>> > g(v, vector<pll> (0));

    for(int i = 0 ;i < e; i++)
    {
        cin >> x >> y >> w;
        h.first = y;
        h.second = w;
        g[x].push_back(h);
    }
    /*
    inequations solver
    v - u <= p
    g[u].push_back({v, p});
    g[v].push_back({u, -1});
    d[s] = 0
    for i in v: g[s].push_back({i, 0})

```

```

*/

rep(i, v-1)
{
    bool mod = 0;
    rep(j, v)
        if(d[j] != INF)
            for(auto it : g[j])
            {
                d[it.first] = min(d[it.first], d[j] + it.second);
                mod = 1;
            }
    if(mod == 0)
        break;
}
bool cyc = 0;
rep(j, v)
    for(auto it : g[j])
        if(d[j] < INF && d[it.first] > d[j] + it.second)
            cyc = 1;

// From
// :https://github.com/stevenhalim/cpbook-code/blob/master/ch4/sssp/bellman
// Faster but doesnt support negative cycles
// SPFA from source S
vl dist(v, INF); dist[s] = 0; // INF = 1e9 here
queue<int> q; q.push(s); // like BFS queue
vl in_queue(v, 0); in_queue[s] = 1; // unique to SPFA
while (!q.empty()) {
    int u = q.front(); q.pop(); in_queue[u] = 0; // pop from queue
    for (auto it : g[u]) { // C++17 style
        if (dist[u]+it.first >= dist[it.second]) continue; // not
        improving, skip
        dist[it.second] = dist[u]+it.first; // relax
        operation
        if (!in_queue[it.second]) { // add to the queue
            q.push(it.second); // only if v is not
            in_queue[it.second] = 1; // already in the
            queue
        }
    }
}

return 0;

```

```
}

```

3.2 BiconnectedComponents

```
// Tarjan
#include "../Header.cpp"

#define ff first
#define ss second
typedef pair<int,int> ii;
vector<int> D, L;
vector<vl> g;
stack<ii> s; int root;

void print_and_remove_bicomp(int u, int v) {
    puts("biconnected component found:");
    ii uv(u,v);
    while (true) {
        ii top = s.top(); s.pop();
        printf("(%d, %d)\n", top.ff, top.ss);
        if (top == uv) break;
    }
}

// general version: find everything
// p: -1, L: 0, D: -1
void dfs(int u, int p, int d) { // (node, parent, depth)
    static num_root_children = 0;
    D[u] = L[u] = d; // u at least can reach itself (ignoring u-p edge)
    for(auto v : g[u]) {
        if (v == p) continue; // direct edge to parent -> ignore
        if (D[v] == -1) { // exploring a new, unvisited child node
            s.emplace(u,v); // add edge to stack
            dfs(v, u, d+1); // explore recursively v's subtree
            // 1) detect articulation points and biconnected components
            if (p == -1) { // 1.1) special case: if u is root
                if (++num_root_children == 2) {
                    // we detected that root has AT LEAST 2 children
                    // therefore root is an articulation point
                    printf("root = %d is articulation point\n", root);
                }
                // whenever we come back to the root, we just finished
                // exploring a whole biconnected component
            }
        }
    }
}
```

```
        print_and_remove_bicomp(u,v);
    } else if (L[v] >= d) { // 1.2) general case: non-root
        printf("u = %d is articulation point\n", u);
        // we entered through and came back to an AP,
        // so we just finished exploring a whole biconnected
        component
        print_and_remove_bicomp(u,v);
    }
    // 2) detect cut edges (a.k.a. bridges)
    if (L[v] > D[u]) {
        printf("(u,v) = (%d, %d) is cut edge\n", u, v);
    }
    // propagate low
    L[u] = min(L[u], L[v]);
} else if (D[v] < d) { // back-edge to proper ancestor
    s.emplace(u,v); // add edge to stack
    L[u] = min(L[u], D[v]); // propagate low
} else { // forward-edge to an already visited descendant
    // => do nothing, because this edge was already considered as a
    // back-edge from v -> u
}
}
}

// find cut edges
void dfs(int u, int p, int d) {
    D[u] = L[u] = d;
    for(auto v : g[u]) {
        if (v == p) continue;
        if (D[v] == -1) {
            dfs(v, u, d+1);
            if (L[v] > D[u]) printf("(u,v) = (%d, %d) is cut edge\n", u,
                v);
            L[u] = min(L[u], L[v]);
        } else L[u] = min(L[u], D[v]);
    }
}

// find articulation points
int root_children = 0;
void dfs(int u, int p, int d) {
    D[u] = L[u] = d;
    for(auto v : g[u]) {
        if (v == p) continue;
        if (D[v] == -1) {
```

```

        dfs(v, u, d+1);
        if (p == -1) { if (++root_children == 2) printf("root = %d is
            AP\n", root); }
        else if (L[v] >= d) printf("u = %d is AP\n", u);
        L[u] = min(L[u], L[v]);
    } else if (D[v] < d) L[u] = min(L[u], D[v]);
}
}

// find biconnected components
void dfs(int u, int p, int d) {
    D[u] = L[u] = d;
    for(auto v : g[u]) {
        if (v == p) continue;
        if (D[v] == -1) {
            s.emplace(u,v);
            dfs(v, u, d+1);
            if (p == -1 or L[v] >= d) print_and_remove_bicomp(u,v);
            L[u] = min(L[u], L[v]);
        } else if (D[v] < d) {
            s.emplace(u,v);
            L[u] = min(L[u], D[v]);
        }
    }
}
}

```

3.3 CentroidDecomposition

```

#include "../Header.cpp"

// all tree diameters pass through the centroid

const int MAXN = 1e5 + 5;
vector<int> g[MAXN]; int n;
bool tk[MAXN];
int fat[MAXN]; // father in centroid decomposition
int szt[MAXN]; // size of subtree
int calcsz(int x, int f){
    szt[x]=1;
    for(auto y:g[x])if(y!=f&&!tk[y])szt[x]+=calcsz(y,x);
    return szt[x];
}
void cdfs(int x=0, int f=-1, int sz=-1){ // O(nlogn)

```

```

        if(sz<0)sz=calcsz(x,-1);
        for(auto y:g[x])if(!tk[y]&&szt[y]*2>=sz){
            szt[x]=0;cdfs(y,f,sz);return;
        }
        tk[x]=true;fat[x]=f;
        for(auto y:g[x])if(!tk[y])cdfs(y,x);
    }
void centroid(){memset(tk,false,sizeof(tk));cdfs();}

int main(){
    ios_base::sync_with_stdio(0);
    cin.tie(0);

    ll t;
    cin >> t;
    for(int T = 1; T <= t; T++) {

        memset(memo, -1, sizeof(memo));
        ll x;
        cin >> N >> K;
        B.clear();
        ac.clear();
        ac.push_back(0);
        for(int i = 0; i < N; i++)
        {
            cin >> x;
            B.push_back(x);
            ac.push_back(x);
            ac[i+1] += ac[i];
        }
        ll acum = 0;
        for(int i = 0; i < N; i++)
        {
            acum += B[i];
            if(acum == ac[i+1])cout<<"1\n";
            else cout <<"0\n";
        }

        ll ans = INF;
        for(int i = 0; i < N; i++)
        {
            ans = min(ans, dp(i, 0, 0));
        }
        if(ans >= INF) ans = -1;
        cout << "Case #" << T << ": ";
    }
}

```

```

    cout << ans << "\n";
}
}

```

3.4 Dijkstra

```

#include "../Header.cpp"

int main()
{
    vl d(v, INF);
    priority_queue<pll, vp, greater<pll> > q; //from low to high
    ll s, t;

    q.push({0, s});
    d[s] = 0;
    while(!q.empty()){
        ll w, u;
        tie(w, u) = q.top();
        q.pop();

        if(w > d[u]) continue;
        for(auto it : g[u])
        {
            if(d[it.second] > w + it.first)
            {
                d[it.second] = w + it.first;
                q.push({d[it.second], it.second});
            }
        }
    }
}

```

3.5 D'Esopo-Pape

```

#include "../Header.cpp"

int main()
{
    ll v,x,y,e;
    pll h;

```

```

vector<ll>b;
cin >> v >> e;
vector<vp > g(v, vp (0));
vl peso(v, INF);

```

```

int w;
for(ll i = 0; i < e; i++)
{
    cin >> x >> y >> w;

    g[x-1].push_back({w, y-1});
    g[y-1].push_back({w, x-1});
}
ll s, t;

vl d(v, INF);
d[s] = 0;
vl m(v, 2);
deque<ll> q;
q.push_back(s);
p.assign(v, -1);

while (!q.empty()) {
    int u = q.front();
    q.pop_front();
    m[u] = 0;
    for (auto it : g[u]) {
        if (d[it.second] > d[u] + it.first) {
            d[it.second] = d[u] + it.first;
            p[it.second] = u;
            if (m[it.second] == 2) {
                m[it.second] = 1;
                q.push_back(it.second);
            } else if (m[it.second] == 0) {
                m[it.second] = 1;
                q.push_front(it.second);
            }
        }
    }
}

return 0;
}

```

3.6 EulerTour

```
#include "../Header.cpp"
```

```
//Euler Tour
vl L, R, d, c;
ll num = -1;
vector<vl>g;
void dfs(ll in, ll p)
{
    num++;
    L[in] = num;
    d.push_back(c[in]);
    for(auto it : g[in])
    {
        if(p != it)
            dfs(it, in);
    }
    R[in] = num;
}
```

3.7 FloydWarshall

```
#include "../Header.cpp"
```

```
ll p[500][500];
void printPath(int i, int j)
{
    if(i != j) printPath(i, p[i][j]);
    cout << j+1 << " ";
}
```

```
int main()
{
    int n, m, q, x, y, w;
    vector<vl > g(n, vl(n, INF));
    rep(i, n)
    {
        g[i][i] = 0;
        //g[i][i] = INF; Detect cheapest positive cycle for each i
    }
    rep(i, m)
    {
```

```
        cin >> x >> y >> w;
        g[x][y] = min(g[x][y], w); // handle repeats
    }

    rep(i, n)
        rep(j, n)
            p[i][j] = i;

    rep(k, n)
        rep(i, n)
            rep(j, n)
                //g[i][j] != (g[i][k] & g[k][j]); to find i is connected
                // with j
                // if at the end g[i][j] & g[j][i], i and j are in the
                // same SCC

                // To find minimal max edge in path from i to j
                //g[i][j] = min(g[i][j], max(g[i][k], g[k][j]));

                if(g[i][k] + g[k][j] < g[i][j])
                {
                    g[i][j] = g[i][k] + g[k][j];
                    p[i][j] = p[k][j];
                }

    rep(k, n)
        rep(i, n)
            rep(j, n)
                if(g[i][k] != INF && g[k][j] != INF
                    && g[k][k] < 0)
                    g[i][j] = -INF;

    rep(i, q)
    {
        cin >> x >> y;
        if(g[x][y] == INF)
            cout << "Impossible\n";
        else if (g[x][y] == -INF)
            cout << "-Infinity\n";
        else
            cout << g[x][y] << "\n";
    }

    return 0;
}
```

3.8 HeavyLightDecomposition

```
#include "../Header.cpp"

class HLD
{
    ST st;
    vi A, H, D, R, P;

    int dfs(vector<vi> &G, int u)
    {
        int ans = 1, M = 0, s;
        for (int v : G[u]) if (v != A[u])
        {
            A[v] = u, D[v] = D[u] + 1;
            s = dfs(G, v), ans += s;
            if (s > M) H[u] = v, M = s;
        }
        return ans;
    }

    template <class OP>
    void path(int u, int v, OP op)
    {
        for (; R[u] != R[v]; v = A[R[v]])
        {
            if (D[R[u]] > D[R[v]]) swap(u, v);
            op(P[R[v]], P[v] + 1);
        }
        if (D[u] > D[v]) swap(u, v);
        op(P[u], P[v] + 1); // VALUES ON VERTEX
        // op(P[u] + 1, P[v] + 1); // VALUES ON EDGE
    }

public:
    HLD(vector<vi> &G, int n) : A(n), D(n), R(n), P(n)
    {
        st = SegmentTree(n);
        H.assign(n, -1); A[0] = -1, D[0] = 0; dfs(G, 0); int p = 0;
        rep(i, n) if (A[i] == -1 || H[A[i]] != i)
            for (int j = i; j != -1; j = H[j]) R[j] = i, P[j] = p++;
    }

    void set(int v, const node &x) { st.set(P[v], x); } // VALUES ON
    VERTEX
    // void set(int u, int v, const node &x) // VALUES ON EDGE
    // {
```

```
// if (D[u] > D[v]) swap(u, v);
// st.set(P[v], x);
// }

void update(int u, int v, const node &x) // OPTIONAL FOR
    RANGE UPDATES
{ path(u, v, [this, &x](int l, int r) { st.update(l, r, x); }); }
node query(int u, int v)
{
    node ans = node();
    path(u, v, [this, &ans](int l, int r) { ans = node(ans,
        st.query(l, r)); });
    return ans;
}

};

// USAGE: HLD<ST<Node>, Node> hld(G, N);

///// NON COMMUTATIVE QUERIES :

class HLD
{
    ST st;
    vi A, H, D, R, P;

    int dfs(vector<vi> &G, int u)
    {
        int ans = 1, M = 0, s;
        for (int v : G[u]) if (v != A[u])
        {
            A[v] = u, D[v] = D[u] + 1;
            s = dfs(G, v), ans += s;
            if (s > M) H[u] = v, M = s;
        }
        return ans;
    }

public:
    node path(int u, int v)
    {
        node ans1, ans2; bool d = 0;
        for (; R[u] != R[v]; v = A[R[v]])
        {
            if (D[R[u]] > D[R[v]]) swap(u, v), d = !d;
            if (d) ans1 = node(st.query(P[R[v]], P[v] + 1), ans1);
            else ans2 = node(st.query(P[R[v]], P[v] + 1), ans2);
```

```

    }
    if (D[u] > D[v]) swap(u, v), d = !d;
    if (d) ans1 = node(st.query(P[u], P[v] + 1), ans1);
    else ans2 = node(st.query(P[u], P[v] + 1), ans2);
    ans1.sw(); return node(ans1, ans2);
}
HLD(vector<vi> &G, int n) : A(n), st(n), D(n), R(n), P(n)
{
    st = SegmentTree(n);
    H.assign(n, -1); A[0] = -1, D[0] = 0; dfs(G, 0); int p = 0;
    rep(i, n) if (A[i] == -1 || H[A[i]] != i)
        for (int j = i; j != -1; j = H[j]) R[j] = i, P[j] = p++;
}
void set(int v, const node &x) { st.set(P[v], x); }
};

```

3.9 Hungarian

```

#include "../Header.cpp"

#define rep(i, n) for (int i = 0; i < (int)n; i++)
#define repx(i, a, b) for (int i = (int)a; i < (int)b; i++)

// Minimum/Maximum cost of a perfect matching in complete graph
// O(n^3)
template<class T>
class Hungarian
{
    T inf = numeric_limits<T>::max() / 2;
    bool maxi, swapped = false;
    vector<vector<T>> cost;
    vector<T> u, v;
    vl p, way;
    int l, r;

public:
    // left/right == partition sizes
    Hungarian(int left, int right, bool maximizing)
    {
        l = left, r = right, maxi = maximizing;
        if (swapped = l > r) swap(l, r);
        cost.assign(l + 1, vector<T>(r + 1, 0));
        u.assign(l + 1, 0); v.assign(r + 1, 0);
    }

```

```

        p.assign(r + 1, 0); way.assign(r + 1, 0);
    }

    void add_edge(int l, int r, T w)
    {
        assert(l and r); // indices start from 1 !!
        if (swapped) swap(l, r);
        cost[l][r] = maxi ? -w : w;
    }

    // execute after all edges were added
    void calculate()
    {
        repx(i, 1, l + 1)
        {
            vector<bool> used(r + 1, false);
            vector<T> minv(r + 1, inf);
            int j0 = 0; p[0] = i;

            while (p[j0])
            {
                int j1, i0 = p[j0]; used[j0] = true;
                T delta = inf;
                repx(j, 1, r + 1) if (not used[j])
                {
                    T cur = cost[i0][j] - u[i0] - v[j];
                    if (cur < minv[j]) minv[j] = cur, way[j] = j0;
                    if (minv[j] < delta) delta = minv[j], j1 = j;
                }
                rep(j, r + 1)
                {
                    if (used[j]) u[p[j]] += delta, v[j] -= delta;
                    else minv[j] -= delta;
                }
                j0 = j1;
            }

            while (j0) p[j0] = p[way[j0]], j0 = way[j0];
        }
    }

    // execute after executing calculate()
    T answer() { return maxi ? v[0] : -v[0]; }

    bool are_matched(int l, int r)

```

```

{
    if (swapped) swap(l, r);
    return p[r] == 1;
}
};

int main(){
    ios_base::sync_with_stdio(0);
    cin.tie(0);

    ll n;
    cin >> n;
    ll d[n][n], pos = (n+1)/2;

    Hungarian<ll> h(pos, pos, 0);

    for(int i = 0; i < n; i++)
        for(int j = 0; j < n; j++)
            cin >> d[i][j];

    for(int i = 0; i < n; i += 2)
    {
        for(int j = 0; j < n; j += 2){
            ll cost = 0;
            if(j > 0) cost += d[i][j-1];
            if(j < n-1) cost += d[i][j+1];
            h.add_edge(i/2+1, j/2+1, cost);
        }
    }
    h.calculate();
    cout << h.answer() << "\n";
}

```

3.10 LCA-SP

```

#include "../Header.cpp"

ll maxlog2(ll x){
    return (63 - __builtin_clzll(x));
}

```

```

// To minimize diameter, connect the center of the diameter of two trees
// min(diam1, diam2, dia1+dia2+1) dia1 = diam1/2 (if diameter odd)+ 1

```

```

struct SparseTableLCA
{
    ll maxlg;
    vector<vl> >SP;
    vector<vl> >MN;
    vl D;
    SparseTableLCA(vector<vl>& g, ll ini)
    {
        ll n = g.size();
        vl vis(n,0), parent(n,-1);
        D.resize(n,INF);D[ini]=0;
        queue<ll> q;
        q.emplace(ini);
        while(!q.empty()){
            ll k=q.front();q.pop();
            if(!vis[k]){
                vis[k]=1;
                for(auto it : g[k])
                    if(!vis[it])
                    {
                        parent[it]=k;
                        D[it]=D[k]+1;
                        q.push(it);
                    }
            }
        }
    }

    SP.clear();
    SP.push_back(parent);
    maxlg = 63 - __builtin_clzll(n);

    repx(i, 1 , maxlg+1)
    {
        vl aux;
        rep(j, n)
        {
            if(SP[i-1][j]!=-1)
                aux.push_back(SP[i-1][SP[i-1][j]]);
            else aux.push_back(-1);
        }
        SP.push_back(aux);
    }
}

```

```

    }
}
SparseTableLCA(vector<vector<pll>>& g, ll ini)
{
    ll n = g.size();
    vl vis(n,0), parent(n,-1), b(n,-1);
    D.resize(n,INF);D[ini]=0;
    queue<ll> q;
    q.emplace(ini);
    while(!q.empty()){
        ll k=q.front();q.pop();
        if(!vis[k]){
            vis[k]=1;
            for(auto it : g[k])
                if(!vis[it.second])
                {
                    b[it.second]=it.first;
                    parent[it.second]=k;
                    D[it.second]=D[k]+1;
                    q.push(it.second);
                }
        }
    }

    SP.clear();
    SP.push_back(parent);
    maxlg= 63 - __builtin_clzll(n);
    for(ll i = 1; i <= maxlg; i++)
    {
        vl c;
        for(ll j=0;j<n;j++)
        {
            if(SP[i-1][j]!=-1)
                c.push_back(SP[i-1][SP[i-1][j]]);
            else c.push_back(-1);
        }
        SP.push_back(c);
    }
    MN.clear();
    MN.push_back(b);

    for(ll i=1;i<=maxlg;i++)
    {
        vl c;
        for(ll j=0;j<n;j++)

```

```

        {
            if(MN[i-1][j]!=-1)
                c.push_back(max(MN[i-1][SP[i-1][j]],MN[i-1][j]));
            else c.push_back(-1);
        }
        MN.push_back(c);
    }
}
ll maxL(ll u,ll v)//arista largo maximo
{
    ll a,b,x=LCA(u, v);
    if(u==x)a =- 1;
    else a = query(D[x], u);
    if(v==x)b =- 1;
    else b = query(D[x], v);
    return max(a, b);
}
ll query(ll a,ll n)
{
    ll maxi=-1;
    while(D[n]!=a)
    {
        maxi = max(maxi, MN[maxlog2(D[n]-a)][n]);
        n=SP[maxlog2(D[n]-a)][n];
    }
    return maxi;
}
ll level(ll a,ll n)// a=distancia
{// lleva n a la profundidad a
    while(D[n] != a)
        n = SP[maxlog2(D[n]-a)][n];
    return n;
}
ll LCA(ll u,ll v)
{
    ll x = u, y = v;
    if(D[u] <= D[v]) swap(x, y);

    if(D[x] != D[y])
        x = level(min(D[x], D[y]), x);

    if(x == y) return x;

    for(ll i = maxlg; i>=0; i--)
    {

```

```

        if(SP[i][x] != SP[i][y] && SP[i][x] != -1)
        {
            x = SP[i][x];
            y = SP[i][y];
        }
    }
    return SP[0][x];
}
11 Dist(11 u, 11 v)
{
    return D[u] + D[v] - 2*D[LCA(u, v)];
}
11 kth_fartest_node(11 u, 11 v, 11 d)
{
    if(Dist(u, LCA(u, v)) < d)
        return level(D[v] - (Dist(u, v) - d), v);

    else
        return level(D[u] - d, u);
}

// move u k steps in path to v
11 next_path(11 u, 11 v, 11 k){

    if(D[u] - D[LCA(u, v)] >= k) return level(D[u] - k, u);
    else return level(D[LCA(u, v)] + k - (D[u] - D[LCA(u, v)]), v);
}
};

```

3.11 LaplacianMatrix

```

#include "../Header.cpp"

// Dimension of input square matrix
#define N 4

// Function to get cofactor of mat[p][q] in temp[][]. n is
// current dimension of mat[][]
void getCofactor(int mat[N][N], int temp[N][N], int p,
                int q, int n)
{
    int i = 0, j = 0;

```

```

// Looping for each element of the matrix
for (int row = 0; row < n; row++)
{
    for (int col = 0; col < n; col++)
    {
        // Copying into temporary matrix only those
        // element which are not in given row and
        // column
        if (row != p && col != q)
        {
            temp[i][j++] = mat[row][col];

            // Row is filled, so increase row index and
            // reset col index
            if (j == n - 1)
            {
                j = 0;
                i++;
            }
        }
    }
}
}

```

```

/* Recursive function for finding determinant of matrix.
n is current dimension of mat[][]. */
int determinantOfMatrix(int mat[N][N], int n)
{
    int D = 0; // Initialize result

    // Base case : if matrix contains single element
    if (n == 1)
        return mat[0][0];

    int temp[N][N]; // To store cofactors

    int sign = 1; // To store sign multiplier

    // Iterate for each element of first row
    for (int f = 0; f < n; f++)
    {
        // Getting Cofactor of mat[0][f]
        getCofactor(mat, temp, 0, f, n);
        D += sign * mat[0][f]
            * determinantOfMatrix(temp, n - 1);
    }
}

```

```

        // terms are to be added with alternate sign
        sign = -sign;
    }

    return D;
}

/* function for displaying the matrix */
void display(int mat[N][N], int row, int col)
{
    for (int i = 0; i < row; i++)
    {
        for (int j = 0; j < col; j++)
            cout << " " << mat[i][j];
        cout << "\n";
    }
}

// Driver program to test above functions
int main()
{
    /* int mat[N][N] = {{6, 1, 1},
                       {4, -2, 5},
                       {2, 8, 7}}; */

    int mat[N][N] = { { 1, 0, 2, -1 },
                      { 3, 0, 0, 5 },
                      { 2, 1, 4, -3 },
                      { 1, 0, 5, 0 } };

    int T[N][N]; //Tutte matrix
    //range of matrix(number of pivots) is # different matching maximum
    ll n, m;
    for(int i = 0; i < m; i++)
    {
        ll x, y, w;
        cin >> x >> y >> w;
        mat[x][y] = -1; //-w;
        mat[y][x] = -1; //-w;
        mat[x][x] += 1; //w;
        mat[y][y] += 1; //w;

        T[x][x] = 0;
        T[x][y] = rand() % 1e9+7;
    }
}

```

```

        T[y][x] = -T[x][y];
    }

    // O(N^3)
    cout << "Number of spanning trees/weight sum of spanning tree : " <<
        determinantOfMatrix(mat, N-1);

    cout << "Number of spanning forest with i in one component and j in
        the other : " << determinantOfMatrix(mat, N-i -j); //delete i/t
        row and column

    if(determinantOfMatrix(T, N) == 0)
        cout << "Does not exist a maximum matching in the general graph
            (need more verify)";
    else
        cout << "Does exist perfect matching";
    cout << "Number of spanning trees/weight sum of spanning tree : " <<
        determinantOfMatrix(T, N);
    return 0;
}

```

3.12 MaxBipartiteMatching

```

#include "../Header.cpp"

// Works with 3-pairing or more (Perfect MCBM)

vl match, vis; // global variables
vector<vl> g;

int Aug(int L) {
    if (vis[L]) return 0; // L visited, return 0
    vis[L] = 1;
    for (auto it : g[L])
        if ((match[it] == -1) || Aug(match[it])) {
            match[it] = L; // flip status
            return 1; // found 1 matching
        }
    return 0; // no matching
}

```

```

int main() {
    ios::sync_with_stdio(false);
    cin.tie(0);
    cout.tie(0);

    ll V, Vleft;
    // Vleft and VRight can have common vertices names
    // match[R] -> L
    match.assign(V, -1);
    ll MCBM = 0;
    for(int L = 0; L < Vleft; L++)
    {
        vis.assign(Vleft, 0);
        MCBM += Aug(L);
    }
    cout << "Found " << MCBM << " matchings\n"; // the answer is 2 for
    Figure 4.38
    cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC <<
    "ms\n";
    return 0;
}

```

3.13 MaxFlowDinic

```

// Time Complexity:
// - general worst case:  $O(|E| * |V|^2)$ 
//  $O(|E| \cdot \max\_flow)$  ford fulkenson
// - unit capacities:  $O(\min(V^{2/3}, \sqrt{E}))$ 
// - Bipartite graph (unit capacities) + source & sink (any capacities):
//    $O(E \sqrt{V})$ 

// minimo corte:
// separa en 2 colores el grafo y el minimo corte
// es la separacin con menos aristas entre distinto color
// mandar infinito a nodos que estan obligados a ser de un colors
// min_cut == max_flow

// max matching = max_flow (grafo bipartito)
// minimo cubrimiento nodos = nodos - max_flow

// maximo matching  $m \cdot \sqrt{n}$ 

```

```

class Dinic
{
    struct Edge { int to, rev; ll f, c; };
    int n, t_; vector<vector<Edge>> G;
    vl D; vi q, W;

    bool bfs(int s, int t)
    {
        W.assign(n, 0); D.assign(n, -1); D[s] = 0;
        int f = 0, l = 0; q[l++] = s;
        while (f < l)
        {
            int u = q[f++];
            for (const Edge &e : G[u]) if (D[e.to] == -1 && e.f < e.c)
                D[e.to] = D[u] + 1, q[l++] = e.to;
        }
        return D[t] != -1;
    }
    ll dfs(int u, ll f)
    {
        if (u == t_) return f;
        for (int &i = W[u]; i < (int)G[u].size(); ++i)
        {
            Edge &e = G[u][i]; int v = e.to;
            if (e.c <= e.f || D[v] != D[u] + 1) continue;
            ll df = dfs(v, min(f, e.c - e.f));
            if (df > 0) { e.f += df, G[v][e.rev].f -= df; return df; }
        }
        return 0;
    }

public:
    Dinic(int N) : n(N), G(N), D(N), q(N) {}
    void addEdge(int u, int v, ll cap)
    {
        G[u].push_back({v, (int)G[v].size(), 0, cap});
        G[v].push_back({u, (int)G[u].size() - 1, 0, 0}); // cap if
        bidirectional
    }
    ll maxFlow(int s, int t)
    {
        t_ = t; ll ans = 0;
        while (bfs(s, t)) while (ll dl = dfs(s, LLONG_MAX)) ans += dl;
        return ans;
    }
}

```



```

    }
};

```

3.14 MaxFlowFordFulkerson

```

#include "../Header.cpp"

// minimo cubrimiento aristas = min-cut
// extremos de aristas cortadas que no son s ni t
// max conj, ind = nodos - minimo cubrimiento aristas

// O(VE^2)
// O(EF)

// Number of vertices in given graph
#define V 6

/* Returns true if there is a path from source 's' to sink 't' in
residual graph. Also fills parent[] to store the path */
int bfs(int rGraph[V][V], int s, int t, int parent[])
{
    // Create a visited array and mark all vertices as not visited
    bool visited[V];
    memset(visited, 0, sizeof(visited));

    // Create a queue, enqueue source vertex and mark source vertex
    // as visited
    queue<int> q;
    q.push(s);
    visited[s] = true;
    parent[s] = -1;

    // Standard BFS Loop
    while (!q.empty())
    {
        int u = q.front();
        q.pop();

        for (int v=0; v<V; v++)
        {
            if (visited[v]==false && rGraph[u][v] > 0)
            {

```

```

                q.push(v);
                parent[v] = u;
                visited[v] = true;
            }
        }
    }

    // If we reached sink in BFS starting from source, then return
    // true, else false
    return (visited[t] == true);
}

// A DFS based function to find all reachable vertices from s. The
// function
// marks visited[i] as true if i is reachable from s. The initial values
// in
// visited[] must be false. We can also use BFS to find reachable vertices
void dfs(int rGraph[V][V], int s, bool visited[])
{
    visited[s] = true;
    for (int i = 0; i < V; i++)
        if (rGraph[s][i] && !visited[i])
            dfs(rGraph, i, visited);
}

// Prints the minimum s-t cut
void minCut(int graph[V][V], int s, int t)
{
    int u, v;

    // Create a residual graph and fill the residual graph with
    // given capacities in the original graph as residual capacities
    // in residual graph
    int rGraph[V][V]; // rGraph[i][j] indicates residual capacity of edge
    i-j
    for (u = 0; u < V; u++)
        for (v = 0; v < V; v++)
            rGraph[u][v] = graph[u][v];

    int parent[V]; // This array is filled by BFS and to store path
    int max_flow = 0; // There is no flow initially
    // Augment the flow while there is a path from source to sink
    while (bfs(rGraph, s, t, parent))
    {
        // Find minimum residual capacity of the edges along the

```

```

// path filled by BFS. Or we can say find the maximum flow
// through the path found.
int path_flow = INT_MAX;
for (v=t; v!=s; v=parent[v])
{
    u = parent[v];
    path_flow = min(path_flow, rGraph[u][v]);
}

// update residual capacities of the edges and reverse edges
// along the path
for (v=t; v != s; v=parent[v])
{
    u = parent[v];
    rGraph[u][v] -= path_flow;
    rGraph[v][u] += path_flow;
}
max_flow += path_flow;
}

// Flow is maximum now, find vertices reachable from s
bool visited[V];
memset(visited, false, sizeof(visited));
dfs(rGraph, s, visited);

// Print all edges that are from a reachable vertex to
// non-reachable vertex in the original graph
for (int i = 0; i < V; i++)
    for (int j = 0; j < V; j++)
        if (visited[i] && !visited[j] && graph[i][j])
            cout << i << " - " << j << endl;

return;
}

// Driver program to test above functions
int main()
{
    // Let us create a graph shown in the above example
    int graph[V][V] = { {0, 16, 13, 0, 0, 0},
                        {0, 0, 10, 12, 0, 0},
                        {0, 4, 0, 0, 14, 0},
                        {0, 0, 9, 0, 0, 20},
                        {0, 0, 0, 7, 0, 4},
                        {0, 0, 0, 0, 0, 0}
    };

```

```

        };

        minCut(graph, 0, 5);

        return 0;
    }

```

3.15 MinCostMaxFlow

```

#include "../Header.cpp"

struct Edge
{
    int from, to, capacity, cost;
};

vector<vector<int>> adj, cost, capacity;

const int INF = 1e9;

void shortest_paths(int n, int v0, vector<int>& d, vector<int>& p) {
    d.assign(n, INF);
    d[v0] = 0;
    vector<bool> inq(n, false);
    queue<int> q;
    q.push(v0);
    p.assign(n, -1);

    while (!q.empty()) {
        int u = q.front();
        q.pop();
        inq[u] = false;
        for (int v : adj[u]) {
            if (capacity[u][v] > 0 && d[v] > d[u] + cost[u][v]) {
                d[v] = d[u] + cost[u][v];
                p[v] = u;
                if (!inq[v]) {
                    inq[v] = true;
                    q.push(v);
                }
            }
        }
    }
}

```

```

}

// flow, source, to;
int min_cost_flow(int N, vector<Edge> edges, int K, int s, int t) {
    adj.assign(N, vector<int>());
    cost.assign(N, vector<int>(N, 0));
    capacity.assign(N, vector<int>(N, 0));
    for (Edge e : edges) {
        adj[e.from].push_back(e.to);
        adj[e.to].push_back(e.from);
        cost[e.from][e.to] = e.cost;
        cost[e.to][e.from] = -e.cost;
        capacity[e.from][e.to] = e.capacity;
    }

    int flow = 0;
    int cost = 0;
    vector<int> d, p;
    while (flow < K) {
        shortest_paths(N, s, d, p);
        if (d[t] == INF)
            break;

        // find max flow on that path
        int f = K - flow;
        int cur = t;
        while (cur != s) {
            f = min(f, capacity[p[cur]][cur]);
            cur = p[cur];
        }

        // apply flow
        flow += f;
        cost += f * d[t];
        cur = t;
        while (cur != s) {
            capacity[p[cur]][cur] -= f;
            capacity[cur][p[cur]] += f;
            cur = p[cur];
        }
    }

    if (flow < K)
        return -1;
    else

```

```

        return cost;
    }

    int sup[55], inf[55];

    int main(){
        int n, q;
        ll ans = 0;
        cin >> n >> q;
        for (int i = 0; i < n; ++i) {
            sup[i] = n;
            inf[i] = 1;
        }
        for (int j = 0; j < q; ++j) {
            int t, l, r, v;
            cin >> t >> l >> r >> v;
            if (t == 1){
                for (int i = l - 1; i <= r - 1; ++i) {
                    inf[i] = max(inf[i], v);
                }
            }else{
                for (int i = l - 1; i <= r - 1; ++i) {
                    sup[i] = min(sup[i], v);
                }
            }
        }
        vector<Edge> ee;
        Edge E;

        for(int i = 0; i < n; i++)
        {
            E.from = 0;
            E.to = i + 2;
            E.capacity = 1;
            E.cost = 0;
            ee.push_back(E);
            for(int j = inf[i]; j <= sup[i]; j++)
            {
                E.from = i + 2;
                E.to = j + n + 1;
                E.capacity = 1;
                E.cost = 0;
                ee.push_back(E);
            }
        }
    }
}

```

```

    }
}
ll id = n + 2 + n;
for(int i = n + 2; i <= n + 2 + n - 1; i++)
{
    for(int j = 0; j < n; j++)
    {
        E.from = i;
        E.to = id;
        E.capacity = 1;
        E.cost = 2 * j + 1;
        ee.push_back(E);
        E.from = id;
        E.to = i;
        E.capacity = 1;
        E.cost = 0;
        ee.push_back(E);
        id++;
    }
}
ans = min_cost_flow(2 * n + n*n + 10, ee, n, 0, 1);
cout << ans << "\n";

cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC <<
      "ms\n";
}

```

3.16 MinCostMaxFlow2

```
#include "../Template.cpp"
```

```

template <class T>
class MCMF
{
    typedef pair<T, T> pTT;
    T INF = numeric_limits<T>::max();
    struct Edge
    {
        int v; T c, w;
        Edge(int v, T c, T w) : v(v), c(c), w(w) {}
    };
};

```

```

int n; vvi E;
vector<Edge> L; vi F; vector<T> D, P; vector<bool> V;

bool dij(int s, int t)
{
    D.assign(n, INF); F.assign(n, -1); V.assign(n, false);
    D[s] = 0;
    rep(_, n)
    {
        int best = -1;
        rep(i, n) if (!V[i] && (best == -1 || D[best] > D[i])) best = i;
        if (D[best] >= INF) break;
        V[best] = true;
        for (int e : E[best])
        {
            Edge ed = L[e];
            if (ed.c == 0) continue;
            T toD = D[best] + ed.w + P[best] - P[ed.v];
            if (toD < D[ed.v]) D[ed.v] = toD, F[ed.v] = e;
        }
    }
    return D[t] < INF;
}

pTT augment(int s, int t)
{
    pTT flow(L[F[t]].c, 0);
    for (int v = t; v != s; v = L[F[v]].v)
        flow.ff = min(flow.ff, L[F[v]].c), flow.ss += L[F[v]].w;
    for (int v = t; v != s; v = L[F[v]].v)
        L[F[v]].c -= flow.ff, L[F[v]].c += flow.ff;
    return flow;
}

public:
MCMF(int n) : n(n), E(n), D(n), P(n, 0), V(n, 0) {}
pTT mcmf(int s, int t)
{
    pTT ans(0, 0);
    if (!dij(s, t)) return ans;
    rep(i, n) if (D[i] < INF) P[i] += D[i];
    while (dij(s, t))
    {
        auto flow = augment(s, t);
        ans.ff += flow.ff, ans.ss += flow.ff * flow.ss;
    }
}

```

```

        rep(i, n) if (D[i] < INF) P[i] += D[i];
    }
    return ans;
}
void addEdge(int u, int v, T c, T w)
{
    E[u].pb(L.size()); L.eb(v, c, w);
    E[v].pb(L.size()); L.eb(u, 0, -w);
}
};

```

3.17 SCC

```
#include "../Header.cpp"
```

```

vl dfs_num, dfs_low, visited;
vector<vl> g, invg;
void Kosaraju(int u, int pass, vl& S) { // pass = 1 (original), 2
    (transpose)
    dfs_num[u] = 1;
    vl &neighbor = (pass == 1) ? g[u] : invg[u];
    for (auto it : neighbor)
        if (dfs_num[it] == -1)
            Kosaraju(it, pass, S);
    S.push_back(u);
}

```

```

// -----
// implementation of Tarjan's SCC algorithm
stack<int> St;
int cont, numSCC;

```

```

void tarjanSCC(int u) {
    dfs_low[u] = dfs_num[u] = cont;
    cont++;
    St.push(u);
    visited[u] = 1;
    for (auto v : g[u]) {
        if (dfs_num[v] == -1)
            tarjanSCC(v);
        if (visited[v])
            dfs_low[u] = min(dfs_low[u], dfs_low[v]);
    }
}

```

```

if (dfs_low[u] == dfs_num[u]) {
    while (1) {
        int v = St.top(); St.pop(); visited[v] = 0;

        if (u == v) break;
    }
    ++numSCC;
}
}

```

```

int main() {

    int n, m; cin >> n >> m;
    vector<vl> g(n);
    while(m--) {
        int u, v; cin >> u >> v; u--, v--;
        g[u].push_back(v);
    }
    // run Tarjan's SCC
    dfs_num.assign(n, 0); dfs_low.assign(n, 0); visited.assign(n, 0);
    while (!St.empty()) St.pop();
    cont = numSCC = 0;
    for (int u = 0; u < n; ++u)
        if (dfs_num[u] == -1)
            tarjanSCC(u);

    //Kosaraju's SCC

    vl S;
    dfs_num.assign(n, -1);
    for (int u = 0; u < n; ++u)
        if (dfs_num[u] == -1)
            Kosaraju(u, 1, S);
    int numSCC = 0;
    dfs_num.assign(n, -1);
    for (int i = n-1; i >= 0; --i){
        vl comp;
        if (dfs_num[S[i]] == -1)
            numSCC++, Kosaraju(S[i], 2, comp); // on transposed
        graph
    }
}

```

```

    return 0;
}

```

3.18 StableMatching

```

#include "../Header.cpp"
// Match the preferences of N clients and M restaurants that no side
// prefer another
// restaurant or client, respectively.

// hospital-residents variation of stable matching
int main(){

    ios_base::sync_with_stdio(0);
    cin.tie(0);
    ll n, m, k, x;
    cin >> n >> m;

    vl cap(m, 1), match(n, -1);

    vector<queue<ll>> pref(n);
    queue<ll> q;
    for(auto &it : cap) cin >> it; // capacity

    for(int i = 0; i < n; i++)
    {
        q.push(i);
        cin >> k;
        while(k--)
        {
            cin >> x;
            pref[i].push(x-1); //client preference list
        }
    }

    vector<unordered_map<ll, ll>> res_pref(m);
    for(int i = 0; i < m; i++)
    {
        ll id = 0;
        cin >> k;
        while(k--)
        {
            cin >> x;

```

```

            res_pref[i][x-1] = -id; // restaurant preference
            list
            id++;
        }
    }

    vector<set<pll>> in_res(m);
    while(!q.empty())
    {
        ll cl = q.front();
        q.pop();

        ll rest = pref[cl].front(); // actual preference restaurant

        in_res[rest].insert({res_pref[rest][cl], cl}); // add
        client to restaurant
        match[cl] = rest;
        pref[cl].pop(); // remove client preference

        if(cap[rest] == 0)
        {
            ll cl_new = (*in_res[rest].begin()).second; //
            erase client with less preference
            in_res[rest].erase(in_res[rest].begin());

            match[cl_new] = -1;
            if(!pref[cl_new].empty()) // add client to queue if
            he has more preferences
                q.push(cl_new);
        }
        else
            cap[rest]--;
    }
    for(int i = 0; i < n; i++)
        if(match[i] != -1) cout << i+1 << " "<< match[i]+1 << "\n";
}

```

3.19 ToposortDFS

```

#include "../Header.cpp"

vl s, v;

```

```

vector<vl > g;
void dfs(int t)
{
    v[t] = 1;
    for(auto it : g[t])
        if(!v[it])
            dfs(it);

    s.pb(t);
}
int main()
{
    ios::sync_with_stdio(false);
    cin.tie(0);
    ll n;
    g.assign(n, vl());
    v.assign(n, 0);

    rep(i, n)
        if(!v[i])
            dfs(i);

    reverse(ALL(s));
    return 0;
}

```

3.20 ToposortKhan

```

#include "../Header.cpp"

// All toposort orderings
vector<vl> g;
ll in;
vl indegree, vis;
vl sorted;
vector<char> ans;
bool possible;
void toposort()
{
    bool flag = 0;

    for(int i = 0; i < in; i++)
    {

```

```

        if(indegree[i] == 0 && !vis[i])
        {
            sorted.push_back(i);

            for(auto it : g[i])
                indegree[it]--;
            vis[i] = 1;
            toposort();
            vis[i] = 0;
            sorted.pop_back();

            for(auto it : g[i])
                indegree[it]++;
            flag = 1;
        }
    }
    if(!flag && sorted.size() == in)
    {
        possible = 1;
        for(int i = 0; i < in; i++)
        {
            if(i > 0) cout << " ";
            cout << ans[sorted[i]];
        }
        cout << "\n";
    }
}

```

```

int main()
{
    ll v,x,y,e,a,b,in=0;
    pll h;
    cin>>v >> e;
    vector<vl > g(v, vl(0));
    for(int i = 0; i < e; i++)
    {
        cin >> x >> y;
        g[x].push_back(y);
    }

    //set indegrees
    vl indegree(v, 0);
    vl sorted;

```

```

for(int i=0; i < v; i++)
{
    for(auto it : g[i])
        indegree[it]++;
}
queue<ll> q;
//agregar par a cola para tener los paquetes o niveles de
    profundidad, sumar
for(int i = 0; i < v; i++)
    if(indegree[i] == 0)
        q.push(i);

while(!q.empty()){

    ll t = q.front();
    q.pop();

    for(auto it : g[t]){

        if(--indegree[it] == 0)
            q.push(it);
    }
}

return 0;
}

```

4 Header

```

#include<bits/stdc++.h>
#pragma GCC optimize("Ofast")
using namespace std;
typedef long long ll;
typedef unsigned long long ull;
typedef vector<ll> vl;
typedef vector<int> vi;
typedef pair<ll,ll> pll;
typedef vector<pll> vp;
typedef double db;
#define INF 1e17

```

```

#define INF32 INT_MAX
#define EPS 1e-7
#define ALL(x) x.begin() , x.end()
#define ALLR(x) x.rbegin() , x.rend()
#define UNIQUE(c) (c).resize(unique(ALL(c)) - (c).begin())
#define PI acos(-1.0)
#define pb push_back
#define rep(i, n) for (int i = 0; i < (int)n; i++)
#define repx(i, a, b) for (int i = (int)a; i < (int)b; i++)

#define DBG 1

#define cerr \
    if (DBG) cerr

int main() {

    ios::sync_with_stdio(false);
    cin.tie(0);
    cout.tie(0);
    srand((unsigned int) time(0));

    // Code here

    // Compile:
    // g++ Code1.cpp && ./a.out < in > out
    // ulimit -s 1048576 more stack size 1gb
    // g++ -std=c++11 Code1.cpp && a.exe < in > out
    cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC <<
        "ms\n";
    return 0;
}

```

5 Math

5.1 ArithmeticEval

```

#include "../Header.cpp"

ll k, n;
string s;

```

```

ll eval(ll l, ll r){
    ll open = 0;
    stack<ll> vals;
    stack<char> ops;

    if(s[l] == '+' || s[l] == '*' || s[r] == '+' || s[r] == '*')return
        -1;
    if(s[l] == '0' && r-l >= 1 && isdigit(s[l+1]))return -1;

    repx(i, l, r+1){
        if(isdigit(s[i])){
            vals.push((s[i] - '0') % k);
            while(i < r && isdigit(s[i+1])){
                i++;
                vals.top() = (vals.top() * 10 + (s[i] -
                    '0')) % k;
            }
        }
        else if(s[i] == '(')
        {
            open++;
            ops.push(s[i]);
        }
        else if(s[i] == ')')
        {
            open--;
            if(open < 0) return -1;
            ll in = i-1;
            while(ops.top() != '('){
                ll aux = vals.top();
                vals.pop();
                if(ops.top() == '+'){
                    vals.top() = (vals.top() + aux) % k;
                }
                else{
                    vals.top() = (vals.top() * aux) % k;
                }
                ops.pop();
            }
            ops.pop();
        }
        else{

```

```

            // higher precedence first
            while(!ops.empty() && ops.top() == '*'){
                ll aux = vals.top();
                vals.pop();
                vals.top() = (vals.top() * aux) % k;
                ops.pop();
            }
            ops.push(s[i]);
        }
    }
    if(open != 0) return -1;

    while(!ops.empty()){
        ll aux = vals.top();
        vals.pop();
        if(ops.top() == '+'){
            vals.top() = (vals.top() + aux) % k;
        }
        else{
            vals.top() = (vals.top() * aux) % k;
        }
        ops.pop();
    }

    return vals.top();
}

int main(){

    ios_base::sync_with_stdio(0);
    cin.tie(0);
    srand((unsigned int) time(0));

    cin >> k >> n;
    cin >> s;

    //cout << eval(0, n-1)<<"\n";
    ll ans = 0;
    rep(i, n){
        repx(j, i, n){
            if(eval(i, j) == 0){
                ans++;
                //cout << i << " " << j << " "<<eval(i,j)<<
                    "\n";
            }
        }
    }
}

```

```

    }
}
cout << ans << "\n";

cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC <<
    "ms\n";
return 0;
}

```

5.2 CRT

```
#include "../Header.cpp"
```

```

inline ll mod(ll x, ll m) { return ((x % m) < 0) ? x+m : x; }
inline ll mul(ll x, ll y, ll m) { return (x * y) % m; }
inline ll add(ll x, ll y, ll m) { return (x + y) % m; }

```

```

// extended euclidean algorithm
// finds g, x, y such that
// a * x + b * y = g = GCD(a,b)
ll gcdext(ll a, ll b, ll& x, ll& y) {
    ll r2, x2, y2, r1, x1, y1, r0, x0, y0, q;
    r2 = a, x2 = 1, y2 = 0;
    r1 = b, x1 = 0, y1 = 1;
    while (r1) {
        q = r2 / r1;
        r0 = r2 % r1;
        x0 = x2 - q * x1;
        y0 = y2 - q * y1;
        r2 = r1, x2 = x1, y2 = y1;
        r1 = r0, x1 = x0, y1 = y0;
    }
    ll g = r2; x = x2, y = y2;
    if (g < 0) g = -g, x = -x, y = -y; // make sure g > 0
    // for debugging (in case you think you might have bugs)
    // assert (g == a * x + b * y);
    // assert (g == __gcd(abs(a),abs(b)));
    return g;
}

```

```
void modInverse(int a, int m)
```

```

{
    int x, y;
    int g = gcdext(a, m, &x, &y);
    if (g != 1)
        cout << "Inverse doesn't exist";
    else
    {
        // m is added to handle negative x
        int res = (x%m + m) % m;
        cout << "Modular multiplicative inverse is " << res;
    }
}

```

```

// =====
// CRT for a system of 2 modular linear equations
// =====
// We want to find X such that:
// 1) x = r1 (mod m1)
// 2) x = r2 (mod m2)
// The solution is given by:
// sol = r1 + m1 * (r2-r1)/g * x' (mod LCM(m1,m2))
// where x' comes from
// m1 * x' + m2 * y' = g = GCD(m1,m2)
// where x' and y' are the values found by extended euclidean algorithm
// (gcdext)
// Useful references:
// https://codeforces.com/blog/entry/61290
// https://forthright48.com/chinese-remainder-theorem-part-1-coprime-moduli
// https://forthright48.com/chinese-remainder-theorem-part-2-non-coprime-moduli
// ** Note: this solution works if lcm(m1,m2) fits in a long long (64
// bits)
pair<ll,ll> CRT(ll r1, ll m1, ll r2, ll m2) {
    ll g, x, y; g = gcdext(m1, m2, x, y);
    if ((r1 - r2) % g != 0) return {-1, -1}; // no solution
    ll z = m2/g;
    ll lcm = m1 * z;
    ll sol = add(mod(r1, lcm), m1*mul(mod(x,z),mod((r2-r1)/g,z),z), lcm);
    // for debugging (in case you think you might have bugs)
    // assert (0 <= sol and sol < lcm);
    // assert (sol % m1 == r1 % m1);
    // assert (sol % m2 == r2 % m2);
    return {sol, lcm}; // solution + lcm(m1,m2)
}

```

```
// =====
// CRT for a system of N modular linear equations
// =====
// Args:
//   r = array of remainders
//   m = array of modules
//   n = length of both arrays
// Output:
//   a pair {X, lcm} where X is the solution of the sytemm
//   X = r[i] (mod m[i]) for i = 0 ... n-1
//   and lcm = LCM(m[0], m[1], ..., m[n-1])
//   if there is no solution, the output is {-1, -1}
// ** Note: this solution works if LCM(m[0],...,m[n-1]) fits in a long
//   long (64 bits)
#define rep(i,a,b) for (int i=a; i<b; ++i)
pair<ll,ll> CRT(ll* r, ll* m, int n) {
    ll r1 = r[0], m1 = m[0];
    rep(i,1,n) {
        ll r2 = r[i], m2 = m[i];
        ll g, x, y; g = gcdext(m1, m2, x, y);
        if ((r1 - r2) % g != 0) return {-1, -1}; // no solution
        ll z = m2/g;
        ll lcm = m1 * z;
        ll sol = add(mod(r1, lcm), m1*mul(mod(x,z),mod((r2-r1)/g,z),z),
                    lcm);
        r1 = sol;
        m1 = lcm;
    }
    // for debugging (in case you think you might have bugs)
    // assert (0 <= r1 and r1 < m1);
    // rep(i,0,n-1) assert (r1 % m[i] == r[i]);
    return {r1, m1};
}
```

5.3 Combinatory

```
#include "../Header.cpp"

const int M = 1e9+7;
// binary exponent
ll expmod(ll b, ll e){
    ll ans = 1;
```

```
    while(e){
        if(e&1) ans = ans*b %M;
        b = b*b %M; e >>= 1;
    }
    return ans;
}

// When M is prime
ll invmod(ll a){ return expmod(a, M-2); }

//inv modular factoriales
const ll MAXN = 1e5 + 1;
ll F[MAXN], INV[MAXN], FI[MAXN];
// ...

F[0] = 1; repx(i, 1, MAXN) F[i] = F[i-1]*i %M;
INV[1] = 1; repx(i, 2, MAXN) INV[i] = M - (ll)(M/i)*INV[M%i]%M;
FI[0] = 1; repx(i, 1, MAXN) FI[i] = FI[i-1]*INV[i] %M;

// combinatory
ll Comb(ll n, ll k){
    if(n < k) return 0;
    return F[n]*FI[k] %M *FI[n-k] %M;
}

// combinatory precalc
ll C[MAXN][MAXK];
// ...
rep(i, MAXN){
    C[i][0] = 1; if(i < MAXN) C[i][i] = 1;
    repx(j, 1, min(i, (int)MAXK))
        C[i][j] = (C[i-1][j-1] + C[i-1][j])%M;
}

// divide a elements into b segments = C[a-1][b-1]
// each segment has at least 1 element

//Wilson theorem
//(p-1)! mod p = -1 if p prime

//https://cp-algorithms.com/algebra/factorial-modulo.html#multiplicity-of-p
// n! mod p with p prime and ignore multiples of p
```

```

int factmod(int n, int p) {
    vector<int> f(p);
    f[0] = 1;
    for (int i = 1; i < p; i++)
        f[i] = f[i-1] * i % p;

    int res = 1;
    while (n > 1) {
        if ((n/p) % 2)
            res = p - res;
        res = res * f[n/p] % p;
        n /= p;
    }
    return res;
}

// number of times p divides n! = v_p, n! % p*v_p = 0
int multiplicity_factorial(int n, int p) {
    int count = 0;
    do {
        n /= p;
        count += n;
    } while (n);
    return count;
}

// combinatoria n = 1e18, primo chico
// lucas
const int M = 3005;
int C[M][M];
// ...
ll lucas(ll n, ll k, int p){
    ll ans = 1;
    while(n + k){
        ans = (ans * C[n%M][k%M]) % M;
        n /= M; k /= M;
    }
    return ans;
}

```

5.4 ErathostenesSieve

```
#include "../Header.cpp"
```

```

vector<bool> criba;
void criba(ll b)
{
    criba.assign(b, 1);
    criba[0] = 0;
    criba[1] = 0;
    repx(k, 2, sqrt(b+1) + 1)
        if(criba[k])
            for(int j=2; (j * k) < b + 1; j++)//optimization j=k
                criba[k*j] = 0;
}

```

5.5 FFT

```

#include "../Header.cpp"

#define M_PI1 3.141592653589793238462643383279502884L

typedef complex<double> C;
typedef vector<double> vd;

void fft(vector<C> &a)
{
    int n = a.size(), L = 31 - __builtin_clz(n);
    static vector<complex<long double>> R(2, 1);
    static vector<C> rt(2, 1);
    for (static int k = 2; k < n; k *= 2)
    {
        R.resize(n);
        rt.resize(n);
        auto x = polar(1.0L, M_PI1 / k);
        repx(i, k, 2 * k) rt[i] = R[i] = i & 1 ? R[i / 2] * x : R[i / 2];
    }
    vector<int> rev(n);
    rep(i, n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i, n) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2) for (int i = 0; i < n; i += 2 * k)
        rep(j, k)
        {
            auto x = (double *)&rt[j + k], y = (double *)&a[i + j + k];
            C z(x[0] * y[0] - x[1] * y[1], x[0] * y[1] + x[1] * y[0]);
            a[i + j + k] = a[i + j] - z;
        }
    }

```

```

        a[i + j] += z;
    }
}

vd conv(const vl &a, const vl &b)
{
    if (a.empty() || b.empty()) return {};
    vd res(a.size() + b.size() - 1);
    int L = 32 - __builtin_clz(res.size()), n = 1 << L;
    vector<C> in(n), out(n);
    copy(a.begin(), a.end(), in.begin());
    rep(i, b.size()) in[i].imag(b[i]);
    fft(in);
    for (auto &x : in) x *= x;
    rep(i, n) out[i] = in[-i & (n - 1)] - conj(in[i]);
    fft(out);
    rep(i, res.size()) res[i] = imag(out[i]) / (4 * n);
    return res;
}

//slower
vl convMod(const vl &a, const vl &b, int M)
{
    if (a.empty() || b.empty()) return {};
    vl res(a.size() + b.size() - 1);
    int B = 32 - __builtin_clz(res.size()), n = 1 << B, cut =
        int(sqrt(M));
    vector<C> L(n), R(n), outs(n), outl(n);
    rep(i, a.size()) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
    rep(i, b.size()) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
    fft(L), fft(R);
    rep(i, n)
    {
        int j = -i & (n - 1);
        outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
        outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
    }
    fft(outl), fft(outs);
    rep(i, res.size())
    {
        ll av = ll(real(outl[i]) + .5), cv = ll(imag(outs[i]) + .5);
        ll bv = ll(imag(outl[i]) + .5) + ll(real(outs[i]) + .5);
        res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
    }
    return res;
}

```

```

}

int main() {
    ios::sync_with_stdio(false);
    cin.tie(0);
    cout.tie(0);
    int n, m;
    cin >> n >> m;
    string s, t;
    cin >> s >> t;
    // SAME SIZE
    vl an(n, 0), am(n, 0);
    vl bn(n, 0), bm(n, 0);
    for (int k = 0; k < n; ++k) {
        if (s[k] == 'a') an[k] = 1;
        else bn[k] = 1;
    }
    for (int k = 0; k < m; ++k) {
        if (t[k] == 'a') am[k] = 1;
        else bm[k] = 1;
    }
    reverse(am.begin(), am.end());
    reverse(bm.begin(), bm.end());
    vd resA = conv(an, am);
    vd resB = conv(bn, bm);
    vector<vector<int>> ans;
    ans.assign(m+1, vector<int>());

    //n > m
    // All complete count mathces
    for (int i = n-1; i < 2*n - m; ++i) {
        ans[m - round(resA[i]) - round(resB[i])].push_back(i-n+2);
    }
    // or these ranges for an and bm with original legnth
    for (int j = m-1; j < n; ++j) {
        for (int j = 0; j <= m; ++j) {
            cout << j << " ";
            for (int u: ans[j]) cout << " " << u;
            cout << "\n";
        }
    }
    cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC <<
        "ms\n";
}

```

5.6 Functions

```
#include "../Header.cpp"

using namespace chrono;
auto start1 = high_resolution_clock::now();
auto stop = high_resolution_clock::now();
auto duration = duration_cast<microseconds>(stop - start1);
//cerr << duration.count()/1000 << "ms" << endl;

default_random_engine generator;
uniform_real_distribution<double> distribution(0,LLONG_MAX);
ll num = distribution(generator);

// files
ifstream input;
input.open("divisibility-tree.in");
input >> n;
ofstream output;
output.open("divisibility-tree.out");
output<<" ";
output.close();

// suma subconjuntos
for i = 0 to n-1
for mask = 0 to (1n) - 1
if (mask & (1i))
dp(mask) += dp(mask - (1i))

// suma divisores
for p    P
for x    S (DE MENOR A MAYOR)
if (p divide a x)
dp(x) += dp(x / p)

// hash pairs unorderedmap<pll,ll,hash_pair>
struct hash_pair {
    template <class T1, class T2>
    size_t operator()(const pair<T1, T2>& p) const
    {
        auto hash1 = hash<T1>{}(p.first);
        auto hash2 = hash<T2>{}(p.second);
        return hash1 ^ hash2;
    }
};
```

```
};
int maxlog2(int x) //potencia de 2 mayor que es menor o igual a x
{
    // ll maxlog = 63 - __builtin_clzll(x);
    int maxlog = 31 - __builtin_clz(x);
    return maxlog;
}
int A[10000]; //Set con reset 0(1), Tambien con Map
int t=1;
bool fin(int x)
{
    return A[x]==t;
}
void borrar()
{
    t++;
}
void inse(int x)
{
    A[x]=t;
}
int res(int a,int b)
{
    int c=1,d;
    for(int i=0;i<b;i++)
    {
        c*=10;
    }
    d=c*10;
    a=a-(a-a%d);
    a=a-(a%c);
    a=a/c;
    return a;
}

//propagate val in mask to all its submask
for (int i = 0; i < p; i++)
{
    for(int mask = 0; mask < (1 << p); mask++)
    {
        if((mask & (1 << i)) == 0)
            f[mask] += f[mask | (1 << i)];
        if(mask & (1 << i)) // to propagate from submasks to mask
    }
}
```

```

        dp[mask] += dp[mask - (1 << i)];
    }
}

// O(3^n)
rep(m, (1 << n)){
    // 2^k k: number of bits in m
    // iterates over all submasks of m in descending order of value
    for(int s = m; ; s = (s-1) & m){
        cout << s << endl;
        if(s == 0) break;
    }
}

int bit_opst(ll N, ll S)
{
    //Obtain the remainder (modulo) of S when it is divided by N (N is a
    power of 2)
    return S & (N - 1);
    //Determine if S is a power of 2.
    return (S & (S - 1)) == 0;
    //Turn on the last bit in S, e.g. S = (40)10 = (101000)2 S = (32)10 =
    (100000)2.
    return S & (S - 1);
    // Turn on the last zero in S, e.g. S = (41)10 = (101001)2 S = (43)10
    = (101011)2.
    return S || (S + 1);
    // Turn on the last consecutive run of ones in S
    return S & (S + 1);
    // Turn on the last consecutive run of zeroes in S
    return S || (S - 1);
    // Turn on all bits
    return S = (1 << 62) - 1;
    // multiply by 2^N
    return S <<= N;
    // Divide by 2^N
    return S >>= N;
    // Turn on the N-th bit
    return S = S || (1 << N);
    // Check if N-th bit is on
    return (S & (1 << N));
    // Turn off the N-th bit
    return S &= ~(1 << N);
    // Alternate status of N-th bit
    return S ^= (1 << N);
}

```

```

    //Value of the least significant bit on from the right
    return N = (S & (-S));
}
//count numbers with i bit set [1, n-1]
ll kol(ll n, ll i)
{
    return (n / (1ll << (i + 1))) * (1ll << i) + max((n % (1ll << (i +
    1))) - (1ll << i), 0ll);
}
kol(r+1, i) - kol(l, i);

```

5.7 Gaussian Elimination

```

#include "../Header.cpp"

const double EPS = 1e-9;
const int INF = 2; // it doesn't actually have to be infinity or a big
number

int gauss (vector < vector<double> > a, vector<double> & ans) {
    int n = (int) a.size();
    int m = (int) a[0].size() - 1;

    vector<int> where (m, -1);
    for (int col=0, row=0; col<m && row<n; ++col) {
        int sel = row;
        for (int i=row; i<n; ++i)
            if (abs (a[i][col]) > abs (a[sel][col]))
                sel = i;
        if (abs (a[sel][col]) < EPS)
            continue;
        for (int i=col; i<=m; ++i)
            swap (a[sel][i], a[row][i]);
        where[col] = row;

        for (int i=0; i<n; ++i)
            if (i != row) {
                double c = a[i][col] / a[row][col];
                for (int j=col; j<=m; ++j)
                    a[i][j] -= a[row][j] * c;
            }
        ++row;
    }
}

```

```

ans.assign(m, 0);
for (int i=0; i<m; ++i)
    if (where[i] != -1)
        ans[i] = a[where[i]][m] / a[where[i]][i];
for (int i=0; i<n; ++i) {
    double sum = 0;
    for (int j=0; j<m; ++j)
        sum += ans[j] * a[i][j];
    if (abs (sum - a[i][m]) > EPS)
        return 0;
}

for (int i=0; i<m; ++i)
    if (where[i] == -1)
        return INF;
return 1;
}

int main(){
    ios_base::sync_with_stdio(0);
    cin.tie(0);

    ll n = 2;

    vector<vl>g (2, vl(3, 0));

    g[0][0] = 1;
    g[1][1] = 1;
    g[0][2] = 1;
    g[1][2] = 2;

    // g: rows: equations, columns: x_1 * p_1 + x_2 * p_2 + x_3 * p_3 = y
    for(int i = 0; i < n-2; i++)
    {
        for(int z = i+1; z < n-1; z++)
        {
            db mul = g[z][i] / g[i][i];
            for(int j = 0; j < n; j++)
                g[z][j] -= mul * g[i][j];
        }
    }
}

```

```

vector<db> vals(n, 0);

for(int i = n-2; i >= 0; i--)
{
    db sum = g[i][n-1];
    for(int j = i+1; j < n-1; j++)

        sum -= g[i][j] * vals[j];

    sum /= g[i][i];
    vals[i] = sum;
}

for(int i = 0; i < n-1; i++)
    cout << vals[i] << " ";

cout << endl;

for(int i = 0; i < n; i++)
{
    for(int j = 0; j < n+1; j++)
        cout << g[i][j] << " ";
    cout << endl;
}
}

```

5.8 MathFuncions

```

#include "../Header.cpp"

// pre overflow
ll mul(ll x, ll y) { if (x > MX / y) return MX; return x * y; }
ll sums(ll x, ll y) { if (MX - x < y) return MX; return x + y; }

const int N = 1e5 + 10, LOG_A = 31;
ll basis[LOG_A], sz;

// O(N * LOG), base that produces the maximum
void insertVector(int mask) {
    for (ll i = LOG_A - 1; i >= 0; i--) {

```



```

        if ((mask & 1 << i) == 0) continue;

        if (!basis[i]) {
            basis[i] = mask;
            sz++;
            return;
        }

        mask ^= basis[i];
    }

}

// inclusion, exclusion
ll ans = 0;
forr(bitmask, 1, (1<<n)){
    // bitmask srepresenta la interseccion actual
    bool resta = __builtin_popcount(bitmask)%2;
    ans = (ans + (resta ? 1 : M-1)*cuenta(bitmask) %M) %M;
}

// Catalan number

/*
    Number of ways to place    pairs of parentheses correctly.
    Number of binary trees with    nodes.
    Number of full binary trees with    +    leaves.
    Number of ways to triangulate a convex    +    sided polygon.
*/

ll CAT[MAXN];
// ...
CAT[0] = CAT[1] = 1;
repx(i, 2, MAXN){
    CAT[i] = 0;
    rep(k, i)
        CAT[i]=(CAT[i]+CAT[k]*CAT[i-1-k]%M)%M;
}
ll F[MAXN], INV[MAXN], FI[MAXN];
ll Cat(int n){
    return F[2*n] *FI[n+1]%M *FI[n]%M;
}

// Stirling numbers

// number of ways to partition a set of n elements into k nonempty subsets

```

```

ll Stirling[MAXN][MAXN];
// ...
repx(i, 1, MAXN)Stirling[i][1] = 1;
repx(i, 2, MAXN)Stirling[1][i] = 0;
repx(i, 2, MAXN)forr(j, 2, MAXN){
    Stirling[i][j] =
        (Stirling[i-1][j-1] + j*Stirling[i-1][j]%MOD) %MOD;
}

// Bell numbers

// Number of partitions of set of n elements

// a deck of n cards is shuffled by repeatedly removing the top card and
// reinserting it anywhere in the deck (including its original position
// at the top of the deck), with exactly n repetitions
// stays the same B_n ways
// Probability B_n / n^n

// nth Bell number equals the number of permutations on n items in which
// no three values that are in sorted order have the last two of these
// three consecutive
ll Stirling[MAXN][MAXN], Bell[MAXN];
// ...
forr(i, MAXN){
    Bell[i] = 0;
    forr(j, MAXN)
        Bell[i] = (Bell[i] + Stirling[i][j]) %MOD;
}

//grundy
int tag[n*n];
int mex(int id)
{
    int ans = 0;
    while(tag[ans] == id) ++ans;
    return ans;
}

ll cn = 0;
for(int i = 0; i < n; i++)
{
    for(int j = 0; j < n; j++)
    {
        ll id = ++cn;
    }
}

```

```

//abajo
for(int k = i - 1; k >= 0; k--)
    tag[grundy[k][j]] = id;

//izquierda
for(int k = j - 1; k >= 0; k--)
    tag[grundy[i][k]] = id;

// diagonal
for(int k = 1; k <= min(i, j); k++)
    tag[grundy[i-k][j-k]] = id;
grundy[i][j] = mex(id);
}
}

// fibonacci numbers
f_i = 1 / sqrt(5 * ((1 + sqrt(5)) / 2) ^ n - ((1 - sqrt(5)) / 2) ^ n);

// catalan numbers
a_n = 1 / (n+1) * comb(2n, n);

```

5.9 Matrices

```

#include "../Header.cpp"

/*
matrix A: transitions Axb
vector b(rows, 1): base case of dp
Represents last |b| states of dp

F_n
...
F2
F1
*/

// a^p = a*p mod P
// if a % p == 0 return 0

// to calculate p, can use p mod (P-1)
struct Mat {
    vector<vl> vec;
    Mat(): vec(1, vl(1, 0)) {}

```

```

Mat(int n): vec(n, vl(n) ) {}
Mat(int n, int m): vec(n, vl(m, 0) ) {}
vl &operator[](int f){ return vec[f]; }
const vl &operator[](int f) const { return vec[f]; }
int size() const { return vec.size(); }
};

Mat operator *(Mat A, Mat B) {
    int n = A.size(), m = A[0].size(), t = B[0].size();
    Mat ans(n, t);
    rep(i, n) rep(j, t) rep(k, m)
        ans[i][j] = (ans[i][j] + A[i][k] * B[k][j] % MOD) % MOD;
    return ans;
}

Mat expmat(Mat A, ll e){
    int n = A.size();
    Mat Ans(n); rep(i, n) Ans[i][i] = 1;
    while(e){
        if(e&1) Ans = Ans*A;
        A = A*A; e >>= 1;
    }
    return Ans;
}

ll Fibo(ll n) {
    Mat V0(1, 2), T(2);
    V0[0] = {1, 1};
    T[0] = {0, 1}; T[1] = {1, 1};
    Mat V = V0*expmat(T, n);
    return V[0][0];
}

```

5.10 PrimeFactorization

```

#include "../Header.cpp"

// stores smallest prime factor for every number
int spf[MAXN];

// Calculating SPF (Smallest Prime Factor) for every
// number till MAXN.
// Time Complexity : O(nloglogn)

```

```

void sieve()
{
    spf[1] = 1;
    for (int i=2; i<MAXN; i++)

        // marking smallest prime factor for every
        // number to be itself.
        spf[i] = i;

    // separately marking spf for every even
    // number as 2
    for (int i=4; i<MAXN; i+=2)
        spf[i] = 2;

    for (int i=3; i*i<MAXN; i++)
    {
        // checking if i is prime
        if (spf[i] == i)
        {
            // marking SPF for all numbers divisible by i
            for (int j=i*i; j<MAXN; j+=i)

                // marking spf[j] if it is not
                // previously marked
                if (spf[j]==j)
                    spf[j] = i;
        }
    }
}

// A O(log n) function returning primefactorization
// by dividing by smallest prime factor at every step
vector<int> getFactorization(int x)
{
    vector<int> ret;
    while (x != 1)
    {
        ret.push_back(spf[x]);
        x = x / spf[x];
    }
    return ret;
}

void primeFactors(ll n)
{

```

```

while (n % 2 == 0)
{
    cout << 2 << " ";
    n = n/2;
}

for (int i = 3; i <= sqrt(n); i = i + 2)
{
    while (n % i == 0)
    {
        cout << i << " ";
        n = n/i;
    }
}
if (n > 2)
    cout << n << " ";
}

```

5.11 Simplex

```

#include "../Header.cpp"

#define fore(i,a,b) for(int i=a,ThxDem=b;i<ThxDem;++i)

namespace Simplex {
vector<int> X,Y;
vector<vector<db>> > A;
vector<db> b,c;
db z;
int n,m;
void pivot(int x,int y){
    swap(X[y],Y[x]);
    b[x]/=A[x][y];
    fore(i,0,m)if(i!=y)A[x][i]/=A[x][y];
    A[x][y]=1/A[x][y];
    fore(i,0,n)if(i!=x&&abs(A[i][y])>EPS){
        b[i]-=A[i][y]*b[x];
        fore(j,0,m)if(j!=y)A[i][j]-=A[i][y]*A[x][j];
        A[i][y]=-A[i][y]*A[x][y];
    }
    z+=c[y]*b[x];
    fore(i,0,m)if(i!=y)c[i]-=c[y]*A[x][i];
    c[y]=-c[y]*A[x][y];
}
}

```

```

}
pair<db,vector<db> > simplex( // maximize  $c^T x$  s.t.  $Ax \leq b$ ,  $x \geq 0$ 
    vector<vector<db> > _A, vector<db> _b, vector<db> _c){
    // returns pair (maximum value, solution vector)
    A=_A;b=_b;c=_c;
    n=b.size();m=c.size();z=0.;
    X=vector<int>(m);Y=vector<int>(n);
    fore(i,0,m)X[i]=i;
    fore(i,0,n)Y[i]=i+m;
    while(1){
        int x=-1,y=-1;
        db mn=-EPS;
        fore(i,0,n)if(b[i]<mn)mn=b[i],x=i;
        if(x<0)break;
        fore(i,0,m)if(A[x][i]<-EPS){y=i;break;}
        if(y<0) return(make_pair(-1, b));
        assert(y>=0); // no solution to  $Ax \leq b$ 
        pivot(x,y);
    }
    while(1){
        db mx=EPS;
        int x=-1,y=-1;
        fore(i,0,m)if(c[i]>mx)mx=c[i],y=i;
        if(y<0)break;
        db mn=INF;
        fore(i,0,n)if(A[i][y]>EPS&&b[i]/A[i][y]<mn)mn=b[i]/A[i][y],x=i;
        assert(x>=0); //  $c^T x$  is unbounded
        pivot(x,y);
    }
    vector<db> r(m);
    fore(i,0,n)if(Y[i]<m)r[Y[i]]=b[i];
    return {z,r};
}
}

int main(){
    ios_base::sync_with_stdio(0);
    cin.tie(0);

    ll n, k, x;
    db y;
    cin >> n >> k >> x;

    vector<db> b, c;
    vector<vector<db> > A;

```

```

for(int i = 0; i < n; i++)
{
    cin >> y;
    c.push_back(y);
}

vector<db>aux(n, 0);
for(int i = 0; i < k; i++)aux[i] = -1;
A.push_back(aux);
b.push_back(-1.);

for(int i = k; i < n; i++)
{
    aux[i - k] = 0;
    aux[i] = -1;
    A.push_back(aux);
    b.push_back(-1);
}
aux.assign(n, 0);
for(int i = 0; i < n; i++)
{
    aux[i] = 1;
    A.push_back(aux);
    b.push_back(1);
    aux[i] = 0;
}
aux.assign(n, 1);
A.push_back(aux);
b.push_back(x);
ll in = 0;
/*for(auto it : A)
{
    for(auto it2: it)cout<<it2<<" ";
    cout<<" "<<b[in];
    in++;
    cout<<"*\n";
}*/

db mx = Simplex::simplex(A,b,c).first;
cout<<(long long)mx<<"\n";

cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC <<
    "ms\n";
return 0;

```

```
}

```

5.12 Simpson

```
const int N = 1000 * 1000; // number of steps (already multiplied by 2)

double simpson_integration(double a, double b){
    double h = (b - a) / N;
    double s = f(a) + f(b); // a = x_0 and b = x_2n
    for (int i = 1; i <= N - 1; ++i) { // Refer to final Simpson's formula
        double x = a + h * i;
        s += f(x) * ((i & 1) ? 4 : 2);
    }
    s *= h / 3;
    return s;
}
```

6 Misc

6.1 AdHoc

```
#include "../Header.cpp"

int joseph(int n,int m)
{
    int Result=0;
    for(int i=1;i<=n;i++)
    {
        Result=(Result+m-1)%i+1;
    }
    return(Result);
}

int joseph(int n,int m)
{
    v1 a(n+1, 0);
    //see eliminated
    bool o = 1;
    for(int i = 0; i < n/2; i++)
    {
```

```
        a[i+1] = (a[i] + m-1)%(n-i);
        if(a[i+1] < n/2 )
        {
            o = 0;
            break;
        }
    }
}

// if k = 2
// move first significant bit to right
int joseph(ll n)
{
    ll bit = 62;
    while(!(n & (1 << bit)))
    {
        bit--;
    }
    n &= ~(1 << bit);
    return 1 + (n << 1);
}

// primes in a n size range n / log(n)

// nim game
// a_1 ^ a_2 ^ ... ^ a_n = 0: player 1 lose

// nim variation: remove stones from [0, k] piles
// a_1 ^_k+1 a_2 ^_k+1 ... ^_k+1 a_n = 0: player 1 lose
// ^_k+1 = xor mod (k+1) k+1 bits = 0 mod (k+1)
// sum of pairs
// a*b + b*c + c*a
// (a + b + c + d)^2 - (a^2 + b^2 + c^2)

// valor{x} = (x, 0)
//combinar((s_1, p_1), (s_2, p_2)) = ((s_1 + s_2),(p_1 + p_2 + s_1 * s_2))

// sum of subconj
// 1 + a + b + c + a*b + b*c + c*a + a*b*c
// (1 + a)*(1 + b)*(1 + c)

// valor{x} = 1 + x
//combinar(a, b) = a*b

// x >= y -> x mod y < x/2 counting decimals
```

```

/*Para un arbol de tamao N, solo hay un arbol para cada divisor(N)
de tamao divisor(N) que lo puede armar solo consigo mismo

```

```

Para hashear un arbol se usan parentesis, el hash es distinto para cada
root,
hay que ordenar los hijos antes de hashear

```

```

everyone loses their hats all at once, and each person puts on a random
hat;
in expectation, how many people get their own hats back?
The probability that the each person gets their own hat is  $1/N$ ,
and then by linearity of expectation,
the total number of instances of someone getting their own hat is  $1/N * N = 1$ .

```

```

expeted value to two people will get their original hat :  $1/2$ 
for 3:  $1/3$ 

```

```

*/

```

```

// Modular sum optimization
if (R >= MOD) R -= MOD;

```

```

/*
euler cycle
all vertex with even degree

```

```

hamiltonian cycle
d(v) >= n/2 vertex degree

```

```

exact partition  $O(3^{(m/3)})$   $O(2^{(m/2)})$ 
m(4) sets and n(3) objects
001 -
010 -
110
011

```

```

for each i in n:
    choose a row with bit i on
    erase all rows with bit i on

```

```

    continue
*/

```

```

// convex hull of max max(X, Y)^(2/3) points in recatangle (0, 0) (X, Y)

```

6.2 Line input

```

#include "Header.cpp"

```

```

int main()
{
    // save strings separated by space in a line
    string line, token;
    getline(cin, line);
    stringstream ss(line);
    while(ss >> token)
    {
        cout << token << "\n";
    }
    return 0;
}

```

6.3 NextGreaterLower

```

#include "../Header.cpp"

```

```

int main(){

    ios_base::sync_with_stdio(0);
    cin.tie(0);

    ll n;
    cin >> n;

    vl c(n);
    // next value with lower/grater value
    // right greater, left greater, right lower, left lower
    vl Rg(n, n), Lg(n, -1), Rl(n, n), Ll(n, -1);

    rep(i, n){
        cin >> c[i];
    }
}

```

```

stack<ll> Sg, Sl;
rep(i, n){
    while(!Sg.empty() && c[Sg.top()] < c[i]){
        Rg[Sg.top()] = i;
        Sg.pop();
    }
    Sg.push(i);

    while(!Sl.empty() && c[Sl.top()] > c[i]){
        Rl[Sl.top()] = i;
        Sl.pop();
    }
    Sl.push(i);
}
while(!Sg.empty()) Sg.pop();
while(!Sl.empty()) Sl.pop();

for(int i = n-1; i >= 0; i--){
    while(!Sg.empty() && c[Sg.top()] <= c[i]){
        Lg[Sg.top()] = i;
        Sg.pop();
    }
    Sg.push(i);

    while(!Sl.empty() && c[Sl.top()] > c[i]){
        Ll[Sl.top()] = i;
        Sl.pop();
    }
    Sl.push(i);
}
cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC << "ms\n";
return 0;
}

```

7 Strings

7.1 AhoCorasick

```

#include "../Header.cpp"
struct AC
{

```

```

ll c = 0, ec = 0, M, A, af = -1;
vector<vl> N, G; vl L, E;
vl val;
// L -> suffix link G -> anti L
// E -> string finish
AC(ll M, ll A) : M(M), A(A), N(M, vl(A, 0)), G(M, vl()), E(M, 0),
    L(M, 0), val(M, 0) {}
ll add(string s) // return endpoint
{
    af++;
    ll p = 0;
    for(char l : s)
    {
        int t = l - 'a';
        if (!N[p][t]) N[p][t] = ++c;
        p = N[p][t];
    }
    val[p] = 1;
    return p;
}
void init()
{
    queue<int> q; q.push(0); L[0] = -1;
    while (!q.empty())
    {
        int p = q.front(); q.pop();
        for(int c = 0; c < A; c++)
        {
            int u = N[p][c]; if (!u) continue;
            L[u] = L[p] == -1 ? 0 : N[L[p]][c], q.push(u);

            G[L[u]].push_back(u);
        }
        if (p) for(int c = 0; c < A; c++) if (!N[p][c]) N[p][c] =
            N[L[p]][c];
    }
}
};

```

7.2 Hashing

```

#include "../Header.cpp"
struct RH
{
    // choose base B random to avoid hacks 33 37 41
    // randomize V(s[i])
    int B = 1777771, M[2] = {999727999, 107077777}, P[2] = {325255434,
        10018302};
    vl H[2], I[2];
    RH(string &s)
    {
        int N = s.size(); rep(k, 2)
        {
            H[k].resize(N + 1), I[k].resize(N + 1);
            H[k][0] = 0, I[k][0] = 1; ll b = 1;
            rep(i, N + 1) if (i)
            {
                H[k][i] = (H[k][i - 1] + b * s[i - 1]) % M[k];
                I[k][i] = (1LL * I[k][i - 1] * P[k]) % M[k];
                b = (b * B) % M[k];
            }
        }
    }
    ll get(int l, int r) // inclusive - exclusive
    {
        ll h0 = (H[0][r] - H[0][l] + M[0]) % M[0];
        h0 = (1LL * h0 * I[0][l]) % M[0];
        ll h1 = (H[1][r] - H[1][l] + M[1]) % M[1];
        h1 = (1LL * h1 * I[1][l]) % M[1];
        return (h0 << 32) | h1;
    }
};
bool compare(int a, int b)
{
    ll l = 0, r = n-1, p, res = -1;
    while(l <= r)
    {
        p = (l + r) / 2;
        if(rhs[a].get(0, p) == rhs[b].get(0, p)) l = p+1;
        else {
            res = p;
            r = p-1;
        }
    }
    if(res == -1) return a < b;
}

```

```

return s[a][res] < s[b][res];
}

```

```

//Suffix Array O(N log^2 N)
rep(n) sa[i] = i;
sort(ALL(sa), compare)

```

7.3 KMP

```

#include "../Header.cpp"

// Build longest proper prefix/suffix array (lps) for pattern
// lps[i] = length of the longest proper prefix which is also suffix in
// pattern[0 .. i]
void init_lps(string& s, int lps[]) {
    int n = s.size();
    lps[0] = 0; // base case: no proper prefix/suffix for pattern[0 .. 0]
    (length 1)
    repx(j, 1, n) { // for each s[0 .. j]
        int i = lps[j-1]; // i points to the char next to lps of previous
        // iteration
        while (s[i] != s[j] and i > 0) i = lps[i-1];
        lps[j] = s[i] == s[j] ? i+1 : 0;

        //optimization to reutilice the lps in O(n)
        if(i > 0 && s[i] == s[lps[i-1]] && lps[i-1] != 0) lps[i-1] =
            lps[lps[i-1]-1];
    }
}

// Count number of matches of pattern string in target string using KMP
// algorithm
int kmp(string& s, string& t) {
    int n = s.size(), m = t.size();
    int lps[n];
    init_lps(s, lps); // build lps array
    int matches = 0;
    int i = 0; // i tracks current char in pattern to compare
    rep(j, m) { // j tracks each char in target to compare
        // try to keep prefix before i as long as possible while ensuring
        // i matches j
        while (s[i] != t[j] && i > 0) i = lps[i-1];
    }
}

```



```

        if (s[i] == t[j]) {
            if (++i == n) { // we matched the whole pattern
                i = lps[n-1]; // shift the pattern so that the longest
                             proper prefix/suffix pair is aligned

                matches++;
            }
        }
    }
    return matches;
}

int main() { // usage
    string target, pattern;
    while (true) {
        cin >> target >> pattern;
        cout << kmp(pattern, target) << " matches\n";
    }
    return 0;
}

```

7.4 LongestCommonSubstring

```

#include "../Header.cpp"

int LCSuff(string& X, string& Y, int m, int n)
{
    // Create a table to store lengths of longest common suffixes of
    // substrings. Notethat LCSuff[i][j] contains length of longest
    // common suffix of X[0..i-1] and Y[0..j-1]. The first row and
    // first column entries have no logical meaning, they are used only
    // for simplicity of program
    int LCSuff[m+1][n+1];
    int result = 0; // To store length of the longest common substring

    /* Following steps build LCSuff[m+1][n+1] in bottom up fashion. */
    for (int i=0; i<=m; i++)
    {
        for (int j=0; j<=n; j++)
        {
            if (i == 0 || j == 0)
                LCSuff[i][j] = 0;

```

```

            else if (X[i-1] == Y[j-1])
            {
                LCSuff[i][j] = LCSuff[i-1][j-1] + 1;
                result = max(result, LCSuff[i][j]);
            }
            else LCSuff[i][j] = 0;
        }
    }
    return result;
}

int main()
{
    string X = "OldSite:GeeksforGeeks.org", Y = "NewSite:GeeksQuiz.com";

    int m = X.size();
    int n = Y.size();

    cout << "Length of Longest Common Substring is " << LCSuff(X, Y, m,
        n) << "\n";
    return 0;
}

```

7.5 Manacher

```

#include "../Header.cpp"

vl manacher(string& s)
{
    int n = s.size();
    // string con # entre medio (2n - 1)
    vl lps(n);
    int l = 0, r = 0, c = 0;
    rep(i, n)
    {
        int j = l+(r-i);
        lps[i] = min(r-i, (int)lps[j]);
        while(i - lps[i] >= 0 && i+lps[i] < n &&
            s[i-lps[i]] == s[i+lps[i]]) lps[i]++;

        // acutalizar l, r

```

```

        if(r < i + lps[i])
        {
            l = i - lps[i];
            r = i + lps[i];
        }
    }
    // returns total size for each index
    return lps;
}

int main()
{
    ios::sync_with_stdio(0);
    cin.tie(0);
    ll n = 5;
    string s = "aaaaa", s2 = "a#a#a#a#a";

1
2
3
2
1

0
1
2
2
1

    // d1 -> number of expansions
    vector<int> d1(n);
    for (int i = 0, l = 0, r = -1; i < n; i++) {
        int k = (i > r) ? 1 : min(d1[l + r - i], r - i + 1);
        while (0 <= i - k && i + k < n && s[i - k] == s[i + k]) {
            k++;
        }
        d1[i] = k--;
        if (i + k > r) {
            l = i - k;
            r = i + k;
        }
    }
    // evens, start at index 1, right -> aaAa
    vector<int> d2(n);
    for (int i = 0, l = 0, r = -1; i < n; i++) {

```

```

        int k = (i > r) ? 0 : min(d2[l + r - i + 1], r - i + 1);
        while (0 <= i - k - 1 && i + k < n && s[i - k - 1] == s[i + k]) {
            k++;
        }
        d2[i] = k--;
        if (i + k > r) {
            l = i - k - 1;
            r = i + k;
        }
    }
    for(auto it : d1) cout<<it<<"\n";
    cout<<"\n";
    for(auto it : d2) cout<<it<<"\n";
    cout<<"\n";
    //v1 t = manacher(s2);
    //for(auto it : t) cout<<it<<"\n";
    cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC << "ms\n";
    return 0;
}

```

7.6 PalindromicTree

```

#include "../Header.cpp"

#define MAXN 2000005
ll M = 51123987;
struct Node
{
    // store start and end indexes of current
    // Node inclusively
    // only for first ocurrence
    ll start, end;

    // stores length of substring
    ll length;

    // stores insertion Node for all characters a-z
    ll insertEdg[26];

    // stores the Maximum Palindromic Suffix Node for
    // the current Node
    ll suffixEdg;

```

```

    ll depht;
};

// two special dummy Nodes as explained above
Node root1, root2;

// stores Node information for constant time access
Node tree[MAXN];

// Keeps track the current Node while insertion
ll currNode;
string s;
ll ptr;

void insert(ll idx)
{
    //STEP 1//

    /* search for Node X such that s[idx] X S[idx]
       is maximum palindrome ending at position idx
       iterate down the suffix link of currNode to
       find X */
    ll tmp = currNode;
    while (true)
    {
        ll curLength = tree[tmp].length;
        if (idx - curLength >= 1 and s[idx] == s[idx-curLength-1])
            break;
        tmp = tree[tmp].suffixEdg;
    }

    /* Now we have found X ....
       * X = string at Node tmp
       * Check : if s[idx] X s[idx] already exists or not*/
    if(tree[tmp].insertEdg[s[idx]-'a'] != 0)
    {
        // s[idx] X s[idx] already exists in the tree
        currNode = tree[tmp].insertEdg[s[idx]-'a'];
        return;
    }

    // creating new Node
    ptr++;

    // making new Node as child of X with

```

```

    // weight as s[idx]
    tree[tmp].insertEdg[s[idx]-'a'] = ptr;

    // calculating length of new Node
    tree[ptr].length = tree[tmp].length + 2;

    // updating end point for new Node
    tree[ptr].end = idx;

    // updating the start for new Node
    tree[ptr].start = idx - tree[ptr].length + 1;

//STEP 2//

    /* Setting the suffix edge for the newly created
       Node tree[ptr]. Finding some String Y such that
       s[idx] + Y + s[idx] is longest possible
       palindromic suffix for newly created Node.*/

    tmp = tree[tmp].suffixEdg;

    // making new Node as current Node
    currNode = ptr;
    if (tree[currNode].length == 1)
    {
        // if new palindrome's length is 1
        // making its suffix link to be null string
        tree[currNode].suffixEdg = 2;
        tree[currNode].depht = 1;
        return;
    }
    while (true)
    {
        ll curLength = tree[tmp].length;
        if (idx-curLength >= 1 and s[idx] == s[idx-curLength-1])
            break;
        tmp = tree[tmp].suffixEdg;
    }

    // Now we have found string Y
    // linking current Nodes suffix link with s[idx]+Y+s[idx]
    tree[currNode].suffixEdg = tree[tmp].insertEdg[s[idx]-'a'];

```

```

    tree[currNode].depht = tree[tree[tmp].insertEdg[s[idx]-'a']].depht +
        1;
}
// para ir al revez currNode = 1, reverse(s)
// para un string nuevo, devolver currNode o currNode = 1

// driver program
int main()
{
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    // initializing the tree
    root1.length = -1;
    root1.suffixEdg = 1;
    root2.length = 0;
    root2.suffixEdg = 1;
    root1.depht = 0;
    root2.depht = 0;

    tree[1] = root1;
    tree[2] = root2;
    ptr = 2;
    currNode = 1;
    ll l;
    cin >> l;
    cin >> s;
    l = s.length();
    cout<<l<<endl;
    vl sums(l+1, 0);
    ll ans = 0;

    for (ll i=0; i<l; i++){
        insert(i);
        ll nod = currNode, depht = 0;
        while(tree[nod].length > 0)
        {
            nod = tree[nod].suffixEdg;
            depht++;
        }
        nod = currNode;
        sums[i+1]=(depht + sums[i])%M;
        depht--;
        while(tree[nod].length > 1)
        {

```

```

            ans += (depht + sums[i] - sums[i - tree[nod].length + 1])%M;
            ans %= M;

            nod = tree[nod].suffixEdg;
            depht--;
        }
    }
    cout<<ans<<"\n";

    // printing all of its distinct palindromic
    // substring
    cout << "All distinct palindromic substring for "
        << s << " : \n";
    for (int i=3; i<=ptr; i++)
    {
        cout << i-2 << " ) ";
        for (int j=tree[i].start; j<=tree[i].end; j++)
            cout << s[j];
        cout << endl;
    }

    cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC << "ms\n";
    return 0;
}

```

7.7 SuffixArray

```

// =====
// Suffix Array Construction : Prefix Doubling + Radix Sort
// =====
// Complexity: O(N*log(N))
// references:
//   https://www.cs.helsinki.fi/u/tpkarkka/opetus/10s/spa/lecture11.pdf
//   https://youtu.be/_TUeAdu-U_k
#include "../Header.cpp"
#define invrep(i,b,a) for(int i = b; i >= a; --i)

struct SA {
    int n; vl counts, rank, rank_, sa, sa_, lcp; // lcp is optional
    inline int gr(int i) { return i < n ? rank[i]: 0; }

```

```

void csort(int maxv, int k) {
    counts.assign(maxv+1, 0);
    repx(i,0,n) counts[gr(i+k)]++;
    repx(i,1,maxv+1) counts[i] += counts[i-1];
    invrep(i,n-1,0) sa[--counts[gr(sa[i]+k)]] = sa[i];
    sa.swap(sa_);
}

void get_sa(vl& s) {
    repx(i,0,n) sa[i] = i;
    sort(sa.begin(), sa.end(), [&s](int i, int j) { return s[i] < s[j]; });
    int r = rank[sa[0]] = 1;
    repx(i,1,n) rank[sa[i]] = (s[sa[i]] != s[sa[i-1]]) ? ++r : r;
    for (int h=1; h < n and r < n; h <= 1) {
        csort(r, h); csort(r, 0); r = rank[sa[0]] = 1;
        repx(i,1,n) {
            if (rank[sa[i]] != rank[sa[i-1]] or
                gr(sa[i]+h) != gr(sa[i-1]+h)) ++r;
            rank[sa[i]] = r;
        } rank.swap(rank_);
    }
}

// LCP construction in O(N) using Kasai's algorithm
// reference: https://codeforces.com/blog/entry/12796?#comment-175287
void get_lcp(vl& s) { // lcp is optional
    lcp.assign(n, 0); int k = 0;
    repx(i,0,n) {
        int r = rank[i]-1;
        if (r == n-1) { k = 0; continue; }
        int j = sa[r+1];
        while (i+k < n and j+k < n and s[i+k] == s[j+k]) k++;
        lcp[r] = k;
        if (k) k--;
    }
}

SA(vl& s) {
    n = s.size();
    rank.resize(n); rank_.resize(n);
    sa.resize(n); sa_.resize(n);
    get_sa(s); get_lcp(s); // lcp is optional
}

};

int main() { // how to use
    string test; cin >> test;

```

```

    vl s;
    for (char c : test) s.push_back(c);
    SA sa(s);
    for (int i : sa.sa) cout << i << ":\t" << test.substr(i) << '\n';
    repx(i,0,s.size()) {
        printf("LCP between %d and %d is %d\n", i, i+1, sa.lcp[i]);
    }
}

```

7.8 Trie

```

#include "../Header.cpp"

struct Trie
{
    static const int MAX = 1e6;
    int N[MAX][26] = {0}, S[MAX] = {0}, c = 0;
    void add(string s, int a = 1)
    {
        int p = 0; S[p] += a;
        for (char l : s)
        {
            int t = l - 'a';
            if (!N[p][t]) N[p][t] = ++c;
            S[p = N[p][t]] += a;
        }
    }
};

struct TrieXOR
{
    static const int MAX = 1e6;
    int N[MAX][2] = {0}, S[MAX] = {0}, c = 0;
    void add(int x, int a = 1)
    {
        int p = 0; S[p] += a;
        rep(i, 31)
        {
            int t = (x >> (30 - i)) & 1;
            if (!N[p][t]) N[p][t] = ++c;
            S[p = N[p][t]] += a;
        }
    }
}

```

```

int get(int x)
{
    if (!S[0]) return -1;
    int p = 0; rep(i, 31)
    {
        int t = ((x >> (30 - i)) & 1) ^ 1;
        if (!N[p][t] || !S[N[p][t]]) t ^= 1;
        p = N[p][t]; if (t) x ^= (1 << (30 - i));
    }
    return x;
}

};

struct Trie {
    vector<vector<int>>> g;
    vector<int> count;
    int vocab;
    Trie(int vocab, int maxdepth = 10000) : vocab(vocab) {
        g.reserve(maxdepth);
        g.emplace_back(vocab, -1);
        count.reserve(maxdepth);
        count.push_back(0);
    }
    int move_to(int u, int c) {
        assert (0 <= c and c < vocab);
        int& v = g[u][c];
        if (v == -1) {
            v = g.size();
            g.emplace_back(vocab, -1);
            count.push_back(0);
        }
        count[v]++;
        return v;
    }
    void insert(const string& s, char ref = 'a') { // insert string
        int u = 0; for (char c : s) u = move_to(u, c - ref);
    }
    void insert(vector<int>& s) { // insert vector<int>
        int u = 0; for (int c : s) u = move_to(u, c);
    }
    db query(const string& s, char ref = 'a')
    {
        int u = 0;
        db cost = 0;
        for (char c : s){

```

```

            ll co = 0;
            for(auto it : g[u]) if(it != -1)co++;

            ll nex = move_to(u, c - ref);
            if(u == 0 || co > 1 || count[u] != count[nex]) cost++;
            u = nex;

        }
        return cost;
    }
    ll dfs(int u, int depht)
    {
        ll ans = INF;
        if(count1[u] == 1 && count2[u] == 1)ans = depht;
        for(int i = 0; i < 26; i++)
        {
            if(g[u][i] != -1) ans = min(ans, dfs(g[u][i], depht + 1));
        }
        return ans;
    }
    int size() { return g.size(); }
};

int main()
{
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    ll n;
    while(cin >> n){
        string s;
        vector<string > c;
        Trie trie(26);
        for(int i = 0; i < n; i++)
        {
            cin >> s;
            c.push_back(s);
            trie.insert(s);
        }
        db sum = 0;
        for(int i = 0; i < n; i++)
        {
            sum += trie.query(c[i]);
        }
    }
}

```

```

        cout<<fixed<<setprecision(2)<< sum / db(n) << "\n";
    }
}

```

8 Structures

8.1 BinarySearch-Ternary

```

#include "../Header.cpp"

// limit
log(valor maximo/precision)/log(2)
    /log(3/2) //para ternaria

ll l = 0, r = n-1, res = -1;
while(l <= r)
{
    ll p = (l + r) / 2;
    if(c[p] <= m) l = p+1;
    else r = p-1;
}

db l = 0, r = PI/2, mini = 1e10;

rep(i, 101)
{
    db d=(r-l)/3.0,m1=l+d,m2=r-d;
    db c1 = value(m1), c2 = value(m2);
    // Para el maximo cambiar r-m2 con l-m1
    if (c1 < c2) r = m2;
    else l = m1;
    mini = min(mini, (c1+c2)/2.0);
}

// non continuous
ll l = 1, r = m, mini = 1e17;
while(l <= r)
{
    ll d = (r-l)/3;

```

```

    ll m1 = l+d, m2 = r-d;
    ll c1 = value(m1), c2 = value(m2);
    // Para el maximo cambiar r-m2 con l-m1
    if (c1 < c2) r = m2-1;
    else l = m1+1;
    mini = min(mini, min(c1,c2));
}
ans += mini;

```

8.2 CDQDivideConquer

```

#include "../Header.cpp"
struct BIT {
    vl bit;
    BIT(ll n) { bit.assign(n+1, 0); }

    ll psq(ll k) {
        ll sum = 0;
        for (; k; k -= (k & -k)) sum += bit[k];
        return sum;
    }
    ll rsq(ll a, ll b) {
        return psq(b) - psq(a-1);
    }

    void add(ll k, ll v) {
        for (; k < bit.size(); k += (k & -k)) bit[k] += v;
    }
};

struct Node {
    ll x, y, z, col = 0, pos;
};
bool sy(Node a, Node b)
{
    return (a.y <= b.y);
}
bool sz(Node a, Node b)
{
    return (a.z >= b.z);
}

// count number of pairs (x_i, y_i, z_i) <= (x_j, y_j, z_j)
//cdq_div_conquer: influence from L to R

```

```

// if there are equal tuples, ans += duplicates * (duplicates - 1) / 2 -
duplicates
ll cdq_div_conq(ll n, ll l, ll r, vector<Node>& c, vector<Node>& aux)
{
    if(l == r)
    {
        aux.pb(c[l]);
        return 0;
    }
    vector<Node> L, R, Z_ord;
    ll ans = cdq_div_conq(2*n, l, (l+r)/2, c, L) +
        cdq_div_conq(2*n+1, (l+r)/2+1, r, c, R);

    rep(i, R.size()) R[i].col = 1;

    aux.resize(r - l + 1);
    merge(ALL(L), ALL(R), aux.begin(), sy); //merge sort by y

    rep(i, aux.size()) //sort inverse by z and save pos in aux vector
    {
        aux[i].pos = i;
        Z_ord.pb(aux[i]);
    }

    sort(ALL(Z_ord), sz);
    BIT bit(r - l + 1);
    for(auto it : Z_ord)
    {
        if(it.col == 1) //update
            bit.add(it.pos+1, 1);
        else if(it.col == 0 && it.pos != r - l){ // count 1s with
            z >= it.z in y >= it.y range
            ans += bit.rsq(it.pos + 2, r - l + 1);
        }
    }
    rep(i, aux.size()) aux[i].col = 0;
    return ans;
}

int main(){
    ll n;
    cin >> n;
    vector<Node> c, aux;
    Node t;

```

```

rep(i, n)
{
    cin >> t.x >> t.y >> t.z;
    c.pb(t);
}
cout << cdq_div_conq(n, 0, n-1, c, aux) << endl;
}

```

8.3 DinamicConnectivity

```

#include "../Header.cpp"
#include "UnionFind.cpp"

// M log M (log M from UF)
struct DinC
{
    vector<vp> DC;
    ll T; UF uf;
    DinC(ll times, ll n)
    {
        T = times;
        DC.assign(4*T, vp());
        uf = UF(n);
    }
    void qry()
    {
        qry(1, 0, T-1);
    }
    void qry(ll n, ll l, ll r)
    {
        for(auto it : DC[n]) uf.join(it.first, it.second);

        if(l == r) // process time l
        {
            for(auto it : ord[l])
            {
                ll x1 = uf.find(it.first);
                ll x2 = uf.find(it.second);
                ans += uf.sz[x1] * uf.sz[x2];
            }
        }
    }
}

```



```

    }
    else{
        qry(2*n,l,(l+r)/2);
        qry(2*n+1,(l+r)/2+1,r);
    }

    for(auto it : DC[n]) uf.rollback();
}
void upd(ll i,ll j, pll v)
{
    return upd(1, 0, T-1, i, j, v);
}
void upd(ll n, ll l, ll r, ll i, ll j, pll v)
{
    if(r < i || j < l) return;
    if(i <= l && r <= j)
    {
        DC[n].pb(v);
        return;
    }

    upd(2*n,l,(l+r)/2,i,j,v);
    upd(2*n+1,(l+r)/2+1,r,i,j,v);
}
};

```

8.4 DisjointIntervals

```

// stores disjoint intervals as [first, second)
struct disjoint_intervals {
    set<pair<int,int> > s;
    void insert(pair<int,int> v){
        if(v.fst>=v.snd) return;
        auto at=s.lower_bound(v);auto it=at;
        if(at!=s.begin()&&(--at)->snd>=v.fst)v.fst=at->fst,--it;
        for(;it!=s.end()&&it->fst<=v.snd;s.erase(it++))
            v.snd=max(v.snd,it->snd);
        segs.insert(v);
    }
};

```

8.5 FenwickTree

```

#include "../Header.cpp"

struct BIT {

    /*****All Index starts at 1*****/

    vl bit;
    BIT(ll n) { bit.assign(n+1, 0); }

    ll psq(ll k) {
        ll sum = 0;
        for (; k; k -= (k & -k)) sum += bit[k];
        return sum;
    }

    ll rsq(ll a, ll b) {
        return psq(b) - psq(a-1);
    }

    // increment k'th value by v (and propagate)
    void add(ll k, ll v) {
        for (; k < bit.size(); k += (k & -k)) bit[k] += v;
    }
    void set(ll k, ll v)
    {
        ll aux = rsq(k,k);
        for (; k < bit.size(); k += (k & -k)) bit[k] += v-aux;
        //bit[idx] = min(bit[idx], val);
    }

    // (1, r)
    ll getmin(ll r) {
        ll ret = INF;
        for (; r >= 0; r = (r & (r + 1)) - 1)
            ret = min(ret, bit[r]);
        return ret;
    }
};

```

8.6 FenwickTree2D

```
#include "../Header.cpp"

struct BIT2D { // BIT = binary indexed tree (a.k.a. Fenwick Tree)

    // *****All Index starts at 1*****

    vector<vector<int>> > bit;
    BIT2D(int n,int m) { bit.assign(n+1, vector<int>(m+1,0)); }
    // prefix sum query (sum in range 1 .. k)
    int psq(int k, int y) {
        int sum = 0;
        for (; k; k -= (k & -k)) for (int ty=y; ty; ty -= (ty & -ty)) sum
            += bit[k][ty];
        return sum;
    }
    // range sum query (sum in range a .. b)
    int rsq(int x1, int y1, int x2, int y2) {
        return psq(x2,y2) - psq(x1-1,y2) - psq(x2,y1-1) + psq(x1-1,y1-1);
    }
    // increment k'th value by v (and propagate)
    void add(int k, int y, int v) {
        for (; k < bit.size(); k += (k & -k)) for (int ty=y; ty <
            bit[k].size(); ty += (ty & -ty)) bit[k][ty] += v;
    }
    void set(int k, int y, int v)
    {
        int aux=rsq(k,y,k,y);
        for (; k < bit.size(); k += (k & -k)) for (int ty=y; ty <
            bit[k].size(); ty += (ty & -ty)) bit[k][ty] += v-aux;
    }
};

int main()
{
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    int t;
    cin>>t;
    while(t-->0)
    {
        int n;
        cin>>n;
```

```
        BIT2D ft2d(n+1,n+1);

        string s;
        while(cin>>s)
        {
            int x,y,v,x2,y2;
            if(s=="END")break;
            if(s=="SET")
            {
                cin>>x>>y>>v;
                ft2d.set(x+1,y+1,v);
            }
            else
            {
                cin>>x>>y>>x2>>y2;
                cout<<ft2d.rsq(x+1,y+1,x2+1,y2+1)<<"\n";
            }
        }
    }
}
```

8.7 Mo

```
#include "../Header.cpp"

/*
a ancestor of b

[start[a], start[b]]

else

[end[a], start[b]] + lca(a, b)

*/

ll block;
vl ans;
vl el(1e6+2, 0);
// F = add-remove
// O((N+Q) FN )
struct Query
```

```

{
    int L, R, id;
};
bool cmp(Query a, Query b){
    if(a.L / block != b.L / block)
        return a.L < b.L;
    return a.L / block % 2 ? a.R < b.R : a.R > b.R;
}
ll add(vl& a, int id)
{
    //cout<<id<<endl;
    return (2 * el[a[id]] + 1) * a[id];
}
ll remove(vl& a, int id)
{
    return (-2 * el[a[id]] + 1) * a[id];
}
void Mo(vl& a, vector<Query>& q)
{
    block = (int)sqrt(a.size());
    ans.assign(q.size(), 0);

    sort(ALL(q), cmp);

    ll cL = 0, cR = 0, cAns = 0;

    for (int i=0; i<q.size(); i++)
    {
        // L and R values of current range
        int L = q[i].L, R = q[i].R;

        while (cR <= R) {
            cAns += add(a, cR);
            el[a[cR]]++;
            cR++;
        }
        while (cL > L) {
            cAns += add(a, cL-1);
            el[a[cL-1]]++;
            cL--;
        }
        while (cR > R+1) {
            cAns += remove(a, cR-1);
            el[a[cR-1]]--;
        }
    }
}

```

```

        cR--;
    }
    while (cL < L) {
        cAns += remove(a, cL);
        el[a[cL]]--;
        cL++;
    }

    ans[q[i].id] = cAns;
}
}

int main()
{
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    int n, t, x, y;
    vl c;
    cin >> n >> t;
    for(int i = 0; i < n; i++)
    {
        cin >> x;
        c.push_back(x);
    }
    Query q;
    vector<Query>Q;
    for(int i = 0; i < t; i++)
    {
        cin >> q.L >> q.R;
        q.L--; q.R--;
        q.id = i;
        Q.push_back(q);
    }
    Mo(c, Q);
    for(int i = 0; i < ans.size(); i++)
    {
        cout << ans[i] << "\n";
    }
    return 0;
}

```

8.8 Partially *persistent*_D *SU*

```

struct PPDSU {
    vector<vector<pair<int, int>>> par;
    int time = 0; //initial time
    PPDSU(int n) : par(n + 1, {{-1, 0}}) {}
    bool merge(int u, int v) {
        ++time;
        if ((u = root(u, time)) == (v = root(v, time))) return 0;
        if (par[u].back().first > par[v].back().first) swap(u, v);
        par[u].push_back({par[u].back().first + par[v].back().first, time});
        par[v].push_back({u, time}); //par[v] = u
        return 1;
    }
    bool same(int u, int v, int t) {
        return root(u, t) == root(v, t);
    }
    int root(int u, int t) { //root of u at time t
        if (par[u].back().first >= 0 && par[u].back().second <= t) return
            root(par[u].back().first, t);
        return u;
    }
    int size(int u, int t) { //size of the component of u at time t
        u = root(u, t);
        int l = 0, r = (int) par[u].size() - 1, ans = 0;
        while (l <= r) {
            int mid = l + r >> 1;
            if (par[u][mid].second <= t) ans = mid, l = mid + 1;
            else r = mid - 1;
        }
        return -par[u][ans].first;
    }
};

```

8.9 PolicyBasedEDD

```

#include "../Header.cpp"

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;

```

```

// use less_equal for multiset

```

```

template <typename T, typename Comparator = less<T>>
using ordered_set = tree<T, null_type, Comparator, rb_tree_tag,
                        tree_order_statistics_node_update>;

// order_of_key(T x)
// -> returns the number of elements strictly smaller than x

// find_by_order(size_t i)
// -> returns iterator to i-th largest element (counting from 0)

int main()
{
    ios::sync_with_stdio(0);
    cin.tie(0);

    int t;
    cin >> t;
    while(t--)
    {
        int n, k, x, y;
        ordered_set<int> m;
        vector<pll> c;
        cin >> n >> k;
        for(int i = 0; i < n; i++)
        {
            cin >> x >> y;
            c.push_back({x, y});
        }
        sort(ALL(c));
        ll ans = 0;
        for(int i = 0; i < n; i++)
        {
            ll num = m.order_of_key(c[i].second + 1);
            if(abs(num - (n-1 - num)) >= k) ans++;
            m.insert(c[i].second);
        }
        cout<<ans<<"\n";
    }

    return 0;
}

```

8.10 SegmentTree

```
#include "../Header.cpp"
struct SegmentTree
{
    vl ST; int N;
    SegmentTree(vl &A)
    {
        N = A.size();
        ST.assign(4*N, 0);
        bd(1,0,N-1,A);
    }
    ll op(ll x, ll y) { return min(x,y); }
    void bd(int n, int l, int r, vl &A)
    {
        if(l == r)
        {
            ST[n] = A[r];
            return;
        }
        bd(2*n,l,(l+r)/2,A);
        bd(2*n+1,(l+r)/2+1,r,A);
        ST[n] = op(ST[2*n], ST[2*n+1]);
    }
    ll qry(int i, int j)
    {
        return qry(1,0,N-1,i,j);
    }
    ll qry(int n, int l, int r, int i, ll j)
    {
        if(r < i || j < l) return 0;
        if(i <= l && r <= j) return ST[n];

        return op(qry(2*n,l,(l+r)/2,i,j),
            qry(2*n+1,(l+r)/2+1,r,i,j));
    }
    void upd(int i, ll v)
    {
        return upd(1,0,N-1,i,v);
    }
    void upd(int n, int l, int r, int i, ll v)
    {
        if(i < l || r < i) return;
        if(l == r)
        {
            ST[n] = v;
            return;
        }
        upd(2*n,l,(l+r)/2,i,v);
        upd(2*n+1,(l+r)/2+1,r,i,v);
        ST[n] = op(ST[2*n], ST[2*n+1]);
    }
};
```

```
        ST[n] = v;
        return;
    }

    upd(2*n,l,(l+r)/2,i,v);
    upd(2*n+1,(l+r)/2+1,r,i,v);
    ST[n] = op(ST[2*n], ST[2*n+1]);
}

};
```

8.11 SegmentTree2D

```
#include "../Header.cpp"

struct SegmentTree{

    vector<ll>ST;
    int N;
    SegmentTree(int Size)
    {
        N = Size;

        ST.assign(4*N,0);
    }
    void upd(int i, ll v)
    {
        return upd(1,0,N-1,i,v);
    }
    void upd(int n, int l, int r, int i, ll v)
    {
        if(i < l || r < i) return;

        if(l == r)
        {
            ST[n] += v;
            return;
        }

        upd(2*n,l,(l+r)/2,i,v);
        upd(2*n+1,(l+r)/2+1,r,i,v);

        ST[n] = ST[2*n]+ST[2*n+1];
    }
};
```

```

11 qry(int i,int j)
{
    return qry(1,0,N-1,i,j);
}
11 qry(int n, int l, int r, int i, int j)
{
    if(r < i || j < l)
        return 0;

    if(i <= l && r <= j)
        return ST[n];

    return query(2*n,l,(l+r)/2,i,j)+query(2*n+1,(l+r)/2+1,r,i,j);
}
};
struct SegmenTree2D
{
    vector<SegmentTree>ST;
    int N;
    SegmenTree2D(int Size)
    {
        N = Size;
        ST.resize(4*N,Size);
    }

    void update(int i, int j, int v)
    {
        return update(1,0,N-1,i,j,v);
    }
    void update(int n, int l, int r, int i, int j, ll v)
    {
        if(i < l || r < i) return;

        if(l == r)
        {
            ST[n].update(j,v);
            return;
        }

        update(2*n,l,(l+r)/2,i,j,v);
        update(2*n+1,(l+r)/2+1,r,i,j,v);

        ST[n].update(j,v);
    }
    11 query(int i1, int i2, int j1, int j2)

```

```

{
    return query(1,0,N-1,i1,i2,j1,j2);
}
11 query(int n, int l, int r, int i1, int i2, int j1, int j2)
{
    if(l > j1 || i1 > r)
        return 0;
    if(i1 <= l && r <= j1)
    {
        return ST[n].query(i2,j2);
    }
    return
        query(2*n,l,(l+r)/2,i1,i2,j1,j2)+query(2*n+1,(l+r)/2+1,r,i1,i2,j1,j2);
}
};
int main()
{
    11 q, n, x, y, l, b, r, t, a;
    SegmenTree2D ST(1025);
    while(cin >> q)
    {
        if(q == 0)
        {
            cin >> n;
        }
        else if(q == 1)
        {
            cin >> x >> y >> a;
            ST.update(x, y, a);
        }
        else if(q == 2)
        {
            cin >> l >> b >> r >> t;
            cout << ST.query(l, b, r, t) << "\n";
        }
        else
            break;
        /*for(int i=0;i<n;i++)
        {
            for(int j=0;j<n;j++)
            {
                cout<<ST.query(i,j,i,j)<<" ";
            }cout<<endl;
        }*/
    }
}

```

```

    return 0;
}

```

8.12 SegmentTreeBeats

```
#include "../Header.cpp"
```

```

struct Node
{
    ll mn, mn2, cmn, mx, mx2, cmx;
    ll Amx, Bmx, Amn, Bmn;
    ll sum;
    Node()
    {
        mn = mn2 = LLONG_MAX;
        mx = mx2 = LLONG_MIN;
        sum = cmn = cmx = 0;
        Bmx = LLONG_MIN;
        Bmn = LLONG_MAX;
        Amx = Amn = 0;
    }
    Node merge(Node r)
    {
        Node p;
        p.sum = sum + r.sum;
        if(r.mn < mn)
        {
            p.mn2 = min(mn, r.mn2);
            p.mn = r.mn;
            p.cmn = r.cmn;
        }
        else if(r.mn == mn)
        {
            p.cmn = cmn + r.cmn;
            p.mn = mn;
            p.mn2 = min(p.mn2, r.mn2);
        }
        else if(mn < r.mn)
        {
            p.mn2 = min(mn2, r.mn);
            p.mn = mn;
            p.cmn = cmn;
        }
    }
}

```

```

    }

    if(r.mx > mx)
    {
        p.mx2 = max(mx, r.mx2);
        p.mx = r.mx;
        p.cmx = r.cmx;
    }
    else if(r.mx == mx)
    {
        p.cmx = cmx + r.cmx;
        p.mx = mx;
        p.mx2 = max(p.mx2, r.mx2);
    }
    else if(mx > r.mx)
    {
        p.mx2 = max(mx2, r.mx);
        p.mx = mx;
        p.cmx = cmx;
    }

    return p;
}

void upd(ll v)
{
    cmn = cmx = 1;
    mn = mx = v;
    sum = v;
}

};

struct SegmentTree
{
    vector<Node> ST;
    ll N;
    vl Lazy, Lazymx, Lazymn, LazySet;
    SegmentTree(vl &A)
    {
        N = A.size();
        ST.assign(4*N, Node());
        Lazy.resize(4*N+5, 0);
        Lazymx.resize(4*N+5, LLONG_MIN);
        Lazymn.resize(4*N+5, LLONG_MAX);
    }
}

```

```

        LazySet.resize(4*N+5, LLONG_MIN);
        bd(1,0,N-1,A);
    }
    void bd(ll n, ll l, ll r, vl &A)
    {
        if(l == r)
        {
            ST[n].upd(A[l]);
            //cout << "n " << n << " " << ST[n].mn << " " <<
                ST[n].mn2 << " " << ST[n].sum << " " <<
                ST[n].cmn << "\n";
            return;
        }

        bd(2*n,l,(l+r)/2,A);
        bd(2*n+1,(l+r)/2+1,r,A);

        ST[n] = ST[2*n].merge(ST[2*n+1]);

        //cout << "n " << n << " " << ST[n].mn << " " <<
            ST[n].mn2 << " " << ST[n].sum << " " << ST[n].cmn <<
            "\n";
    }
    void up(ll n, ll l, ll r)
    {
        //set
        if(LazySet[n] != LLONG_MIN)
        {
            ST[n].mn = LazySet[n];
            ST[n].mn2 = LLONG_MAX;
            ST[n].sum = (r-l+1)*LazySet[n];
            ST[n].cmn = r-l+1;
        }
        ST[n].mx2 = LLONG_MIN;
        ST[n].mx = LazySet[n];
        ST[n].cmx = r-l+1;

        //cout << "nlazy " << n << "--" << r << " "
            << ST[n].mn << " " << ST[n].mn2 << " "
            << ST[n].sum << " " << ST[n].cmn << "\n";
    }
    else{
        ST[n].sum += (r-l+1)*Lazy[n];
        ST[n].mn += Lazy[n];
    }
    ST[n].mx += Lazy[n];

```

```

//historical maximum/minimum
ST[n].Bmx += Lazy[n];
ST[n].Bmn += Lazy[n];
        if(ST[n].mn2 != LLONG_MAX)ST[n].mn2 +=
            Lazy[n];
        if(ST[n].mx2 != LLONG_MIN)ST[n].mx2 += Lazy[n];
    }

    // mx op
    ST[n].Amx = max(ST[n].Amx, Lazymx[n]);
    push_min(n, Lazymx[n]);

    // mn op
    ST[n].Amn = min(ST[n].Amn, Lazymn[n]);
    push_max(n, Lazymn[n]);

    //cout << l << "--" << r << " " << Lazy[n] << " "
        << Lazymx[n] << " " << ST[n].sum << endl;

    if(l != r)
    {
        Lazy[n*2] += Lazy[n];
        Lazy[n*2+1] += Lazy[n];

        Lazymx[n*2] = ST[n].mn;
        Lazymx[n*2+1] = ST[n].mn;

        Lazymn[n*2] = ST[n].mx;
        Lazymn[n*2+1] = ST[n].mx;
        if(LazySet[n] != LLONG_MIN)
        {
            LazySet[n*2] = LazySet[n];
            LazySet[n*2+1] = LazySet[n];
        }

        // historical maximum
        // max(Amx + x, Bmx)
        ST[n*2].Amx = ST[n].Amx + ST[n*2].Amx;
        ST[n*2].Bmx = max(ST[n*2].Bmx, ST[n].Bmx + ST[n*2].Amx);
        ST[n*2+1].Amx = ST[n].Amx + ST[n*2+1].Amx;
        ST[n*2+1].Bmx = max(ST[n*2+1].Bmx, ST[n].Bmx + ST[n*2+1].Amx);

        // historical minimum
        // min(Amn + x, Bmn)
        ST[n*2].Amn = ST[n].Amn + ST[n*2].Amn;
        ST[n*2].Bmn = min(ST[n*2].Bmn, ST[n].Bmn + ST[n*2].Amn);

```



```

    ST[n*2+1].Amn = ST[n].Amn + ST[n*2+1].Amn;
    ST[n*2+1].Bmn = min(ST[n*2+1].Bmn, ST[n].Bmn + ST[n*2+1].Amn);

    }
    Lazy[n] = 0;
    Lazymx[n] = LLONG_MIN;
    Lazymn[n] = LLONG_MAX;
    LazySet[n] = LLONG_MIN;
}

// op max
void push_min(ll n, ll v){
    if(v <= ST[n].mn) return;
    ST[n].sum += (v-ST[n].mn)*ST[n].cmn;
    ST[n].mn = v;
}

// op min
void push_max(ll n, ll v){
    if(v >= ST[n].mx) return;
    ST[n].sum += (v-ST[n].mx)*ST[n].cmx;
    ST[n].mx = v;
}

// max(a[i], v)
void updmx(ll n, ll l, ll r, ll i, ll j, ll v)
{
    up(n,l,r);
    if(l > j || r < i || v <= ST[n].mn) return;
    if(i <= l && r <= j && v < ST[n].mn2)
    {
        push_min(n,v);
        up(n,l,r);
        return;
    }
    updmx(2*n,l,(l+r)/2,i,j,v);
    updmx(2*n+1,(l+r)/2+1,r,i,j,v);

    ST[n] = ST[2*n].merge(ST[2*n+1]);
}

// min(a[i], v)
void updmn(ll n, ll l, ll r, ll i, ll j, ll v)
{
    up(n,l,r);
    if(l > j || r < i || v >= ST[n].mx) return;
    if(i <= l && r <= j && v > ST[n].mx2)
    {
        push_max(n,v);

```

```

    up(n,l,r);
    return;
}
updmn(2*n,l,(l+r)/2,i,j,v);
updmn(2*n+1,(l+r)/2+1,r,i,j,v);

ST[n] = ST[2*n].merge(ST[2*n+1]);
}

Node qry(ll n, ll l, ll r, ll i, ll j)
{
    if(r < i || j < l)
    {
        Node p;
        return p;
    }
    up(n,l,r);

    if(i <= l && r <= j) {
        //cout << l << " " << r << " " << ST[n].sum << "\n";
        return ST[n];
    }
    return
        qry(2*n,l,(l+r)/2,i,j).merge(qry(2*n+1,(l+r)/2+1,r,i,j));
}

void upd_add(ll n, ll l, ll r, ll i, ll j, ll v)
{
    up(n,l,r);
    if(l > j || r < i) return;

    if(i <= l && r <= j)
    {
        //cout << l << " " << r << " " << ST[n].sum << "\n";
        Lazy[n] += v;
        up(n, l, r);
        return;
    }
    upd_add(2*n,l,(l+r)/2,i,j,v);
    upd_add(2*n+1,(l+r)/2+1,r,i,j,v);

    ST[n] = ST[2*n].merge(ST[2*n+1]);
}

void upd_set(ll n, ll l, ll r, ll i, ll j, ll v)
{
    up(n,l,r);

```

```

    if(l > j || r < i) return;

    if(i <= l && r <= j)
    {
        //cout << l << " " << r << " "<<ST[n].sum << "\n";
        LazySet[n] = v;
        up(n, l, r);
        return;
    }
    upd_set(2*n,l,(l+r)/2,i,j,v);
    upd_set(2*n+1,(l+r)/2+1,r,i,j,v);

    ST[n] = ST[2*n].merge(ST[2*n+1]);
}
Node qry(ll i, ll j){return qry(1,0,N-1,i,j);}
void updmx(ll i, ll j, ll v){return updmx(1,0,N-1,i,j,v);}
void updmn(ll i, ll j, ll v){return updmn(1,0,N-1,i,j,v);}
void upd_add(ll i, ll j, ll v){return upd_add(1,0,N-1,i,j,v);}
void upd_set(ll i, ll j, ll v){return upd_set(1,0,N-1,i,j,v);}
};

int main(){

    ios_base::sync_with_stdio(0);
    cin.tie(0);
    srand((unsigned int) time(0));

    vl c = {0, 0, 0, 0, 0, 0};
    SegmentTree ST(c);
    rep(i, c.size()){
        cout << ST.qry(i, i).sum << " ";
    }
    cout << endl;

    ST.upd_add(2, 3, 2);
    cout << ST.qry(2, 3).sum << endl;
    rep(i, c.size()){
        cout << ST.qry(i, i).sum << " ";
    }
    cout << endl;

    ST.updmx(0, 3, 3);
    cout << ST.qry(0, 3).sum << endl;

```

```

    rep(i, c.size()){
        cout << ST.qry(i, i).sum << " ";
    }
    cout << endl;

    ST.updmx(3, 5, 1);
    cout << ST.qry(3, 5).sum << endl;
    rep(i, c.size()){
        cout << ST.qry(i, i).sum << " ";
    }
    cout << endl;

    ST.upd_add(0, 5, -3);
    cout << ST.qry(0, 5).sum << endl;
    rep(i, c.size()){
        cout << ST.qry(i, i).sum << " ";
    }
    cout << endl;

    ST.upd_set(0, 5, -2);
    cout << ST.qry(0, 5).sum << endl;
    rep(i, c.size()){
        cout << ST.qry(i, i).sum << " ";
    }cout << endl;

    ST.upd_set(3, 3, 33);
    cout << ST.qry(0, 5).sum << endl;
    rep(i, c.size()){
        cout << ST.qry(i, i).sum << " ";
    }cout << endl;

    cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC <<
        "ms\n";
    return 0;
}

```

8.13 SegmentTreeBeats2

```

#include "../Header.cpp"

struct Node
{
    ll mn, mn2, cmn, mx, mx2, cmx;
    ll sum;
    Node()
    {
        mn = mn2 = LLONG_MAX;
        mx = mx2 = LLONG_MIN;
        sum = cmn = cmx = 0;
    }
    Node merge(Node r)
    {
        Node p;
        p.sum = sum + r.sum;
        if(r.mn < mn)
        {
            p.mn2 = min(mn, r.mn2);
            p.mn = r.mn;
            p.cmn = r.cmn;
        }
        else if(r.mn == mn)
        {
            p.cmn = cmn + r.cmn;
            p.mn = mn;
            p.mn2 = min(p.mn2, r.mn2);
        }
        else if(mn < r.mn)
        {
            p.mn2 = min(mn2, r.mn);
            p.mn = mn;
            p.cmn = cmn;
        }

        if(r.mx > mx)
        {
            p.mx2 = max(mx, r.mx2);
            p.mx = r.mx;
            p.cmx = r.cmx;
        }
        else if(r.mx == mx)
        {
            p.cmx = cmx + r.cmx;

```

```

            p.mx = mx;
            p.mx2 = max(p.mx2, r.mx2);
        }
        else if(mx > r.mx)
        {
            p.mx2 = max(mx2, r.mx);
            p.mx = mx;
            p.cmx = cmx;
        }

        return p;
    }
    void upd(ll v)
    {
        cmn = cmx = 1;
        mn = mx = v;
        sum = v;
    }
};

struct SegmentTree
{
    vector<Node> ST;
    ll N;
    vl Lazy, Lazymx, Lazymn, LazySet;
    SegmentTree(vl &A)
    {
        N = A.size();
        ST.assign(4*N, Node());
        Lazy.resize(4*N+5, 0);
        Lazymx.resize(4*N+5, LLONG_MIN);
        Lazymn.resize(4*N+5, LLONG_MAX);
        LazySet.resize(4*N+5, LLONG_MIN);
        bd(1,0,N-1,A);
    }
    void bd(ll n, ll l, ll r, vl &A)
    {
        if(l == r)
        {
            ST[n].upd(A[l]);
            //cout << "n " << n << " " << ST[n].mn << " " <<
            ST[n].mn2 << " " << ST[n].sum << " " <<
            ST[n].cmn << "\n";
            return;

```

```

}

bd(2*n,1,(1+r)/2,A);
bd(2*n+1,(1+r)/2+1,r,A);

ST[n] = ST[2*n].merge(ST[2*n+1]);

//cout << "n " << l << " "<<r << " " << ST[n].mn << " " <<
ST[n].mn2 << " " << ST[n].sum << " " << ST[n].cmn <<
"\n";
}
void up(ll n, ll l, ll r)
{
    //set
    if(LazySet[n] != LLONG_MIN)
    {
        ST[n].mn = LazySet[n];
        ST[n].mn2 = LLONG_MAX;
        ST[n].sum = (r-l+1)*LazySet[n];
        ST[n].cmn = r-l+1;
    }
    ST[n].mx2 = LLONG_MIN;
    ST[n].mx = LazySet[n];
    ST[n].cmx = r-l+1;

    //cout << "nlazy " << l << "--" << r << " "
    << ST[n].mn << " " << ST[n].mn2 << " "
    << ST[n].sum << " " << ST[n].cmn << "\n";
}
else{
    ST[n].sum += (r-l+1)*Lazy[n];
    ST[n].mn += Lazy[n];
    ST[n].mx += Lazy[n];

    if(ST[n].mn2 != LLONG_MAX)ST[n].mn2 +=
        Lazy[n];
    if(ST[n].mx2 != LLONG_MIN)ST[n].mx2 += Lazy[n];
}

// mx op
push_min(n, Lazymx[n], l == r);
// mn op
push_max(n, Lazymn[n], l == r);

//cout << l << "--" << r << " " << Lazy[n] << " "
<< Lazymx[n] << " " << ST[n].sum << endl;

```

```

        if(l != r)
        {
            Lazy[n*2] += Lazy[n];
            Lazy[n*2+1] += Lazy[n];

            Lazymx[n*2] = ST[n].mn;
            Lazymx[n*2+1] = ST[n].mn;

            Lazymn[n*2] = ST[n].mx;
            Lazymn[n*2+1] = ST[n].mx;
            if(LazySet[n] != LLONG_MIN)
            {
                LazySet[n*2] = LazySet[n];
                LazySet[n*2+1] = LazySet[n];
            }
        }
        Lazy[n] = 0;
        Lazymx[n] = LLONG_MIN;
        Lazymn[n] = LLONG_MAX;
        LazySet[n] = LLONG_MIN;
    }
}
// op max
void push_min(ll n, ll v, bool l){
    if(v <= ST[n].mn) return;
    ST[n].sum += (v-ST[n].mn)*ST[n].cmn;
    ST[n].mn = v;

    if (l) {
        ST[n].mx = ST[n].mn;
    }
    else if (v >= ST[n].mx) {
        ST[n].mx = v;
    } else if (v > ST[n].mx2) {
        ST[n].mx2 = v;
    }
}

// op min
void push_max(ll n, ll v, bool l){
    if(v >= ST[n].mx) return;
    ST[n].sum += (v-ST[n].mx)*ST[n].cmx;
    ST[n].mx = v;

    if (l) {

```

```

        ST[n].mn = ST[n].mx;
    }
    else if (v <= ST[n].mn) {
        ST[n].mn = v;
    } else if (v < ST[n].mn2) {
        ST[n].mn2 = v;
    }
}
// a[i]=max(a[i], v)
void updmx(ll n, ll l, ll r, ll i, ll j, ll v)
{
    up(n,l,r);
    if(l > j || r < i || v <= ST[n].mn) return;
    if(i <= l && r <= j && v < ST[n].mn2)
    {
        push_min(n,v,l==r);
        up(n,l,r);
        return;
    }
    updmx(2*n,l,(l+r)/2,i,j,v);
    updmx(2*n+1,(l+r)/2+1,r,i,j,v);

    ST[n] = ST[2*n].merge(ST[2*n+1]);
}
// a[i]=min(a[i], v)
void updmn(ll n, ll l, ll r, ll i, ll j, ll v)
{
    up(n,l,r);
    if(l > j || r < i || v >= ST[n].mx) return;
    if(i <= l && r <= j && v > ST[n].mx2)
    {
        push_max(n,v,l==r);
        up(n,l,r);
        return;
    }
    updmn(2*n,l,(l+r)/2,i,j,v);
    updmn(2*n+1,(l+r)/2+1,r,i,j,v);

    ST[n] = ST[2*n].merge(ST[2*n+1]);
}
Node qry(ll n, ll l, ll r, ll i, ll j)
{
    if(r < i || j < l)

```

```

{
    Node p;
    return p;
}
up(n,l,r);

if(i <= l && r <= j) {
    //cout << l << " "<<r<< "*" << ST[n].sum<<"\n";
    return ST[n];
}
return
    qry(2*n,l,(l+r)/2,i,j).merge(qry(2*n+1,(l+r)/2+1,r,i,j));
}
void upd_add(ll n, ll l, ll r, ll i, ll j, ll v)
{
    up(n,l,r);
    if(l > j || r < i) return;

    if(i <= l && r <= j)
    {
        //cout << l << " "<< r << " "<<ST[n].sum << "\n";
        Lazy[n] += v;
        up(n, l, r);
        return;
    }
    upd_add(2*n,l,(l+r)/2,i,j,v);
    upd_add(2*n+1,(l+r)/2+1,r,i,j,v);

    ST[n] = ST[2*n].merge(ST[2*n+1]);
}
void upd_set(ll n, ll l, ll r, ll i, ll j, ll v)
{
    up(n,l,r);
    if(l > j || r < i) return;

    if(i <= l && r <= j)
    {
        //cout << l << " "<< r << " "<<ST[n].sum << "\n";
        LazySet[n] = v;
        up(n, l, r);
        return;
    }
    upd_set(2*n,l,(l+r)/2,i,j,v);
    upd_set(2*n+1,(l+r)/2+1,r,i,j,v);

```

```

        ST[n] = ST[2*n].merge(ST[2*n+1]);
    }
    Node qry(ll i, ll j){return qry(1,0,N-1,i,j);}
    void updmx(ll i, ll j, ll v){return updmx(1,0,N-1,i,j,v);}
    void updmn(ll i, ll j, ll v){return updmn(1,0,N-1,i,j,v);}
    void upd_add(ll i, ll j, ll v){return upd_add(1,0,N-1,i,j,v);}
    void upd_set(ll i, ll j, ll v){return upd_set(1,0,N-1,i,j,v);}
};

int main(){

    ios_base::sync_with_stdio(0);
    cin.tie(0);
    srand((unsigned int) time(0));

    vl c = {0, 0, 0, 0, 0, 0}, d = c;
    SegmentTree ST(c);

    rep(i, c.size()){
        cout << ST.qry(i, i).sum << " ";
    }
    cout << endl;

    ST.upd_add(2, 3, 2);
    cout << ST.qry(2, 3).sum << endl;
    rep(i, c.size()){
        cout << ST.qry(i, i).sum << " ";
    }
    cout << endl;

    ST.updmx(0, 3, 3);
    cout << ST.qry(0, 3).sum << endl;
    rep(i, c.size()){
        cout << ST.qry(i, i).sum << " ";
    }
    cout << endl;

    ST.updmx(3, 5, 1);
    cout << ST.qry(3, 5).sum << endl;
    rep(i, c.size()){
        cout << ST.qry(i, i).sum << " ";
    }
    cout << endl;
}

```

```

ST.upd_add(0, 5, -3);
cout << ST.qry(0, 5).sum << endl;
rep(i, c.size()){
    cout << ST.qry(i, i).sum << " ";
}
cout << endl;

```

```

cerr << "\nTime elapsed: " << 1000 * clock() / CLOCKS_PER_SEC <<
    "ms\n";
return 0;

```

8.14 SegmentTreeIterative

```
#include "../Header.cpp"
```

```

struct Node
{
    int v;
    Node() { v = 0; } // neutro
    Node(int v) : v(v) {}
    Node(const Node &a, const Node &b) { v = a.v + b.v; }
};

// 0 - indexed / inclusive - exclusive
template <class node>
struct ST
{
    vector<node> t; int n;

    ST(vector<node> &arr, int N) : n(N), t(N * 2)
    {
        copy(arr.begin(), arr.end(), t.begin() + n);
        for (int i = n - 1; i > 0; --i) t[i] = node(t[i << 1], t[i << 1 | 1]);
    }
    void set(int p, const node &value)
    {
        for (t[p += n] = value; p >>= 1;)
            t[p] = node(t[p << 1], t[p << 1 | 1]);
    }
}

```

```

}
node query(int l, int r)
{
    node ans1, ansr;
    for (l += n, r += n; l < r; l >>= 1, r >>= 1)
    {
        if (l & 1) ans1 = node(ans1, t[l++]);
        if (r & 1) ansr = node(t[--r], ansr);
    }
    return node(ans1, ansr);
}
};

```

8.15 SegmentTreeLazy

```
#include "../Header.cpp"
```

```

struct SegmentTree
{
    vector<ll> ST, Lazy;
    int N; ll Nul = 0;
    SegmentTree(vector<ll> &A)
    {
        N = A.size();
        ST.resize(4*N+5,0);
        Lazy.resize(4*N+5,Nul);

        bd(1,0,N-1,A);
    }
    void up(int n, int l, int r)
    {
        ST[n] += Lazy[n];
        if(l != r)
        {
            Lazy[n*2] += Lazy[n];
            Lazy[n*2+1] += Lazy[n];
        }
        Lazy[n] = Nul;
    }
    ll op(ll x, ll y) { return min(x,y); }
    void bd(int n, int l, int r, vl &A)
    {
        if(l == r)

```

```

        {
            ST[n] = A[r];
            return;
        }

        bd(2*n,l,(l+r)/2,A);
        bd(2*n+1,(l+r)/2+1,r,A);
        ST[n] = op(ST[2*n], ST[2*n+1]);
    }

    ll qry(int i, int j)
    {
        return qry(1,0,N-1,i,j);
    }
    ll qry(int n, int l, int r, int i, int j)
    {
        if(r < i || j < l) return Nul;
        if(Lazy[n] != Nul) up(n,l,r);
        if(i <= l && r <= j) return ST[n];
        return op(qry(2*n,l,(l+r)/2,i,j),
            qry(2*n+1,(l+r)/2+1,r,i,j));
    }
    void upd(int i, int j, ll v)
    {
        return upd(1,0,N-1,i,j,v);
    }
    void upd(int n, int l, int r, int i, int j, ll v)
    {
        if(Lazy[n] != Nul) up(n,l,r);
        if(l > j || r < i) return;

        if(i <= l && r <= j)
        {
            Lazy[n] += v;
            if(Lazy[n] != Nul) up(n, l, r);
            return;
        }

        upd(2*n,l,(l+r)/2,i,j,v);
        upd(2*n+1,(l+r)/2+1,r,i,j,v);
        ST[n] = op(ST[2*n], ST[2*n+1]);
    }
};

```

8.16 SegmentTreePersistent

```
#include "../Header.cpp"

struct SegmentTree
{
    vector<vl> ST; vector<vi> Leftv, Rightv;
    int N;
    SegmentTree(vl &A)
    {
        N = A.size();
        ST.resize(4*N, vl());
        // ST.resize(4*N, vl(1, 0)); whitout build, init with 0s
        Leftv.resize(4*N, vi(1, 0)); // all conected to version 0
        Rightv.resize(4*N, vi(1, 0));
        bd(1,0,N-1,A);
    }
    ll op(ll x, ll y) { return min(x,y); }
    void bd(int n, int l, int r, vl &A)
    {
        if(l==r)
        {
            ST[n].push_back(A[r]);
            return;
        }

        bd(2*n,l,(l+r)/2,A);
        bd(2*n+1,(l+r)/2+1,r,A);

        ST[n].push_back(op(ST[2*n][0], ST[2*n+1][0]));
    }
    ll qry(int i, int j, int vs)
    {
        return qry(1,0,N-1,i,j, vs);
    }
    ll qry(int n, int l, int r, int i, int j, int vs)
    {
        if(r < i || j < l) return 0;

        if(i <= l && r <= j) return ST[n][vs];

        return op(qry(2*n,l,(l+r)/2,i,j, Leftv[n][vs]),
            qry(2*n+1,(l+r)/2+1,r,i,j, Rightv[n][vs]));
    }
}
```

```
void upd(int i, ll v)
{
    return upd(1,0,N-1,i,v);
}
void upd(int n, int l, int r, int i, ll v)
{
    if(i < l || r < i) return;

    if(l == r)
    {
        ST[n].push_back(v); // ST[n].push_back(v +
            ST[n].back()) add
        return;
    }

    upd(2*n,l,(l+r)/2,i,v);
    upd(2*n+1,(l+r)/2+1,r,i,v);

    ST[n].push_back(op(ST[2*n].back(), ST[2*n+1].back()));
    Leftv[n].push_back(ST[2*n].size()-1);
    Rightv[n].push_back(ST[2*n+1].size()-1);
}
};
```

8.17 SegmentTreeSubarraySum

```
#include "../Header.cpp"

// Max subarray sum
struct Node
{
    //maxPrefixSum, maxSuffixSum, Totalsum, maxSubarraySum
    ll mxP, mxS, sum, subSum;
    Node()
    {
        mxP = mxS = sum = subSum = -INF;
    }
    Node merge(Node r)
    {
        Node p;
        p.mxP = max(mxP, sum + r.mxP);
```



```

        p.mxS = max(r.mxS, r.sum + mxS);
        p.sum = sum + r.sum;
        p.subSum = max({subSum, r.subSum, mxS + r.mxP});
        return p;
    }
    void upd(ll v)
    {
        mxP = mxS = sum = subSum = v;
    }
    void nul()
    {
        mxP = mxS = subSum = -INF;
        sum = 0;
    }
};

```

// Node version

```

struct SegmentTree
{
    vector<Node> ST;
    int N;
    SegmentTree(vl &A)
    {
        N = A.size();
        ST.assign(4*N, Node());
        bd(1,0,N-1,A);
    }
    void bd(int n, int l, int r, vl &A)
    {
        if(l == r)
        {
            ST[n].upd(A[l]);
            return;
        }

        bd(2*n,l,(l+r)/2,A);
        bd(2*n+1,(l+r)/2+1,r,A);

        ST[n] = ST[2*n].merge(ST[2*n+1]);
    }
    Node qry(int i, int j)
    {
        return qry(1,0,N-1,i,j);
    }
}

```

```

Node qry(int n, int l, int r, int i, int j)
{
    if(r < i || j < l)
    {
        Node p;
        p.nul();
        return p;
    }

    if(i <= l && r <= j) return ST[n];

    return
        qry(2*n,l,(l+r)/2,i,j).merge(qry(2*n+1,(l+r)/2+1,r,i,j));
}

void upd(int i, ll v)
{
    return upd(1,0,N-1,i,v);
}
void upd(int n, int l, int r, int i, ll v)
{
    if(i < l || r < i) return;

    if(l == r)
    {
        ST[n].upd(v);
        return;
    }
    upd(2*n,l,(l+r)/2,i,v);
    upd(2*n+1,(l+r)/2+1,r,i,v);

    ST[n] = ST[2*n].merge(ST[2*n+1]);
}
};

```

8.18 SparseTable

```
#include "../Header.cpp"
```

```

struct SparseTable
{

```

```

vector<vl >SP;

SparseTable(vl&A)
{
    int n = A.size();
    SP.push_back(A);
    ll maxlog = 31 - __builtin_clz(n);
    rep(x(i, 1 ,maxlog+1)
        {
            vl aux;
            rep(j, n-(1<<i)+1)
            {
                aux.push_back(max(SP[i-1][j],SP[i-1][j+(1<<(i-1))]));
            }
            SP.push_back(aux);
        }
    }

    ll op(int l, int r)
    {
        ll maxlog = 31 - __builtin_clz(r-l+1);
        return max(SP[maxlog][l],SP[maxlog][r-(1<<maxlog)+1]);
    }

    ll find(int l, int r, ll m) // maxi
    {
        ll maxlog = 31 - __builtin_clz(r-l+1);
        for(int i = maxlog; i >= 0; i--){
            if(l + (1<<i) <= r && SP[i][l] < m){
                l += (1<<i);
            }
        }
        return l;
    }
};

int main()
{
    ios::sync_with_stdio(0);
    cin.tie(0);
    ll n,m,x,y,h,v;

    vector<int>A = {7,10,19,3,1,2,7,7};
    SparseTable SP(A);
    cout<<SP.op(1,3)<<endl;
    return 0;
}

```

```

}

```

8.19 Treap

```

#include "../Header.cpp"
typedef struct item *pitem;
struct item {
    int pr,key,cnt;
    pitem l,r;
    item(int key):key(key),pr(rand()),cnt(1),l(0),r(0) {}
};

int cnt(pitem t){return t?t->cnt:0;}
void upd_cnt(pitem t){if(t)t->cnt=cnt(t->l)+cnt(t->r)+1;}
void split(pitem t, int key, pitem& l, pitem& r){ // l: < key, r: >= key
    if(!t)l=r=0;
    else if(key<t->key)split(t->l,key,l,t->l),r=t;
    else split(t->r,key,t->r,r),l=t;
    upd_cnt(t);
}

void insert(pitem& t, pitem it){
    if(!t)t=it;
    else if(it->pr>t->pr)split(t,it->key,it->l,it->r),t=it;
    else insert(it->key<t->key?t->l:t->r,it);
    upd_cnt(t);
}

void merge(pitem& t, pitem l, pitem r){
    if(!l||!r)t=l?l:r;
    else if(l->pr>r->pr)merge(l->r,l->r,r),t=l;
    else merge(r->l,l,r->l),t=r;
    upd_cnt(t);
}

void erase(pitem& t, int key){
    if(t->key==key)merge(t,t->l,t->r);
    else erase(key<t->key?t->l:t->r,key);
    upd_cnt(t);
}

void unite(pitem& t, pitem l, pitem r){
    if(!l||!r){t=l?l:r;return;}
    if(l->pr<r->pr)swap(l,r);
    pitem p1,p2;split(r,l->key,p1,p2);
    unite(l->l,l->l,p1);unite(l->r,l->r,p2);
    t=l;upd_cnt(t);
}

```

```

pitem kth(pitem t, int k){
    if(!t)return 0;
    if(k==cnt(t->l))return t;
    return k<cnt(t->l)?kth(t->l,k):kth(t->r,k-cnt(t->l)-1);
}

pair<int,int> lb(pitem t, int key){ // position and value of lower_bound
    if(!t)return {0,1<<30}; // (special value)
    if(key>t->key){
        auto w=lb(t->r,key);w.fst+=cnt(t->l)+1;return w;
    }
    auto w=lb(t->l,key);
    if(w.fst==cnt(t->l))w.snd=t->key;
    return w;
}

pitem ss;
int n,q;

int find(int x){
    int s=1,e=n+1;
    while(e-s>1){
        int m=(s+e)/2;
        if(m-lb(ss,m).fst>x)e=m;
        else s=m;
    }
    return s;
}

int main(){
    scanf("%d%d",&n,&q);
    while(q--){
        char c[4];int k;
        scanf("%s%d",c,&k);
        if(c[0]=='D')insert(ss,new item(find(k)));
        else printf("%d\n",find(k));
    }
    fore(i,0,cnt(ss))assert(lb(ss,kth(ss,i)->key).fst==i);
    return 0;
}

```

8.20 TreapImplicit

```

// example that supports range reverse and addition updates, and range
// sum query
// (commented parts are specific to this problem)
#include "../Header.cpp"
typedef struct item *pitem;
struct item {
    int pr,cnt,val;
    // int sum; // (parameters for range query)
    // bool rev;int add; // (parameters for lazy prop)
    pitem l,r;
    item(int val):
        pr(rand()),cnt(1),val(val),l(0),r(0),/*sum(val),rev(0),add(0)*/
        {}
};

void push(pitem it){
    if(it){
        /*if(it->rev){
            swap(it->l,it->r);
            if(it->l)it->l->rev^=true;
            if(it->r)it->r->rev^=true;
            it->rev=false;
        }
        it->val+=it->add;it->sum+=it->cnt*it->add;
        if(it->l)it->l->add+=it->add;
        if(it->r)it->r->add+=it->add;
        it->add=0;*/
    }
}

int cnt(pitem t){return t?t->cnt:0;}
// int sum(pitem t){return t?push(t),t->sum:0;}
void upd_cnt(pitem t){
    if(t){
        t->cnt=cnt(t->l)+cnt(t->r)+1;
        // t->sum=t->val+sum(t->l)+sum(t->r);
    }
}

void merge(pitem& t, pitem l, pitem r){
    push(l);push(r);
    if(!l||!r)t=l?l:r;
    else if(l->pr>r->pr)merge(l->r,l->r,r),t=l;
    else merge(r->l,l,r->l),t=r;
    upd_cnt(t);
}

void split(pitem t, pitem& l, pitem& r, int sz){ // sz:desired size of l
    if(!t){l=r=0;return;}
}

```

```

    push(t);
    if(sz<=cnt(t->l))split(t->l,l,t->l,sz),r=t;
    else split(t->r,t->r,r,sz-1-cnt(t->l)),l=t;
    upd_cnt(t);
}
void output(pitem t){ // useful for debugging
    if(!t)return;
    push(t);
    output(t->l);printf(" %d",t->val);output(t->r);
}
// use merge and split for range updates and queries

int n,q;
char s[100005];

int main(){
    string s;
    cin >> s;
    pitem t=0;
    rep(i, s.size())merge(t,t,new item(s[i]-'a'));

    ll q, x;
    cin >> q;
    while(q--){
        cin >> x;
        pitem r;
        split(t, t, r, x);
        if(t) {t->rev^=true; t->add+=1} if(r) r->rev^=true;
        merge(t, t, r);
    }
    ans(t);
}

```

8.21 TreapImplicitFather

```

// node father is useful to keep track of the chain of each node
// alternative: splay tree
// IMPORTANT: add pointer f in struct item
#include "../Header.cpp"
#define fore(i,a,b) for(int i=a,ThxDem=b;i<ThxDem;++i)
void merge(pitem& t, pitem l, pitem r){
    push(l);push(r);

```

```

    if(!l||!r)t=1?l:r;
    else if(l->pr>r->pr)merge(l->r,l->r,r),l->r->f=t=l;
    else merge(r->l,l,r->l),r->l->f=t=r;
    upd_cnt(t);
}
void split(pitem t, pitem& l, pitem& r, int sz){
    if(!t){l=r=0;return;}
    push(t);
    if(sz<=cnt(t->l)){
        split(t->l,l,t->l,sz);r=t;
        if(l)l->f=0;
        if(t->l)t->l->f=t;
    }
    else {
        split(t->r,t->r,r,sz-1-cnt(t->l));l=t;
        if(r)r->f=0;
        if(t->r)t->r->f=t;
    }
    upd_cnt(t);
}
void push_all(pitem t){
    if(t->f)push_all(t->f);
    push(t);
}
pitem root(pitem t, int& pos){ // get root and position for node t
    push_all(t);
    pos=cnt(t->l);
    while(t->f){
        pitem f=t->f;
        if(t==f->r)pos+=cnt(f->l)+1;
        t=f;
    }
    return t;
}

```

```

int n,m,c,q;
map<pair<int,int>,int> w; // owner

pitem t[105][8005];

bool join(int k, int x, int y){
    int a,b;
    pitem r0=root(t[k][x],a),r1=root(t[k][y],b);

```

```

    if(a&& a<cnt(r0)-1 || b&& b<cnt(r1)-1){puts("Forbidden:
        monopoly.");return false;}
    if(r0==r1){puts("Forbidden: redundant.");return false;}
    if(a==0)r0->rev^=1;
    if(b!=0)r1->rev^=1;
    //printf(" %d %d %d %d\n",a,b,cnt(r0),cnt(r1));
    pitem _;
    merge(_,r0,r1);
    return true;
}

void disjoin(int k, int x, int y){
    int a,b;
    pitem r0=root(t[k][x],a),r1=root(t[k][y],b);
    assert(r0==r1);assert(abs(a-b)==1);
    pitem _,_;
    //split(a<b?t[k][y]:t[k][x],_,_);
    split(r0,_,_,max(a,b));
}

int main(){
    fore(i,0,105)fore(j,0,8005)t[i][j]=new item();
    while(scanf("%d%d%d%d",&n,&m,&c,&q),n){
        fore(i,0,c)fore(j,0,n)t[i][j]->l=t[i][j]->r=t[i][j]->f=0;
        w.clear();
        fore(i,0,m){
            int x,y,k;
            scanf("%d%d%d",&x,&y,&k);x--;y--;k--;
            w[{x,y}]=k;
            assert(join(k,x,y));
        }
        while(q--){
            int x,y,k;
            scanf("%d%d%d",&x,&y,&k);x--;y--;k--;
            if(!w.count({x,y})){puts("No such
                cable.");continue;}
            int kk=w[{x,y}];
            if(kk==k){puts("Already owned.");continue;}
            if(join(k,x,y)){
                w[{x,y}]=k;
                disjoin(kk,x,y);
                puts("Sold.");
            }
        }
        puts("");
    }
}

```

```

    }
    return 0;
}

```

8.22 UnionFind

```

#include "../Header.cpp"

struct UF{
    vl p, r, sz;
    UF();
    UF(ll n)
    {
        r.assign(n, 0);
        sz.assign(n, 1);
        rep(i, n)
            p.push_back(i);
    }
    ll find(ll x)
    {return p[x] = p[x] == x ? x : find(p[x]);}
    void join(ll x, ll y)
    {
        if ((x = find(x)) == (y = find(y))) return;

        if(r[x] < r[y]) swap(x, y);
        if(r[x] == r[y]) r[x]++;
        p[y] = x;
        sz[x] += sz[y];
    }
};

// With rollback
struct UF{
    vl p, r, sz;
    stack<vl> S;
    UF () {}
    UF(ll n)
    {
        r.assign(n, 0);
        sz.assign(n, 1);
        for(ll i = 0; i < n; i++)
            p.push_back(i);
    }
}

```

```

}
ll find(ll x)
{return p[x] == x ? x : find(p[x]);}
void join(ll x, ll y)
{
    if ((x = find(x)) == (y = find(y))) return;

    if(r[x] < r[y]) swap(x, y);
    if(r[x] == r[y]) r[x]++;
    S.push({x, y, p[x], p[y]});
    p[y] = x;

    sz[x] += sz[y];
}
void rollback()
{
    auto a = S.top(); S.pop();
    p[a[0]] = a[2];
    p[a[1]] = a[3];
    sz[a[0]] -= sz[a[1]];
}
};

```

8.23 WaveletTree

```

#include "../Header.cpp"
typedef vector<int>::iterator iter;

//Wavelet tree with succinct representation of bitmaps
struct WaveTreeSucc {
    vector<vector<int> > C; int s;

    // sigma = size of the alphabet, ie., one more than the maximum element
    // in S.
    WaveTreeSucc(vector<int> &A, int sigma) : C(sigma*2), s(sigma) {
        build(A.begin(), A.end(), 0, s-1, 1);
    }

    void build(iter b, iter e, int L, int U, int u) {
        if (L == U)
            return;
        int M = (L+U)/2;

```

```

        // C[u][i] contains number of zeros until position i-1: [0,i)
        C[u].reserve(e-b+1); C[u].push_back(0);
        for (iter it = b; it != e; ++it)
            C[u].push_back(C[u].back() + (*it<=M));

        iter p = stable_partition(b, e, [=](int i){return i<=M;});

        build(b, p, L, M, u*2);
        build(p, e, M+1, U, u*2+1);
    }

    // Count occurrences of number c until position i.
    // ie, occurrences of c in positions [i,j]
    int rank(int c, int i) const {
        // Internally we consider an interval open on the left: [0, i)
        i++;
        int L = 0, U = s-1, u = 1, M, r;
        while (L != U) {
            M = (L+U)/2;
            r = C[u][i]; u*=2;
            if (c <= M)
                i = r, U = M;
            else
                i -= r, L = M+1, ++u;
        }
        return i;
    }

    // Find the k-th smallest element in positions [i,j].
    // The smallest element is k=1
    int quantile(int k, int i, int j) const {
        // internally we consider an interval open on the left: [i, j)
        j++;
        int L = 0, U = s-1, u = 1, M, ri, rj;
        while (L != U) {
            M = (L+U)/2;
            ri = C[u][i]; rj = C[u][j]; u*=2;
            if (k <= rj-ri)
                i = ri, j = rj, U = M;
            else
                k -= rj-ri, i -= ri, j -= rj,
                L = M+1, ++u;
        }
        return U;
    }
}

```

```

// Count number of occurrences of numbers in the range [a, b]
// present in the sequence in positions [i, j], ie, if representing a
// grid it
// counts number of points in the specified rectangle.
mutable int L, U;
int range(int i, int j, int a, int b) const {
    if (b < a or j < i)
        return 0;
    L = a; U = b;
    return range(i, j+1, 0, s-1, 1);
}

int range(int i, int j, int a, int b, int u) const {
    if (b < L or U < a)
        return 0;
    if (L <= a and b <= U)
        return j-i;
    int M = (a+b)/2, ri = C[u][i], rj = C[u][j];
    return range(ri, rj, a, M, u*2) +
        range(i-ri, j-rj, M+1, b, u*2+1);
}
};

//https://github.com/mhunicken/icpc-team-notebook-el-vasito/blob/master/data_structures/wavelet_tree.cpp
struct WT {
    vector<int> wt[1<<20]; int n;
    void init(int k, int s, int e){
        if(s+1==e)return;
        wt[k].clear(); wt[k].pb(0);
        int m=(s+e)/2;
        init(2*k,s,m); init(2*k+1,m,e);
    }
};

```

```

void add(int k, int s, int e, int v){
    if(s+1==e)return;
    int m=(s+e)/2;
    if(v<m)wt[k].pb(wt[k].back()),add(2*k,s,m,v);
    else wt[k].pb(wt[k].back()+1),add(2*k+1,m,e,v);
}
int query0(int k, int s, int e, int a, int b, int i){
    if(s+1==e)return s;
    int m=(s+e)/2;
    int q=(b-a)-(wt[k][b]-wt[k][a]);
    if(i<q)return query0(2*k,s,m,a-wt[k][a],b-wt[k][b],i);
    else return query0(2*k+1,m,e,wt[k][a],wt[k][b],i-q);
}
void upd(int k, int s, int e, int i){
    if(s+1==e)return;
    int m=(s+e)/2;
    int v0=wt[k][i+1]-wt[k][i],v1=wt[k][i+2]-wt[k][i+1];
    if(!v0&&!v1)upd(2*k,s,m,i-wt[k][i]);
    else if(v0&&v1)upd(2*k+1,m,e,wt[k][i]);
    else if(v0)wt[k][i+1]--;
    else wt[k][i+1]++;
}
void init(int _n){n=_n;init(1,0,n);} // (values in range [0,n))
void add(int v){add(1,0,n,v);}
int query0(int s, int e, int a, int b, int i){ // ith element in range [a,b)
    return query0(1,0,n,a,b,i); // (if it was sorted)
}
void upd(int i){ // swap positions i,i+1
    upd(1,0,n,i);
}
};

```