



|                                                |              |     |         |                  |                        |             |
|------------------------------------------------|--------------|-----|---------|------------------|------------------------|-------------|
| GENERAL NOTES:                                 |              |     |         |                  |                        |             |
| For your safety, check weight before handling: |              |     |         |                  |                        |             |
| 0-5kg Light    5-15kg Normal    15+kg Heavy    |              |     |         |                  |                        |             |
| MATERIAL LIST FOR PART - x50                   |              |     |         | 5 PARTS REQUIRED |                        |             |
| POS. No.                                       | PROFILE      | No. | GRADE   | L (mm)           | AREA (m <sup>2</sup> ) | WEIGHT (kg) |
| x50                                            | RHS100X100X6 | 1   | S355J2H | 4650             | 1.8                    | 78.6 !!     |
| TOTAL WEIGHT FOR                               |              |     |         | 5                | PARTS                  | 393.2       |

|           |      |
|-----------|------|
| Part list | Qty. |
| VX        | 5    |

|                                                                                                                                                  |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Execution class: EXC 2                                                                                                                           |  |
| No utilization on drawings = over 50%                                                                                                            |  |
| V-SEAM<br>Utilization under 50%<br>EXC 2=> Acc. to process control<br>EXC 3=> 20% UT<br>Utilization over 50%<br>EXC 2=> 10% UT<br>EXC 3=> 20% UT |  |

|                                                                                                                                                         |                                      |                       |                                        |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|-----------------------|----------------------------------------|
| * o 3 0 4 8 0 - 2 *  <b>DS</b> <i>Skalkonstruktion</i> * W x 5 0 * |                                      |                       |                                        |
| PROJECT                                                                                                                                                 | Akkasæter Lager- og vedlikeholdshall |                       | PHASE    2 / Phase 2                   |
| MEMBER                                                                                                                                                  | Vind-X                               | QUANTITY:    5        | PROJECT No    30480-2                  |
| REVISION                                                                                                                                                |                                      | ISSUED:    07.11.2025 | DRAFTER:    ZLL<br>BIM control:    SST |
|                                                                                                                                                         |                                      |                       | DRAWING No.    x.50                    |