

Computational Imaging Group R Project Template

Group R

Number of students: 2

1. General Description

In this project, students are asked to address a computational imaging problem by combining different methodological families, in order to understand both classical and modern approaches and to critically compare their behavior under the same experimental conditions. The goal is not only to obtain good reconstruction results, but also to reason about the strengths and limitations of each method.

2. Dataset

Dataset to be used: Mendeley LBC cervical cancer

Download link: [Mendeley LBC Cervical Cancer](#)

Students are expected to carefully inspect the dataset, understand its structure, and define a consistent preprocessing pipeline. This includes normalization, resizing if needed, and splitting into training, validation, and testing sets when applicable. Any preprocessing choice must be clearly justified and documented.

3. Task Definition

Target task: Deblur and denoise

Consider a subset of about 4000 images of the original dataset. The images must be resized to 256x256.

The task must be formulated as an inverse problem where a degraded observation is mapped back to a high-quality reconstruction.

Parameters of the degradation process:

Gaussian Deblur:

sigma = 2, kernel size = 9
noise level = 0.005, 0.01, 0.05, 0.1

Students must ensure all methods use the same degraded inputs.

4. Methodological Requirements

The students are expected to test and compare multiple methods on the same data. In particular:

Variational method: regularization with Total Variation (TV)

End-to-end method: Select one appropriate method within the following list of architectures: UNet, ViT, or NAF-Net. Choose specific architecture and training in relation to the task properties.

Generative method: Diffusion with DiffPir, suitably adapted to this task, explain usage.

Hybrid method: Weighted Total variation (see paper: Morotti, Elena, et al. "Adaptive Weighted Total Variation boosted by learning techniques in few-view tomographic imaging." *arXiv preprint arXiv:2501.09845* (2025)).

If the group is constituted by only 2 students, they can choose three of the previous four methods, by excluding one of the last three ones (they can also do all the four, obviously!).

Each of the previous method has its own set of parameters that needs to be chosen, e.g. the number of diffusion steps for DPS or the regularization parameter. The students are expected to identify the values of such parameters heuristically and discuss the final choice, together with a description of how they set them, at the oral presentation.

5. Deliverables

During the oral presentation, the students are expected to provide a comparison of the tested methods in terms of the following:

Quantitative: PSNR, SSIM.

Visual: reconstructed images and comparisons.

In particular, they should include a comparison plot within all methods, a report with methods, setup, and discussion.

Finally, we expect the student to provide a code with documentation, possibly pushed on [Github](#) whose link should be delivered during the oral presentation.

During the oral presentation, the students should have a PowerPoint / Beamer presentation reporting all the deliverables and the discussion as indicated in the project description.