

# **1. TECHNOLOGIES FOR MICROFABRICATION OF MEMS DEVICES**

## **1.1.1 MOTIVATIONS AND GOALS**

## **1.1.2 A MEMS PROCESS AT A GLANCE**

### **1.1.2.1 An example from the ST ThELMA micromachining process**

## **1.1.3 STRUCTURAL LAYER GROWTH AND DEFINITION**

### **1.1.3.1 Epitaxial growth**

### **1.1.3.2 Deep reactive ion etching (DRIE)**

### **1.1.3.3 Release**

## **1.1.4 MEMS PACKAGING**

### **1.1.4.1 Glass-frit and eutectic bonding**

## **1.1.5 CONCLUSIONS ABOUT THE FABRICATION PROCESS**

# **2. THE LINEAR AND TORSIONAL SPRING-MASS-DAMPER SYSTEM**

## **2.1.1 MOTIVATIONS AND GOALS**

## **2.1.2 KINEMATICS OF RELATIVE MOTION**

### **2.1.2.1 Reference systems (inertial, non-inertial)**

### **2.1.2.2 Equations for traslational motion**

## **2.1.3 THE LINEAR SPRING-MASS-DAMPER SYSTEM**

### **2.1.3.1 Time description**

### **2.1.3.2 Frequency description**

### **2.1.3.3 MEMS operating regions**

## **2.1.4 THE TORSIONAL SPRING-MASS-DAMPER SYSTEM**

## **2.1.5 ELECTROSTATIC FORCES**

### **2.1.5.1 Parallel plates**

### **2.1.5.2 Comb fingers**

## **2.1.6 CONCLUSIONS ABOUT THE LINEAR SPRING-MASS-DAMPER SYSTEM**

# **3. THE CAPACITIVE MEMS ACCELEROMETER**

## **3.1 ACCELEROMETERS PART 1: OVERVIEW, SENSITIVITY, PULL-IN ISSUES**

## **3.1.1 MOTIVATIONS AND GOALS**

## **3.1.2 GENERAL ARCHITECTURE OF A PP CONFIGURATION**

### **3.1.2.1 Coupling to a sample front-end**

### **3.1.2.2 Charge transfer**

### **3.1.2.3 Output voltage vs displacement**

### 3.1.3 EFFECTS OF ELECTROSTATIC FORCES IN PP ACCELEROMETERS

#### 3.1.3.1 Equivalent electrostatic negative stiffness

#### 3.1.3.2 Pull-in instability

#### 3.1.3.3 Mechanical stoppers

### 3.1.4 ACCELEROMETER OVERALL SENSITIVITY

### 3.1.5 CONCLUSIONS ABOUT PART 1 OF ACCELEROMETERS

## 3.2 ACCELEROMETERS PART 2: BANDWIDTH AND NOISE CONSIDERATIONS

### 3.2.1 MOTIVATIONS AND GOALS

### 3.2.2 CONSIDERATIONS ON THE SENSITIVITY

#### 3.2.2.1 Linearity

#### 3.2.2.2 Comparison with a CF approach

### 3.2.3 ACCELEROMETER BANDWIDTH AND OPERATING REGION

#### 3.2.3.1 Transfer function vs Q

### 3.2.4 THERMO-MECHANICAL NOISE IN MEMS DEVICES

#### 3.2.4.1 Brownian noise origin

#### 3.2.4.2 Noise equivalent acceleration density

#### 3.2.4.3 Optimum Q

### 3.2.5 CONCLUSIONS ABOUT PART 2 OF ACCELEROMETERS

## 3.3 ACCELEROMETERS PART 3: SPRINGS AND TYPICAL ARCHITECTURES

### 3.3.1 MOTIVATIONS AND GOALS

### 3.3.2 FLEXURAL SPRINGS

#### 3.3.2.1 Young's modulus and axial stiffness

#### 3.3.2.2 In-plane stiffness

#### 3.3.2.3 Out-of-plane stiffness

#### 3.3.2.4 Free end vs guided end springs

### 3.3.3 TORSIONAL SPRINGS

#### 3.3.3.1 Simple configuration and stiffness calculation

### 3.3.4 COMMON SPRINGS ARCHITECTURES

#### 3.3.4.1 Process nonuniformities and folded springs

#### 3.3.4.2 Example of single-axis, 2-axis and 3-axis accelerometers

### 3.3.5 CONCLUSIONS ABOUT PART 3 OF ACCELEROMETERS

## 3.4 ACCELEROMETERS PART 4: OFFSET AND OTHER ELECTRONIC READOUT

### 3.4.1 MOTIVATIONS AND GOALS

### 3.4.2 MECHANICAL OFFSET

#### 3.4.2.1 Offset sources

#### 3.4.2.2 Effects on input-referred acceleration

#### 3.4.2.3 Effects on sensitivity

#### 3.4.2.4 Trade-offs with FSR

- 3.4.3 ELECTRONIC OFFSET
  - 3.4.3.1 Modulation to bypass amplifier offsets
  - 3.4.3.2 Drift of the feedback capacitance
- 3.4.4 ALTERNATIVE READOUT TOPOLOGIES FOR NEXT GENERATION ACCELEROMETERS
  - 3.4.4.1 Force feedback: concept and examples
  - 3.4.4.2 Charge control: concept and examples
- 3.4.5 CONCLUSIONS ABOUT MEMS ACCELEROMETERS

## **4. MEMS RESONATORS**

### **4.1 RESONATORS PART 1: ACTUATION, READOUT, ELECTRICAL MODEL**

- 4.1.1 MOTIVATIONS AND GOALS
- 4.1.2 COMB RESONATOR OVERVIEW
  - 4.1.2.1 Overview
  - 4.1.2.2 Electrostatic actuation (and transduction factor)
  - 4.1.2.3 Motional current detection (and transduction factor)
- 4.1.3 ELECTRICAL ADMITTANCE
  - 4.1.3.1 At resonance
  - 4.1.3.2 In the Laplace domain
- 4.1.4 EQUIVALENT ELECTRICAL MODEL
  - 4.1.4.1 RLC equivalent circuit
  - 4.1.4.2 Dissipation: quality factor and equivalent resistance
- 4.1.5 CONCLUSIONS ABOUT PART 1 OF RESONATORS

### **4.2 RESONATORS PART 2: MEMS-BASED OSCILLATOR CIRCUITS**

- 4.2.1 MOTIVATIONS AND GOALS
- 4.2.2 OSCILLATOR CONDITIONS
  - 4.2.2.1 Barkhausen criterion
  - 4.2.2.2 Compensation of the equivalent resistance
- 4.2.3 CIRCUITS BASED ON LINEAR AMPLIFICATION AND SATURATION
  - 4.2.3.1 Trans-resistance front-end
  - 4.2.3.2 Nonlinearity
  - 4.2.3.3 Driving amplitude decrease
- 4.2.4 CIRCUITS BASED ON COMPARATORS
  - 4.2.4.1 Charge amplifier front-end
  - 4.2.4.2 Comparator
  - 4.2.4.3 Need for a start-up circuit
- 4.2.5 CONCLUSIONS ABOUT PART 2 OF RESONATORS

### **4.3 RESONATORS PART 3: EFFECTS OF FEEDTHROUGH CAPACITANCE**

- 4.3.1 MOTIVATIONS AND GOALS
- 4.3.2 ELECTRICAL MODEL WITH PARASITICS
  - 4.3.2.1 Feedthrough capacitance
  - 4.3.2.2 Effects on the electrical admittance
- 4.3.3 EFFECTS OF FEEDTHROUGH ON ELECTRONIC CIRCUITS
  - 4.3.3.1 Loop gain with feedthrough
  - 4.3.3.2 Compensation through poles
  - 4.3.3.3 Compensation through ancillary circuits
- 4.3.4 COMMON RESONATOR TOPOLOGIES
  - 4.3.4.1 Tang resonator
  - 4.3.4.2 Tunable tang resonator
  - 4.3.4.3 Clamped-clamped beam resonator
- 4.3.5 CONCLUSIONS ABOUT RESONATORS

## **5. THE CAPACITIVE MEMS GYROSCOPE**

### **5.1 GYROSCOPES PART 1: CORIOLIS FORCE, DRIVE MODE, SENSITIVITY**

- 5.1.1 MOTIVATIONS AND GOALS
- 5.1.2 THE CORIOLIS FORCE
  - 5.1.2.1 Kinematics of relative motion in presence of rotation
  - 5.1.2.2 Expression of the Coriolis force
  - 5.1.2.3 Measurement of angular rates
- 5.1.3 MEMS GYROSCOPES AT A GLANCE
  - 5.1.3.1 Architecture and working principle overview
  - 5.1.3.2 The drive resonator: drive motion and velocity
  - 5.1.3.3 The sense frame: capacitive detection
- 5.1.4 CALCULATION OF THE SENSITIVITY
  - 5.1.4.1 Sensitivity as a function of drive displacement and bandwidth
- 5.1.5 CONCLUSIONS ABOUT PART 1 OF GYROSCOPES

### **5.2 GYROSCOPES PART 2: OVERALL SENSITIVITY AND ADVANCED ARCHITECTURES**

- 5.2.1 MOTIVATIONS AND GOALS
- 5.2.2 DRIVE LOOP: AMPLITUDE CONTROL IN MEMS GYROSCOPES
  - 5.2.2.1 Summary of basic working principle and sensitivity
  - 5.2.2.2 Need for AGC circuits
  - 5.2.2.3 AGC examples
- 5.2.3 OVERALL SENSITIVITY CALCULATION
  - 5.2.3.1 Capacitive readout
  - 5.2.3.2 Charge amplifier differential readout
  - 5.2.3.3 Overall system view
- 5.2.4 ADVANCED GYROSCOPES ARCHITECTURES
  - 5.2.4.1 Effects of accelerations and vibrations

- 5.2.4.2 Dual-mass, tuning force gyroscopes
- 5.2.4.3 Levered sense mode

## 5.2.5 CONCLUSIONS ABOUT PART 2 OF GYROSCOPES

## 5.3 GYROSCOPES PART 3: BANDWIDTH AND NOISE

### 5.3.1 MOTIVATIONS AND GOALS

### 5.3.2 MODE-MATCHED GYROSCOPE BANDWIDTH

- 5.3.2.1 Quality factor and -3dB bandwidth
- 5.3.2.2 Trade-offs between bandwidth and sensitivity

### 5.3.3 MODE-MATCHED GYROSCOPE NOISE

- 5.3.3.1 Thermomechanical noise of the gyro frames
- 5.3.3.2 Trade-offs between noise density and bandwidth
- 5.3.3.3 Noise equivalent angular rate density (NERD)

### 5.3.4 ELECTRONIC NOISE CONTRIBUTIONS

- 5.3.4.1 Feedback resistance noise
- 5.3.4.2 Operational amplifier noise
- 5.3.4.3 Phase noise

## 5.3.5 CONCLUSIONS ABOUT PART 3 OF GYROSCOPES

## 5.4 GYROSCOPES PART 4: MODE-SPLIT OPERATION

### 5.4.1 MOTIVATIONS AND GOALS

### 5.4.2 BRIEF SUMMARY OF GYROSCOPES IN MODE-MATCHED OPERATIONS

- 5.4.2.1 Sensitivity and trade-offs
- 5.4.2.2 Frequency mismatch and frequency vs T
- 5.4.2.3 Q factor vs T

### 5.4.3 MODE-SPLIT OPERATION

- 5.4.3.1 Analysis of the transfer function in mode-split
- 5.4.3.2 Sensitivity in mode-split operation

### 5.4.4 BANDWIDTH IN MODE-SPLIT OPERATION

- 5.4.4.1 +-3dB definition
- 5.4.4.2 Effects of LPF electronics

## 5.4.5 CONCLUSIONS ABOUT PART 4 OF GYROSCOPES

## 5.5 GYROSCOPES PART 5: NOISE & ROBUSTNESS IN MODE-SPLIT OPERATION

### 5.5.1 MOTIVATIONS AND GOALS

### 5.5.2 BRIEF SUMMARY OF GYROSCOPES IN MODE-SPLIT OPERATION

- 5.5.2.1 Sensitivity
- 5.5.2.2 Bandwidth

### 5.5.3 MODE-SPLIT GYROSCOPE NOISE

- 5.5.3.1 Calculation of thermomechanical noise
- 5.5.3.2 Effects of electronics noise

#### 5.5.4 MODE-SPLIT GYROSCOPE ROBUSTNESS

##### 5.5.4.1 Immunity to T changes

##### 5.5.4.2 Immunity to Q changes

#### 5.5.5 CONCLUSIONS ABOUT PART 5 OF GYROSCOPES

### 5.6 GYROSCOPES PART 6: QUADRATURE ERROR AND ITS COMPENSATION

#### 5.6.1 MOTIVATIONS AND GOALS

#### 5.6.2 QUADRATURE ERROR ISSUES FROM SPRING DEFECTS

##### 5.6.2.1 Preliminary considerations

##### 5.6.2.2 Quadrature error modeling

##### 5.6.2.3 Spring mismatch

#### 5.6.3 ELECTRONIC COMPENSATION OF QUADRATURE AND EFFECTS OF WRONG COMPENSATION

#### 5.6.4 ELECTROMECHANICAL COMPENSATION

##### 5.6.4.1 Tatar scheme (Z-axis)

##### 5.6.4.2 Tatar scheme (X/Y-axis)

#### 5.6.5 CONCLUSIONS ABOUT GYROSCOPES

## 6. MEMS MAGNETOMETERS

### 6.1 MAGNETOMETERS PART 1: WORKING PRINCIPLE AND RESONANT OPERATION

#### 6.1.1 MOTIVATIONS AND GOALS

#### 6.1.2 LORENTZ FORCE MAGNETOMETERS

##### 6.1.2.1 The Lorentz force principle

##### 6.1.2.2 Basic architecture

##### 6.1.2.3 Sensitivity

#### 6.1.3 RESONANT OPERATION ISSUES

##### 6.1.3.1 Bandwidth

##### 6.1.3.2 Brownian noise

#### 6.1.4 ELECTRONIC NOISE

##### 6.1.4.1 Power dissipation

#### 6.1.5 CONCLUSIONS ABOUT PART 1 OF MAGNETOMETERS

### 6.2 MAGNETOMETERS PART 2: ADVANCED ARCHITECTURES AND OPERATION MODES

#### 6.2.1 MOTIVATIONS AND GOALS

#### 6.2.2 ADVANCED ARCHITECTURES

##### 6.2.2.1 Differential architecture for OOP magnetometers

##### 6.2.2.2 Differential architecture for IP magnetometers

#### 6.2.3 OFF-RESONANCE (MODE-SPLIT) OPERATION

##### 6.2.3.1 Sensitivity

##### 6.2.3.2 Bandwidth and noise density trade off

6.2.3.3 Drive signal generation and stability against drifts

## 6.2.4 MULTI-LOOP ARCHITECTURES

6.2.4.1 Improvements in sensitivity and noise

## 6.2.5 CONCLUSIONS ABOUT PART 2 OF MAGNETOMETERS

# 6.3 MAGNETOMETERS PART 3: MULTI-LOOP ARCHITECTURES (AND A SHORT REVIEW OF THE OTHER MEMS SENSORS)

## 6.3.1 MOTIVATIONS AND GOALS

## 6.3.2 SYSTEM-LEVEL CONSIDERATIONS ON POWER CONSUMPTION

6.3.2.1 Front-end electronic noise vs current

## 6.3.3 MONOLITHIC MULTI-LOOP ARCHITECTURES

6.3.3.1 Area occupation

6.3.3.2 Examples of monolithic 3-axis sensors

## 6.3.4 EXAMPLES OF OTHER CAPACITIVE MEMS SENSORS

6.3.4.1 Pressure sensors

6.3.4.2 Microphones

## 6.3.5 CONCLUSIONS ABOUT MAGNETOMETERS

# 7. ADVANCED MEMS CHARACTERIZATION: IMUs AND THE ALLAN VARIANCE METHOD

## 7.1.1 MOTIVATIONS AND GOALS

## 7.1.2 CASE STUDY: UNASSISTED NAVIGATION

7.1.2.1 Issues with GPS or other signals

7.1.2.2 Use of inertial sensors

7.1.2.3 Integration of signals and offset issues

## 7.1.3 CASE STUDY ON GYROSCOPE

7.1.3.1 Noise and random walk

7.1.3.2 Final angle distribution for white noise

## 7.1.4 ALLAN VARIANCE

7.1.4.1 Definition

7.1.4.2 Examples with white and 1/f noise

7.1.4.3 Practical use

## 7.1.5 CONCLUSIONS ABOUT MEMS CHARACTERIZATION AND ALLAN VARIANCE METHOD

# 8. CMOS IMAGE SENSORS

## 8.1 CMOS IMAGE SENSORS PART 1: BASICS OF DIGITAL IMAGING AND SYSTEM OVERVIEW

### 8.1.1 MOTIVATIONS AND GOALS

### 8.1.2 THE HUMAN VISUAL SYSTEM

#### 8.1.2.1 The eye at a first glance

#### 8.1.2.2 Image formation and focusing

### 8.1.3 THE PHOTORECEPTORS

#### 8.1.3.1 Cones and rods (and their sensitivity)

#### 8.1.3.2 Spatial and spectral distributions

#### 8.1.3.3 Photoreceptors stimuli

#### 8.1.3.4 Brain elaboration and color sensation

### 8.1.4 DIGITAL IMAGUING PIPELINE

### 8.1.5 PHYSICS OF LIGHT SOURCES

### 8.1.6 CONCLUSIONS ABOUT PART 1 OF CMOS IMAGE SENSORS

## 8.2 CMOS IMAGE SENSORS PART 2

### 8.2.1 MOTIVATION AND FOCUS

### 8.2.2 GEOMETRIC OPTICS

#### 8.2.2.1 Snell's and lens-maker formula

#### 8.2.2.2 Magnification factor

#### 8.2.2.3 Focal (and equivalent focal) length

### 8.2.3 REALISTIC LENS BEHAVIOR

#### 8.2.3.1 Spherical aberrations

#### 8.2.3.2 Chromatic aberrations

### 8.2.4 F# NUMBER AND DIFFRACTION

#### 8.2.4.1 Airy spot size

#### 8.2.4.2 Answers to initial questions

### 8.2.5 CONCLUSIONS ABOUT PART 2 OF CMOS IMAGE SENSORS

# 9. CMOS ACTIVE PIXEL SENSORS (APS3T)

## 9.1 CMOS APS3T PART 1: SENSOR OVERVIEW AND SIGNAL GENERATION

### 9.1.1 MOTIVATIONS AND GOALS

### 9.1.2 PHOTOGENERATION IN THE SIMPLEST PN JUNCTION

#### 9.1.2.1 Photon absorption

#### 9.1.2.2 Charge generation and collection

#### 9.1.2.3 Quantum efficiency and responsivity

### 9.1.3 SIGNAL AND NOISE

#### 9.1.3.1 Signal generation

#### 9.1.3.2 Dark current (offset)

#### 9.1.3.3 Noise overview

### 9.1.4 CONCLUSIONS ABOUT PART 1 OF CMOS APS3T



## **9.2 CMOS APS3T PART 2: 3T TOPOLOGY WORKING PRINCIPLE AND SNR**

### **9.2.1 MOTIVATIONS AND GOALS**

### **9.2.2 CMOS ACTIVE PIXEL SENSOR**

#### **9.2.2.1 Further considerations**

#### **9.2.2.2 Operating principle of the 3T topology**

#### **9.2.2.3 Rolling shutter scanning scheme**

### **9.2.3 LINEARITY**

#### **9.2.3.1 Integration on a varying capacitance**

#### **9.2.3.2 Well saturation**

### **9.2.4 SNR OF THE 3T TOPOLOGY**

#### **9.2.4.1 Signal calculation**

#### **9.2.4.2 kTC noise calculation**

#### **9.2.4.3 Shot noise calculation**

#### **9.2.4.4 SNR dependencies**

### **9.2.5 CONCLUSIONS ABOUT PART 2 OF CMOS APS3T**

## **9.3 CMOS APS3T PART 3: 3T TOPOLOGY DR, FPN SOURCES AND THEIR CORRECTION**

### **9.3.1 MOTIVATIONS AND GOALS**

### **9.3.2 DYNAMIC RANGE OF THE 3T TOPOLOGY**

#### **9.3.2.1 Definition and calculation**

#### **9.3.2.2 Analysis of dependencies with examples**

### **9.3.3 DR VS MAXIMUM SNR**

#### **9.3.3.1 DR calculated from SNR graphs**

### **9.3.4 FIXED-PATTERN NOISE (FPN)**

#### **9.3.4.1 General considerations**

#### **9.3.4.2 Dark signal nonuniformity (DSNU)**

#### **9.3.4.3 Photo-response nonuniformity (PRNU)**

### **9.3.5 CONCLUSIONS ABOUT CMOS APS3T**

# **10. CMOS ACTIVE PIXEL SENSORS (APS4T)**

## **10.1 CMOS APS4T PART 1: 4T TOPOLOGY, PINNED PHOTODIODE AND CORRELATED DOUBLE SAMPLING**

### **10.1.1 MOTIVATIONS AND GOALS**

### **10.1.2 MAIN LIMITATIONS OF THE 3T TOPOLOGY**

#### **10.1.2.1 Linearity and conversion gain**

#### **10.1.2.2 Reset noise**

#### **10.1.2.3 Dark current noise**

### **10.1.3 PINNED PHOTODIODE AND THE 4T TOPOLOGY**

#### **10.1.3.1 Simplified device description**

#### **10.1.3.2 Working principle**

10.1.3.3 Solutions to the limitations of the 3T approach

10.1.4 CDS

10.1.4.1 Reset noise compensation

10.1.5 THE PHOTON TRANSFER CURVE

10.1.5.1 Definition and practical uses

10.1.6 CONCLUSIONS ABOUT THE PART 1 OF APS4T

## **10.2 CMOS APS4T PART 2: COLOR ACQUISITION AND BASIC SIGNAL PROCESSING**

10.2.1 MOTIVATIONS AND GOALS

10.2.2 COLOR ACQUISITION

10.2.2.1 CFA-Bayer pattern

10.2.2.2 Layered junctions

10.2.3 COLOR SPACES AND COLOR CONVERSION MATRIX

10.2.3.1 Human visual system color spaces

10.2.3.2 Device dependent color spaces

10.2.3.3 Color conversion matrix (CCM)

10.2.4 WHITE BALANCE OPERATION

10.2.4.1 Color constancy of the human visual system

10.2.4.2 The Von Kries assumption

10.2.4.3 WB matrix correction

10.2.5 CONCLUSIONS ABOUT IMAGE SENSORS