

Thymio, an example of open source hardware robot for formal education

Francesco Mondada¹, Michael Bonani², Fanny Riedo², Manon Briad¹,
Léa Pereyre¹, Philippe Rétornaz¹ and Stéphane Magnenat¹

I. INTRODUCTION

Mobile robots are interesting tools for education because of both the enthusiasm they raise and the multidisciplinary nature of their technology. Because autonomous mobile robots sense the environment and take actions based on their perception, they seem to display *intentions of their own*. This fascinates the users of the robot and creates feelings of accomplishment and power in the creators. The permeating presence of robots in science fiction and their projected use in our society increases these emotions by giving a sense of touching the future. Children can spend hours looking at a robot interacting with its environment and adults can approach robots as a new hobby that replaces radio and electronics kits. Robots embed various technologies and therefore give access to a wide range of fields, such as complex mechanics, sensors, wireless transmission, mathematics, computer science, etc. The emotional potential of mobile robots and their varied technology makes them the ideal tool for education at large.

Despite this potential, robots are still not widespread in schools as they could be and this for several reasons. Among them we can mention:

- 1) Although there are many robotic projects developing educational robots, few reach a sufficient maturity to become distributed and accessible to schools.
- 2) A robot performing interesting behaviors is a complex piece of technology and therefore expensive. Indeed, for having an educational value and providing an interesting level of interaction, a robot must embed a wide set of sensors and actuators. Existing platforms with these features cost several hundred Euros. This prevents most schools, which have a limited budget for equipment, to acquire interesting robots.

*This research was partially supported by the Swiss National Center of Competence in Research “Robotics” (Thymio robot development and deployment), partially by GebertRuf Stiftung (design of accessories), partially by the Swiss NSF project CRAGP2 151543 “Robotics in schools”, and partially by the EU-FP7 project ASSISIbf, no. 601074 (survey on open hardware). Many thank to Luc Bergeron and his team at cal.ch for the industrial design of Thymio; Didier Roy, David Sherman and all the INRIA team for their contributions and diffusion in France; Gordana Gerber for the educational material; all the Mobsya team for the effort in production and sale.

¹Francesco Mondada and Stéphane Magnenat are with the Laboratoire de Systèmes Robotiques, Ecole Polytechnique Fédérale de Lausanne (EPFL), Switzerland francesco.mondada@epfl.ch and stephane.magnenat@epfl.ch

²Michael Bonani and Fanny Riedo are with Mobsya Association, Ecublens, Switzerland michael.bonani@mobsya.org and fanny.riedo@mobsya.org

- 3) Introducing robotic tools into teaching activities requires investment in time and training for the teachers. In Europe, despite a trend in including more and more technological tools into the learning process, teachers are still insufficiently trained and are reluctant to introduce these tools in their teaching activity [1]. To be accepted by teachers, robots must be therefore both accessible with minimal effort and be associated with well prepared educational material. Moreover an infrastructure should allow the exchange of educational material among the teachers.
- 4) Robot construction, use, and programming is often perceived as a boyish activity in our society [2], [3]. This strongly limits the potential of robots as general-purpose educational tools, especially in schools.
- 5) Finally, many teachers are reluctant to follow volatile trends, especially if based on purely commercial arguments. Teachers prefer to invest in stable tools, and this is the opposite of todays consumer technology, often very volatile and based on continuos renewal rather than on durability.

Open source hardware projects can address several of these issues in a different way than pure commercial products. By open source hardware we understand, following the definition of the Open Source Hardware Association¹, “hardware whose design is made publicly available so that anyone can study, modify, distribute, make, and sell the design or hardware based on that design”. In this paper, we show that this concept, implemented as a project in a community of users, developers and producers, brings a very interesting added value to the robot and to the educational methods. This is illustrated by the results achieved with Thymio and is compared with the feedback of a group of engineers active in open source hardware design. We can well observe both similarities and differences between our education-centered project and other open source hardware projects, pointing to challenges and opportunities. More details on the robot and the related results can be found in [4], [5].

II. RELATED WORK

There is a very large number of publications presenting educational robots with different prices and features, from very low-cost systems targeting, for instance, education in Africa [6], [7] to extremely sophisticated humanoids [8], [9]. Among those, only very few are commercially available,

¹<http://www.oshwa.org/definition/>

limiting their validation by education scientists. This results in 90% of publications about validation of educational results made on LEGO Mindstorm [10]. The LEGO Mindstorm EV3² is expensive (~400 \$) but offers a wide range of possibilities, especially at the mechanical level using LEGO bricks and at the software level with its graphical programming environment. At a lower price, LEGO proposes the WeDo system (~80 \$). The WeDo is similar to EV3 but only reads one sensor and controls one actuator and must always be connected to a desktop computer. The BeeBot robot³ is a cheap (~90 \$) autonomous system. However, it is not a real robot but rather an automaton: There is no perception of the environment, just a good encoder for precise movements and a simple programming interface based on buttons giving directions for the movements.

Among these widely used robots, none is part of an open source hardware project. The only effort in this direction comes from LEGO, that made public all the schematics of the EV3 in an hardware developer kit, to allow the design of extensions. Otherwise, only few educational robots are both used in schools and are issued from an open hardware project: Scribbler2, produced and sold by Parallax⁴ (~180 \$), is a 188 mm large robot, designed to run on the ground and equipped with few light sensors, one distance sensor, two ground sensors and few LEDs display. It runs on standard AA batteries and has a hacker port for interfacing electronic extensions. It is programmable with a graphic or text code interface. The main weakness of Scribbler2 is its performance per price ratio and the limited compatibility with other systems. The e-puck [11] robot is a robot targeting university-level education. Well equipped with sensors and actuators, modular and compact, it can be programmed with professional environments. Several simulators allow to run experiments of high complexity. Its main weakness is its high price (~870 \$). Finch⁵ (~99 \$) is a very simple robot that has been designed around a wired connection to the computer. This connection reduces electronics requirements, such as batteries or wireless communication, and allows to implement the control entirely on the computer. This results in a very broad set of possible programming languages available, the real force of this robot. On the other hand the cable does not allow real autonomy and mobility of the robot. Finally the mBot⁶ is a mobile platform based on the Arduino board. The very cheap and simple electronics allow to drastically reduce the price of the system (~75 \$) but also reduces the perception possibilities to a couple of sensors.

In respect to these robots, Thymio has a compact size (120 mm), many interaction possibilities, an affordable price and a large set of sensors. Its design makes the best use of the recent cheap components coming from the explosive growth of the mobile devices market. To the best of our knowledge, beside Thymio there are no educational products

exploiting this and providing many sensors and actuators at a price below 130 \$.

For teachers, the motivation to use robotic tools in their classes depends on many factors [12]. Among them, the availability of material and training plays a key role. The BeeBot mentioned previously, because of its radical simplicity, is one of the tools that needs the least training. Moreover its use in learning activities is based on a simple grid on a printed mat on the ground, allowing fast and easy integration in existing lessons. These are probably two important factors for its success in schools [13], [14] and the availability of a rich set of educational material⁷. However, the total lack of sensors reduces the BeeBot to an automaton, easy to use but limited to very simple activities for young kids, without much potential in teaching computational thinking or robotics concepts.

For more complex robots, both the development of educational material and the training of teachers requires a very important effort, requiring a good mix between robotics and educational skills. Moreover, educational material changes very much from school to school, as education is very dependent from local educational programs and languages, for instance. In the particular case of Switzerland, for instance, every of the 26 states composing the confederation has its own school program and its own language among the four official ones. Educational material and the related training has therefore to be developed for each situation, which requires a huge effort. Even for large companies like LEGO this development is not affordable. A solution is to have an active community of users contributing to the development of the material in a distributed manner, adapting the material to the local situation. LEGO itself is moving in the direction of promoting communities of users [15] with a user-producer interaction close to those of open hardware projects. The open source community regrouping developers, producers and final users is therefore a very interesting model to address the distributed development and sharing of educational material, and the diffusion of training sessions. Communities around projects like Arduino are extremely good examples of this type of mechanism [16].

III. DESIGN CHOICES

We designed the Thymio robot along seven main axes: a low price to address a larger number of users, a feature set that suits both genders and multiple ages from young children to adults, a combination of sensors, actuators, and programming features that facilitates learning, a mechanical design that allows creative extensions by the users themselves, a set of ready-to-use behaviors to get a demonstration right out of the box, an accessible programming environment, and an open source community contributing to the design and disseminating the results. The result is a miniature (10 cm) differential-wheeled robot suited for use on a desktop. The robot is robust enough to be mishandled by children, as

²<http://mindstorms.lego.com>

³<http://www.beebot.org.uk>

⁴<http://www.parallax.com>

⁵<http://www.finchrobot.com/>

⁶<http://www.makeblock.cc/mbot/>

⁷<https://www.learningplace.com.au/deliver/content.asp?pid=38840> and
<http://beebots.skola.edu.mt/>




Fig. 1: The Thymio robot and its main components.

it can fall from a table without breaking itself. It features a translucent white hull and a wide range of sensors and actuators (see 1). The robot embeds a battery, rechargeable by USB, that provides an autonomy of about 2 hours.

We start by presenting here the first six main axes, before moving to the next section devoted the open hardware specificities.

A. Low Price

Our main concern during the mechatronic design of Thymio was to keep a low production cost. Price is a primary factor for the adoption of the robot by schools [17]. In our previous experience with designing robots, most of the costs was due to the electronics and the sensors [18], not to the mechanical parts. As we wanted Thymio to be an affordable robot, we selected electronic components with great care and explored different design solutions in order to limit the number of expensive components. In particular, we focused on low-cost sensors that allow rich interaction possibilities, with both the environment and the user. The resulting Thymio robot possesses a large number of sensors: Seven horizontal infrared distance sensors, with a range of about 13 cm. They enable many interactions with the environment, like following an object or avoiding an obstacle. Two ground infrared sensors allow to follow a line or to detect the edge of a table. A three-axis accelerometer measures the orientation of the robot with respect to gravity, and can detect shocks

and free falls. Five capacitive touch buttons organized as an arrow form an intuitive user interface. Compared to physical buttons, these simplify the plastic hull of the robot and make it more robust. A remote control receiver provides additional distant buttons. A microphone can record sounds and detect claps. Finally, a thermistor measures temperature. Most of these sensors cost less than 0.2 \$, the most expensive being the accelerometer with a cost of about 0.8 \$, which is an acceptable price given the possibilities it brings to the robot. The omnipresence of this type of sensors in smartphones and compact cameras has drastically lowered their prices over the last decade. We also chose low-cost toy motors and control them in speed (max. 13 cm/s) using a custom-designed electronics. By measuring the back-electromotive force, speed control is possible without additional encoders.

However, choosing the optimal combination of sensors and processor is a difficult problem, as hardware interfaces are limited on a microcontroller and therefore compromises must be made. We evaluated several microcontrollers and chose the PIC24F from Microchip because it integrates a USB interface and can drive capacitive touch buttons directly, saving additional components. This microcontroller controls all sensors and actuators, excepted the battery recharging logic, which uses a specific chip for safety reasons. This choice of a single microcontroller led us to non-trivial design decisions like using low-cost shift registers to drive the many LEDs. Moreover, instead of directly connecting the infrared sensors to an analogical input, we interface them using a comparator that transforms the analogical signal into a binary one with a pulse having a duration proportional to the intensity of the original signal [19]. This design saves CPU-time, reduces power consumption (it allows a shorter infrared pulse than with an analogical design) and allows to use the sensor for communication.

In addition, we conceived Thymio to fit the requirements of series production. This is a very critical choice in open source hardware projects, and we will discuss this issue in detail in the next section. We produced until now more than 10'000 robots by batches of 1'000 units. Because manual work is expensive in western countries, we produce through subcontractors in China. Indeed, while most of the electronics consists of SMD components mounted by a robot, some are soldered (sensors, microphone, LEDs) by hand and the robot is also assembled by hand. We streamlined the production of plastic parts (Thymio has only 5 parts while our previous prototype had 11) and opted for injection molding. The plastic hull consists of two main parts screwed together to facilitate the vertical assembly and disassembly of the robot. Moreover, when selecting features we took into consideration the complexity of the injection mold.

B. Multi-age and Gender-neutral Feature Set

While we optimized Thymio for cost, we also targeted a large range of users thanks to an important contribution by industrial designers of the University of Art and Design

of Lausanne⁸. The variety of sensors, the multiple ways of interacting with the robot, its hull design, and its customization make Thymio accessible to girls and boys of different age groups. The white hull is initially neutral and children can choose their own color using the RGB LEDs or attach accessories to the hull. The robot can be used from children as young as 6 years old to adults: The youngest play with the robot through a set of basic behaviors (see section III-E) and the older can program it (see section III-F). The different basic behaviors are selectable using the capacitive buttons and show some of the capabilities of the robot, such as obstacle avoidance, slope climbing, etc. By interacting with the different behaviors, for instance by blocking the robot with the hand and seeing it avoiding it, children can discover the concept of the sensory-motor loop. As every behavior has a different color, children can also understand that different *programs* run on the robot. Children around 6 can use Thymio as a support for handicrafts or construction. For example, they can create kinetic sculptures. For children above 9 years old and adults, Thymio is suited to introduce programming and robotics. Learners can start by programming new interactive behaviors and can go on with constructing around the robot and programming a behavior that interplays with the construction. High-school and university students can use the robot to learn advanced robotics concepts through the integration with ROS [20]. Teachers can use this flexibility of use to adapt the look and the behavior of Thymio to their teaching activities, or even introduce this adaptation as activity in handicraft or computer science lessons. Moreover users looking for additional hardware features can interface Thymio with other open hardware devices, such as computer boards⁹ or other robotic mechanics¹⁰. Finally, because of the open-source and open-hardware nature of the project, advanced programmers can improve their skills in C by modifying the firmware or in electronics by disassembling the robot.

C. Facilitating Learning

When designing Thymio, we took care of providing many incentives for the users to learn new things throughout their direct interaction with the robot. This translates into specific hardware and software choices.

At the hardware level, we render visible the activity of the sensors by adding a LED next to each of them, for a total of 39 LEDs. These LEDs locally color the hull and allow the user to see immediately where and when the robot perceives a change in its environment. There is a LED next to each proximity sensor that lights up as soon as an object is close enough to be seen, and shines brighter the closer the object gets. Similarly, a combination of blue and red LEDs show the temperature, and the infrared remote control receiver and the microphone both have LEDs that flash when they detect

something. On the top of the robot, a circle of 8 LEDs shows the 3D inclination of the robot thanks to the accelerometer. This circle is also used to reflect some of the behaviors of Thymio. Finally, two strong RGB LEDs color the whole top of the robot. In addition to a visual feedback, the capacitive buttons also have an acoustic feedback. The link between a sensor and its feedback can be turned off when programming the robot to use the LEDs and the loudspeaker for other purposes.

At the software level, our programming environment (see section III-F) provides a set of tools enabling beginners to discover progressively the basic rules of programming using a graphical interface, then the construction of a syntax by graphic blocs, and finally a full text-based coding environment with advanced debugging tools, such as real-time inspection of the variables of the robot and plotting features, providing a visual way to understand time-related concepts.

D. Promoting Creativity

We wanted the robot to be a starting point for the users to invent their own creations. Therefore, we thought Thymio as a support for handicrafts and constructions. Its white color is meant to be seen as a blank page that can be decorated and drawn upon, and its shape allows easy integration into a structure. The robot features a hole in its middle to insert a marker for drawing. It also has a slot for an SD card, allowing users to add their own sounds or to load a pre-compiled code by the simple insertion of a dedicated card.

The square format of the hull allows to use the robot as a base for driving the user's own constructions. To that end, Thymio is compatible with LEGO bricks: There are four attachment positions on the top of the robot and two LEGO Technics crosses on each side. Additionally, the two wheels have attach points, which permits to use them to actuate elements elsewhere in the structure (see Figure 2, third row left) or to lift the robot's own weight (see Figure 2, third row right). Therefore we chose more powerful motors than strictly necessary to move the robot around. The same fixation points used for LEGO bricks can be used to attach paper structures. Paper can allow to simply change the body shape and add some body movements, as illustrated in Figure 2 by the orca, opening and closing its mouth while moving forward or by the bat, moving its wings. But paper and cardboard can also radically change the locomotion principle, as illustrated in the second row of Figure 2 by the zombie, where the robot's wheel activate the legs. The paper structure can be also used to interact with the sensors, as illustrated in the second row of Figure 2 by the bear, who extends his paw in front of the sensors to drive its iceberg. The same fixation points can be used to attach 3D printed customized parts, as illustrated by the winder shown in the fourth row of Figure 2. Finally one can use paper to create environments, either flat with patterns that can be used in association to the ground sensors (see Figure 2 bottom) or 3D object, like the trees beside the zombie in Figure 2. Finally, it is also possible to link several Thymio by software, allowing the coordination of complex multi-Thymio robotic structures.

⁸<http://www.ecal.ch>

⁹Interface with a Raspberry PI under <https://www.thymio.org/en:thymioexplorer>

¹⁰Interaction with the Poppy open source hardware under https://youtu.be/0otXtF8J_Z4



Fig. 2: Examples of extensions of the Thymio basic robot with paper or cardboard body extensions (top four images), using LEGOTM structural extensions (third row), using 3D-printed extensions (fourth row) or using a printed environment (bottom).

mode	color	sensors	behavior
friendly	green	infrared (IR)	follows an object at distance
explorer	yellow	IR	moves avoiding obstacles
fearful	red	acc., IR	flees, notifies shocks and falls
investigator	cyan	IR	follows a black track
obedient	magenta	buttons, IR	follows moving orders
attentive	blue	mic.	moves following sound

TABLE I: The different basic behaviors with sensors used.

E. Short time to demo

Many existing robots need to be built or configured before having the first operational behavior. This is a barrier for many users and we wanted to avoid it carefully, having a robot able to show interesting behaviors right out of the box. Therefore Thymio provides 6 different basic behaviors (see table I), which are accessible as soon as the robot is started. These allow people encountering Thymio for the first time to immediately interact with it, while providing insights into the many possibilities of the robot. The behaviors are interactive and oriented towards the user. For each behavior, the robot's body has a different color, allowing the user to easily recognize it. The user can navigate between the colors with the buttons and select the behavior she/he wants to use. Basic behaviors can be exploited in a construction to create reactivity without the use of programming (see Figure 2, the top four paper creations can be used with basic behaviors).

F. Programming

Thymio runs the Aseba open-source programming environment [21]. Aseba is designed to enable novices to program robots easily. On the robot side, it provides a lightweight virtual machine that runs on microcontrollers like the PIC24F. A virtual machine allows instantaneous upload and safe execution of code. On the desktop side, Aseba provides an IDE which allows to program in a purely graphical mode, or using a scripting language (see Figure 3) or in a mixed way, assembling code in a graphical way using the Blockly environment¹¹.

The IDE integrates a help documentation¹². In addition, the wiki pages of the project provide tutorials on programming with Thymio and a detailed description of the programming interface.

Aseba integrates with ROS [20] through the *asebaros*¹³ bridge. ROS is one of the most widely used software framework in robotics research, and this integration allows to run sophisticated algorithms, such as simultaneous localization and mapping, in conjunction with Thymio. This makes the robot suitable for university-level education.

IV. OPEN SOURCE HARDWARE, CHOICES AND IMPACT

The choice of developing a robot within an open source hardware project has an impact on the robot design and the way this device is used in the community of users. In this

¹¹<https://developers.google.com/blockly/>

¹²currently English, French, and German

¹³<http://www.ros.org/wiki/asebaros>




Fig. 3: Aseba Studio, the integrated development environment




Fig. 4: Motivation of the people participating to the survey.

section we analyze more in detail the implications of this choice in the context of educational robotics. We compare these implications with the result of a survey we did among 25 people active in various open source hardware projects based on a worldwide call for contributions. Among these 25 people, 6 are project leaders, 10 are part of the core design team, 6 are contributors and 3 are enthusiastic users. 60% of these respondents are between 25 and 35 years old and 80% either work in an academic environment or are students.

A. Motivation

When asked about their motivation to participate to open source hardware projects, the people participating to the survey give as main motivation a link to their professional activity and to the specific project, followed by a more general motivation by the nature of the project and finally by the engineering practice. The more abstract goal of improving our society is mentioned only by few respondents.

In the Thymio project, most engineering contributors were hired for a research project developing the robot. Industrial designers also contributed as part of an institutional project. Therefore the link with the professional activity and the particular project is evident. On another side, the motivation of contributing to society is much stronger in our team, as developing a robot targeting education has a strong societal component.

It is more interesting to look at what people expect as benefits in participating in such a project. Most of the




Fig. 5: Motivation of the people participating to the survey.

answers mention impact, networking and learning. In these answers we can observe both a technological component in getting better results and impact, and a human-relations component that is not in the basic definition of open hardware but results from the community created around the project. People expect to work with other people to achieve more together, to create a network of competences or users, to learn through new experience and contacts.

In the Thymio project we had similar expectations. Working together with several partners was for everybody a win-win situation, and creating a community of users was the only solution to allow the development of high quality accessories and educational material. A wiki¹⁴ has been established as meeting point for the learners, the robot developers, and the teachers. It introduces the robot, explains the basic behaviors, gives access to the programming environment and its documentation, and provides code samples and examples of constructions. The wiki is open for editing by anyone, and although we initially provided most of the material, the other members of the community have started to contribute. One of the most important contribution to the wiki, in term of effort, has been its translation into four languages.

In addition to those elements, in our project we expected another important benefit from open hardware in term of image: we wanted a match between the non-profit nature of the project and the non-profit nature of education in general.

B. License of project and license of tools

When starting an open source hardware project, one of the typical questions is about which license to use when disseminating the project source files. We will not discuss this matter here, as it is a very common and well covered issue.

There is another licensing issue which is not well known and that we discovered very late in our project: the constraints of the license of the mechanical and electronic CAD tools. Indeed, asked about this issue, the participants to our survey seem generally not aware of the fact that CAD licenses can be very restrictive about the way the source files can be published. Around the half of respondents to our survey, also among the project leaders, state that they were not aware that this could be an issue, and only one third checked the license of their CAD software. Among the respondents, some stated that they did not check the license because they were sure

¹⁴<http://www.thymio.org>




Fig. 6: Awareness about CAD tool licenses limitations by people participating to the survey.

they can freely publish their design, but half of them are using software not allowing the publication of source files when using educational licenses, and all these respondents are academic or students. This issue is very serious, as most contributors of open source hardware projects are academic and use academic or educational licenses. Most licenses do not allow to use the design created with this version of the software for commercial activities. As producing or selling the product is part of the definition of open hardware, these licenses simply forbid publication under the standard open source hardware conditions.

To clarify this issue we contacted twelve of the major editors of mechanical CAD and PCB routing software. We asked them if their educational license allows the publication of the source files, and we specified that the published files could have been downloaded by a company to produce the system for commercial purposes. Figure 7 summarizes the result of this survey. Only three of the twelve editors have education licenses allowing this type of publication. Two others explicitly mentioned the possibility to ask for permission before publication. A large mechanical CAD editor was puzzled by our questions and after realizing the impact of the license, introduced a special condition allowing publication of files in clearly labeled open source hardware projects. In previous situations of open source publication, the same editor asked the universities to purchase commercial licenses to permit publication. This can multiply by a factor of some hundreds the price of the CAD license. This blocking factor for open hardware also apply to the publication of scientific results, as promoted by many governments in the last decade and generally called “open science”. The change of policy in CAD files publication that we obtained is a sign of the very positive trend set by open hardware and by open science in general.

As a conclusion, this legal issue is totally underestimated by both people participating to the projects and by the CAD editors. In a period where editors are looking for additional revenues and are attacking universities for misuse of licenses¹⁵, this can be a very dangerous situation.

¹⁵We are aware, just in Switzerland, of two situations where large amounts of money are asked to universities for non-respect of software licenses.

mechanics PCB design	Software	Editor	Free publication of source files from educational license	Explicit mention of possible publication after editor approval	Publication needs research or commercial license	Price increase between the educational license and one allowing publication
<input checked="" type="radio"/>	AUTOCAD or INVENTOR	AUTODESK	YES			0%
<input checked="" type="radio"/>	Diptrace	Diptrace	YES			0%
<input checked="" type="radio"/>	Eagle	CADsoftUSA	YES*			0%
<input checked="" type="radio"/>	CREO	PTC	NO	YES**		0%
<input checked="" type="radio"/>	Allegro PCB design	Europractice / Cadence	NO	YES		0%
<input checked="" type="radio"/>	Targa3001	Ing.-Büro FRIEDRICH	NO	YES		0%
<input checked="" type="radio"/>	Altium Designer	Altium	NO	NO	YES***	193%
<input checked="" type="radio"/>	Varicad	Varicad	NO	NO	YES	658%
<input checked="" type="radio"/>	Cobalt	Ashlar	NO	NO	YES	875%
<input checked="" type="radio"/>	Vectorworks Fundamentals	Vectorworks	Not answered after two months			
<input checked="" type="radio"/>	CATIA or SolidWorks	Dassault Systems	Final answer not arrived in two months			
<input checked="" type="radio"/>	NX or SolidEdge	Siemens	Legal staff too busy to answer in two months			

* if explicit open source license
** approval automatically granted for open source and European research projects
*** academic package can include a commercial license

Reaction to this survey

Fig. 7: Publication possibilities as function of the CAD editors, situation in February 2016.

C. Who designs and produces the hardware

Among the fundamental choices when starting an open source hardware project, there is the choice of the type of production. In the definition of open hardware we gave, it is stated that one should offer an “hardware whose design is made publicly available so that anyone can ... make... the ... hardware”. Behind the “anyone” should we consider every single person or only companies able to produce the product? This choice has implications on who designs the system and how. In our project we have two different types of hardware: the robot itself and the accessories used in specific activities. The robot is the expensive part and has a very neutral design, allowing adaptation to specific situations. This adaptation is achieved by custom accessories that increase the attraction of the robot in its specific role, enabling activity for different ages and genders.

For the robot itself we opted for the second interpretation of the definition, considering under “anyone” only the professional structures able to produce hardware in a professional way, for a reason of price and complexity of the product. When looking for the best performance per price ratio, we decided to use techniques that require heavy equipment. For instance we decided to produce all mechanical parts by injection molds. This ensures a price per part of some cents, which cannot be achieved by others techniques. Letting end-user produce their own parts would result in higher prices for less performances. This choice has another implication: only a core team of highly skilled engineers can contribute to the project. It is not trivial to design a mechanical part that can be molded in the simplest possible way.

For the accessories, less technically challenging and stronger linked with creativity and educational value, we promoted techniques that are accessible to “anyone” in the broader sense: paper, cardboard, LEGO constructions and 3D printing, as explained in section III-D and illustrated in Figure 2. This allows a much broader spectrum of contributor, especially among the teachers.

When looking at the results of the survey (see Figure 8), we can observe that the most common production method




Fig. 8: Production methods in the projects mentioned by the people participating to the survey.

is a centralized one by commercial companies. Indeed, large open source hardware projects like Arduino are based on this model. One could advocate that this choice of central production and sale of hardware can bring these robotic projects closer to standard commercial models, ending in users not involved in the project and not feeling close to the developers. In our case we decided to counterbalance this apparently business oriented model by creating a non-profit association, called Mobsya, in charge of producing and selling the robots. This is also a very well represented production method in our survey. Of course anybody else could produce the Thymio based on more business-oriented models, but at least the initial production has been done respecting a coherent and global non-profit strategy, in line with educational values of the community of users. Moreover the user are better integrated is the second layer of open source hardware consisting in accessories, where anybody can contribute with own designs.

Another strong difference between a standard consumer product and our vision of open hardware, is that Thymio should be durable. Schools do not have large budget for technological tools and make strong investment in training of their teachers when adopting a new tool. Therefore the life time of the products should be as long as possible. The open hardware approach gives to the user, or to a generic technician, better conditions to repair the system. Supporting this type of operation has an impact on the robot design; for instance Thymio can be easily opened with four standard screws, and we introduced connectors between key elements such as motors, speaker, or the battery and the main printed circuit.

Another key element in supporting repair by the users are the calibration methods. When choosing very low cost components, we get into large dispersion of characteristics. In our case, for instance, the motors can have very different characteristics, resulting in the robot not going straight when asked to apply the same speed on both wheels. To correct this, one interesting solution is to introduce factory calibration, storing correction factors that are specific for each robot, in the microcontroller memory . To allow the user to replace a broken motor, it is essential to give him also the possibility to re-calibrate the robot and adjust the parameters of the new motors. In Thymio, this results in the

design and the documentation of calibration processes that can be performed by anyone, getting close to the original definition of open source hardware.

D. Validated added value of open source hardware

Beside the sale of more than 10'000 robots by a non-profit organization producing it, there are several elements that show a specific advantage of having chosen an open source hardware model. The first element is the very high acceptance of the robot by universities and their offices in charge of promotion of science. Although these are not the primary user targeted by the robot, these are institutions with high visibility and influence on school programs. In particular INRIA in France and the University of Cambridge in the United Kingdoms decided to use Thymio as tool for promotion of their activities and introduced it into schools. In France, INRIA developed several teaching units and supported the training of more than 1000 teachers to the use of this particular robot. This finally resulted in having the Thymio robot included as one of the reference tools for the education of digital science in the reference books of the French Academy of Science and its foundation for promotion of science in education, "La main à la pâte." The fact that Thymio is open source allows these institution to have a better control on the tool they use, as they can ensure maintenance and even further development of it.

In some cases, the open source nature of this project was a crucial political argument for the choice of this platform. In the state of Geneva, the government decided to move toward open source non proprietary tools in education. All primary school- and most secondary school computers have been installed with the Ubuntu distribution of Linux. On this operating system the LEGO Mindstorms software tools are not available, and their proprietary nature is not compatible with the philosophy dictated by the government. Thymio was therefore extremely welcome, and the state of Geneva organized own training courses for teachers, ported several educational materials into their curriculum and organized a lending system for all schools that cannot afford to buy the robots.

Finally the non-profit nature of the project, including the production infrastructure, has contributed to reduce the obstacle toward the acquisition of this platform for many schools, especially at the beginning of the process.

E. Problems of open-source project

The very specific structure of an open project has also drawbacks. Asked about problems met in the project, the participants to our survey mention the management of the community, the evolution of the project, the efforts in documentation, production and distribution and the limited resources. There are here two kind of problems: one of management of people, the other in the development of the project after the first design. The management of the project seems a recurrent problem and is related to the nature of this type of structure, mainly built by academic people with engineering background. Most of the projects, following our




Fig. 9: Problems observed by participants to open source hardware projects.

Description	Price (USD)
electronic components	15 \$
microcontroller	4 \$
motors	2 \$
plastic parts (hull, wheels, and light guides)	4 \$
assembling	8 \$
transport	2 \$
Total	35 \$

TABLE II: Production cost of Thymio.

survey, are managed by the founder of the initiative and not by the most expert in the field, which is perhaps not the best objective choice. It is very difficult to evolve from a phase where the engineering is the core of the project, to a new phase where communication and management play an increasing role. The same holds for several other factors, like the efforts in documenting, producing and distributing the product. Also here there is a change of activity from the very appealing design phase, to a phase of documentation and, in some cases, production and distribution which is not at all the same work and requires different skills. This requires extra efforts and motivation, which are often missing, especially for jobs like documentation that are not appreciated by engineers. In general many respondents to our survey identified the development of the project as a general issue, which summarizes the several aspects mentioned above.

In the Thymio project we had very similar issues and tried to address them by having several partners, each of them specialized in one aspect: design, production and sale, creation of educational material, etc. Despite this approach, we had also problems of management of the community, and issues in finding the right long term vision, especially having so many partners. The long term vision of a sales person is not the same of an engineer, and those confrontation result in conflicts in a community with a very flat hierarchy. A key element that allowed to keep cohesion in our community was to share, among all partners, strong basic values about improvement of society through education.

XXXXXX historical, should we keep this?

We reached our price target thanks to our careful selection of components and our production in China. Thymio costs 35 \$ per unit to produce in batch of 1k units (see II), with fixed fees of 15 k \$ (13 k \$ for the mold and 2 k \$ for the CE certification). This allows a selling price of 100 CHF (\approx

106 \$). This small ratio of selling-over-production price is made possible by our non-profit business model.

XXXXXX end of historical

V. CONCLUSION

The introduction of robots in formal education is a very challenging task, not only because of technical requirements such as low cost, performances and interactivity, but also because of factors depending on the school environment, such as the diversity of the educational programs, the dependence on local structures and languages, or the required training of teachers. Most of the current robotic tools for education capitalize upon existing hardware platforms, programming environments, or robot architectures. Because they do not consider all elements at stake, these tools fail to meet some challenges of the field. On the contrary, in this paper we presented a global approach that tackles these questions in a holistic way, based on open source and non-profit principles. The result is the Thymio robot and its surrounding open source community including engineers, art designers, production and sales people, and teachers. The open source hardware and the related contributions are split in two categories: the robot itself, produced by a non-profit organization and requiring very advanced skills in both design and production, and the accessories for activities, based on techniques broadly accessible and with a larger panel of contributors.

By making a survey among a panel of people contributing to open source hardware projects, we could observe that our project shares some characteristics with the majority of the projects represented in the survey. We also had problems of management of the community, we chose production and distributions methods that are broadly applied, and we share most of the motivation elements that are behind other projects. We identified an underestimated legal issue for open source hardware projects in the licensing term of CAD software. Indeed only very few editors have licenses allowing the publication of source files created with educational license. Two surveys among the users and the CAD editors shows that both people contributing or leading open source hardware projects and the editors themselves are now aware of this issue. Finally we could show some elements that differentiate our project from other open source hardware ones, being specific to educational robotics. In particular our project takes advantage from an alignment between the principles underlying open source project and the nature of education institutions. This fits with a political trend toward open source in education and in science in general. We also found a solution to the struggling question of production methods by splitting our hardware in two categories, enabling both very advanced hardware and inclusion of a broad community of end users. This addresses durability of equipment and gender issues that are critical in education.

REFERENCES

- [1] CERI, "New millennium learners," in *OECD/CERI International Conference "Learning in the 21st Century: Research, Innovation and Policy"*, OECD, 2008.

- [2] L. Leonard, "LEGO® MINDSTORMS® for Schools in Early Years Education," in *Kreativität und Innovationskompetenz im digitalen Netz: Wie kommt das „Neue“ mit Hilfe von Internettechnologien in die Welt?* (V. H.-P. und Michaela Luckmann, ed.), ch. 8, pp. 316–324, Salzburg Research, 2009.
- [3] I. Nourbakhsh, "Robot diaries: Creative technology fluency for middle school girls [education]," *Robotics & Automation Magazine, IEEE*, vol. 16, no. 1, pp. 16–18, 2009.
- [4] F. Riedo, *Thymio: a holistic approach to designing accessible educational robots*. PhD thesis, STI, Lausanne, 2015.
- [5] S. Magnenat, J. Shin, F. Riedo, R. Siegwart, and M. Ben-Ari, "Teaching a core cs concept through robotics," in *Proceedings of the 2014 Conference on Innovation & Technology in Computer Science Education, ITiCSE '14*, (New York, USA), pp. 315–320, ACM, 2014.
- [6] M. Rubenstein, B. Cimino, and R. Nagpal, "AERobot : An Affordable One-Robot-Per-Student System for Early Robotics Education," in *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 6107–6113, 2015.
- [7] E. B. B. Gyebi, M. Hanheide, and G. Cielniak, "Affordable Mobile Robotic Platforms for Teaching Computer Science at African Universities," in *Proceedings of the 6th International Conference on Robotics in Education*, (Yverdon-les-Bains), 2015.
- [8] D. Hood, S. Lemaignan, and P. Dillenbourg, "When children teach a robot to write: an autonomous teachable humanoid which uses simulated handwriting," in *International Conference for Human-Robot Interaction HRI '15*, pp. 83–90, 2015.
- [9] E. Mazzoni and M. Benvenuti, "A Robot-Partner for Preschool Children Learning English Using Socio-Cognitive Conflict," vol. 18, no. 4, pp. 474–485, 2016.
- [10] F. B. V. Benitti, "Exploring the educational potential of robotics in schools: A systematic review," *Computers & Education*, vol. 58, no. 3, pp. 978–988, 2012.
- [11] F. Mondada, M. Bonani, X. Raemy, J. Pugh, C. Cianci, A. Klaptoz, S. Magnenat, J.-C. Zufferey, D. Floreano, and A. Martinoli, "The e-puck, a robot designed for education in engineering," in *Proceedings of the 9th conference on autonomous robot systems and competitions*, vol. 1, pp. 59–65, IPCB: Instituto Politécnico de Castelo Branco, 2009.
- [12] M. Chevalier, F. Riedo, and F. Mondada, "How do teachers perceive educational robots in formal education? a study based on the thymio robot," *Robotics & Automation Magazine, IEEE*, 2016.
- [13] K. Highfield, J. Mulligan, and J. Hedberg, "Early mathematics learning through exploration with programable toys," in *Proceedings of the Joint Conference Psychology of Mathematics Education (PME 32-PMEENAXXX)*, pp. 17–21, 2008.
- [14] M. Demichele, G. Demo, and S. Siega, "A piedmont schoolnet for a k-12 mini-robots programming project: Experiences in primary schools," in *Workshop Proceedings of Int'l. Conf. on Simulation, Modeling and Programming for Autonomous Robots (SIMPAR 2010)*, 2008.
- [15] C. Hienerth, C. Lettl, and P. Keinz, "Synergies among producer firms, lead users, and user communities: The case of the LEGO producer-user ecosystem," *Journal of Product Innovation Management*, vol. 31, no. 4, pp. 848–866, 2014.
- [16] P. Jamieson, "Arduino for teaching embedded systems. are computer scientists and engineering educators missing the boat?," in *Proceeding of the 2010 International Conference on Frontiers in Education: Computer Science and Computer Engineering*, pp. 289–294, 2010.
- [17] S. Kradolfer, S. Dubois, F. Riedo, F. Mondada, and F. Fassa, "A sociological contribution to understanding the use of robots in schools: the thymio robot," in *Social Robotics*, pp. 217–228, Springer, 2014.
- [18] M. Bonani, *Robotique collective et auto-assemblage*. PhD thesis, École Polytechnique Fédérale de Lausanne, Lausanne, 2010.
- [19] A. Kettler, M. Szymanski, J. Liedke, and H. Wörn, "Introducing wanda - a new robot for research, education, and arts," in *Intelligent Robots and Systems (IROS), 2010 IEEE/RSJ International Conference on*, pp. 4181–4186, October 2010.
- [20] M. Quigley, K. Conley, B. Gerkey, J. Faust, T. Foote, J. Leibs, R. Wheeler, and A. Ng, "ROS: an open-source Robot Operating System," in *ICRA Workshop on Open Source Software*, IEEE Press, 2009.
- [21] S. Magnenat, P. Réturnaz, M. Bonani, V. Longchamp, and F. Mondada, "ASEBA: A Modular Architecture for Event-Based Control of Complex Robots," *IEEE/ASME Transactions on Mechatronics*, no. 99, pp. 1–9, 2010.