

# Formal Methods - 03\_Temporal\_Logics

Francesco Penasa

February 22, 2020

material lect 03 2020/02/21:

HANDOUTS : [http://disi.unitn.it/~rseba/DIDATTICA/fm2020/03\\_TEMPORAL\\_LOGICS\\_HANDOUT.pdf](http://disi.unitn.it/~rseba/DIDATTICA/fm2020/03_TEMPORAL_LOGICS_HANDOUT.pdf)

SLIDES : [http://disi.unitn.it/~rseba/DIDATTICA/fm2020/03\\_TEMPORAL\\_LOGICS\\_SLIDES.pdf](http://disi.unitn.it/~rseba/DIDATTICA/fm2020/03_TEMPORAL_LOGICS_SLIDES.pdf)

## 1 Boolean logic

TRUE; FALSE;

1. Boolean formula:  $\top = true$   $\perp = false$
2. Atoms( $\phi$ ): the set of atoms occurring in  $\phi$
3. Literal
4. Clause  $\vee_j l_j$  (disjunction)
5. Cube  $\wedge_j l_j$  (conjunction)

$$(A_1 \rightarrow A_2) \leftrightarrow (\neg A_1 \vee A_2)$$

$$XOR \Rightarrow \neg(A_1 \leftrightarrow A_2) \Leftrightarrow (A_1 \vee A_2) \wedge (\neg A_1 \vee \neg A_2)$$

Directed Acyclic Graph (DAG) representation of boolean formulas can be up to exponentially smaller than trees.

### 1.1 Basic notation & definitions

**Total truth assignment:** all atoms have to be assigned

**Partial Truth assignment** lazy evaluation of boolean, we just require to have the atoms needed for the satisfiability about the others we don't care. Actually, all of his extensions to total truth assignment satisfy the formula.  $\phi$  is **satisfiable** iff  $\mu \models \phi$  for some  $\mu$   $\phi_1$  **entails**  $\phi_2$  ( $\phi_1 \models \phi_2$ ): iff  $\mu \models \phi_1 \Rightarrow \mu \models \phi_2$  for every  $\mu$   $\phi$  **is entails** ( $\models \phi$ ): iff  $\mu \models \phi$  for every  $\mu$   $\phi$  is valid  $\Leftrightarrow \neg\phi$  is not satisfiable

## 1.2 Equivalence and equi-satisfiability

When we use **validity-preserving transformation**

$\phi_1$  and  $\phi_2$  are **equivalent** iff for every  $\mu$ ,  $\mu \models \phi_1$  iff  $\mu \models \phi_2$

When we use **satisfiability-preserving transformation**

$\phi_1$  and  $\phi_2$  are **equi-satisfiable** iff exists  $\mu_1$  s.t.  $\mu_1 \models \phi_1$  iff exists  $\mu_2$  s.t.  $\mu_2 \models \phi_2$

equi-satisfiable tells us nothing about the relations of the two models.

## 1.3 Complexity

For  $N$  variables, there are up to  $2^N$  truth assignments to be checked

## 1.4 POLARITY

intuition:  $\phi_1$  occurs positively [negatively] in  $\phi$  iff it occurs under the scope of an (implicit) even [odd] number of negations. **If we transform the formula, we watch where if there is a lnot or if it is positive.**

**Polarity: the number of nested negations modulo 2**

## 1.5 Substitution principle

$$\phi[\phi_1|\phi_2]$$

we substitute in  $\phi$ ,  $\phi_2$  over all occurrences of  $\phi_1$ .

1. if equivalent then guess, it is easy
2. if entails, then it entails but only if applied on something that occurs only positively.

### 1.5.1 Negative normal form (NNF)

If it is formed only by  $\wedge$  and  $\vee$  to literals

1. substitute all implications ( $\rightarrow$  and  $\leftrightarrow$ )
2. push down negations to the literals  $\neg(A_1 \vee A_2) \Rightarrow (\neg A_1 \wedge \neg A_2)$

The reduction to NNF is linear if it is represented as a DAG and the equivalence is preserved.

### 1.5.2 Conjunctive normal form (CNF)

$$\bigwedge_{i=1}^L \bigvee_{j_i=1}^{K_i} l_{j_i}$$

### Classic CNF conversion

1. convert to NNF
2. apply recursively the Demorgan's Rule:

$$(\phi_1 \wedge \phi_2) \vee \phi_3 \Rightarrow (\phi_1 \vee \phi_3) \wedge (\phi_2 \vee \phi_3)$$

3. exponential time
4. but equivalent

**Labeling CNF conversion** We use some alias to reduce the complexity

1. linear time
2. equi-satisfiable

Of course further optimizations can be executed.

## 2 Questions

POLARITY third point slide 14/108