

Statistical mechanics of autoregressive models: towards a theory of Self-Attention

Francesco D'Amico

Supervisors:

Matteo Negri

Chiara Cammarota



SAPIENZA
UNIVERSITÀ DI ROMA

Dipartimento di Fisica

PhD talks, October 16, 2025

Outline of the talk

1 Introduction

- Associative memories (Hopfield networks)
- Self-Attention and LLMs

2 Our results

- Self-Attention as pseudolikelihood optimization
- Pseudolikelihood produces associative memories
- Vector-spin associative memories

3 Next steps

Introduction

- Associative memories (Hopfield networks)
- Self-Attention and LLMs

Associative memories (Hopfield networks)

- Network of N binary neurons, $\vec{\sigma} \in \{-1, +1\}^N$



$$H = - \sum_{(i,j)} J_{ij} \sigma_i \sigma_j \quad , \quad J_{ij} := \frac{1}{N} \sum_{\mu}^P \xi_i^{\mu} \xi_j^{\mu} \quad \leftarrow \text{Hebb's rule}$$

Associative memories (Hopfield networks)

- Network of N binary neurons, $\vec{\sigma} \in \{-1, +1\}^N$



$$H = - \sum_{(i,j)}^N J_{ij} \sigma_i \sigma_j \quad , \quad J_{ij} := \frac{1}{N} \sum_{\mu}^P \xi_i^{\mu} \xi_j^{\mu} \quad \leftarrow \text{Hebb's rule}$$

- P random *patterns* $\vec{\xi}^{\mu} \in \{-1, +1\}^N$ are the *memories*
- $\alpha = \frac{P}{N}$ is the control parameter

Associative memories (Hopfield networks)

- Network of N binary neurons, $\vec{\sigma} \in \{-1, +1\}^N$



$$H = - \sum_{(i,j)}^N J_{ij} \sigma_i \sigma_j \quad , \quad J_{ij} := \frac{1}{N} \sum_{\mu}^P \xi_i^{\mu} \xi_j^{\mu} \quad \leftarrow \text{Hebb's rule}$$

- P random *patterns* $\vec{\xi}^{\mu} \in \{-1, +1\}^N$ are the *memories*
- $\alpha = \frac{P}{N}$ is the control parameter
- $T=0$ dynamical rule:

$$\sigma_i(t + \Delta t) = \text{sign} \left[\sum_{j(\neq i)} J_{ij} \sigma_j(t) \right]$$

Associative memories (Hopfield networks)

$$\xi_i^\mu = \text{sign} \left[\xi_i^\mu + \mathcal{O} \left(\sqrt{\frac{P}{N}} \right) \right] \Rightarrow \text{memories are fixed points of dynamics}$$

Associative memories (Hopfield networks)

$$\xi_i^\mu = \text{sign} \left[\xi_i^\mu + \mathcal{O} \left(\sqrt{\frac{P}{N}} \right) \right] \Rightarrow \text{memories are fixed points of dynamics}$$




Associative memories (Hopfield networks)

$$\xi_i^\mu = \text{sign} \left[\xi_i^\mu + \mathcal{O} \left(\sqrt{\frac{P}{N}} \right) \right] \Rightarrow \text{memories are fixed points of dynamics}$$



Input




Associative memories (Hopfield networks)

$$\xi_i^\mu = \text{sign} \left[\xi_i^\mu + \mathcal{O} \left(\sqrt{\frac{P}{N}} \right) \right] \Rightarrow \text{memories are fixed points of dynamics}$$



Input



Retrieval




Associative memories (Hopfield networks)

$$\xi_i^\mu = \text{sign} \left[\xi_i^\mu + \mathcal{O} \left(\sqrt{\frac{P}{N}} \right) \right] \Rightarrow \text{memories are fixed points of dynamics}$$



Input




Retrieval



Phase diagram of retrieval


Amit et al. (1987)

Statistical Mechanics of Neural Networks Near Saturation



Self-Attention and LLMs


- Transformer architecture:
Vaswani et al. (2017) Attention Is All You Need



Self-Attention and LLMs

- Transformer architecture:
Vaswani et al. (2017) Attention Is All You Need
- Input and output: N vectors in d dimension

$$\{\vec{X}_i\}_{i=1,\dots,N} ; \vec{X}_i \in \mathbb{R}^d$$



Self-Attention and LLMs


- Transformer architecture:
Vaswani et al. (2017) Attention Is All You Need
- Input and output: N vectors in d dimension

$$\{\vec{X}_i\}_{i=1,\dots,N}; \vec{X}_i \in \mathbb{R}^d$$

- Building block: Self-Attention layer

$$\vec{X}_i^{\text{out}} = \sum_{j=1}^N \text{softmax}_j \left[\left(\mathbf{K} \vec{X}_i \right)^T \left(\mathbf{Q} \vec{X}_j \right) \right] \mathbf{V} \vec{X}_j$$

$\mathbf{K}, \mathbf{Q} \in \mathbb{R}^{r \times d}$, $\mathbf{V} \in \mathbb{R}^{d \times d}$ are learnable matrices



Self-Attention and LLMs

- Transformer architecture:
Vaswani et al. (2017) Attention Is All You Need
- Input and output: N vectors in d dimension

$$\{\vec{X}_i\}_{i=1,\dots,N}; \vec{X}_i \in \mathbb{R}^d$$


- Building block: Self-Attention layer

$$\vec{X}_i^{\text{out}} = \sum_{j=1}^N \text{softmax}_j \left[\left(\mathbf{K} \vec{X}_i \right)^T \left(\mathbf{Q} \vec{X}_j \right) \right] \mathbf{V} \vec{X}_j$$

$\mathbf{K}, \mathbf{Q} \in \mathbb{R}^{r \times d}$, $\mathbf{V} \in \mathbb{R}^{d \times d}$ are learnable matrices


- Simplified version: $\mathbf{K}^T \cdot \mathbf{Q} = \mathbf{V} = \mathbf{J}$

$$\vec{X}_i^{\text{out}} = \sum_{j=1}^N \text{softmax}_j \left[\vec{X}_i^T \mathbf{J} \vec{X}_j \right] \mathbf{J} \vec{X}_j$$




Self-Attention and LLMs

GPT models: autoregressive task in language



Self-Attention and LLMs

GPT models: autoregressive task in language



State-of-the-art of Large Language Models (LLMs)

Our work

- Self-Attention as pseudolikelihood optimization
- Pseudolikelihood produces associative memories
- Vector-spin associative memories

Self-Attention as pseudolikelihood optimization

Self-attention as an attractor network: transient memories without backpropagation

1st Francesco D'Amico

2nd Matteo Negri

- Layer of simplified Self-Attention: weights tensor $\mathbb{J} \in \mathbb{R}^{N \times N \times d \times d}$

$$\vec{X}_i^{t+1} = \sum_{j(\neq i)} \alpha_{i \leftarrow j} \mathbf{J}_{ij} \vec{X}_j^t \quad (1)$$

$$\alpha_{i \leftarrow j} = \text{softmax}_j \left[\lambda \vec{X}_i^t \cdot \mathbf{J}_{ij} \vec{X}_j^t \right] \quad (2)$$

Self-Attention as pseudolikelihood optimization

Self-attention as an attractor network: transient memories without backpropagation

1st Francesco D'Amico

2nd Matteo Negri

- Layer of simplified Self-Attention: weights tensor $\mathbb{J} \in \mathbb{R}^{N \times N \times d \times d}$

$$\vec{X}_i^{t+1} = \sum_{j(\neq i)} \alpha_{i \leftarrow j} \mathbf{J}_{ij} \vec{X}_j^t \quad (1)$$

$$\alpha_{i \leftarrow j} = \text{softmax}_j \left[\lambda \vec{X}_i^t \cdot \mathbf{J}_{ij} \vec{X}_j^t \right] \quad (2)$$

- t layer index \rightarrow promoted to time index

Self-Attention as pseudolikelihood optimization

Self-attention as an attractor network: transient memories without backpropagation

1st Francesco D'Amico

2nd Matteo Negri

- Layer of simplified Self-Attention: weights tensor $\mathbb{J} \in \mathbb{R}^{N \times N \times d \times d}$

$$\vec{X}_i^{t+1} = \sum_{j(\neq i)} \alpha_{i \leftarrow j} \mathbf{J}_{ij} \vec{X}_j^t \quad (1)$$

$$\alpha_{i \leftarrow j} = \text{softmax}_j \left[\lambda \vec{X}_i^t \cdot \mathbf{J}_{ij} \vec{X}_j^t \right] \quad (2)$$

- t layer index \rightarrow promoted to time index
- Eq. 1: minimization dynamics of cost

$$F(\{\vec{X}_i\}; J) = -\frac{1}{\lambda} \sum_i \log \left[\sum_{j(\neq i)} \exp(\lambda \vec{X}_i \cdot \mathbf{J}_{ij} \vec{X}_j) \right] = \sum_i e_i(\{\vec{X}_i\}; \mathbb{J}) \quad (3)$$

Self-Attention as pseudolikelihood optimization

Self-attention as an attractor network: transient memories without backpropagation

1st Francesco D'Amico

2nd Matteo Negri

- Layer of simplified Self-Attention: weights tensor $\mathbb{J} \in \mathbb{R}^{N \times N \times d \times d}$

$$\vec{X}_i^{t+1} = \sum_{j(\neq i)} \alpha_{i \leftarrow j} \mathbf{J}_{ij} \vec{X}_j^t \quad (1)$$

$$\alpha_{i \leftarrow j} = \text{softmax}_j \left[\lambda \vec{X}_i^t \cdot \mathbf{J}_{ij} \vec{X}_j^t \right] \quad (2)$$

- t layer index \rightarrow promoted to time index
- Eq. 1: minimization dynamics of cost

$$F(\{\vec{X}_i\}; J) = -\frac{1}{\lambda} \sum_i \log \left[\sum_{j(\neq i)} \exp(\lambda \vec{X}_i \cdot \mathbf{J}_{ij} \vec{X}_j) \right] = \sum_i e_i(\{\vec{X}_i\}; \mathbb{J}) \quad (3)$$

$$\vec{X}_i^{t+1} = -\nabla_{\vec{X}} F(\{\vec{X}_i\}; J) \quad (4)$$

Pseudolikelihood produces associative memories

Step back:

What happens for the simplest possible model trained with pseudolikelihood?

Pseudolikelihood produces associative memories

Step back:

What happens for the simplest possible model trained with pseudolikelihood?



**Pseudo-likelihood produces associative memories able to generalize,
even for asymmetric couplings**

Francesco D'Amico,^{1,2} Dario Bocchi,^{1,2} Luca Maria Del Bono,^{1,2} Saverio Rossi,¹ and Matteo Negri^{1,2}

¹*Physics Department, Sapienza University of Rome, Piazzale Aldo Moro 5, 00185 Rome, Italy*

²*Institute of Nanotechnology, National Research Council of Italy, CNR-NANOTEC, Rome Unit*

Pseudolikelihood produces associative memories

Pseudolikelihood on random data: same setting as Hopfield

Pseudolikelihood produces associative memories

Pseudolikelihood on random data: same setting as Hopfield

- N neurons, $\vec{\sigma} \in \{\pm 1\}^N$, T=0 dynamics:
$$\sigma_i(t + \Delta t) = \text{sign} \left[\sum_{j(\neq i)} J_{ij} \sigma_j(t) \right]$$
- P random memories $\vec{\xi}^\mu \in \{\pm 1\}^N$, $\alpha = \frac{P}{N}$ control parameter

Pseudolikelihood produces associative memories

Pseudolikelihood on random data: same setting as Hopfield

- N neurons, $\vec{\sigma} \in \{\pm 1\}^N$, T=0 dynamics:
 $\sigma_i(t + \Delta t) = \text{sign} \left[\sum_{j(\neq i)} J_{ij} \sigma_j(t) \right]$
- P random memories $\vec{\xi}^\mu \in \{\pm 1\}^N$, $\alpha = \frac{P}{N}$ control parameter
- J_{ij} as negative log-pseudolikelihood minimizer at fixed $\|\mathbf{J}\| = \lambda$

$$NLP = \sum_{i=1}^N \ell_i(J_i) = \sum_{i=1}^N \sum_{\mu=1}^P \log \left(1 + e^{-\xi_i^\mu \sum_{j \neq i} J_{ij} \xi_j^\mu} \right)$$

Pseudolikelihood produces associative memories

Pseudolikelihood on random data: same setting as Hopfield

- N neurons, $\vec{\sigma} \in \{\pm 1\}^N$, T=0 dynamics:
 $\sigma_i(t + \Delta t) = \text{sign} \left[\sum_{j \neq i} J_{ij} \sigma_j(t) \right]$
- P random memories $\vec{\xi}^\mu \in \{\pm 1\}^N$, $\alpha = \frac{P}{N}$ control parameter
- J_{ij} as negative log-pseudolikelihood minimizer at fixed $\|\mathbf{J}\| = \lambda$

$$NLP = \sum_{i=1}^N \ell_i(J_i) = \sum_{i=1}^N \sum_{\mu=1}^P \log \left(1 + e^{-\xi_i^\mu \sum_{j \neq i} J_{ij} \xi_j^\mu} \right)$$

- Quantity of interest: stabilities


$$\Delta_i^\mu = \xi_i^\mu \left(\sum_{j \neq i} J_{ij} \xi_j^\mu \right)$$

Pseudolikelihood produces associative memories

Pseudolikelihood on random data: Gardner computation

Pseudolikelihood produces associative memories


Pseudolikelihood on random data: Gardner computation




At fixed norm $\|\mathbf{J}\| = \lambda$

Pseudolikelihood produces associative memories

Pseudolikelihood on random data: Gardner computation



At fixed norm $\|\mathbf{J}\| = \lambda$



GD at free norm

Vector-spin associative memories

Vector spins: towards Self-Attention

Vector spins: towards Self-Attention

Statistical mechanics of vector Hopfield network near and above saturation

Flavio Nicoletti,^{1,2,*} Francesco D'Amico,^{2,3,†} and Matteo Negri^{2,3,‡}

¹*Department of Computer Science and Engineering Chalmers University of Technology and University of Gothenburg SE-41296 Gothenburg, Sweden*

²*Dipartimento di Fisica, Sapienza Università di Roma, 00185 Rome, Italy*

³*Institute of Nanotechnology, National Research Council of Italy, CNR-NANOTEC, Rome Unit*

Vector spins: towards Self-Attention

Statistical mechanics of vector Hopfield network near and above saturation

Flavio Nicoletti,^{1,2,*} Francesco D'Amico,^{2,3,†} and Matteo Negri^{2,3,‡}

¹*Department of Computer Science and Engineering Chalmers University of Technology and University of Gothenburg SE-41296 Gothenburg, Sweden*

²*Dipartimento di Fisica, Sapienza Università di Roma, 00185 Rome, Italy*

³*Institute of Nanotechnology, National Research Council of Italy, CNR-NANOTEC, Rome Unit*

- N spherical vector spins $\{\vec{S}_i\}_{i=1,\dots,N} \in \mathbb{R}^d$, $\|\vec{S}_i\| = 1$

Vector spins: towards Self-Attention

Statistical mechanics of vector Hopfield network near and above saturation

Flavio Nicoletti,^{1,2,*} Francesco D'Amico,^{2,3,†} and Matteo Negri^{2,3,‡}

¹*Department of Computer Science and Engineering Chalmers University of Technology and University of Gothenburg SE-41296 Gothenburg, Sweden*

²*Dipartimento di Fisica, Sapienza Università di Roma, 00185 Rome, Italy*

³*Institute of Nanotechnology, National Research Council of Italy, CNR-NANOTEC, Rome Unit*

- N spherical vector spins $\{\vec{S}_i\}_{i=1,\dots,N} \in \mathbb{R}^d$, $\|\vec{S}_i\| = 1$
- P memories $\{\vec{\xi}_i\}^\mu$

Vector spins: towards Self-Attention

Statistical mechanics of vector Hopfield network near and above saturation

Flavio Nicoletti,^{1,2,*} Francesco D'Amico,^{2,3,†} and Matteo Negri^{2,3,‡}

¹*Department of Computer Science and Engineering Chalmers University of Technology and University of Gothenburg SE-41296 Gothenburg, Sweden*

²*Dipartimento di Fisica, Sapienza Università di Roma, 00185 Rome, Italy*

³*Institute of Nanotechnology, National Research Council of Italy, CNR-NANOTEC, Rome Unit*

- N spherical vector spins $\{\vec{S}_i\}_{i=1,\dots,N} \in \mathbb{R}^d$, $\|\vec{S}_i\| = 1$
- P memories $\{\vec{\xi}_i\}^\mu$
- $H = -\frac{1}{2} \sum_{i \neq j}^{1,N} \vec{S}_i \cdot \mathbb{J}_{ij} \vec{S}_j$

Vector spins: towards Self-Attention

Statistical mechanics of vector Hopfield network near and above saturation

Flavio Nicoletti,^{1,2,*} Francesco D'Amico,^{2,3,†} and Matteo Negri^{2,3,‡}

¹*Department of Computer Science and Engineering Chalmers University of Technology and University of Gothenburg SE-41296 Gothenburg, Sweden*

²*Dipartimento di Fisica, Sapienza Università di Roma, 00185 Rome, Italy*

³*Institute of Nanotechnology, National Research Council of Italy, CNR-NANOTEC, Rome Unit*

- N spherical vector spins $\{\vec{S}_i\}_{i=1,\dots,N} \in \mathbb{R}^d$, $\|\vec{S}_i\| = 1$
- P memories $\{\vec{\xi}_i\}^\mu$
- $H = -\frac{1}{2} \sum_{i \neq j}^{1,N} \vec{S}_i \cdot \mathbb{J}_{ij} \vec{S}_j$
- Hebb's couplings $\mathbb{J}_{ij} = \frac{1}{N} \sum_{\mu=1}^P \vec{\xi}_i^\mu \times \vec{\xi}_j^\mu \Rightarrow \mathbb{J}_{ij} \in \mathbb{R}^{d \times d}$


Vector-spin associative memories

Phase diagram of retrieval at equilibrium

Vector-spin associative memories

Phase diagram of retrieval at equilibrium

Two order parameters: $\alpha = \frac{P}{N}$, $\alpha'' = \frac{Pd}{N}$




Vector-spin associative memories

First step denoising



Vector-spin associative memories

First step denoising





Vector-spin associative memories

First step denoising



Vector-spin associative memories

First step denoising



$$\Rightarrow P = \alpha' Nd$$

Final step

$$J_{ij} = \sum_{\mu} \xi_i^{\mu} \xi_j^{\mu}$$

Pseudolikelihood

$$s_i \in \{\pm 1\}$$

✓ *Amit et al. (1987)*

$$s_i \in s_{d-1}$$

Final step

$$s_i \in \{\pm 1\}$$

$$J_{ij} = \sum_{\mu} \xi_i^{\mu} \xi_j^{\mu}$$

Pseudolikelihood


✓ Amit et al. (1987)



✓ D'Amico, Bocchi, Del
Bono, Rossi, Negri
(2025)

$$s_i \in s_{d-1}$$

Final step



Final step

