

Pixture — C++ Code Style Guide

Naming conventions

Element	Convention	Example
Classes	PascalCase	CanvasWidget, FrameListModel
Methods	camelCase	pixelClicked(), addFrame()
Variables	camelCase, no prefix (for private members, etc...)	penColor, activeFrameIndex
Enum values	snake_case	PenMode::shape_select

Indentation

Use 1 tab per indentation (displayed as 4 spaces in Qt Creator).

Braces

Context	Rule	Example
Functions	Opening brace on same line	<pre>void addFrame() { ... }</pre>
Control flow	Opening brace on same line	<pre>if(x > 0) { ... }</pre>
Single-line if	Braces not required	<pre>if(frames.empty()) return;</pre>

Whitespace

Rule	Example
No space before parentheses	<pre>if(, not if (</pre>
No space inside parentheses	<pre>(row, col), not (row, col)</pre>
Space after commas	<pre>drawPixel(point, color)</pre>
Blank line between method definitions	

Comments

Requirement	Example
File header on every file	<pre>/** * Date: 3/23/2026 * Authors: Francisco, Joshua * (references) * * This class... */</pre>
Doxygen on public methods in headers	<pre>/** * @brief getFrame - Returns the frame at the index * @param index - the location of the desired frame * @return Frame* - a pointer to the frame at the index */</pre>
Inline // for explanations	<pre>// Using modulo to loop back</pre>
No unnecessary comments	<pre>// TODO // (dead code) // (comments to self)</pre>

