

Fashion Shows

January 2, 2018

Contents

1	App	2
2	App_Test	3
3	Designer_Test	4
4	Fashion_Designer	5
5	Fashion_Show	6
6	Main	11
7	Model	12
8	Model_In_Runway	14
9	Model_In_Runway_Test	15
10	Model_Look	16
11	Model_Look_Test	18
12	Model_Test	19
13	MyTestCase	20
14	Regular_User	20
15	Regular_User_Test	22
16	Reviewer	23
17	Reviewer_Test	24
18	Show_Test	25
19	User	28
20	WorkShop	29
21	WorkShop_Test	32

1 App

```
class App
types
-- TODO Define types here

    public Users = set of Regular_User;
    public Shows = set of Fashion_Show;

values
-- TODO Define values here
instance variables
-- TODO Define instance variables here

    public users : Users := {};
    public shows : Shows := {};

operations
-- TODO Define operations here

    --Construtor

    public App: () ==> App
    App() == (
        return self;
    );

    --Retorna os utilizadores da aplica o

    public pure getUsers : () ==> Users
    getUsers() ==
    (
        return users;
    );

    --Retorna os shows da aplica o

    public pure getShows : () ==> Shows
    getShows() ==
    (
        return shows;
    );

    --Adiciona um utilizador   aplica o

    public addUserToApp : (Regular_User) ==> ()
    addUserToApp(User) ==
    (
        users := users union {User};
        return;
    )
    pre User not in set users
    post User in set users;

    --Remove um utilizador   aplica o

    public rmvUserToApp : (Regular_User) ==> ()
    rmvUserToApp(User) ==
    (
        users := users \ {User};
        return;
    )
    pre User in set users
```

```

post User not in set users;

--Adiciona um show   aplica o

public addShowToApp : (Fashion_Show) ==> ()
addShowToApp(Fashion_Show) ==
(
  shows := shows union {Fashion_Show};
  return;
)
pre Fashion_Show not in set shows
post Fashion_Show in set shows;

--Remove um show   aplica o

public rmvShowToApp : (Fashion_Show) ==> ()
rmvShowToApp(Fashion_Show) ==
(
  shows := shows \ {Fashion_Show};
  return;
)
pre Fashion_Show in set shows
post Fashion_Show not in set shows;

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end App

```

Function or operation	Line	Coverage	Calls
App	20	100.0%	7
addShowToApp	60	100.0%	7
addUserToApp	40	100.0%	7
getShows	33	100.0%	21
getUsers	26	100.0%	21
rmvShowToApp	70	100.0%	7
rmvUserToApp	50	100.0%	7
App.vdmpp		100.0%	77

2 App_Test

```

class App_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestApp :() ==> ()
TestApp() ==

```

```

(
  -- constructor
  dcl app : App := new App();
  dcl user : Regular_User := new Regular_User("Diolinda", <Feminino>, "diolinda@gmail.com", "
    password_diolinda", false);
  dcl show : Fashion_Show := new Fashion_Show("Porto", "Primavera", 2017, 12, 31, 23, 59);

  -- users
  assertEquals(app.getUsers(), {});
  app.addUserToApp(user);
  assertEquals(app.getUsers(), {user});
  app.rmUserToApp(user);
  assertEquals(app.getUsers(), {});

  -- shows
  assertEquals(app.getShows(), {});
  app.addShowToApp(show);
  assertEquals(app.getShows(), {show});
  app.rmShowToApp(show);
  assertEquals(app.getShows(), {});

  return;
);

public static main_test: () ==> ()
main_test() ==
(
  IO`print("TestApp -> ");
  new App_Test().TestApp();
  IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end App_Test

```

Function or operation	Line	Coverage	Calls
TestApp	11	100.0%	7
main_test	37	100.0%	7
App_Test.vdmpp		100.0%	14

3 Designer_Test

```

class Designer_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

```

```

public TestDesigner :() ==> ()
TestDesigner() ==
(
  -- constructor
  dcl designer : Fashion_Designer := new Fashion_Designer("Andre Correia",54);

  -- gets
  assertEquals(designer.getName(),"Andre Correia");
  assertEquals(designer.getAge(),54);

  return;
);

public static main_test: () ==> ()
main_test() ==
(
  IO`print("TestDesigner -> ");
  new Designer_Test().TestDesigner();
  IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Designer_Test

```

Function or operation	Line	Coverage	Calls
TestDesigner	11	100.0%	7
main_test	25	100.0%	7
Designer_Test.vdmpp		100.0%	14

4 Fashion Designer

```

class Fashion_Designer
types
-- TODO Define types here
  public String = seq of char;
values
-- TODO Define values here

instance variables
-- TODO Define instance variables here
  private name : String;
  private age : nat1;
operations
-- TODO Define operations here

  --Construtor

  public Fashion_Designer: String * nat1 ==> Fashion_Designer
  Fashion_Designer(name1,age1) == (

```

```

    name := name1;
    age := age1;
    return self;
);

-- Retorna o nome

public pure getName : () ==> String
getName() ==
(
    return name;
);

-- Retorna a idade

public pure getAge : () ==> nat1
getAge() ==
(
    return age;
);

functions
-- TODO Define functiones here

traces
-- TODO Define Combinatorial Test Traces here
end Fashion_Designer

```

Function or operation	Line	Coverage	Calls
Fashion_Designer	16	100.0%	35
getAge	31	100.0%	7
getName	24	100.0%	7
Fashion_Designer.vdmpp		100.0%	49

5 Fashion_Show

```

class Fashion_Show
types
-- TODO Define types here
    public String = seq of char;
    public Date :: year : nat month: nat1 day : nat1 hour : nat minute : nat
        inv mk_Date(y,m,d,h,min) == m <= 12 and d <= DaysOfMonth(m,y) and h < 24 and min < 60;
    public Models_to_Designers = map Fashion_Designer to seq of Model_In_Runway;
    public listOfWorkshops = set of WorkShop;
    public listOfDesigners = set of Fashion_Designer;
    public listOfCritics = map Reviewer to Critic;
    public programShow = map Date to Fashion_Designer;
    public listOfDates = set of Date;
    public Critic :: description : String rate: nat
        inv v == v.rate <= 5;

values
-- TODO Define values here
instance variables
-- TODO Define instance variables here

```

```

private location : String;
private date : Date;
private theme : String;
private models : Models_to_Designers := {|->};
private workshops : listOfWorkshops := {};
private critics : listOfCritics := {|->};
private program : programShow := {|->};

operations
-- TODO Define operations here

--Construtor

public Fashion_Show: String * String * nat * nat1 * nat1 * nat * nat ==> Fashion_Show
Fashion_Show(location1,themel,year, month, day, hour, minute) == (
  location := location1;
  theme := themel;
  date := mk_Date(year, month, day, hour, minute);
  return self;
);

-- Retorna a localidade

public pure getLocation : () ==> String
getLocation() ==
(
  return location;
);

-- Retorna o tema

public pure getTheme : () ==> String
getTheme() ==
(
  return theme;
);

-- Retorna a data

public pure getDate : () ==> Date
getDate() ==
(
  return date;
);

-- Retorna os designers

public pure getDesigners : () ==> listOfWorkshops
getDesigners() ==
(
  return dom models;
);

-- Retorna os modelos por designer

public pure getModels : () ==> Models_to_Designers
getModels() ==
(
  return models;
);

-- Retorna o programa do evento

public pure getProgramShow : () ==> programShow

```

```

getProgramShow() ==
(
  return program;
);

-- Retorna os modelos de um dado designer

public pure getModelsOfDesigner : (Fashion_Designer) ==> listOfWorkshops
getModelsOfDesigner(Fashion_Designer) ==
(
  return models(Fashion_Designer);
)
pre Fashion_Designer in set dom models;

-- Retorna os workshops do show

public pure getWorkShops : () ==> listOfWorkshops
getWorkShops() ==
(
  return workshops;
);

-- Retorna os workshops do show

public pure getCritics : () ==> listOfCritics
getCritics() ==
(
  return critics;
);

-- Adiciona um designer ao desfile

public addDesignerToShow : (Fashion_Designer) ==> ()
addDesignerToShow(Fashion_Designer)==
(
  models := models ++ {Fashion_Designer|->[]};
)
pre Fashion_Designer not in set dom models
post Fashion_Designer in set dom models;

-- Remove um designer ao desfile

public rmvDesignerToShow : (Fashion_Designer) ==> ()
rmvDesignerToShow(Fashion_Designer)==
(
  models := {Fashion_Designer} <-: models ;
)
pre Fashion_Designer in set dom models
post Fashion_Designer not in set dom models;

-- Adiciona um modelo ao designer

public addModelToShow : Fashion_Designer * Model_In_Runway ==> ()
addModelToShow(Fashion_Designer, Model)==
(
  models(Fashion_Designer) := models(Fashion_Designer)^[Model];
)
pre Model not in set elems models(Fashion_Designer) and Fashion_Designer in set dom models
post Model in set elems models(Fashion_Designer);

-- Remove um modelo do designer

public removeModelToShow : Fashion_Designer * Model_In_Runway ==> ()
removeModelToShow(Fashion_Designer, Model)==
(

```



```

dcl seqAux : listOfModels := [];

for all i in set inds models(Fashion_Designer) do
if models(Fashion_Designer)(i) <> Model
then seqAux := seqAux^[models(Fashion_Designer)(i)];

models(Fashion_Designer) := seqAux;
)
pre Model in set elems models(Fashion_Designer) and Fashion_Designer in set dom models
post Model not in set elems models(Fashion_Designer);

-- Adiciona um designer ao programa

public addDesignerToProgramShow : Date * Fashion_Designer ==> ()
addDesignerToProgramShow(dateShow, designer) ==
(
program := program ++ {dateShow |-> designer};
)
pre dateShow.year = date.year and dateShow.month = date.month and dateShow.day = date.day and
dateShow.hour >= date.hour and dateShow.minute >= date.minute and dateShow not in set dom
program
post dateShow in set dom program;

-- Remove um designer do programa

public removeDesignerFromProgramShow : Date ==> ()
removeDesignerFromProgramShow(dateShow) ==
(
program := {dateShow} <-: program;
)
pre dateShow in set dom program
post dateShow not in set dom program;

-- Retorna o designer para uma determinada data do programa

public pure getDesignerByDate : (Date) ==> Fashion_Designer
getDesignerByDate(dateShow) ==
(
return program(dateShow);
)
pre dateShow in set dom program;

-- Retorna as datas do programa para um determinado designer

public pure getListOfDatesByDesigner : (Fashion_Designer) ==> listOfDates
getListOfDatesByDesigner(designer) ==
(
dcl m : map Date to Fashion_Designer := program :> {designer};
dcl l : listOfDates := {};

for all d in set dom m do l := l union {d};

return l;
)
pre designer in set rng program;

-- Adiciona um workshop ao show

public addWorkShopToShow : WorkShop ==> ()
addWorkShopToShow(WorkShop) ==
(
workshops := workshops union {WorkShop};
)
pre WorkShop not in set workshops
post WorkShop in set workshops;

```

```

-- Remove um workshop ao show

public rmvWorkShopToShow : Workshop ==> ()
rmvWorkShopToShow(WorkShop) ==
(
  workshops := workshops \ {WorkShop};
)
pre Workshop in set workshops
post Workshop not in set workshops;

-- Reservar um workshop

public workshopBooking : Workshop * Regular_User ==> ()
workshopBooking(WorkShop, User) ==
(
  Workshop.addUserToWorkshop(User);
)
pre card Workshop.getUsers() < Workshop.getLotation();

-- Editor adiciona a sua critica ao show

public addCritic : Reviewer * Critic ==> ()
addCritic(Reviewer, Critic) ==
(
  critics := critics ++ {Reviewer|->Critic};
)
pre Reviewer not in set dom critics
post Reviewer in set dom critics;

-- Editor remove a sua critica ao show

public rmvCritic : Reviewer ==> ()
rmvCritic(Reviewer) ==
(
  critics := {Reviewer} <-: critics;
)
pre Reviewer in set dom critics
post Reviewer not in set dom critics;

-- Media critica ao show

public getAvgReview : () ==> (real)
getAvgReview() ==
(
  dcl sum : real :=0;

  for all reviewer in set dom critics do
    sum := sum + critics(reviewer).rate;
  if (card dom critics > 0) then
    return sum / card dom critics
  else
    return sum;
);

functions
-- TODO Define functiones here

-- Retorna o nmero de dias do ms num dado ano

public static DaysOfMonth(month, year : nat1) r : nat1 == (
  if month = 1 or month = 3 or month = 5 or month = 7 or month = 8 or month = 10 or month = 12
  then
    31
  else if month = 2 and ((year mod 4 = 0 and year mod 100 <> 0) or year mod 400 = 0) then

```

```

    29
    else if month = 2 then
    28
    else
    30
    )

traces
-- TODO Define Combinatorial Test Traces here
end Fashion_Show

```

Function or operation	Line	Coverage	Calls
DaysOfMonth	249	100.0%	26
Fashion_Show	34	100.0%	28
addCritic	214	100.0%	12
addDesignerToProgramShow	149	100.0%	42
addDesignerToShow	107	100.0%	28
addModelToShow	125	100.0%	28
addWorkShopToShow	188	100.0%	12
getAvgReview	232	100.0%	30
getCritics	100	100.0%	35
getDate	57	100.0%	7
getDesignerByDate	167	100.0%	24
getDesigners	64	100.0%	35
getListOfDatesByDesigner	175	100.0%	12
getLocation	43	100.0%	7
getModels	71	100.0%	14
getModelsOfDesigner	85	100.0%	30
getProgramShow	78	100.0%	196
getTheme	50	100.0%	7
getWorkShops	93	100.0%	35
removeDesignerFromProgramShow	158	100.0%	42
removeModelToShow	134	100.0%	2
rmvCritic	223	100.0%	12
rmvDesignerToShow	116	100.0%	14
rmvWorkShopToShow	197	100.0%	12
workShopBooking	206	100.0%	36
Fashion_Show.vdmpp		100.0%	726

6 Main

```

class Main
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
    private static model_test: Model_Test := new Model_Test();

```

```

private static designer_test : Designer_Test := new Designer_Test();
private static show_test : Show_Test := new Show_Test();
private static user_test : Regular_User_Test := new Regular_User_Test();
private static workshop_test : WorkShop_Test := new WorkShop_Test();
private static app_test : App_Test := new App_Test();
private static reviewer_test : Reviewer_Test := new Reviewer_Test();
private static model_look_test : Model_Look_Test := new Model_Look_Test();
private static model_in_runway_test : Model_In_Runway_Test := new Model_In_Runway_Test();

operations
-- TODO Define operations here

public static main: () ==> ()
main() ==
(
  model_test.main_test();
  designer_test.main_test();
  show_test.main_test();
  user_test.main_test();
  workshop_test.main_test();
  app_test.main_test();
  reviewer_test.main_test();
  model_look_test.main_test();
  model_in_runway_test.main_test();
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Main

```

Function or operation	Line	Coverage	Calls
main	20	100.0%	5
Main.vdmpp		100.0%	5

7 Model

```

class Model
types
-- TODO Define types here
  public String = seq of char;
  public Gender = <Masculino> | <Feminino>;

values
-- TODO Define values here
  public minAge = 18;

instance variables
-- TODO Define instance variables here
  private name : String;
  private age : nat1;
  private gender : Gender;
  private height : real;
  private weight : real;
  inv age >= minAge;

```

```

operations
-- TODO Define operations here

--Construtor

public Model: String * nat1 * Gender * real * real ==> Model
Model(name1,age1,gender1,height1,weight1) == (
  name := name1;
  age := age1;
  gender := gender1;
  height := height1;
  weight := weight1;
  return self;
)
pre age1 >= minAge;

-- Retorna o nome

public pure getName : () ==> String
getName() ==
(
  return name;
);

-- Retorna a idade

public pure getAge : () ==> nat1
getAge() ==
(
  return age;
);

-- Retorna o genero

public pure getGender : () ==> Gender
getGender() ==
(
  return gender;
);

-- Retorna a altura

public pure getHeight : () ==> real
getHeight() ==
(
  return height;
);

-- Retorna o peso

public pure getWeight : () ==> real
getWeight() ==
(
  return weight;
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Model

```

Function or operation	Line	Coverage	Calls
Model	24	100.0%	54
getAge	43	100.0%	7
getGender	50	100.0%	7
getHeight	57	100.0%	7
getName	36	100.0%	7
getWeight	64	100.0%	7
Model.vdmpp		100.0%	89

8 Model_In_Runway

```

class Model_In_Runway
types
  public Image = seq of char;

values
  -- TODO Define values here

instance variables
  private model : Model;
  private photo : [Image] := nil;
  private date : Fashion_Show`Date;

operations

  --Construtor

  public Model_In_Runway: Model * Fashion_Show`Date ==> Model_In_Runway
  Model_In_Runway(model1,date1) == (
    model := model1;
    date := date1;
    return self;
  );

  -- Retorna o modelo

  public pure getModel : () ==> Model
  getModel() ==
  (
    return model;
  );

  -- Retorna a fotografia

  public pure getPhoto : () ==> Image
  getPhoto() ==
  (
    return photo;
  )
  pre photo <> nil;

  -- Retorna a data

  public pure getDate : () ==> Fashion_Show`Date
  getDate() ==
  (
    return date;
  );

```

```

-- Define a data

public setDate : (Fashion_Show`Date) ==> ()
setDate(date1) ==
(
  date := date1;
)
post date = date1;

-- Guarda fotografia

public setPhoto : (Image) ==> ()
setPhoto(photo1) ==
(
  photo := photo1;
)
post photo = photo1;

-- Remove fotografia

public removePhoto : () ==> ()
removePhoto() ==
(
  photo := nil;
)
pre photo <> nil
post photo = nil;

functions
-- TODO Define functiones here

traces
-- TODO Define Combinatorial Test Traces here

end Model_In_Runway

```

Function or operation	Line	Coverage	Calls
Model_In_Runway	16	100.0%	29
getDate	39	100.0%	9
getModel	24	100.0%	5
getPhoto	31	100.0%	5
removePhoto	62	100.0%	5
setDate	46	100.0%	4
setPhoto	54	100.0%	5
Model_In_Runway.vdmpp		100.0%	62

9 Model_In_Runway_Test

```

class Model_In_Runway_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables

```

```

-- TODO Define instance variables here
operations
-- TODO Define operations here

public TestModelInRunaway :() ==> ()
TestModelInRunaway () ==
(
  -- constructor
  dcl modell : Model := new Model("Pedro Faria",67,<Masculino>,1.78,74.32);
  dcl modell_rw : Model_In_Runway := new Model_In_Runway(modell, mk_Fashion_Show`Date(2017, 12,
    31, 20, 00));

  -- gets
  assertEquals(modell_rw.getModel(),modell);
  assertEquals(modell_rw.getDate(),mk_Fashion_Show`Date(2017, 12, 31, 20, 00));
  modell_rw.setPhoto("picture.png");
  assertEquals(modell_rw.getPhoto(),"picture.png");
  modell_rw.removePhoto();

  -- no pode devolver foto se no existir - pre-condi o
  -- assertEquals(modell_rw.getPhoto(),nil);

  modell_rw.setDate(mk_Fashion_Show`Date(2017, 11,10, 15, 00));
  assertEquals(modell_rw.getDate(),mk_Fashion_Show`Date(2017, 11,10, 15, 00));

  return;
);

public static main_test: () ==> ()
main_test () ==
(
  IO`print("TestModelInRunaway -> ");
  new Model_In_Runway_Test().TestModelInRunaway();
  IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Model_In_Runway_Test

```

Function or operation	Line	Coverage	Calls
TestDesigner	11	100.0%	5
TestModelInRunaway	11	100.0%	5
main_test	25	100.0%	2
Model_In_Runway_Test.vdmpp		100.0%	12

10 Model Look

```

class Model_Look
types

```



```

public String = seq of char;

values
-- TODO Define values here

instance variables

private model : Model;
private fashion_show : Fashion_Show;
private date : Fashion_Show'Date;
private description : String;

operations

--Construtor

public Model_Look: Model * Fashion_Show * Fashion_Show'Date * String ==> Model_Look
Model_Look(model1,fashion_show1,date1,description1) == (
  model := model1;
  fashion_show := fashion_show1;
  date := date1;
  description := description1;
  return self;
);

--Retorna o modelo do look

public pure getModel : () ==> Model
getModel() ==
(
  return model;
);

--Retorna o Fashion Show

public pure getFashionShow : () ==> Fashion_Show
getFashionShow() ==
(
  return fashion_show;
);

--Retorna o momento em que o modelo passou na passerela com este look

public pure getDate : () ==> Fashion_Show'Date
getDate() ==
(
  return date;
);

--Retorna a descricao do look

public pure getDescription : () ==> String
getDescription() ==
(
  return description;
);

functions
-- TODO Define functiones here

traces
-- TODO Define Combinatorial Test Traces here
end Model_Look

```

Function or operation	Line	Coverage	Calls
Model_Look	18	100.0%	14
getDate	42	100.0%	7
getDescription	49	100.0%	7
getFashionShow	35	100.0%	7
getModel	28	100.0%	7
Model_Look.vdmpp		100.0%	42

11 Model_Look_Test

```

class Model_Look_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestModelLook :() ==> ()
TestModelLook() ==
(
-- constructor
dcl model : Model := new Model("Pedro Faria",67,<Masculino>,1.78,74.32);
dcl show : Fashion_Show := new Fashion_Show("Porto","Primavera",2017, 12, 31, 23, 59);
dcl model_look : Model_Look := new Model_Look(model,show, mk_Fashion_Show'Date(2017, 12, 31,
23, 00),"vestido azul e cor de rosa");

-- gets
assertEqual(model_look.getModel(),model);
assertEqual(model_look.getFashionShow(),show);
assertEqual(model_look.getDate(),mk_Fashion_Show'Date(2017, 12, 31, 23, 00));
assertEqual(model_look.getDescription(),"vestido azul e cor de rosa");

return;
);

public static main_test: () ==> ()
main_test() ==
(
IO`print("TestModelLook -> ");
new Model_Look_Test().TestModelLook();
IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Model_Look_Test

```

Function or operation	Line	Coverage	Calls
TestModelLook	11	100.0%	7
main_test	29	100.0%	7
Model_Look_Test.vdmpp		100.0%	14

12 Model_Test

```

class Model_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestModel :() ==> ()
TestModel() ==
(
  -- constructor
  dcl model : Model := new Model("Pedro Faria",67,<Masculino>,1.78,74.32);

  -- gets
  assertEquals(model.getName(),"Pedro Faria");
  assertEquals(model.getAge(),67);
  assertEquals(model.getGender(),<Masculino>);
  assertEquals(model.getHeight(),1.78);
  assertEquals(model.getWeight(),74.32);

  return;
);

public static main_test: () ==> ()
main_test() ==
(
  IO`print("TestModel -> ");
  new Model_Test().TestModel();
  IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Model_Test

```

Function or operation	Line	Coverage	Calls
TestModel	11	100.0%	7
main_test	28	100.0%	7
Model_Test.vdmpp		100.0%	14

13 MyTestCase

```

class MyTestCase
/*
  Superclass for test classes, simpler but more practical than VDMUnit`TestCase.
  For proper use, you have to do: New -> Add VDM Library -> IO.
  JPF, FEUP, MFES, 2014/15.
*/

operations

-- Simulates assertion checking by reducing it to pre-condition checking.
-- If 'arg' does not hold, a pre-condition violation will be signaled.

protected assertTrue: bool ==> ()
assertTrue(arg) ==
  return
pre arg;

-- Simulates assertion checking by reducing it to post-condition checking.
-- If values are not equal, prints a message in the console and generates
-- a post-conditions violation.

protected assertEquals: ? * ? ==> ()
assertEquals(expected, actual) ==
  if expected <> actual then (
    IO`print("Actual value ");
    IO`print(actual);
    IO`print(") different from expected (");
    IO`print(expected);
    IO`println("\n")
  )
post expected = actual

end MyTestCase

```

Function or operation	Line	Coverage	Calls
assertEquals	20	38.8%	0
assertTrue	12	0.0%	0
MyTestCase.vdmpp		35.0%	0

14 Regular_User

```

class Regular_User is subclass of User
types
-- TODO Define types here
  public String = seq of char;
  public Looks = set of Model_Look;
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
  private favorite_looks : Looks := {};
  private premium_user : bool := false;

```

```

operations
-- TODO Define operations here

--Construtor

public Regular_User: String * Gender * String * String * bool ==> Regular_User
Regular_User(name1, gender1, email1, password1, premium_user1) == (
  name := name1;
  gender := gender1;
  email := email1;
  password := password1;
  premium_user := premium_user1;
  return self;
);

--Retorna se    um user premium ou nao

public pure getPremium : () ==> bool
getPremium() ==
(
  return premium_user;
);

--Retorna os looks favoritos

public pure getFavoriteLooks : () ==> Looks
getFavoriteLooks() ==
(
  return favorite_looks;
);

-- Adiciona um look aos looks favoritos

public addLookToFavoriteLooks : Model_Look ==> ()
addLookToFavoriteLooks(look)==
(
  favorite_looks := favorite_looks union {look};
)
pre look not in set favorite_looks
post look in set favorite_looks;

-- Remove um look dos looks favoritos

public removeLookFromFavoriteLooks : Model_Look ==> ()
removeLookFromFavoriteLooks(look)==
(
  favorite_looks := favorite_looks \ {look};
)
pre look in set favorite_looks
post look not in set favorite_looks;

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Regular_User

```

Function or operation	Line	Coverage	Calls
Regular_User	17	100.0%	42
addLookToFavoriteLooks	42	100.0%	6

getFavoriteLooks	35	100.0%	18
getPremium	28	100.0%	12
removeLookFromFavoriteLooks	51	100.0%	12
Regular_User.vdmpp		100.0%	90

15 Regular_User_Test

```

class Regular_User_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestUser :() ==> ()
TestUser() ==
(
-- constructor
dcl user : Regular_User := new Regular_User("Diolinda", <Feminino>, "diolinda@gmail.com", "
password_diolinda", true);
dcl user2 : Regular_User := new Regular_User("Diofeia", <Feminino>, "diofeia@gmail.com", "
password_diofeia", false);
dcl model : Model := new Model("Pedro Faria",67,<Masculino>,1.78,74.32);
dcl show : Fashion_Show := new Fashion_Show("Porto","Primavera",2017, 12, 31, 23, 59);
dcl model_look : Model_Look := new Model_Look(model,show, mk_Fashion_Show'Date(2017, 12, 31,
23, 00),"vestido azul e cor de rosa");

-- gets
assertEqual(user.getName(),"Diolinda");
assertEqual(user2.getName(),"Diofeia");
assertEqual(user.getPremium(),true);
assertEqual(user2.getPremium(),false);
assertEqual(user.getGender(),<Feminino>);
assertEqual(user2.getGender(),<Feminino>);
assertEqual(user.getEmail(),"diolinda@gmail.com");
assertEqual(user2.getEmail(),"diofeia@gmail.com");
assertEqual(user.getPassword(),"password_diolinda");
assertEqual(user2.getPassword(),"password_diofeia");

-- looks
assertEqual(user.getFavoriteLooks(),{});
user.addLookToFavoriteLooks(model_look);
assertEqual(user.getFavoriteLooks(),{model_look});
user.removeLookFromFavoriteLooks(model_look);
assertEqual(user.getFavoriteLooks(),{});

return;
);

public static main_test: () ==> ()
main_test() ==
(
IO`print("TestUser -> ");
new Regular_User_Test().TestUser();
IO`println("Passed");

```

```

);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Regular_User_Test

```

Function or operation	Line	Coverage	Calls
TestUser	11	100.0%	6
main_test	43	100.0%	12
Regular_User_Test.vdmpp		100.0%	18

16 Reviewer

```

class Reviewer is subclass of User
types
-- TODO Define types here
    public String = seq of char;
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
    private age : nat1;

operations
-- TODO Define operations here

    --Construtor

    public Reviewer: String * nat1 * Gender * String * String ==> Reviewer
    Reviewer(name1,age1,gender1,email1,password1) == (
        name := name1;
        age := age1;
        gender := gender1;
        email := email1;
        password := password1;
        return self;
    );

    -- Retorna a idade

    public pure getAge : () ==> nat1
    getAge() ==
    (
        return age;
    );

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Reviewer

```

Function or operation	Line	Coverage	Calls
Reviewer	15	100.0%	18
getAge	26	100.0%	7
Reviewer.vdmpp		100.0%	25

17 Reviewer_Test

```

class Reviewer_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestReviewer :() ==> ()
TestReviewer() ==
(
  -- constructor
  dcl reviewer : Reviewer := new Reviewer("Ana Bacalhau",39,<Feminino>,"anabacalhau@gmail.com",
    "password_anabacalhau");

  -- gets
  assertEquals(reviewer.getName(),"Ana Bacalhau");
  assertEquals(reviewer.getAge(),39);
  assertEquals(reviewer.getGender(),<Feminino>);
  assertEquals(reviewer.getEmail(),"anabacalhau@gmail.com");
  assertEquals(reviewer.getPassword(),"password_anabacalhau");

  return;
);

public static main_test: () ==> ()
main_test() ==
(
  IO`print("TestReviewer -> ");
  new Reviewer_Test().TestReviewer();
  IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Reviewer_Test

```

Function or operation	Line	Coverage	Calls
TestReviewer	11	100.0%	7
main_test	27	100.0%	6
Reviewer_Test.vdmpp		100.0%	13

18 Show_Test

```
class Show_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

public TestShow :() ==> ()
TestShow() ==
(
-- constructor

dcl show : Fashion_Show := new Fashion_Show("Porto","Primavera",2017, 12, 31, 9, 00);
dcl designer1 : Fashion_Designer := new Fashion_Designer("Andre Correia",54);
dcl designer2 : Fashion_Designer := new Fashion_Designer("Francisco Loua",64);
dcl designer3 : Fashion_Designer := new Fashion_Designer("Afonso Martins",58);
dcl designer4 : Fashion_Designer := new Fashion_Designer("Carlos Silva",62);
--dcl designer5 : Fashion_Designer := new Fashion_Designer("Mario Andrade",59);
dcl model1 : Model := new Model("Pedro Faria",67,<Masculino>,1.78,74.32);
dcl model2 : Model := new Model("Sara Sampaio",24,<Feminino>,1.82,53.24);
dcl model3 : Model := new Model("Daniela Hanganu",26,<Feminino>,1.79,52.78);
dcl model4 : Model := new Model("Dariiia",23,<Feminino>,1.85,56.91);
dcl model1_rw : Model_In_Runway := new Model_In_Runway(model1, mk_Fashion_Show'Date(2017, 12,
31, 20, 00));
dcl model2_rw : Model_In_Runway := new Model_In_Runway(model2, mk_Fashion_Show'Date(2017, 12,
31, 20, 00));
dcl model3_rw : Model_In_Runway := new Model_In_Runway(model3, mk_Fashion_Show'Date(2017, 12,
31, 20, 00));
dcl model4_rw : Model_In_Runway := new Model_In_Runway(model4, mk_Fashion_Show'Date(2017, 12,
31, 20, 00));
dcl workshop : WorkShop := new WorkShop("Como costurar um boto?", mk_Fashion_Show'Date(2017,
12, 31, 20, 00), mk_Fashion_Show'Date(2017, 12, 31, 21, 00), 20, "Joo Botes Correia",
"A7");
dcl workshop2 : WorkShop := new WorkShop("Como se maquilhar?", mk_Fashion_Show'Date(2017, 12,
31, 19, 00), mk_Fashion_Show'Date(2017, 12, 31, 20, 00), 20, "Joo Botes Correia", "A9"
);
dcl user1 : Regular_User := new Regular_User("Diolinda",<Feminino>, "diolinda@gmail.com", "
password_diolinda",true);
dcl user2 : Regular_User := new Regular_User("Diofeia",<Feminino>, "diofeia@gmail.com", "
password_diofeia",false);
dcl reviewer : Reviewer := new Reviewer("Ana Bacalhau",39,<Feminino>,"anabacalhau@gmail.com",
password_anabacalhau");
dcl reviewer2 : Reviewer := new Reviewer("Ana Moura",45,<Feminino>,"anamoura@gmail.com",
password_anamoura");
dcl data1 : Fashion_Show'Date := mk_Fashion_Show'Date(2017, 12, 31, 10, 30);
dcl data2 : Fashion_Show'Date := mk_Fashion_Show'Date(2017, 12, 31, 11, 00);
dcl data3 : Fashion_Show'Date := mk_Fashion_Show'Date(2017, 12, 31, 12, 30);
dcl data4 : Fashion_Show'Date := mk_Fashion_Show'Date(2017, 12, 31, 14, 00);
dcl data5 : Fashion_Show'Date := mk_Fashion_Show'Date(2017, 12, 31, 15, 30);
dcl data6 : Fashion_Show'Date := mk_Fashion_Show'Date(2017, 12, 31, 17, 00);
dcl data7 : Fashion_Show'Date := mk_Fashion_Show'Date(2017, 12, 31, 18, 30);
dcl critic : Fashion_Show'Critic := mk_Fashion_Show'Critic("Melhor festival de moda que
participei!",5);
dcl critic2 : Fashion_Show'Critic := mk_Fashion_Show'Critic("Evento agum das expectativas."
,2);

-- gets
```

```

assertEqual(show.getTheme(),"Primavera");
assertEqual(show.getLocation(),"Porto");
assertEqual(show.getDate(),mk_Fashion_Show`Date(2017, 12, 31, 9, 00));
assertEqual(show.getModels(),{|->});
assertEqual(show.getProgramShow(),{|->});

-- get designers
assertEqual(show.getDesigners(),{});
show.addDesignerToShow(designer1);
assertEqual(show.getDesigners(),{designer1});
show.addDesignerToShow(designer2);
assertEqual(show.getDesigners(),{designer1,designer2});
show.rmvDesignerToShow(designer1);
assertEqual(show.getDesigners(),{designer2});
show.rmvDesignerToShow(designer2);
assertEqual(show.getDesigners(),{});

--get models
show.addDesignerToShow(designer1);
show.addDesignerToShow(designer2);
assertEqual(show.getModelsOfDesigner(designer1),[]);
assertEqual(show.getModelsOfDesigner(designer2),[]);
assertEqual(show.getModels(),{designer1|->[],designer2|->[]});
show.addModelToShow(designer1,model1_rw);
show.addModelToShow(designer1,model2_rw);
show.addModelToShow(designer1,model3_rw);
show.addModelToShow(designer2,model4_rw);
assertEqual(show.getModelsOfDesigner(designer1),[model1_rw,model2_rw,model3_rw]);
assertEqual(show.getModelsOfDesigner(designer2),[model4_rw]);
show.removeModelToShow(designer1,model2_rw);
assertEqual(show.getModelsOfDesigner(designer1),[model1_rw,model3_rw]);

-- workshops
assertEqual(show.getWorkShops(),{});
show.addWorkShopToShow(workshop);
assertEqual(show.getWorkShops(),{workshop});
show.addWorkShopToShow(workshop2);
assertEqual(show.getWorkShops(),{workshop,workshop2});
assertEqual(workshop.getUsers(),{});
show.workShopBooking(workshop, user1);
assertEqual(workshop.getUsers(),{user1});
show.workShopBooking(workshop, user2);
assertEqual(workshop.getUsers(),{user1,user2});
show.rmvWorkShopToShow(workshop);
assertEqual(show.getWorkShops(),{workshop2});
show.rmvWorkShopToShow(workshop2);
assertEqual(show.getWorkShops(),{});

-- program
show.addDesignerToProgramShow(data1,designer1);
assertEqual(show.getProgramShow(),{data1|->designer1});
assertEqual(card dom show.getProgramShow(),1);
show.addDesignerToProgramShow(data2,designer2);
assertEqual(show.getProgramShow(),{data1|->designer1,data2|->designer2});
assertEqual(card dom show.getProgramShow(),2);
show.addDesignerToProgramShow(data3,designer3);
assertEqual(show.getProgramShow(),{data1|->designer1,data2|->designer2,data3|->designer3});
assertEqual(card dom show.getProgramShow(),3);
show.addDesignerToProgramShow(data4,designer4);
assertEqual(show.getProgramShow(),{data1|->designer1,data2|->designer2,data3|->designer3,
    data4|->designer4});
assertEqual(card dom show.getProgramShow(),4);

--invalid entry (try to break pre-condition by adding another event with already existing
    same date)

```

```

--show.addDesignerToProgramShow(data1,designer2);

--get designers by date
assertEqual(show.getDesignerByDate(data1),designer1);
assertEqual(show.getDesignerByDate(data2),designer2);
assertEqual(show.getDesignerByDate(data3),designer3);
assertEqual(show.getDesignerByDate(data4),designer4);

--add same designer to another date
show.addDesignerToProgramShow(data5,designer1);
assertEqual(show.getProgramShow(),{data1|->designer1,data2|->designer2,data3|->designer3,
    data4|->designer4,data5|->designer1});
assertEqual(card dom show.getProgramShow(),5);
show.addDesignerToProgramShow(data6,designer2);
assertEqual(show.getProgramShow(),{data1|->designer1,data2|->designer2,data3|->designer3,
    data4|->designer4,data5|->designer1,data6|->designer2});
assertEqual(card dom show.getProgramShow(),6);
show.addDesignerToProgramShow(data7,designer1);
assertEqual(show.getProgramShow(),{data1|->designer1,data2|->designer2,data3|->designer3,
    data4|->designer4,data5|->designer1,data6|->designer2,data7|->designer1});
assertEqual(card dom show.getProgramShow(),7);

--get list of dates by designer
assertEqual(show.getListOfDatesByDesigner(designer1),{data1,data5,data7});
assertEqual(show.getListOfDatesByDesigner(designer2),{data2,data6});

--invalid entry (try to break pre-condition by retriving list of dates by a designer that not
    exists on program)
--assertEqual(show.getListOfDatesByDesigner(designer5),{});

--remove date from program show
show.removeDesignerFromProgramShow(data7);
assertEqual(show.getProgramShow(),{data1|->designer1,data2|->designer2,data3|->designer3,
    data4|->designer4,data5|->designer1,data6|->designer2});
assertEqual(card dom show.getProgramShow(),6);
show.removeDesignerFromProgramShow(data6);
assertEqual(show.getProgramShow(),{data1|->designer1,data2|->designer2,data3|->designer3,
    data4|->designer4,data5|->designer1});
assertEqual(card dom show.getProgramShow(),5);
show.removeDesignerFromProgramShow(data5);
assertEqual(show.getProgramShow(),{data1|->designer1,data2|->designer2,data3|->designer3,
    data4|->designer4});
assertEqual(card dom show.getProgramShow(),4);

--invalid entry (try to break pre-condition by removing a date that not exists on program)
--show.removeDesignerFromProgramShow(data5);

show.removeDesignerFromProgramShow(data4);
assertEqual(show.getProgramShow(),{data1|->designer1,data2|->designer2,data3|->designer3});
assertEqual(card dom show.getProgramShow(),3);

--invalid entry (try to break pre-condition by removing a date that not exists on program)
--show.removeDesignerFromProgramShow(data4);

show.removeDesignerFromProgramShow(data3);
assertEqual(show.getProgramShow(),{data1|->designer1,data2|->designer2});
assertEqual(card dom show.getProgramShow(),2);

show.removeDesignerFromProgramShow(data2);
assertEqual(show.getProgramShow(),{data1|->designer1});
assertEqual(card dom show.getProgramShow(),1);

show.removeDesignerFromProgramShow(data1);
assertEqual(show.getProgramShow(),{});

```

```

-- critics
assertEqual(show.getCritics(),{|->});
assertEqual(show.getAvgReview(),0);
show.addCritic(reviewer, critic);
assertEqual(show.getCritics(),{reviewer|->critic});
assertEqual(show.getAvgReview(),5);
show.addCritic(reviewer2, critic2);
assertEqual(show.getCritics(),{reviewer|->critic,reviewer2|->critic2});
assertEqual(show.getAvgReview(),3.5);
show.rmvCritic(reviewer);
assertEqual(show.getCritics(),{reviewer2|->critic2});
assertEqual(show.getAvgReview(),2);
show.rmvCritic(reviewer2);
assertEqual(show.getCritics(),{|->});
assertEqual(show.getAvgReview(),0);

--test functions
assertEqual(show.DaysOfMonth(1,2000),31);
assertEqual(show.DaysOfMonth(4,2000),30);
assertEqual(show.DaysOfMonth(2,2000),29);
assertEqual(show.DaysOfMonth(2,1900),28);

return;

);

public static main_test: () ==> ()
main_test() ==
(
  IO`print("TestShow -> ");
  new Show_Test().TestShow();
  IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Show_Test

```

Function or operation	Line	Coverage	Calls
TestShow	11	100.0%	3
main_test	192	100.0%	2
Show_Test.vdmpp		100.0%	5

19 User

```

class User
types
-- TODO Define types here
  public String = seq of char;
  public Gender = <Masculino> | <Feminino>;
values
-- TODO Define values here
instance variables

```

```

-- TODO Define instance variables here
protected name : String := "Default_Name";
protected gender : Gender := <Masculino>;
protected email : String := "";
protected password : String := "";
operations
-- TODO Define operations here

--Retorna o nome

public pure getName : () ==> String
getName() ==
(
  return name;
);

--Retorna o genero

public pure getGender : () ==> Gender
getGender() ==
(
  return gender;
);

--Retorna o email

public pure getEmail : () ==> String
getEmail() ==
(
  return email;
);

--Retorna a password

public pure getPassword : () ==> String
getPassword() ==
(
  return password;
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end User

```

Function or operation	Line	Coverage	Calls
getEmail	32	100.0%	18
getGender	25	100.0%	18
getName	18	100.0%	18
getPassword	39	100.0%	18
User.vdmpp		100.0%	72

20 WorkShop

```

class WorkShop

```

```

types
-- TODO Define types here
public String = seq of char;
public Users = set of Regular_User;

values
-- TODO Define values here
instance variables
-- TODO Define instance variables here

private theme : String;
private begin_date : Fashion_Show'Date;
private end_date : Fashion_Show'Date;
private lotation : nat1;
private orator : String;
private registered_users : Users := {};
private room : String;
inv card registered_users <= lotation;

operations
-- TODO Define operations here

public Workshop: String * Fashion_Show'Date * Fashion_Show'Date * nat1 * String * String ==>
    Workshop
    Workshop(theme1, begin_date1, end_date1, lotation1, orator1, room1) == (

        theme := theme1;
        begin_date := begin_date1;
        end_date := end_date1;
        lotation := lotation1;
        orator := orator1;
        room := room1;

        return self;
    );

--Retorna o tema do workshop

public pure getTheme : () ==> String
getTheme() ==
(
    return theme;
);

--Retorna a data de inicio

public pure getBeginDate : () ==> Fashion_Show'Date
getBeginDate() ==
(
    return begin_date;
);

--Retorna a data de fim

public pure getEndDate : () ==> Fashion_Show'Date
getEndDate() ==
(
    return end_date;
);

--Retorna a lota o

public pure getLotation : () ==> nat1

```

```

getLotation() ==
(
  return lotation;
);

--Retorna o orador

public pure getOrator : () ==> String
getOrator() ==
(
  return orator;
);

--Retorna a sala do workshop

public pure getRoom : () ==> String
getRoom() ==
(
  return room;
);

--Retorna os utilizadores que participam

public pure getUsers : () ==> Users
getUsers() ==
(
  return registered_users;
);

--Adiciona um utilizador  workshop

public addUserToWorkshop : (Regular_User) ==> ()
addUserToWorkshop(Regular_User) ==
(
  registered_users := registered_users union {Regular_User};
  return;
)
pre Regular_User not in set registered_users and card registered_users < lotation
post Regular_User in set registered_users;

--Remove um utilizador  workshop

public rmvUserToWorkshop : (Regular_User) ==> ()
rmvUserToWorkshop(Regular_User) ==
(
  registered_users := registered_users \ {Regular_User};
  return;
)
pre Regular_User in set registered_users
post Regular_User not in set registered_users;

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Workshop

```

Function or operation	Line	Coverage	Calls
WorkShop	25	100.0%	21
addUserToWorkshop	88	100.0%	28

getBeginDate	46	100.0%	7
getEndDate	53	100.0%	7
getLotation	60	100.0%	21
getOrator	67	100.0%	7
getRoom	74	100.0%	7
getTheme	39	100.0%	7
getUsers	81	100.0%	70
rmvUserToWorkshop	98	100.0%	14
WorkShop.vdmpp		100.0%	189

21 WorkShop_Test

```

class WorkShop_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestWorkShop :() ==> ()
TestWorkShop() ==
(
-- constructor
dcl workshop : WorkShop := new WorkShop("Como costurar um boto?", mk_Fashion_Show`Date(2017,
12, 31, 20, 00), mk_Fashion_Show`Date(2017, 12, 31, 21, 00), 20, "Joo Botes Correia",
"A7");
dcl user1 : Regular_User := new Regular_User("Diolinda",<Feminino>, "diolinda@gmail.com", "
password_diolinda",true);
dcl user2: Regular_User := new Regular_User("Diofeia",<Feminino>, "diofeia@gmail.com", "
password_diofeia",false);

-- gets
assertEqual(workshop.getTheme(),"Como costurar um boto?");
assertEqual(workshop.getBeginDate(),mk_Fashion_Show`Date(2017, 12, 31, 20, 00));
assertEqual(workshop.getEndDate(),mk_Fashion_Show`Date(2017, 12, 31, 21, 00));
assertEqual(workshop.getLotation(),20);
assertEqual(workshop.getOrator(),"Joo Botes Correia");
assertEqual(workshop.getRoom(),"A7");
assertEqual(workshop.getUsers(),{});

-- Adicionar utilizadores ao workshop
workshop.addUserToWorkshop(user1);
assertEqual(workshop.getUsers(),{user1});
workshop.addUserToWorkshop(user2);
assertEqual(workshop.getUsers(),{user1,user2});
workshop.rmvUserToWorkshop(user1);
assertEqual(workshop.getUsers(),{user2});
workshop.rmvUserToWorkshop(user2);
assertEqual(workshop.getUsers(),{});

return;
);

```



```

public static main_test: () ==> ()
main_test() ==
(
  IO`print("TestWorkShop -> ");
  new WorkShop_Test().TestWorkShop();
  IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end WorkShop_Test

```

Function or operation	Line	Coverage	Calls
TestWorkShop	11	100.0%	7
main_test	41	100.0%	12
WorkShop_Test.vdmpp		100.0%	19