

Fashion Shows

January 2, 2018

Contents

1	App	2
2	App_Test	3
3	Designer_Test	4
4	Fashion_Designer	5
5	Fashion_Show	6
6	Main	11
7	Model	12
8	Model_Look	13
9	Model_Look_Test	15
10	Model_Test	16
11	MyTestCase	17
12	Regular_User	17
13	Regular_User_Test	19
14	Reviewer	20
15	Reviewer_Test	21
16	Show_Test	22
17	User	25
18	WorkShop	26
19	WorkShop_Test	29

1 App

```
class App
types
-- TODO Define types here

    public Users = set of Regular_User;
    public Shows = set of Fashion_Show;

values
-- TODO Define values here
instance variables
-- TODO Define instance variables here

    public users : Users := {};
    public shows : Shows := {};

operations
-- TODO Define operations here

    --Construtor

    public App: () ==> App
    App() == (
        return self;
    );

    --Retorna os utilizadores da aplica o

    public pure getUsers : () ==> Users
    getUsers() ==
    (
        return users;
    );

    --Retorna os shows da aplica o

    public pure getShows : () ==> Shows
    getShows() ==
    (
        return shows;
    );

    --Adiciona um utilizador   aplica o

    public addUserToApp : (Regular_User) ==> ()
    addUserToApp(User) ==
    (
        users := users union {User};
        return;
    )
    pre User not in set users
    post User in set users;

    --Remove um utilizador   aplica o

    public rmvUserToApp : (Regular_User) ==> ()
    rmvUserToApp(User) ==
    (
        users := users \ {User};
        return;
    )
    pre User in set users
```

```

post User not in set users;

--Adiciona um show   aplica o

public addShowToApp : (Fashion_Show) ==> ()
addShowToApp(Fashion_Show) ==
(
  shows := shows union {Fashion_Show};
  return;
)
pre Fashion_Show not in set shows
post Fashion_Show in set shows;

--Remove um show   aplica o

public rmvShowToApp : (Fashion_Show) ==> ()
rmvShowToApp(Fashion_Show) ==
(
  shows := shows \ {Fashion_Show};
  return;
)
pre Fashion_Show in set shows
post Fashion_Show not in set shows;

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end App

```

Function or operation	Line	Coverage	Calls
App	20	100.0%	3
addShowToApp	60	100.0%	3
addUserToApp	40	100.0%	3
getShows	33	100.0%	9
getUsers	26	100.0%	9
rmvShowToApp	70	100.0%	3
rmvUserToApp	50	100.0%	6
App.vdmpp		100.0%	36

2 App_Test

```

class App_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestApp :() ==> ()
TestApp() ==

```

```

(
  -- constructor
  dcl app : App := new App();
  dcl user : Regular_User := new Regular_User("Diolinda", <Feminino>, "diolinda@gmail.com", "
    password_diolinda", false);
  dcl show : Fashion_Show := new Fashion_Show("Porto", "Primavera", 2017, 12, 31, 23, 59);

  -- users
  assertEquals(app.getUsers(), {});
  app.addUserToApp(user);
  assertEquals(app.getUsers(), {user});
  app.rmVUserToApp(user);
  assertEquals(app.getUsers(), {});

  -- shows
  assertEquals(app.getShows(), {});
  app.addShowToApp(show);
  assertEquals(app.getShows(), {show});
  app.rmVShowToApp(show);
  assertEquals(app.getShows(), {});

  return;
);

public static main_test: () ==> ()
main_test() ==
(
  IO`print("TestApp -> ");
  new App_Test().TestApp();
  IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end App_Test

```

Function or operation	Line	Coverage	Calls
TestApp	11	100.0%	3
main_test	37	100.0%	3
App_Test.vdmpp		100.0%	6

3 Designer_Test

```

class Designer_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

```

```

public TestDesigner :() ==> ()
TestDesigner() ==
(
  -- constructor
  dcl designer : Fashion_Designer := new Fashion_Designer("Andre Correia",54);

  -- gets
  assertEquals(designer.getName(),"Andre Correia");
  assertEquals(designer.getAge(),54);

  return;
);

public static main_test: () ==> ()
main_test() ==
(
  IO`print("TestDesigner -> ");
  new Designer_Test().TestDesigner();
  IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Designer_Test

```

Function or operation	Line	Coverage	Calls
TestDesigner	11	100.0%	3
main_test	25	100.0%	3
Designer_Test.vdmpp		100.0%	6

4 Fashion Designer

```

class Fashion_Designer
types
-- TODO Define types here
  public String = seq of char;
values
-- TODO Define values here

instance variables
-- TODO Define instance variables here
  private name : String;
  private age : nat1;
operations
-- TODO Define operations here

  --Construtor

  public Fashion_Designer: String * nat1 ==> Fashion_Designer
  Fashion_Designer(name1,age1) == (

```

```

    name := name1;
    age := age1;
    return self;
);

-- Retorna o nome

public pure getName : () ==> String
getName() ==
(
    return name;
);

-- Retorna a idade

public pure getAge : () ==> nat1
getAge() ==
(
    return age;
);

functions
-- TODO Define functiones here

traces
-- TODO Define Combinatorial Test Traces here
end Fashion_Designer

```

Function or operation	Line	Coverage	Calls
Fashion_Designer	16	100.0%	15
getAge	31	100.0%	3
getName	24	100.0%	3
Fashion_Designer.vdmpp		100.0%	21

5 Fashion_Show

```

class Fashion_Show
types
-- TODO Define types here
    public String = seq of char;
    public Date :: year : nat month: nat1 day : nat1 hour : nat minute : nat
        inv mk_Date(y,m,d,h,min) == m <= 12 and d <= DaysOfMonth(m,y) and h < 24 and min < 60;
    public Models_to_Designers = map Fashion_Designer to set of Model;
    public listOfWorkshops = set of Workshop;
    public listOfDesigners = set of Fashion_Designer;
    public listOfCritics = map Reviewer to Critic;
    public programShow = map Date to Fashion_Designer;
    public listOfDates = set of Date;
    public Critic :: description : String rate: nat
        inv v == v.rate <= 5;

values
-- TODO Define values here
instance variables
-- TODO Define instance variables here

```

```

private location : String;
private date : Date;
private theme : String;
private models : Models_to_Designers := {|->};
private workshops : listOfWorkshops := {};
private critics : listOfCritics := {|->};
private program : programShow := {|->};

operations
-- TODO Define operations here

--Construtor

public Fashion_Show: String * String * nat * nat1 * nat1 * nat * nat ==> Fashion_Show
Fashion_Show(location1,themel,year, month, day, hour, minute) == (
  location := location1;
  theme := themel;
  date := mk_Date(year, month, day, hour, minute);
  return self;
);

-- Retorna a localidade

public pure getLocation : () ==> String
getLocation() ==
(
  return location;
);

-- Retorna o tema

public pure getTheme : () ==> String
getTheme() ==
(
  return theme;
);

-- Retorna a data

public pure getDate : () ==> Date
getDate() ==
(
  return date;
);

-- Retorna os designers

public pure getDesigners : () ==> listOfWorkshops
getDesigners() ==
(
  return dom models;
);

-- Retorna os modelos por designer

public pure getModels : () ==> Models_to_Designers
getModels() ==
(
  return models;
);

-- Retorna o programa do evento

public pure getProgramShow : () ==> programShow

```

```

getProgramShow() ==
(
  return program;
);

-- Retorna os modelos de um dado designer

public pure getModelsOfDesigner : (Fashion_Designer) ==> listOfWorkshops
getModelsOfDesigner(Fashion_Designer) ==
(
  return models(Fashion_Designer);
)
pre Fashion_Designer in set dom models;

-- Retorna os workshops do show

public pure getWorkShops : () ==> listOfWorkshops
getWorkShops() ==
(
  return workshops;
);

-- Retorna os workshops do show

public pure getCritics : () ==> listOfCritics
getCritics() ==
(
  return critics;
);

-- Adiciona um designer ao desfile

public addDesignerToShow : (Fashion_Designer) ==> ()
addDesignerToShow(Fashion_Designer)==
(
  models := models ++ {Fashion_Designer|->{}};
)
pre Fashion_Designer not in set dom models
post Fashion_Designer in set dom models;

-- Remove um designer ao desfile

public rmvDesignerToShow : (Fashion_Designer) ==> ()
rmvDesignerToShow(Fashion_Designer)==
(
  models := {Fashion_Designer} <-: models ;
)
pre Fashion_Designer in set dom models
post Fashion_Designer not in set dom models;

-- Adiciona um modelo ao designer

public addModelToShow : Fashion_Designer * Model ==> ()
addModelToShow(Fashion_Designer, Model)==
(
  models(Fashion_Designer) := models(Fashion_Designer) union {Model};
)
pre Model not in set models(Fashion_Designer) and Fashion_Designer in set dom models
post Model in set models(Fashion_Designer);

-- Adiciona um designer ao programa

public addDesignerToProgramShow : Date * Fashion_Designer ==> ()
addDesignerToProgramShow(dateShow, designer)==
(

```



```

    program := program ++ {dateShow |-> designer};
  )
pre dateShow.year = date.year and dateShow.month = date.month and dateShow.day = date.day and
    dateShow not in set dom program
post dateShow in set dom program;

-- Remove um designer do programa

public removeDesignerFromProgramShow : Date ==> ()
removeDesignerFromProgramShow(dateShow)==
(
    program := {dateShow} <-: program;
)
pre dateShow in set dom program
post dateShow not in set dom program;

-- Retorna o designer para uma determinada data do programa

public pure getDesignerByDate : (Date) ==> Fashion_Designer
getDesignerByDate(dateShow) ==
(
    return program(dateShow);
)
pre dateShow in set dom program;

-- Retorna as datas do programa para um determinado designer

public pure getListOfDatesByDesigner : (Fashion_Designer) ==> listOfDates
getListOfDatesByDesigner(designer) ==
(
    dcl m : map Date to Fashion_Designer := program :> {designer};
    dcl l : listOfDates := {};

    for all d in set dom m do l := l union {d};

    return l;
)
pre designer in set rng program;

-- Adiciona um workshop ao show

public addWorkShopToShow : WorkShop ==> ()
addWorkShopToShow(WorkShop)==
(
    workshops := workshops union {WorkShop};
)
pre WorkShop not in set workshops
post WorkShop in set workshops;

-- Remove um workshop ao show

public rmvWorkShopToShow : WorkShop ==> ()
rmvWorkShopToShow(WorkShop)==
(
    workshops := workshops \ {WorkShop};
)
pre WorkShop in set workshops
post WorkShop not in set workshops;

-- Reservar um workshop

public workShopBooking : WorkShop * Regular_User ==> ()
workShopBooking(WorkShop, User) ==
(
    WorkShop.addUserToWorkshop(User);

```

```

)
pre card Workshop.getUsers() < Workshop.getLotation();

-- Editor adiciona a sua critica ao show

public addCritic : Reviewer * Critic ==> ()
addCritic(Reviewer, Critic) ==
(
  critics := critics ++ {Reviewer|->Critic};
)
pre Reviewer not in set dom critics
post Reviewer in set dom critics;

-- Editor remove a sua critica ao show

public rmvCritic : Reviewer ==> ()
rmvCritic(Reviewer) ==
(
  critics := {Reviewer} <-: critics;
)
pre Reviewer in set dom critics
post Reviewer not in set dom critics;

-- Mdia critica ao show

public getAvgReview : () ==> (real)
getAvgReview() ==
(
  dcl sum : real :=0;

  for all reviewer in set dom critics do
    sum := sum + critics(reviewer).rate;
  if (card dom critics > 0) then
    return sum / card dom critics
  else
    return sum;
);

functions
-- TODO Define functiones here

-- Retorna o nmero de dias do ms num dado ano

public static DaysOfMonth(month,year : nat1) r : nat1 == (
  if month = 1 or month = 3 or month = 5 or month = 7 or month = 8 or month = 10 or month = 12
  then
    31
  else if month = 2 and ((year mod 4 = 0 and year mod 100 <> 0) or year mod 400 = 0) then
    29
  else if month = 2 then
    28
  else
    30
)

traces
-- TODO Define Combinatorial Test Traces here
end Fashion_Show

```

Function or operation	Line	Coverage	Calls
-----------------------	------	----------	-------

DaysOfMonth	234	100.0%	81
Fashion_Show	34	100.0%	12
addCritic	199	100.0%	6
addDesignerToProgramShow	134	100.0%	21
addDesignerToShow	107	100.0%	12
addModelToShow	125	100.0%	12
addWorkShopToShow	173	100.0%	6
getAvgReview	217	100.0%	15
getCritics	100	100.0%	15
getDate	57	100.0%	3
getDesignerByDate	152	100.0%	24
getDesigners	64	100.0%	15
getListOfDatesByDesigner	160	100.0%	6
getLocation	43	100.0%	3
getModels	71	100.0%	6
getModelsOfDesigner	85	100.0%	12
getProgramShow	78	100.0%	84
getTheme	50	100.0%	3
getWorkShops	93	100.0%	15
removeDesignerFromProgramShow	143	100.0%	21
rmvCritic	208	100.0%	6
rmvDesignerToShow	116	100.0%	6
rmvWorkShopToShow	182	100.0%	6
workShopBooking	191	100.0%	6
Fashion_Show.vdmpp		100.0%	396

6 Main

```

class Main
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
    private static model_test: Model_Test := new Model_Test();
    private static designer_test : Designer_Test := new Designer_Test();
    private static show_test : Show_Test := new Show_Test();
    private static user_test : Regular_User_Test := new Regular_User_Test();
    private static workshop_test : WorkShop_Test := new WorkShop_Test();
    private static app_test : App_Test := new App_Test();
    private static reviewer_test : Reviewer_Test := new Reviewer_Test();
    private static model_look_test : Model_Look_Test := new Model_Look_Test();

operations
-- TODO Define operations here

    public static main: () ==> ()
    main() ==
    (
        model_test.main_test();
        designer_test.main_test();

```

```
show_test.main_test();
user_test.main_test();
workshop_test.main_test();
app_test.main_test();
reviewer_test.main_test();
model_look_test.main_test();
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Main
```

Function or operation	Line	Coverage	Calls
main	20	100.0%	3
Main.vdmpp		100.0%	3

7 Model

```
class Model
types
-- TODO Define types here
    public String = seq of char;
    public Gender = <Masculino> | <Feminino>;

values
-- TODO Define values here
    public minAge = 18;

instance variables
-- TODO Define instance variables here
    private name : String;
    private age : nat1;
    private gender : Gender;
    private height : real;
    private weight : real;
    inv age >= minAge;

operations
-- TODO Define operations here

    --Construtor

    public Model: String * nat1 * Gender * real * real ==> Model
    Model(name1,age1,gender1,height1,weight1) == (
        name := name1;
        age := age1;
        gender := gender1;
        height := height1;
        weight := weight1;
        return self;
    )
    pre age1 >= minAge;

    -- Retorna o nome
```

```

public pure getName : () ==> String
getName() ==
(
  return name;
);

-- Retorna a idade

public pure getAge : () ==> nat1
getAge() ==
(
  return age;
);

-- Retorna o genero

public pure getGender : () ==> Gender
getGender() ==
(
  return gender;
);

-- Retorna a altura

public pure getHeight : () ==> real
getHeight() ==
(
  return height;
);

-- Retorna o peso

public pure getWeight : () ==> real
getWeight() ==
(
  return weight;
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Model

```

Function or operation	Line	Coverage	Calls
Model	24	100.0%	21
getAge	43	100.0%	3
getGender	50	100.0%	3
getHeight	57	100.0%	3
getName	36	100.0%	3
getWeight	64	100.0%	3
Model.vdmpp		100.0%	36

8 Model Look

```

class Model_Look
types
  public String = seq of char;

values
  -- TODO Define values here

instance variables

  private model : Model;
  private fashion_show : Fashion_Show;
  private date : Fashion_Show`Date;
  private description : String;

operations

  --Construtor

  public Model_Look: Model * Fashion_Show * Fashion_Show`Date * String ==> Model_Look
  Model_Look(model1,fashion_show1,date1,description1) == (
    model := model1;
    fashion_show := fashion_show1;
    date := date1;
    description := description1;
    return self;
  );

  --Retorna o modelo do look

  public pure getModel : () ==> Model
  getModel() ==
  (
    return model;
  );

  --Retorna o Fashion Show

  public pure getFashionShow : () ==> Fashion_Show
  getFashionShow() ==
  (
    return fashion_show;
  );

  --Retorna o momento em que o modelo passou na passerela com este look

  public pure getDate : () ==> Fashion_Show`Date
  getDate() ==
  (
    return date;
  );

  --Retorna a descricao do look

  public pure getDescription : () ==> String
  getDescription() ==
  (
    return description;
  );

functions
  -- TODO Define functiones here
traces
  -- TODO Define Combinatorial Test Traces here
end Model_Look

```

Function or operation	Line	Coverage	Calls
Model_Look	18	100.0%	6
getDate	42	100.0%	3
getDescription	49	100.0%	3
getFashionShow	35	100.0%	3
getModel	28	100.0%	3
Model_Look.vdmpp		100.0%	18

9 Model_Look_Test

```

class Model_Look_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestModelLook :() ==> ()
TestModelLook() ==
(
-- constructor
dcl model : Model := new Model("Pedro Faria",67,<Masculino>,1.78,74.32);
dcl show : Fashion_Show := new Fashion_Show("Porto","Primavera",2017, 12, 31, 23, 59);
dcl model_look : Model_Look := new Model_Look(model,show, mk_Fashion_Show'Date(2017, 12, 31,
23, 00),"vestido azul e cor de rosa");

-- gets
assertEqual(model_look.getModel(),model);
assertEqual(model_look.getFashionShow(),show);
assertEqual(model_look.getDate(),mk_Fashion_Show'Date(2017, 12, 31, 23, 00));
assertEqual(model_look.getDescription(),"vestido azul e cor de rosa");

return;
);

public static main_test: () ==> ()
main_test() ==
(
IO`print("TestModelLook -> ");
new Model_Look_Test().TestModelLook();
IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Model_Look_Test

```

Function or operation	Line	Coverage	Calls
TestModelLook	11	100.0%	3
main_test	29	100.0%	6
Model_Look_Test.vdmpp		100.0%	9

10 Model_Test

```

class Model_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestModel :() ==> ()
TestModel() ==
(
-- constructor
dcl model : Model := new Model("Pedro Faria",67,<Masculino>,1.78,74.32);

-- gets
assertEqual(model.getName(),"Pedro Faria");
assertEqual(model.getAge(),67);
assertEqual(model.getGender(),<Masculino>);
assertEqual(model.getHeight(),1.78);
assertEqual(model.getWeight(),74.32);

return;
);

public static main_test: () ==> ()
main_test() ==
(
IO`print("TestModel -> ");
new Model_Test().TestModel();
IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Model_Test

```

Function or operation	Line	Coverage	Calls
TestModel	11	100.0%	3
main_test	28	100.0%	3
Model_Test.vdmpp		100.0%	6

11 MyTestCase

```
class MyTestCase
/*
  Superclass for test classes, simpler but more practical than VDMUnit`TestCase.
  For proper use, you have to do: New -> Add VDM Library -> IO.
  JPF, FEUP, MFES, 2014/15.
*/

operations

-- Simulates assertion checking by reducing it to pre-condition checking.
-- If 'arg' does not hold, a pre-condition violation will be signaled.

protected assertTrue: bool ==> ()
  assertTrue(arg) ==
    return
pre arg;

-- Simulates assertion checking by reducing it to post-condition checking.
-- If values are not equal, prints a message in the console and generates
-- a post-conditions violation.

protected assertEquals: ? * ? ==> ()
  assertEquals(expected, actual) ==
    if expected <> actual then (
      IO`print("Actual value (");
      IO`print(actual);
      IO`print(") different from expected (");
      IO`print(expected);
      IO`println(")\n")
    )
  post expected = actual
end MyTestCase
```

Function or operation	Line	Coverage	Calls
assertEquals	20	38.8%	0
assertTrue	12	0.0%	0
MyTestCase.vdmpp		35.0%	0

12 Regular_User

```
class Regular_User is subclass of User
types
-- TODO Define types here
  public String = seq of char;
  public Looks = set of Model_Look;
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
  private favorite_looks : Looks := {};
  private premium_user : bool := false;
```

```

operations
-- TODO Define operations here

--Construtor

public Regular_User: String * Gender * String * String * bool ==> Regular_User
Regular_User(name1, gender1, email1, password1, premium_user1) == (
  name := name1;
  gender := gender1;
  email := email1;
  password := password1;
  premium_user := premium_user1;
  return self;

);

--Retorna se um user premium ou nao
public pure getPremium : () ==> bool
getPremium() ==
(
  return premium_user;

);

--Retorna os looks favoritos
public pure getFavoriteLooks : () ==> Looks
getFavoriteLooks() ==
(
  return favorite_looks;

);

-- Adiciona um look aos looks favoritos
public addLookToFavoriteLooks : Model_Look ==> ()
addLookToFavoriteLooks(look) ==
(
  favorite_looks := favorite_looks union {look};
)
pre look not in set favorite_looks
post look in set favorite_looks;

-- Remove um look dos looks favoritos
public removeLookFromFavoriteLooks : Model_Look ==> ()
removeLookFromFavoriteLooks(look) ==
(
  favorite_looks := favorite_looks \ {look};
)
pre look in set favorite_looks
post look not in set favorite_looks;

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Regular_User

```

Function or operation	Line	Coverage	Calls
Regular_User	17	100.0%	21
addLookToFavoriteLooks	39	100.0%	3

getFavoriteLooks	32	100.0%	9
getPremium	25	100.0%	6
removeLookFromFavoriteLooks	48	100.0%	3
Regular_User.vdmpp		100.0%	42

13 Regular_User_Test

```

class Regular_User_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestUser :() ==> ()
TestUser() ==
(
-- constructor
dcl user : Regular_User := new Regular_User("Diolinda", <Feminino>, "diolinda@gmail.com", "
password_diolinda", true);
dcl user2 : Regular_User := new Regular_User("Diofeia", <Feminino>, "diofeia@gmail.com", "
password_diofeia", false);
dcl model : Model := new Model("Pedro Faria",67,<Masculino>,1.78,74.32);
dcl show : Fashion_Show := new Fashion_Show("Porto","Primavera",2017, 12, 31, 23, 59);
dcl model_look : Model_Look := new Model_Look(model,show, mk_Fashion_Show'Date(2017, 12, 31,
23, 00),"vestido azul e cor de rosa");

-- gets
assertEqual(user.getName(),"Diolinda");
assertEqual(user2.getName(),"Diofeia");
assertEqual(user.getPremium(),true);
assertEqual(user2.getPremium(),false);
assertEqual(user.getGender(),<Feminino>);
assertEqual(user2.getGender(),<Feminino>);
assertEqual(user.getEmail(),"diolinda@gmail.com");
assertEqual(user2.getEmail(),"diofeia@gmail.com");
assertEqual(user.getPassword(),"password_diolinda");
assertEqual(user2.getPassword(),"password_diofeia");

-- looks
assertEqual(user.getFavoriteLooks(),{});
user.addLookToFavoriteLooks(model_look);
assertEqual(user.getFavoriteLooks(),{model_look});
user.removeLookFromFavoriteLooks(model_look);
assertEqual(user.getFavoriteLooks(),{});

return;
);

public static main_test: () ==> ()
main_test() ==
(
IO`print("TestUser -> ");
new Regular_User_Test().TestUser();
IO`println("Passed");

```

```

);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Regular_User_Test

```

Function or operation	Line	Coverage	Calls
TestUser	11	100.0%	3
main_test	39	100.0%	3
Regular_User_Test.vdmpp		100.0%	6

14 Reviewer

```

class Reviewer is subclass of User
types
-- TODO Define types here
    public String = seq of char;
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
    private age : nat1;

operations
-- TODO Define operations here

    --Construtor
    public Reviewer: String * nat1 * Gender * String * String ==> Reviewer
    Reviewer(namel,age1,gender1,emaill,password1) == (

        name := namel;
        age := age1;
        gender := gender1;
        email := emaill;
        password := password1;
        return self;
    );

    -- Retorna a idade

    public pure getAge : () ==> nat1
    getAge() ==
    (
        return age;
    );

functions

-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Reviewer

```

Function or operation	Line	Coverage	Calls
Reviewer	17	100.0%	3
getAge	26	100.0%	1
getGender	33	0.0%	0
Reviewer.vdmpp		100.0%	4

15 Reviewer_Test

```

class Reviewer_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestReviewer :() ==> ()
TestReviewer() ==
(
  -- constructor
  dcl reviewer : Reviewer := new Reviewer("Ana Bacalhau",39,<Feminino>,"anabacalhau@gmail.com",
    "password_anabacalhau");

  -- gets
  assertEquals(reviewer.getName(),"Ana Bacalhau");
  assertEquals(reviewer.getAge(),39);
  assertEquals(reviewer.getGender(),<Feminino>);
  assertEquals(reviewer.getEmail(),"anabacalhau@gmail.com");
  assertEquals(reviewer.getPassword(),"password_anabacalhau");

  return;
);

public static main_test: () ==> ()
main_test() ==
(
  IO`print("TestReviewer -> ");
  new Reviewer_Test().TestReviewer();
  IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Reviewer_Test

```

Function or operation	Line	Coverage	Calls
TestReviewer	11	100.0%	3
main_test	25	100.0%	3

16 Show_Test

```

class Show_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

public TestShow :() ==> ()
TestShow() ==
(
-- constructor

dcl show : Fashion_Show := new Fashion_Show("Porto","Primavera",2017, 12, 31, 23, 59);
dcl designer1 : Fashion_Designer := new Fashion_Designer("Andre Correia",54);
dcl designer2 : Fashion_Designer := new Fashion_Designer("Francisco Loua",64);
dcl designer3 : Fashion_Designer := new Fashion_Designer("Afonso Martins",58);
dcl designer4 : Fashion_Designer := new Fashion_Designer("Carlos Silva",62);
--dcl designer5 : Fashion_Designer := new Fashion_Designer("Mario Andrade",59);
dcl model1 : Model := new Model("Pedro Faria",67,<Masculino>,1.78,74.32);
dcl model2 : Model := new Model("Sara Sampaio",24,<Feminino>,1.82,53.24);
dcl model3 : Model := new Model("Daniela Hanganu",26,<Feminino>,1.79,52.78);
dcl model14 : Model := new Model("Dariia",23,<Feminino>,1.85,56.91);
dcl workshop : WorkShop := new WorkShop("Como costurar um boto?", mk_Fashion_Show`Date(2017,
12, 31, 20, 00), mk_Fashion_Show`Date(2017, 12, 31, 21, 00), 20, "Joo Botes Correia",
"A7");
dcl workshop2 : WorkShop := new WorkShop("Como se maquilhar?", mk_Fashion_Show`Date(2017, 12,
31, 19, 00), mk_Fashion_Show`Date(2017, 12, 31, 20, 00), 20, "Joo Botes Correia", "A9"
);
dcl user1 : Regular_User := new Regular_User("Diolinda",<Feminino>, "diolinda@gmail.com", "
password_diolinda",true);
dcl user2 : Regular_User := new Regular_User("Diofeia",<Feminino>, "diofeia@gmail.com", "
password_diofeia",false);
dcl reviewer : Reviewer := new Reviewer("Ana Bacalhau",39,<Feminino>,"anabacalhau@gmail.com", "
password_anabacalhau");
dcl reviewer2 : Reviewer := new Reviewer("Ana Moura",45,<Feminino>,"anamoura@gmail.com", "
password_anamoura");
dcl data1 : Fashion_Show`Date := mk_Fashion_Show`Date(2017, 12, 31, 10, 30);
dcl data2 : Fashion_Show`Date := mk_Fashion_Show`Date(2017, 12, 31, 11, 00);
dcl data3 : Fashion_Show`Date := mk_Fashion_Show`Date(2017, 12, 31, 12, 30);
dcl data4 : Fashion_Show`Date := mk_Fashion_Show`Date(2017, 12, 31, 14, 00);
dcl data5 : Fashion_Show`Date := mk_Fashion_Show`Date(2017, 12, 31, 15, 30);
dcl data6 : Fashion_Show`Date := mk_Fashion_Show`Date(2017, 12, 31, 17, 00);
dcl data7 : Fashion_Show`Date := mk_Fashion_Show`Date(2017, 12, 31, 18, 30);
dcl critic : Fashion_Show`Critic := mk_Fashion_Show`Critic("Melhor festival de moda que
participei!",5);
dcl critic2 : Fashion_Show`Critic := mk_Fashion_Show`Critic("Evento aquem das expectativas."
,2);

-- gets
assertEqual(show.getTheme(),"Primavera");
assertEqual(show.getLocation(),"Porto");
assertEqual(show.getDate(),mk_Fashion_Show`Date(2017, 12, 31, 23, 59));
assertEqual(show.getModels(),{|->});

```

```

assertEqual(show.getProgramShow(),{<->});

-- get designers
assertEqual(show.getDesigners(),{});
show.addDesignerToShow(designer1);
assertEqual(show.getDesigners(),{designer1});
show.addDesignerToShow(designer2);
assertEqual(show.getDesigners(),{designer1,designer2});
show.rmvDesignerToShow(designer1);
assertEqual(show.getDesigners(),{designer2});
show.rmvDesignerToShow(designer2);
assertEqual(show.getDesigners(),{});

--get models
show.addDesignerToShow(designer1);
show.addDesignerToShow(designer2);
assertEqual(show.getModelsOfDesigner(designer1),{});
assertEqual(show.getModelsOfDesigner(designer2),{});
assertEqual(show.getModels(),{designer1->{},designer2->{}});
show.addModelToShow(designer1,model1);
show.addModelToShow(designer1,model2);
show.addModelToShow(designer1,model3);
show.addModelToShow(designer2,model4);
assertEqual(show.getModelsOfDesigner(designer1),{model1,model2,model3});
assertEqual(show.getModelsOfDesigner(designer2),{model4});

-- workshops
assertEqual(show.getWorkShops(),{});
show.addWorkShopToShow(workshop);
assertEqual(show.getWorkShops(),{workshop});
show.addWorkShopToShow(workshop2);
assertEqual(show.getWorkShops(),{workshop,workshop2});
assertEqual(workshop.getUsers(),{});
show.workShopBooking(workshop, user1);
assertEqual(workshop.getUsers(),{user1});
show.workShopBooking(workshop, user2);
assertEqual(workshop.getUsers(),{user1,user2});
show.rmvWorkShopToShow(workshop);
assertEqual(show.getWorkShops(),{workshop2});
show.rmvWorkShopToShow(workshop2);
assertEqual(show.getWorkShops(),{});

-- program
show.addDesignerToProgramShow(data1,designer1);
assertEqual(show.getProgramShow(),{data1->designer1});
assertEqual(card dom show.getProgramShow(),1);
show.addDesignerToProgramShow(data2,designer2);
assertEqual(show.getProgramShow(),{data1->designer1,data2->designer2});
assertEqual(card dom show.getProgramShow(),2);
show.addDesignerToProgramShow(data3,designer3);
assertEqual(show.getProgramShow(),{data1->designer1,data2->designer2,data3->designer3});
assertEqual(card dom show.getProgramShow(),3);
show.addDesignerToProgramShow(data4,designer4);
assertEqual(show.getProgramShow(),{data1->designer1,data2->designer2,data3->designer3,
data4->designer4});
assertEqual(card dom show.getProgramShow(),4);

--invalid entry (try to break pre-condition by adding another event with already existing
same date)
--show.addDesignerToProgramShow(data1,designer2);

--get designers by date
assertEqual(show.getDesignerByDate(data1),designer1);
assertEqual(show.getDesignerByDate(data2),designer2);
assertEqual(show.getDesignerByDate(data3),designer3);

```

```

assertEqual(show.getDesignerByDate(data4), designer4);

--add same designer to another date
show.addDesignerToProgramShow(data5, designer1);
assertEqual(show.getProgramShow(), {data1|->designer1, data2|->designer2, data3|->designer3,
    data4|->designer4, data5|->designer1});
assertEqual(card dom show.getProgramShow(), 5);
show.addDesignerToProgramShow(data6, designer2);
assertEqual(show.getProgramShow(), {data1|->designer1, data2|->designer2, data3|->designer3,
    data4|->designer4, data5|->designer1, data6|->designer2});
assertEqual(card dom show.getProgramShow(), 6);
show.addDesignerToProgramShow(data7, designer1);
assertEqual(show.getProgramShow(), {data1|->designer1, data2|->designer2, data3|->designer3,
    data4|->designer4, data5|->designer1, data6|->designer2, data7|->designer1});
assertEqual(card dom show.getProgramShow(), 7);

--get list of dates by designer
assertEqual(show.getListOfDatesByDesigner(designer1), {data1, data5, data7});
assertEqual(show.getListOfDatesByDesigner(designer2), {data2, data6});

--invalid entry (try to break pre-condition by retriving list of dates by a designer that not
    exists on program)
--assertEqual(show.getListOfDatesByDesigner(designer5), {});

--remove date from program show
show.removeDesignerFromProgramShow(data7);
assertEqual(show.getProgramShow(), {data1|->designer1, data2|->designer2, data3|->designer3,
    data4|->designer4, data5|->designer1, data6|->designer2});
assertEqual(card dom show.getProgramShow(), 6);
show.removeDesignerFromProgramShow(data6);
assertEqual(show.getProgramShow(), {data1|->designer1, data2|->designer2, data3|->designer3,
    data4|->designer4, data5|->designer1});
assertEqual(card dom show.getProgramShow(), 5);
show.removeDesignerFromProgramShow(data5);
assertEqual(show.getProgramShow(), {data1|->designer1, data2|->designer2, data3|->designer3,
    data4|->designer4});
assertEqual(card dom show.getProgramShow(), 4);

--invalid entry (try to break pre-condition by removing a date that not exists on program)
--show.removeDesignerFromProgramShow(data5);

show.removeDesignerFromProgramShow(data4);
assertEqual(show.getProgramShow(), {data1|->designer1, data2|->designer2, data3|->designer3});
assertEqual(card dom show.getProgramShow(), 3);

--invalid entry (try to break pre-condition by removing a date that not exists on program)
--show.removeDesignerFromProgramShow(data4);

show.removeDesignerFromProgramShow(data3);
assertEqual(show.getProgramShow(), {data1|->designer1, data2|->designer2});
assertEqual(card dom show.getProgramShow(), 2);

show.removeDesignerFromProgramShow(data2);
assertEqual(show.getProgramShow(), {data1|->designer1});
assertEqual(card dom show.getProgramShow(), 1);

show.removeDesignerFromProgramShow(data1);
assertEqual(show.getProgramShow(), {});

-- critics
assertEqual(show.getCritics(), {});
assertEqual(show.getAvgReview(), 0);
show.addCritic(reviewer, critic);
assertEqual(show.getCritics(), {reviewer|->critic});

```



```

    assertEquals(show.getAvgReview(),5);
    show.addCritic(reviewer2, critic2);
    assertEquals(show.getCritics(),{reviewer|->critic,reviewer2|->critic2});
    assertEquals(show.getAvgReview(),3.5);
    show.rmvCritic(reviewer);
    assertEquals(show.getCritics(),{reviewer2|->critic2});
    assertEquals(show.getAvgReview(),2);
    show.rmvCritic(reviewer2);
    assertEquals(show.getCritics(),{|->});
    assertEquals(show.getAvgReview(),0);

    --test functions
    assertEquals(show.DaysOfMonth(1,2000),31);
    assertEquals(show.DaysOfMonth(4,2000),30);
    assertEquals(show.DaysOfMonth(2,2000),29);
    assertEquals(show.DaysOfMonth(2,1900),28);

    return;
};

public static main_test: () ==> ()
main_test() ==
(
    IO`print("TestShow -> ");
    new Show_Test().TestShow();
    IO`println("Passed");
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end Show_Test
```

Function or operation	Line	Coverage	Calls
TestShow	11	100.0%	3
main_test	188	100.0%	3
Show_Test.vdmpp		100.0%	6

17 User

```

class User
types
-- TODO Define types here
    public String = seq of char;
    public Gender = <Masculino> | <Feminino>;
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
    protected name : String := "Default_Name";
    protected gender : Gender := <Masculino>;
    protected email : String := "";
    protected password : String := "";
operations
```

```

-- TODO Define operations here

--Retorna o nome
public pure getName : () ==> String
getName() ==
(
  return name;
);

--Retorna o genero
public pure getGender : () ==> Gender
getGender() ==
(
  return gender;
);

--Retorna o email
public pure getEmail : () ==> String
getEmail() ==
(
  return email;
);

--Retorna a password
public pure getPassword : () ==> String
getPassword() ==
(
  return password;
);

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end User

```

Function or operation	Line	Coverage	Calls
getEmail	32	100.0%	9
getGender	25	100.0%	9
getName	16	100.0%	9
getPassword	39	100.0%	9
User.vdmpp		100.0%	36

18 WorkShop

```

class WorkShop
types
-- TODO Define types here
public String = seq of char;
public Users = set of Regular_User;

```

```

values
-- TODO Define values here
instance variables
-- TODO Define instance variables here

    private theme : String;
    private begin_date : Fashion_Show`Date;
    private end_date : Fashion_Show`Date;
    private lotation : nat1;
    private orator : String;
    private registered_users : Users := {};
    private room : String;
    inv card registered_users <= lotation;

operations
-- TODO Define operations here

    public Workshop: String * Fashion_Show`Date * Fashion_Show`Date * nat1 * String * String ==>
        Workshop
    Workshop(theme1, begin_date1, end_date1, lotation1, orator1, room1) == (

        theme := theme1;
        begin_date := begin_date1;
        end_date := end_date1;
        lotation := lotation1;
        orator := orator1;
        room := room1;

        return self;
    );

    --Retorna o tema do workshop

    public pure getTheme : () ==> String
    getTheme() ==
    (
        return theme;
    );

    --Retorna a data de inicio

    public pure getBeginDate : () ==> Fashion_Show`Date
    getBeginDate() ==
    (
        return begin_date;
    );

    --Retorna a data de fim

    public pure getEndDate : () ==> Fashion_Show`Date
    getEndDate() ==
    (
        return end_date;
    );

    --Retorna a lota o

    public pure getLotation : () ==> nat1
    getLotation() ==
    (
        return lotation;
    );

    --Retorna o orador

```

```

public pure getOrator : () ==> String
getOrator() ==
(
  return orator;
);

--Retorna a sala do workshop

public pure getRoom : () ==> String
getRoom() ==
(
  return room;
);

--Retorna os utilizadores que participam

public pure getUsers : () ==> Users
getUsers() ==
(
  return registered_users;
);

--Adiciona um utilizador  workshop

public addUserToWorkshop : (Regular_User) ==> ()
addUserToWorkshop(Regular_User) ==
(
  registered_users := registered_users union {Regular_User};
  return;
)
pre Regular_User not in set registered_users and card registered_users < lotation
post Regular_User in set registered_users;

--Remove um utilizador  workshop

public rmvUserToWorkshop : (Regular_User) ==> ()
rmvUserToWorkshop(Regular_User) ==
(
  registered_users := registered_users \ {Regular_User};
  return;
)
pre Regular_User in set registered_users
post Regular_User not in set registered_users;

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end WorkShop

```

Function or operation	Line	Coverage	Calls
WorkShop	25	100.0%	9
addUserToWorkshop	88	100.0%	12
getBeginDate	46	100.0%	3
getEndDate	53	100.0%	3
getLotation	60	100.0%	9
getOrator	67	100.0%	3
getRoom	74	100.0%	3

getTheme	39	100.0%	3
getUsers	81	100.0%	30
rmvUserToWorkshop	98	100.0%	6
WorkShop.vdmpp		100.0%	81

19 WorkShop_Test

```

class WorkShop_Test is subclass of MyTestCase
types
-- TODO Define types here
values
-- TODO Define values here
instance variables
-- TODO Define instance variables here
operations
-- TODO Define operations here

private TestWorkShop :() ==> ()
TestWorkShop() ==
(
-- constructor
dcl workshop : WorkShop := new WorkShop("Como costurar um boto?", mk_Fashion_Show`Date(2017,
12, 31, 20, 00), mk_Fashion_Show`Date(2017, 12, 31, 21, 00), 20, "Joo Botes Correia",
"A7");
dcl user1 : Regular_User := new Regular_User("Diolinda",<Feminino>, "diolinda@gmail.com", "
password_diolinda",true);
dcl user2: Regular_User := new Regular_User("Diofeia",<Feminino>, "diofeia@gmail.com", "
password_diofeia",false);

-- gets
assertEqual(workshop.getTheme(),"Como costurar um boto?");
assertEqual(workshop.getBeginDate(),mk_Fashion_Show`Date(2017, 12, 31, 20, 00));
assertEqual(workshop.getEndDate(),mk_Fashion_Show`Date(2017, 12, 31, 21, 00));
assertEqual(workshop.getLotation(),20);
assertEqual(workshop.getOrator(),"Joo Botes Correia");
assertEqual(workshop.getRoom(),"A7");
assertEqual(workshop.getUsers(),{});

-- Adicionar utilizadores ao workshop
workshop.addUserToWorkshop(user1);
assertEqual(workshop.getUsers(),{user1});
workshop.addUserToWorkshop(user2);
assertEqual(workshop.getUsers(),{user1,user2});
workshop.rmvUserToWorkshop(user1);
assertEqual(workshop.getUsers(),{user2});
workshop.rmvUserToWorkshop(user2);
assertEqual(workshop.getUsers(),{});

return;
);

public static main_test: () ==> ()
main_test() ==
(
IO`print("TestWorkShop -> ");
new WorkShop_Test().TestWorkShop();
IO`println("Passed");
);

```

```

functions
-- TODO Define functiones here
traces
-- TODO Define Combinatorial Test Traces here
end WorkShop_Test

```

Function or operation	Line	Coverage	Calls
TestWorkShop	11	100.0%	3
main_test	42	100.0%	3
WorkShop_Test.vdmpp		100.0%	6