



Performance

Vertex Buffer Objects



Data Preparation

- Allocate and fill arrays with vertices and indices (optional)

```
// array for vertices
float *vertexB;
// fill arrays with vertex values

// array for indices
unsigned int *indices;
// fill arrays with indices
```



VBOs - Initialization

- Enable Buffer Functionality
 - Do once during initialization of the app

```
glEnableClientState(GL_VERTEX_ARRAY);
```



Buffer Initialization

- Generate Vertex Buffer Objects

```
// buffers is a global variable
// n is the number of buffers - one buffer per array
GLuint buffers[n];
...
glGenBuffers(n, buffers);
```

- For Each Buffer

- Set buffer active

```
glBindBuffer(GL_ARRAY_BUFFER, buffers[0]);
```

- Fill buffer

```
glBufferData(GL_ARRAY_BUFFER, arraySize, vertexB, GL_STATIC_DRAW);
```

in bytes



Index Buffer Initialization

- Generate Index Buffer Object

```
// indexes is a global variable
```

```
GLuint indexes[1];
```

```
...
```

```
glGenBuffers(n, indexes);
```

- Set buffer active

```
glBindBuffer(GL_ELEMENT_ARRAY_BUFFER, indexes);
```

- Fill buffer

```
glBufferData(GL_ELEMENT_ARRAY_BUFFER, arraySize,  
             indices, GL_STATIC_DRAW);
```



VBOs - Drawing

- Step 1: Set buffer active and define the semantics

```
glBindBuffer(GL_ARRAY_BUFFER, buffers[0]);  
glVertexPointer(3, GL_FLOAT, 0, 0);
```

- Step 2 : Draw VBOs

- With index list

```
glBindBuffer(GL_ELEMENT_ARRAY_BUFFER, indicesBuff);  
glDrawElements(GL_TRIANGLES, count, GL_UNSIGNED_INT, NULL);
```

- Without index list

```
glDrawArrays(GL_TRIANGLES, first, count);
```

`first` – the starting index

`count` – the number of vertices (not triangles) to draw



Frames per Second

```
int time;  
time = glutGet(GLUT_ELAPSED_TIME);
```

- Returns the number of milliseconds since GLUT has been initialized

...

```
frame++;  
time=glutGet(GLUT_ELAPSED_TIME);  
if (time - timebase > 1000) {  
    fps = frame*1000.0/(time-timebase);  
    timebase = time;  
    frame = 0;  
}
```

...

- Use function `glutSetWindowTitle(char *s)` to display the fps counter (`sprintf`)



Practical Assignment

- Define vertex buffers for the cylinder (without indices)
- Initialization:
 - Create the arrays with the suitable dimension for the vertices of the cylinder
 - Number of vertices = $\text{sides} \times 3 + \text{sides} \times 6 + \text{sides} \times 3$

topbodybottom
 - Each vertex takes three floats
 - Fill the vertex array with the appropriate values to draw the cylinder
 - Generate and enable the VBOs



Practical Assignment


- Render:
 - Bind the array
 - Define the semantic for the vertex buffer
 - Use `glDrawArrays` to draw the cylinder
- Compute the FPS values obtained with and without VBOs for several cylinders and fill the grid below:

Mode\sides	4096	16384	65536	262144
Immediate mode				
VBO				



Installing GLEW (Win)

- Add the content of “glew.zip” to the toolkits folder such that the final configuration looks as follows:



- Run Cmake and fill the TOOLKITS_FOLDER field with the correct path



Installing GLEW (Linux)

- Install GLEW
 - `sudo apt-get install libglew-dev`



OpenGL > 1.1 (Win & Linux)

- GLEW – library that facilitates access to OpenGL functionality post version 1.1 (Win)

```
#include <GL/glew.h> // before including glut.h
```

- In the main function (after GLUT's callback registry):

```
glewInit(); // before calling any OpenGL function
```