

Pokemon Pocket Angular - Codigo del proyecto

Ruta: /Users/franciscorodriguezpons/Documents/New project/pokemon-pocket-angular

Generado: 2026-05-30 17:02

Archivos incluidos: 36

Excluido: node_modules, dist, .angular, .git, package-lock.json y binarios.

Indice

- .vscode/extensions.json
- .vscode/launch.json
- .vscode/mcp.json
- .vscode/tasks.json
- README.md
- angular.json
- package.json
- public/foil-worklet.js
- src/app/app.config.ts
- src/app/app.html
- src/app/app.scss
- src/app/app.spec.ts
- src/app/app.ts
- src/app/core/models/pokemon-card.model.ts
- src/app/core/services/fx.service.ts
- src/app/core/services/game.service.ts
- src/app/core/services/hand-layout.service.ts
- src/app/features/arena/arena.component.html
- src/app/features/arena/arena.component.scss
- src/app/features/arena/arena.component.ts
- src/app/features/card/card.component.html
- src/app/features/card/card.component.scss
- src/app/features/card/card.component.ts
- src/app/features/fx-layer/fx-layer.component.html
- src/app/features/fx-layer/fx-layer.component.scss
- src/app/features/fx-layer/fx-layer.component.ts
- src/app/features/hand/hand.component.html
- src/app/features/hand/hand.component.scss
- src/app/features/hand/hand.component.ts
- src/app/shared/directives/tilt.directive.ts
- src/index.html
- src/main.ts
- src/styles.scss
- tsconfig.app.json
- tsconfig.json
- tsconfig.spec.json

.vscode/extensions.json

```
1 {  
2   // For more information, visit: https://go.microsoft.com/fwlink/?linkid=827846  
3   "recommendations": ["angular.ng-template"]  
4 }
```

.vscode/launch.json

```
1 {
2   // For more information, visit: https://go.microsoft.com/fwlink/?linkid=830387
3   "version": "0.2.0",
4   "configurations": [
5     {
6       "name": "ng serve",
7       "type": "chrome",
8       "request": "launch",
9       "preLaunchTask": "npm: start",
10      "url": "http://localhost:4200/"
11    },
12    {
13      "name": "ng test",
14      "type": "chrome",
15      "request": "launch",
16      "preLaunchTask": "npm: test",
17      "url": "http://localhost:9876/debug.html"
18    }
19  ]
20 }
```

.vscode/mcp.json

```
1 {  
2   // For more information, visit: https://angular.dev/ai/mcp  
3   "servers": {  
4     "angular-cli": {  
5       "command": "npx",  
6       "args": ["-y", "@angular/cli", "mcp"]  
7     }  
8   }  
9 }
```

.vscode/tasks.json

```
1 {
2   // For more information, visit: https://go.microsoft.com/fwlink/?LinkId=733558
3   "version": "2.0.0",
4   "tasks": [
5     {
6       "type": "npm",
7       "script": "start",
8       "isBackground": true,
9       "problemMatcher": {
10        "owner": "typescript",
11        "pattern": "$tsc",
12        "background": {
13          "activeOnStart": true,
14          "beginsPattern": {
15            "regexp": "Changes detected"
16          },
17          "endsPattern": {
18            "regexp": "bundle generation (complete|failed)"
19          }
20        }
21      },
22    },
23    {
24      "type": "npm",
25      "script": "test",
26      "isBackground": true,
27      "problemMatcher": {
28        "owner": "typescript",
29        "pattern": "$tsc",
30        "background": {
31          "activeOnStart": true,
32          "beginsPattern": {
33            "regexp": "Changes detected"
34          },
35          "endsPattern": {
36            "regexp": "bundle generation (complete|failed)"
37          }
38        }
39      },
40    }
41  ]
42 }
```

README.md

```
1 # PokemonPocketAngular
2
3 This project was generated using [Angular CLI](https://github.com/angular/angular-cli) version
  21.2.12.
4
5 ## Development server
6
7 To start a local development server, run:
8
9 '''bash
10 ng serve
11 '''
12
13 Once the server is running, open your browser and navigate to 'http://localhost:4200/'. The
  application will automatically reload whenever you modify any of the source files.
14
15 ## Code scaffolding
16
17 Angular CLI includes powerful code scaffolding tools. To generate a new component, run:
18
19 '''bash
20 ng generate component component-name
21 '''
22
23 For a complete list of available schematics (such as 'components', 'directives', or 'pipes'), run:
24
25 '''bash
26 ng generate --help
27 '''
28
29 ## Building
30
31 To build the project run:
32
33 '''bash
34 ng build
35 '''
36
37 This will compile your project and store the build artifacts in the 'dist/' directory. By default,
  the production build optimizes your application for performance and speed.
38
39 ## Running unit tests
40
41 To execute unit tests with the [Vitest](https://vitest.dev/) test runner, use the following command:
42
43 '''bash
44 ng test
45 '''
46
47 ## Running end-to-end tests
48
49 For end-to-end (e2e) testing, run:
50
51 '''bash
52 ng e2e
53 '''
54
55 Angular CLI does not come with an end-to-end testing framework by default. You can choose one that
  suits your needs.
56
57 ## Additional Resources
58
59 For more information on using the Angular CLI, including detailed command references, visit the
  [Angular CLI Overview and Command Reference](https://angular.dev/tools/cli) page.
```

angular.json

```
1 {
2   "$schema": "./node_modules/@angular/cli/lib/config/schema.json",
3   "version": 1,
4   "cli": {
5     "packageManager": "npm"
6   },
7   "newProjectRoot": "projects",
8   "projects": {
9     "pokemon-pocket-angular": {
10      "projectType": "application",
11      "schematics": {
12        "@schematics/angular:component": {
13          "style": "scss"
14        }
15      },
16      "root": "",
17      "sourceRoot": "src",
18      "prefix": "app",
19      "architect": {
20        "build": {
21          "builder": "@angular/build:application",
22          "options": {
23            "browser": "src/main.ts",
24            "tsConfig": "tsconfig.app.json",
25            "inlineStyleLanguage": "scss",
26            "assets": [
27              {
28                "glob": "**/*",
29                "input": "public"
30              }
31            ],
32            "styles": [
33              "src/styles.scss"
34            ]
35          },
36          "configurations": {
37            "production": {
38              "budgets": [
39                {
40                  "type": "initial",
41                  "maximumWarning": "500kB",
42                  "maximumError": "1MB"
43                },
44                {
45                  "type": "anyComponentStyle",
46                  "maximumWarning": "4kB",
47                  "maximumError": "8kB"
48                }
49              ],
50              "outputHashing": "all"
51            },
52            "development": {
53              "optimization": false,
54              "extractLicenses": false,
55              "sourceMap": true
56            }
57          },
58          "defaultConfiguration": "production"
59        },
60        "serve": {
61          "builder": "@angular/build:dev-server",
62          "configurations": {
63            "production": {
64              "buildTarget": "pokemon-pocket-angular:build:production"
65            },
66            "development": {
67              "buildTarget": "pokemon-pocket-angular:build:development"
68            }
69          },
70          "defaultConfiguration": "development"
71        },
72        "test": {
```

```
73         "builder": "@angular/build:unit-test"
74     }
75 }
76 }
77 }
78 }
```

package.json

```
1  {
2    "name": "pokemon-pocket-angular",
3    "version": "0.0.0",
4    "scripts": {
5      "ng": "ng",
6      "start": "ng serve",
7      "build": "ng build",
8      "watch": "ng build --watch --configuration development",
9      "test": "ng test"
10   },
11   "private": true,
12   "packageManager": "npm@11.12.1",
13   "dependencies": {
14     "@angular/common": "^21.2.0",
15     "@angular/compiler": "^21.2.0",
16     "@angular/core": "^21.2.0",
17     "@angular/forms": "^21.2.0",
18     "@angular/platform-browser": "^21.2.0",
19     "@angular/router": "^21.2.0",
20     "gsap": "^3.13.0",
21     "rxjs": "~7.8.0",
22     "tslib": "^2.3.0"
23   },
24   "devDependencies": {
25     "@angular/build": "^21.2.12",
26     "@angular/cli": "^21.2.12",
27     "@angular/compiler-cli": "^21.2.0",
28     "jsdom": "^28.0.0",
29     "prettier": "^3.8.1",
30     "typescript": "~5.9.2",
31     "vitest": "^4.0.8"
32   }
33 }
```

public/foil-worklet.js

```
1  if (typeof registerPaint === 'function') {
2    registerPaint('foil-shine', class {
3      static get inputProperties() {
4        return ['--foil-accent'];
5      }
6    }
7    paint(ctx, size, props) {
8      const accent = props.get('--foil-accent').toString().trim() || '#8be9fd';
9      const gradient = ctx.createLinearGradient(0, 0, size.width, size.height);
10     gradient.addColorStop(0, 'rgba(255,255,255,0)');
11     gradient.addColorStop(0.22, accent);
12     gradient.addColorStop(0.45, 'rgba(255,255,255,0.82)');
13     gradient.addColorStop(0.68, '#7df7ff');
14     gradient.addColorStop(1, 'rgba(255,255,255,0)');
15
16     ctx.globalAlpha = 0.28;
17     ctx.fillStyle = gradient;
18     ctx.fillRect(0, 0, size.width, size.height);
19
20     ctx.globalAlpha = 0.24;
21     ctx.strokeStyle = 'rgba(255,255,255,0.72)';
22     ctx.lineWidth = 1;
23     for (let y = -size.height; y < size.height * 2; y += 14) {
24       ctx.beginPath();
25       ctx.moveTo(-20, y);
26       ctx.bezierCurveTo(size.width * 0.28, y + 24, size.width * 0.66, y - 24, size.width + 20, y +
18);
27       ctx.stroke();
28     }
29   }
30 });
31 }
32
```

src/app/app.config.ts

```
1 import { ApplicationConfig, provideBrowserGlobalErrorListeners } from '@angular/core';
2
3 export const appConfig: ApplicationConfig = {
4   providers: [
5     provideBrowserGlobalErrorListeners(),
6   ]
7 };
8
```

src/app/app.html

```
1 <app-arena></app-arena>  
2 <app-fx-layer></app-fx-layer>
```

src/app/app.scss

```
1 :host {  
2   display: block;  
3   min-height: 100dvh;  
4 }
```

src/app/app.spec.ts

```
1 import { TestBed } from '@angular/core/testing';
2 import { App } from './app';
3
4 describe('App', () => {
5   beforeEach(async () => {
6     await TestBed.configureTestingModule({
7       imports: [App],
8     }).compileComponents();
9   });
10
11   it('should create the app', () => {
12     const fixture = TestBed.createComponent(App);
13     const app = fixture.componentInstance;
14     expect(app).toBeTruthy();
15   });
16
17   it('should render the arena', async () => {
18     const fixture = TestBed.createComponent(App);
19     fixture.detectChanges();
20     await fixture.whenStable();
21     const compiled = fixture.nativeElement as HTMLElement;
22     expect(compiled.querySelector('app-arena')).toBeTruthy();
23   });
24 });
```

src/app/app.ts

```
1 import { Component } from '@angular/core';
2 import { ArenaComponent } from '../features/arena/arena.component';
3 import { FxLayerComponent } from '../features/fx-layer/fx-layer.component';
4
5 @Component({
6   selector: 'app-root',
7   imports: [ArenaComponent, FxLayerComponent],
8   templateUrl: './app.html',
9   styleUrls: ['./app.scss']
10 })
11 export class App {}
```

src/app/core/models/pokemon-card.model.ts

```
1 export interface PokemonCard {  
2   id: string;  
3   name: string;  
4   hp: number;  
5   types: string[];  
6   rarity: 'common' | 'rare' | 'ex';  
7   imageUrl: string;  
8   accent: string;  
9 }  
10
```

src/app/core/services/fx.service.ts

```
1 import { Injectable } from '@angular/core';
2 import { Subject } from 'rxjs';
3
4 export type FxEventType = 'damage' | 'heal' | 'draw';
5
6 export interface FxEvent {
7   type: FxEventType;
8   value?: number;
9   x: number;
10  y: number;
11 }
12
13 @Injectable({ providedIn: 'root' })
14 export class FxService {
15   private readonly eventsSubject = new Subject<FxEvent>();
16   readonly events$ = this.eventsSubject.asObservable();
17
18   emit(event: FxEvent): void {
19     this.eventsSubject.next(event);
20   }
21
22   damage(value: number, x: number, y: number): void {
23     this.emit({ type: 'damage', value, x, y });
24   }
25
26   heal(value: number, x: number, y: number): void {
27     this.emit({ type: 'heal', value, x, y });
28   }
29
30   draw(x: number, y: number): void {
31     this.emit({ type: 'draw', x, y });
32   }
33 }
34
```

src/app/core/services/game.service.ts

```
1 import { computed, Injectable, signal } from '@angular/core';
2 import { PokemonCard } from '../models/pokemon-card.model';
3 import { FxService } from '../fx.service';
4
5 const STARTER_DECK: PokemonCard[] = [
6   {
7     id: 'charizard-ex',
8     name: 'Charizard ex',
9     hp: 180,
10    types: ['Fire'],
11    rarity: 'ex',
12    imageUrl:
13      'https://raw.githubusercontent.com/PokeAPI/sprites/master/sprites/pokemon/other/official-artwork/6.png',
14    accent: '#ff6a3d'
15  },
16  {
17    id: 'blastoise',
18    name: 'Blastoise',
19    hp: 160,
20    types: ['Water'],
21    rarity: 'rare',
22    imageUrl:
23      'https://raw.githubusercontent.com/PokeAPI/sprites/master/sprites/pokemon/other/official-artwork/9.png',
24    accent: '#47a3ff'
25  },
26  {
27    id: 'venusaur',
28    name: 'Venusaur',
29    hp: 170,
30    types: ['Grass'],
31    rarity: 'rare',
32    imageUrl:
33      'https://raw.githubusercontent.com/PokeAPI/sprites/master/sprites/pokemon/other/official-artwork/3.png',
34    accent: '#55d88a'
35  },
36  {
37    id: 'pikachu',
38    name: 'Pikachu',
39    hp: 90,
40    types: ['Lightning'],
41    rarity: 'common',
42    imageUrl:
43      'https://raw.githubusercontent.com/PokeAPI/sprites/master/sprites/pokemon/other/official-artwork/25.png',
44    accent: '#ffd84d'
45  },
46  {
47    id: 'mewtwo',
48    name: 'Mewtwo',
49    hp: 160,
50    types: ['Psychic'],
51    rarity: 'ex',
52    imageUrl:
53      'https://raw.githubusercontent.com/PokeAPI/sprites/master/sprites/pokemon/other/official-artwork/150.png',
54    accent: '#c28cff'
55  },
56  {
57    id: 'lucario',
58    name: 'Lucario',
59    hp: 130,
60    types: ['Fighting'],
61    rarity: 'rare',
62    imageUrl:
63      'https://raw.githubusercontent.com/PokeAPI/sprites/master/sprites/pokemon/other/official-artwork/448.png',
64    accent: '#6da6ff'
65  },
66  {
```

```

61     id: 'gengar',
62     name: 'Gengar',
63     hp: 140,
64     types: ['Ghost'],
65     rarity: 'rare',
66     imageUrl:
'https://raw.githubusercontent.com/PokeAPI/sprites/master/sprites/pokemon/other/official-
artwork/94.png',
67     accent: '#9b67ff'
68   }
69 ];
70
71 @Injectable({ providedIn: 'root' })
72 export class GameService {
73   readonly deck = signal<PokemonCard[]>(STARTER_DECK.slice(4));
74   readonly hand = signal<PokemonCard[]>(STARTER_DECK.slice(0, 4));
75   readonly activePokemon = signal<PokemonCard>(STARTER_DECK[0]);
76   readonly discard = signal<PokemonCard[]>([]);
77
78   readonly deckCount = computed(() => this.deck().length);
79   readonly handCount = computed(() => this.hand().length);
80
81   constructor(private readonly fx: FxService) {}
82
83   drawCard(origin?: { x: number; y: number }): void {
84     const [nextCard, ...remainingDeck] = this.deck();
85     if (!nextCard || this.hand().length >= 7) {
86       return;
87     }
88
89     this.deck.set(remainingDeck);
90     this.hand.update((hand) => [...hand, nextCard]);
91     this.fx.draw(origin?.x ?? window.innerWidth * 0.5, origin?.y ?? window.innerHeight * 0.72);
92   }
93
94   setActivePokemon(card: PokemonCard, origin?: { x: number; y: number }): void {
95     this.activePokemon.set(card);
96     this.hand.update((hand) => hand.filter((item) => item.id !== card.id));
97     this.fx.emit({
98       type: 'draw',
99       x: origin?.x ?? window.innerWidth * 0.5,
100       y: origin?.y ?? window.innerHeight * 0.64
101     });
102   }
103
104   damageActive(value = 30, origin?: { x: number; y: number }): void {
105     const current = this.activePokemon();
106     this.activePokemon.set({ ...current, hp: Math.max(0, current.hp - value) });
107     this.fx.damage(value, origin?.x ?? window.innerWidth * 0.5, origin?.y ?? window.innerHeight *
0.34);
108   }
109
110   healActive(value = 20, origin?: { x: number; y: number }): void {
111     const current = this.activePokemon();
112     this.activePokemon.set({ ...current, hp: current.hp + value });
113     this.fx.heal(value, origin?.x ?? window.innerWidth * 0.5, origin?.y ?? window.innerHeight *
0.34);
114   }
115
116   reset(): void {
117     this.deck.set(STARTER_DECK.slice(4));
118     this.hand.set(STARTER_DECK.slice(0, 4));
119     this.activePokemon.set(STARTER_DECK[0]);
120     this.discard.set([]);
121   }
122 }
123

```

src/app/core/services/hand-layout.service.ts

```
1 import { Injectable } from '@angular/core';
2
3 export interface HandCardTransform {
4   x: number;
5   y: number;
6   angle: number;
7   zIndex: number;
8 }
9
10 @Injectable({ providedIn: 'root' })
11 export class HandLayoutService {
12   getTransform(index: number, total: number): HandCardTransform {
13     if (total <= 1) {
14       return { x: 0, y: 0, angle: 0, zIndex: 10 };
15     }
16
17     const center = (total - 1) / 2;
18     const normalized = (index - center) / Math.max(center, 1);
19     const spread = Math.min(76, 36 + total * 8);
20     const radius = Math.max(360, 460 - total * 10);
21     const theta = normalized * 0.42;
22
23     return {
24       x: Math.sin(theta) * spread,
25       y: Math.cos(theta) * radius - radius + Math.abs(normalized) * 18,
26       angle: normalized * 18,
27       zIndex: Math.round(100 - Math.abs(normalized) * 10 + index)
28     };
29   }
30
31   toCssTransform(index: number, total: number): string {
32     const transform = this.getTransform(index, total);
33     return `translate3d(${transform.x}px, ${transform.y}px, 0) rotate(${transform.angle}deg)`;
34   }
35 }
36
```

src/app/features/arena/arena.component.html

```
1 <main class="arena-shell">
2   <section class="opponent-zone">
3     <div class="opponent-card"></div>
4     <div class="opponent-card is-raised"></div>
5     <div class="opponent-card"></div>
6   </section>
7
8   <section class="battlefield">
9     <div class="bench-line"></div>
10
11     <div class="active-slot">
12       <app-card [card]="game.activePokemon()" [active]="true"></app-card>
13     </div>
14
15     <div class="controls">
16       <button type="button" (click)="game.damageActive(30, { x: $event.clientX, y: $event.clientY
17     })">Damage 30</button>
18       <button type="button" (click)="game.healActive(20, { x: $event.clientX, y: $event.clientY
19     })">Heal 20</button>
20       <button type="button" (click)="game.reset()">Reset</button>
21     </div>
22   </section>
23
24   <app-hand></app-hand>
25 </main>
```

src/app/features/arena/arena.component.scss

```
1  .arena-shell {
2    background:
3      radial-gradient(circle at 50% 18%, rgb(84 156 255 / 0.28), transparent 26rem),
4      radial-gradient(circle at 18% 70%, rgb(255 187 91 / 0.16), transparent 18rem),
5      linear-gradient(160deg, #101827 0%, #182231 44%, #101218 100%);
6    color: white;
7    min-height: 100dvh;
8    overflow: hidden;
9    position: relative;
10 }
11
12 .arena-shell::before {
13   background:
14     linear-gradient(rgb(255 255 255 / 0.055) 1px, transparent 1px),
15     linear-gradient(90deg, rgb(255 255 255 / 0.045) 1px, transparent 1px);
16   background-size: 64px 64px;
17   content: '';
18   inset: 0;
19   mask-image: linear-gradient(to bottom, transparent, black 18%, black 82%, transparent);
20   position: absolute;
21 }
22
23 .opponent-zone {
24   display: flex;
25   gap: 1rem;
26   justify-content: center;
27   padding-top: 1.25rem;
28   position: relative;
29   z-index: 1;
30 }
31
32 .opponent-card {
33   aspect-ratio: 0.714;
34   background: linear-gradient(145deg, #2a3345, #151b27);
35   border: 1px solid rgb(255 255 255 / 0.14);
36   border-radius: 12px;
37   box-shadow: 0 16px 28px rgb(0 0 0 / 0.28);
38   width: clamp(3.3rem, 6vw, 4.6rem);
39 }
40
41 .opponent-card.is-raised {
42   transform: translateY(0.8rem);
43 }
44
45 .battlefield {
46   align-items: center;
47   display: grid;
48   inset: 0;
49   justify-items: center;
50   padding-bottom: 9rem;
51   padding-top: 4rem;
52   position: absolute;
53   z-index: 2;
54 }
55
56 .bench-line {
57   background: radial-gradient(ellipse, rgb(125 211 252 / 0.2), transparent 70%);
58   border: 1px solid rgb(255 255 255 / 0.12);
59   border-radius: 50%;
60   height: clamp(13rem, 34vw, 23rem);
61   position: absolute;
62   top: 28%;
63   width: min(74vw, 48rem);
64 }
65
66 .active-slot {
67   position: relative;
68   z-index: 2;
69 }
70
71 .active-slot::before {
72   background: radial-gradient(ellipse, rgb(255 255 255 / 0.36), transparent 62%);
```

```

73     bottom: -2.1rem;
74     content: '';
75     filter: blur(8px);
76     height: 4rem;
77     left: 50%;
78     position: absolute;
79     transform: translateX(-50%);
80     width: 130%;
81 }
82
83 .controls {
84     bottom: 11rem;
85     display: flex;
86     flex-wrap: wrap;
87     gap: 0.5rem;
88     justify-content: center;
89     position: fixed;
90     z-index: 30;
91 }
92
93 .controls button {
94     background: rgb(255 255 255 / 0.1);
95     border: 1px solid rgb(255 255 255 / 0.18);
96     border-radius: 8px;
97     color: white;
98     cursor: pointer;
99     font: inherit;
100    font-size: 0.82rem;
101    font-weight: 800;
102    padding: 0.65rem 0.85rem;
103 }
104
105 .controls button:hover {
106     background: rgb(255 255 255 / 0.18);
107 }
108
109 @media (max-width: 720px) {
110     .battlefield {
111         padding-bottom: 7.5rem;
112     }
113
114     .controls {
115         bottom: 8.5rem;
116     }
117 }
118

```

src/app/features/arena/arena.component.ts

```
1 import { Component } from '@angular/core';
2 import { GameService } from '../../../core/services/game.service';
3 import { CardComponent } from '../../../card/card.component';
4 import { HandComponent } from '../../../hand/hand.component';
5
6 @Component({
7   selector: 'app-arena',
8   imports: [CardComponent, HandComponent],
9   templateUrl: './arena.component.html',
10  styleUrls: ['./arena.component.scss']
11 })
12 export class ArenaComponent {
13   constructor(readonly game: GameService) {}
14 }
15
```

```
1 <article
2   appTilt
3   [strength]="compact ? 7 : 12"
4   class="pokemon-card"
5   [class.is-active]="active"
6   [class.is-compact]="compact"
7   [style.--foil-accent]="card.accent"
8 >
9   <div class="card-surface">
10     <div class="foil-layer"></div>
11     <div class="shine-layer"></div>
12
13     <header class="card-header">
14       <span class="card-name">{{ card.name }}</span>
15       <span class="card-hp">{{ card.hp }} HP</span>
16     </header>
17
18     <div class="art-frame">
19       <img
20         [src]="card.imageUrl"
21         [alt]="card.name"
22         loading="lazy"
23         (load)="imageLoaded = true"
24         [class.is-loaded]="imageLoaded"
25       />
26     </div>
27
28     <footer class="card-footer">
29       <div class="type-row">
30         <span *ngFor="let type of card.types" class="type-chip">{{ type }}</span>
31       </div>
32       <span class="rarity">{{ card.rarity | uppercase }}</span>
33     </footer>
34   </div>
35 </article>
36
```

src/app/features/card/card.component.scss

```
1  :host {
2    --card-accent: #8be9fd;
3    display: block;
4  }
5
6  .pokemon-card {
7    width: clamp(8.5rem, 16vw, 13rem);
8    aspect-ratio: 0.714;
9    border: 1px solid color-mix(in srgb, var(--card-accent), white 20%);
10   border-radius: 16px;
11   background: #10151f;
12   box-shadow: 0 18px 38px rgb(0 0 0 / 0.36), 0 0 28px color-mix(in srgb, var(--card-accent),
transparent 72%);
13   cursor: pointer;
14   overflow: hidden;
15   position: relative;
16   transform-style: preserve-3d;
17   transition: transform 160ms ease, box-shadow 180ms ease, border-color 180ms ease;
18   will-change: transform;
19 }
20
21 .pokemon-card:hover,
22 .pokemon-card.is-active {
23   border-color: color-mix(in srgb, var(--card-accent), white 52%);
24   box-shadow: 0 24px 56px rgb(0 0 0 / 0.42), 0 0 34px color-mix(in srgb, var(--card-accent),
transparent 48%);
25 }
26
27 .pokemon-card.is-compact {
28   width: clamp(6.8rem, 12vw, 10rem);
29 }
30
31 .card-surface {
32   position: absolute;
33   inset: 0;
34   display: grid;
35   grid-template-rows: auto 1fr auto;
36   gap: 0.55rem;
37   padding: 0.7rem;
38   background:
39     radial-gradient(circle at var(--mouse-x, 50%) var(--mouse-y, 28%), color-mix(in srgb,
var(--card-accent), white 45%), transparent 34%),
40     linear-gradient(145deg, #263041 0%, #111827 48%, #060910 100%);
41   isolation: isolate;
42 }
43
44 .foil-layer,
45 .shine-layer {
46   border-radius: inherit;
47   inset: 0;
48   pointer-events: none;
49   position: absolute;
50 }
51
52 .foil-layer {
53   background:
54     paint(foil-shine),
55     repeating-linear-gradient(112deg, rgb(255 255 255 / 0.08) 0 1px, transparent 1px 10px);
56   mix-blend-mode: screen;
57   opacity: 0.78;
58   transform: translateZ(1px);
59 }
60
61 .shine-layer {
62   background: radial-gradient(circle at var(--mouse-x, 50%) var(--mouse-y, 50%), rgb(255 255 255 /
0.62), transparent 28%);
63   mix-blend-mode: overlay;
64   opacity: 0.6;
65 }
66
67 @supports not (background: paint(foil-shine)) {
68   .foil-layer {
```

```

69     animation: foilSweep 3s linear infinite;
70     background: linear-gradient(110deg, transparent 0%, color-mix(in srgb, var(--card-accent),
71     white 50%) 36%, rgb(255 255 255 / 0.85) 48%, transparent 64%);
72     background-size: 220% 100%;
73 }
74
75 .card-header,
76 .card-footer {
77     align-items: center;
78     display: flex;
79     justify-content: space-between;
80     position: relative;
81     z-index: 1;
82 }
83
84 .card-name {
85     color: white;
86     font-size: clamp(0.78rem, 1.2vw, 0.98rem);
87     font-weight: 800;
88     overflow: hidden;
89     text-overflow: ellipsis;
90     text-shadow: 0 1px 2px rgb(0 0 0 / 0.4);
91     white-space: nowrap;
92 }
93
94 .card-hp,
95 .rarity {
96     color: #fef3c7;
97     font-size: 0.68rem;
98     font-weight: 800;
99     white-space: nowrap;
100 }
101
102 .art-frame {
103     align-items: center;
104     align-self: stretch;
105     background:
106         radial-gradient(circle at 50% 38%, rgb(255 255 255 / 0.22), transparent 46%),
107         color-mix(in srgb, var(--card-accent), #0b1020 74%);
108     border: 1px solid rgb(255 255 255 / 0.22);
109     border-radius: 12px;
110     display: flex;
111     justify-content: center;
112     min-height: 0;
113     overflow: hidden;
114     position: relative;
115     z-index: 1;
116 }
117
118 .art-frame img {
119     filter: drop-shadow(0 18px 14px rgb(0 0 0 / 0.34));
120     max-height: 94%;
121     max-width: 94%;
122     opacity: 0;
123     transform: translateY(6px) scale(0.96);
124     transition: opacity 240ms ease, transform 240ms ease;
125 }
126
127 .art-frame img.is-loaded {
128     opacity: 1;
129     transform: translateY(0) scale(1);
130 }
131
132 .type-row {
133     display: flex;
134     flex-wrap: wrap;
135     gap: 0.28rem;
136     min-width: 0;
137 }
138
139 .type-chip {
140     background: rgb(255 255 255 / 0.14);
141     border: 1px solid rgb(255 255 255 / 0.2);
142     border-radius: 999px;

```

```
143     color: #f8fafc;
144     font-size: 0.64rem;
145     font-weight: 700;
146     padding: 0.16rem 0.4rem;
147 }
148
149 @keyframes foilSweep {
150     from {
151         background-position: 150% 0;
152     }
153
154     to {
155         background-position: -80% 0;
156     }
157 }
158
```

src/app/features/card/card.component.ts

```
1 import { CommonModule } from '@angular/common';
2 import { Component, HostBinding, Input, OnInit } from '@angular/core';
3 import { PokemonCard } from '../../../../core/models/pokemon-card.model';
4 import { TiltDirective } from '../../../../../shared/directives/tilt.directive';
5
6 @Component({
7   selector: 'app-card',
8   imports: [CommonModule, TiltDirective],
9   templateUrl: './card.component.html',
10  styleUrls: ['./card.component.scss']
11 })
12 export class CardComponent implements OnInit {
13   @Input({ required: true }) card!: PokemonCard;
14   @Input() active = false;
15   @Input() compact = false;
16
17   imageLoaded = false;
18
19   @HostBinding('style.--card-accent')
20   get accent(): string {
21     return this.card?.accent ?? '#8be9fd';
22   }
23
24   ngOnInit(): void {
25     const cssApi = CSS as typeof CSS & { paintWorklet?: { addModule(path: string): Promise<void> } };
26     cssApi.paintWorklet?.addModule('/foil-worklet.js').catch(() => undefined);
27   }
28 }
```

src/app/features/fx-layer/fx-layer.component.html

```
1 <canvas #canvas class="fx-canvas" aria-hidden="true"></canvas>  
2
```

src/app/features/fx-layer/fx-layer.component.scss

```
1 :host {
2   inset: 0;
3   pointer-events: none;
4   position: fixed;
5   z-index: 100;
6 }
7
8 .fx-canvas {
9   display: block;
10  height: 100%;
11  width: 100%;
12 }
13
14 :host ::ng-deep .float-number {
15   font-size: clamp(1.45rem, 3vw, 2.5rem);
16   font-weight: 950;
17   left: 0;
18   line-height: 1;
19   pointer-events: none;
20   position: fixed;
21   text-shadow: 0 3px 12px rgb(0 0 0 / 0.42);
22   top: 0;
23   transform: translate(-50%, 0);
24   white-space: nowrap;
25 }
26
```

src/app/features/fx-layer/fx-layer.component.ts

```
1 import { CommonModule } from '@angular/common';
2 import { AfterViewInit, Component, ElementRef, OnDestroy, ViewChild } from '@angular/core';
3 import { Subscription } from 'rxjs';
4 import { FxEvent, FxService } from '../../../core/services/fx.service';
5
6 interface Particle {
7   x: number;
8   y: number;
9   vx: number;
10  vy: number;
11  life: number;
12  maxLife: number;
13  color: string;
14  size: number;
15 }
16
17 @Component({
18   selector: 'app-fx-layer',
19   imports: [CommonModule],
20   templateUrl: './fx-layer.component.html',
21   styleUrls: ['./fx-layer.component.scss']
22 })
23 export class FxLayerComponent implements AfterViewInit, OnDestroy {
24   @ViewChild('canvas', { static: true }) private readonly canvasRef!:
25     ElementRef<HTMLCanvasElement>;
26
27   private ctx!: CanvasRenderingContext2D;
28   private particles: Particle[] = [];
29   private animationFrame = 0;
30   private subscription?: Subscription;
31   private gsap?: { to: (target: Element, vars: Record<string, unknown>) => void; fromTo: (target:
32     Element, from: Record<string, unknown>, to: Record<string, unknown>) => void };
33
34   constructor(
35     private readonly fx: FxService,
36     private readonly host: ElementRef<HTMLElement>
37   ) {}
38
39   async ngAfterViewInit(): Promise<void> {
40     const context = this.canvasRef.nativeElement.getContext('2d');
41     if (!context) {
42       return;
43     }
44
45     this.ctx = context;
46     this.resize();
47     window.addEventListener('resize', this.resize);
48     this.subscription = this.fx.events$.subscribe((event) => this.play(event));
49     this.animationFrame = requestAnimationFrame(() => this.tick());
50
51     try {
52       const module = await import('gsap');
53       this.gsap = module.gsap;
54     } catch {
55       this.gsap = undefined;
56     }
57
58     ngOnDestroy(): void {
59       window.removeEventListener('resize', this.resize);
60       this.subscription?.unsubscribe();
61       cancelAnimationFrame(this.animationFrame);
62     }
63
64     private readonly resize = (): void => {
65       const canvas = this.canvasRef.nativeElement;
66       const ratio = window.devicePixelRatio || 1;
67       canvas.width = Math.floor(window.innerWidth * ratio);
68       canvas.height = Math.floor(window.innerHeight * ratio);
69       canvas.style.width = `${window.innerWidth}px`;
70       canvas.style.height = `${window.innerHeight}px`;
71       this.ctx?.setTransform(ratio, 0, 0, ratio, 0, 0);
72     }
73   }
74 }
```

```

71     };
72
73     private play(event: FxEvent): void {
74         const color = event.type === 'damage' ? '#ff5f6d' : event.type === 'heal' ? '#5dffae' :
75         '#7dd3fc';
76         this.spawnNumber(event, color);
77         this.spawnParticles(event.x, event.y, color, event.type === 'draw' ? 18 : 28);
78     }
79
80     private spawnNumber(event: FxEvent, color: string): void {
81         const element = document.createElement('div');
82         element.className = 'float-number ${event.type}';
83         element.textContent = event.type === 'draw' ? '+1' : `${event.type === 'heal' ? '+' :
84         '-'}${event.value ?? 0}`;
85         element.style.left = `${event.x}px`;
86         element.style.top = `${event.y}px`;
87         element.style.color = color;
88         this.host.nativeElement.appendChild(element);
89
90         if (this.gsap) {
91             this.gsap.fromTo(
92                 element,
93                 { y: 10, opacity: 0, scale: 0.7 },
94                 {
95                     y: -82,
96                     opacity: 1,
97                     scale: 1.18,
98                     duration: 0.82,
99                     ease: 'power3.out',
100                    onComplete: () => this.gsap?.to(element, { opacity: 0, duration: 0.18, onComplete: () =>
101                    element.remove() })
102                }
103            );
104            return;
105        }
106
107        element.animate(
108            [
109                { transform: 'translate(-50%, 10px) scale(0.72)', opacity: 0 },
110                { transform: 'translate(-50%, -72px) scale(1.14)', opacity: 1 },
111                { transform: 'translate(-50%, -88px) scale(1)', opacity: 0 }
112            ],
113            { duration: 900, easing: 'cubic-bezier(.2,.9,.2,1)', fill: 'forwards' }
114        ).finished.finally(() => element.remove());
115    }
116
117    private spawnParticles(x: number, y: number, color: string, count: number): void {
118        for (let i = 0; i < count; i += 1) {
119            const angle = Math.random() * Math.PI * 2;
120            const speed = 1.2 + Math.random() * 4.2;
121            this.particles.push({
122                x,
123                y,
124                vx: Math.cos(angle) * speed,
125                vy: Math.sin(angle) * speed - 1.5,
126                life: 0,
127                maxLife: 34 + Math.random() * 24,
128                color,
129                size: 2 + Math.random() * 4
130            });
131        }
132    }
133
134    private tick(): void {
135        this.ctx.clearRect(0, 0, window.innerWidth, window.innerHeight);
136        this.particles = this.particles.filter((particle) => particle.life < particle.maxLife);
137
138        for (const particle of this.particles) {
139            particle.life += 1;
140            particle.x += particle.vx;
141            particle.y += particle.vy;
142            particle.vy += 0.08;
143
144            const alpha = 1 - particle.life / particle.maxLife;
145            this.ctx.globalAlpha = alpha;

```

```
143     this.ctx.fillStyle = particle.color;
144     this.ctx.beginPath();
145     this.ctx.arc(particle.x, particle.y, particle.size * alpha, 0, Math.PI * 2);
146     this.ctx.fill();
147 }
148
149     this.ctx.globalAlpha = 1;
150     this.animationFrame = requestAnimationFrame(() => this.tick());
151 }
152 }
153
```

src/app/features/hand/hand.component.html

```
1 <section class="hand-zone" aria-label="Player hand">
2   <button class="deck-button" type="button" (click)="game.drawCard({ x: $event.clientX, y:
3     $event.clientY })">
4     <span>{{ game.deckCount() }}</span>
5     Deck
6   </button>
7   <div class="hand-stage">
8     <button
9       *ngFor="let card of game.hand(); let i = index"
10      class="hand-card"
11      type="button"
12      [style.transform]="cardTransform(i)"
13      [style.z-index]="cardZIndex(i)"
14      (click)="play(card, $event)"
15      [attr.aria-label]="'Play ' + card.name"
16    >
17      <app-card [card]="card" [compact]="true"></app-card>
18    </button>
19  </div>
20 </section>
21
```

src/app/features/hand/hand.component.scss

```
1  .hand-zone {
2    align-items: flex-end;
3    bottom: 0;
4    display: grid;
5    grid-template-columns: 6.5rem minmax(0, 1fr) 6.5rem;
6    left: 0;
7    min-height: 15.5rem;
8    padding: 0 1rem 1.1rem;
9    pointer-events: none;
10   position: fixed;
11   right: 0;
12   z-index: 20;
13 }
14
15 .deck-button {
16   align-items: center;
17   align-self: end;
18   background: linear-gradient(145deg, #232b3a, #121722);
19   border: 1px solid rgb(255 255 255 / 0.16);
20   border-radius: 10px;
21   box-shadow: 0 14px 28px rgb(0 0 0 / 0.36);
22   color: #dbeafe;
23   display: flex;
24   flex-direction: column;
25   font: inherit;
26   font-size: 0.72rem;
27   font-weight: 800;
28   gap: 0.2rem;
29   height: 7.4rem;
30   justify-content: center;
31   letter-spacing: 0;
32   pointer-events: auto;
33   text-transform: uppercase;
34   width: 5.2rem;
35 }
36
37 .deck-button span {
38   color: white;
39   font-size: 1.5rem;
40 }
41
42 .hand-stage {
43   align-items: end;
44   display: flex;
45   height: 13.5rem;
46   justify-content: center;
47   min-width: 0;
48   pointer-events: none;
49   position: relative;
50 }
51
52 .hand-card {
53   background: transparent;
54   border: 0;
55   bottom: 0;
56   display: block;
57   left: calc(50% - clamp(3.4rem, 6vw, 5rem));
58   padding: 0;
59   pointer-events: auto;
60   position: absolute;
61   transform-origin: center 92%;
62   transition: transform 260ms cubic-bezier(0.2, 0.9, 0.2, 1.2), filter 180ms ease;
63   will-change: transform;
64 }
65
66 .hand-card:hover {
67   filter: brightness(1.1);
68 }
69
70 @media (max-width: 720px) {
71   .hand-zone {
72     grid-template-columns: 4.8rem minmax(0, 1fr);
```

```
73     min-height: 12rem;
74     padding-inline: 0.55rem;
75 }
76
77 .deck-button {
78     height: 6.2rem;
79     width: 4.4rem;
80 }
81 }
```

src/app/features/hand/hand.component.ts

```
1 import { CommonModule } from '@angular/common';
2 import { Component } from '@angular/core';
3 import { PokemonCard } from '../../../core/models/pokemon-card.model';
4 import { GameService } from '../../../core/services/game.service';
5 import { HandLayoutService } from '../../../core/services/hand-layout.service';
6 import { CardComponent } from '../../card/card.component';
7
8 @Component({
9   selector: 'app-hand',
10  imports: [CommonModule, CardComponent],
11  templateUrl: './hand.component.html',
12  styleUrls: ['./hand.component.scss']
13 })
14 export class HandComponent {
15   constructor(
16     readonly game: GameService,
17     readonly layout: HandLayoutService
18   ) {}
19
20   play(card: PokemonCard, event: MouseEvent): void {
21     this.game.setActivePokemon(card, { x: event.clientX, y: event.clientY });
22   }
23
24   cardTransform(index: number): string {
25     return this.layout.toCssTransform(index, this.game.hand().length);
26   }
27
28   cardZIndex(index: number): number {
29     return this.layout.getTransform(index, this.game.hand().length).zIndex;
30   }
31 }
32
```

src/app/shared/directives/tilt.directive.ts

```
1 import { Directive, ElementRef, HostListener, Input, Renderer2 } from '@angular/core';
2
3 @Directive({
4   selector: '[appTilt]'
5 })
6 export class TiltDirective {
7   @Input() strength = 12;
8
9   constructor(
10     private readonly el: ElementRef<HTMLElement>,
11     private readonly renderer: Renderer2
12   ) {}
13
14   @HostListener('mousemove', ['$event'])
15   onMouseMove(event: MouseEvent): void {
16     const element = this.el.nativeElement;
17     const rect = element.getBoundingClientRect();
18     const x = event.clientX - rect.left;
19     const y = event.clientY - rect.top;
20     const rotateX = ((y - rect.height / 2) / (rect.height / 2)) * -this.strength;
21     const rotateY = ((x - rect.width / 2) / (rect.width / 2)) * this.strength;
22
23     this.renderer.setStyle(element, '--mouse-x', `${(x / rect.width) * 100}%`);
24     this.renderer.setStyle(element, '--mouse-y', `${(y / rect.height) * 100}%`);
25     this.renderer.setStyle(element, 'transform', `perspective(900px) rotateX(${rotateX}deg)
26 rotateY(${rotateY}deg) translateZ(14px)`);
27   }
28
29   @HostListener('mouseleave')
30   onMouseLeave(): void {
31     this.renderer.setStyle(this.el.nativeElement, 'transform', `perspective(900px) rotateX(0deg)
32 rotateY(0deg) translateZ(0)`);
33   }
34 }
```

src/index.html

```
1 <!doctype html>
2 <html lang="en">
3 <head>
4   <meta charset="utf-8">
5   <title>PokemonPocketAngular</title>
6   <base href="/">
7   <meta name="viewport" content="width=device-width, initial-scale=1">
8   <link rel="icon" type="image/x-icon" href="favicon.ico">
9 </head>
10 <body>
11   <app-root></app-root>
12 </body>
13 </html>
```

src/main.ts

```
1 import { bootstrapApplication } from '@angular/platform-browser';
2 import { appConfig } from './app/app.config';
3 import { App } from './app/app';
4
5 bootstrapApplication(App, appConfig)
6   .catch((err) => console.error(err));
```

src/styles.scss

```
1  * {  
2    box-sizing: border-box;  
3  }  
4  
5  html,  
6  body {  
7    margin: 0;  
8    min-height: 100%;  
9  }  
10  
11 body {  
12   background: #101218;  
13   font-family: Inter, ui-sans-serif, system-ui, -apple-system, BlinkMacSystemFont, "Segoe UI", sans-  
14   serif;  
15 }  
16 button,  
17 input,  
18 textarea,  
19 select {  
20   font: inherit;  
21 }
```

tsconfig.app.json

```
1  /* To learn more about Typescript configuration file:
   https://www.typescriptlang.org/docs/handbook/tsconfig-json.html. */
2  /* To learn more about Angular compiler options: https://angular.dev/reference/configs/angular-
   compiler-options. */
3  {
4    "extends": "../tsconfig.json",
5    "compilerOptions": {
6      "outDir": "../out-tsc/app",
7      "types": []
8    },
9    "include": [
10     "src/**/*.ts"
11   ],
12   "exclude": [
13     "src/**/*.spec.ts"
14   ]
15 }
```

tsconfig.json

```
1  /* To learn more about Typescript configuration file:
   https://www.typescriptlang.org/docs/handbook/tsconfig-json.html. */
2  /* To learn more about Angular compiler options: https://angular.dev/reference/configs/angular-
   compiler-options. */
3  {
4    "compileOnSave": false,
5    "compilerOptions": {
6      "strict": true,
7      "noImplicitOverride": true,
8      "noPropertyAccessFromIndexSignature": true,
9      "noImplicitReturns": true,
10     "noFallthroughCasesInSwitch": true,
11     "skipLibCheck": true,
12     "isolatedModules": true,
13     "experimentalDecorators": true,
14     "importHelpers": true,
15     "target": "ES2022",
16     "module": "preserve"
17   },
18   "angularCompilerOptions": {
19     "enableI18nLegacyMessageIdFormat": false,
20     "strictInjectionParameters": true,
21     "strictInputAccessModifiers": true,
22     "strictTemplates": true
23   },
24   "files": [],
25   "references": [
26     {
27       "path": "./tsconfig.app.json"
28     },
29     {
30       "path": "./tsconfig.spec.json"
31     }
32   ]
33 }
```

tsconfig.spec.json

```
1  /* To learn more about Typescript configuration file:
   https://www.typescriptlang.org/docs/handbook/tsconfig-json.html. */
2  /* To learn more about Angular compiler options: https://angular.dev/reference/configs/angular-
   compiler-options. */
3  {
4    "extends": "./tsconfig.json",
5    "compilerOptions": {
6      "outDir": "./out-tsc/spec",
7      "types": [
8        "vitest/globals"
9      ]
10   },
11   "include": [
12     "src/**/*.d.ts",
13     "src/**/*.spec.ts"
14   ]
15 }
```