

Поиск файлов. Перенаправление ввода-вывода. Просмотр запущенных процессов

Лабораторная работа №6

Нати Ф. Б.

Российский университет дружбы народов, Москва, Россия

Информация

- Нати Франсиску Бунда
- студент 1 курса, группа НММбд-02-22
- Российский университет дружбы народов



Вводная часть

- Инструменты поиска файлов и фильтрации текстовых данных
- Файлы и текстовые данные

- Ознакомление с инструментами поиска файлов и фильтрации текстовых данных.
Приобретение практических навыков: по управлению процессами (и заданиями), по проверке использования диска и обслуживанию файловых систем.

- Ознакомиться и разобрать на практике основные инструменты поиска файлов и фильтрации текстовых данных.
- Выполнить упражнения.
- Ответить на контрольные вопросы.

Выполнение лабораторной работы №6

Команды поиска и фильтрации

```
[fbnati@fedora ~]$ find /etc > file.txt
```

```
[fbnati@fedora ~]$ find ~ >> file.txt
```

```
[fbnati@fedora ~]$ grep ".conf$" file.txt
/etc/ethtool.conf
/etc/opansc-x86_64.conf
/etc/resolv.conf
/etc/NetworkManager/NetworkManager.conf
/etc/PackageKit/CommandNotFound.conf
/etc/PackageKit/PackageKit.conf
/etc/PackageKit/Vendor.conf
/etc/UPower/UPower.conf
/etc/X11/xinit/xinput.d/ibus.conf
/etc/X11/xorg.conf.d/90-keyboard.conf
/etc/abrt/plugins/CCpp.conf
/etc/abrt/plugins/java.conf
/etc/abrt/plugins/oops.conf
/etc/abrt/plugins/python3.conf
/etc/abrt/plugins/vmcore.conf
/etc/abrt/plugins/xorg.conf
```

Запуск команд в фоновом режиме

```
[fbnati@fedora ~]$ ls -lR | grep log > logfile &  
[4] 125436
```

Открыть ▾		logfile	
		~/	
1	fbnati fbnati	0	999K 12 21:18 logfile

```
[fbnati@fedora ~]$ gedit &  
[4] 125545
```

Определение идентификатора процесса

```
[fbnat@fedora ~]$ ps aux | grep gedit
fbnat1  125545  2.2  4.3 791812 74148 pts/0    Sl   21:10   0:00 gedit
fbnat1  125577  0.8  0.1 222192  2372 pts/0    S+   21:28   0:00 grep --color=
auto gedit
```

```
[fbnat@fedora ~]$ pgrep gedit
125545
```

```
[fbnat@fedora ~]$ pidof gedit
125545
```

Комманда kill

```
[fbnati@fedora ~]$ man kill
```

```
fbnati@fedora:~ — man kill
KILL(1)                                User Commands                                KILL(1)

NAME
    kill - terminate a process

SYNOPSIS
    kill [-signal|-s signal|-p] [-q value] [-a] [--timeout milliseconds
    signal] [--] pid/name...

    kill -l [number] | -L

DESCRIPTION
    The command kill sends the specified signal to the specified processes
    or process groups.

    If no signal is specified, the TERM signal is sent. The default action
    for this signal is to terminate the process. This signal should be used
    in preference to the KILL signal (number 9), since a process may
    install a handler for the TERM signal in order to perform clean-up
    steps before terminating in an orderly fashion. If a process does not
    terminate after a TERM signal has been sent, then the KILL signal may
    be used; be aware that the latter signal cannot be caught, and so does
    not give the target process the opportunity to perform any clean-up
```

```
[fbnati@fedora ~]$ kill 125545
[4]  Завершено      gedit
```

Команды df, du

```
[fbnati@fedora ~]$ man df
```

```
fbnati@fedora:~ -- man df
DF(1)                                User Commands                                DF(1)

NAME
  df - report file system space usage

SYNOPSIS
  df [OPTION]... [FILE]...

DESCRIPTION
  This manual page documents the GNU version of df. df displays the
  amount of space available on the file system containing each file name
  argument. If no file name is given, the space available on all cur-
  rently mounted file systems is shown. Space is shown in 1K blocks by
  default, unless the environment variable POSIXLY_CORRECT is set, in
  which case 512-byte blocks are used.

  If an argument is the absolute file name of a device node containing a
  mounted file system, df shows the space available on that file system
  rather than on the file system containing the device node. This ver-
  sion of df cannot show the space available on unmounted file systems,
  because on most kinds of systems doing so requires very nonportable in-
  timate knowledge of file system structures.

Manual page df(1) line 1 (press h for help or q to quit)
```

```
[fbnati@fedora ~]$ man du
```

Команды df, du

```
fbnati@fedora:~$ man du
DU(1)                                User Commands                                DU(1)

NAME
    du - estimate file space usage

SYNOPSIS
    du [OPTION]... [FILE]...
    du [OPTION]... --files0-from=F

DESCRIPTION
    Summarize device usage of the set of FILES, recursively for directories.

    Mandatory arguments to long options are mandatory for short options too.

    -0, --null
        end each output line with NUL, not newline

    -a, --all
        write counts for all files, not just directories

    --apparent-size
        Manual page du(1), line 1 (press h for help or q to quit)
```

```
[fbnati@fedora ~]$ df
df: /media/sf_2: Ошибка протокола
Файловая система 1K-блоков  Использовано  Доступно  Использованое%  Смонтировано в
devtmpfs          4096            0          4096              0% /dev
tmpfs             851020           0          851020             0% /dev/shm
tmpfs            340403          2352         338056             1% /run
/dev/sda2        82836480       10743284       70947292          14% /
tmpfs           851020       134624       716396             16% /tmp
/dev/sda2        82836480       10743284       70947292          14% /home
/dev/sda1         996780        175744       752224             19% /boot
pe0             123901848      113786476      10115372           92% /media/sf_
tmpfs           170204           172         170032             1% /run/user/1000
z_cen          976744444       514830456     461913988          53% /media/sf_2
[fbnati@fedora ~]$
```

```
[fbnati@fedora ~]$ du
8      ./mozilla/extensions/[ec838f7-c20a-464f-9b0e-13a3a9e07384]
8      ./mozilla/extensions
0      ./mozilla/plugins
0      ./mozilla/firefox/Crash Reports/events
4      ./mozilla/firefox/Crash Reports
0      ./mozilla/firefox/Pending Pings
0      ./mozilla/firefox/kkehShia.default-release/mindumps
0      ./mozilla/firefox/kkehShia.default-release/crashes/events
4      ./mozilla/firefox/kkehShia.default-release/crashes
2732   ./mozilla/firefox/kkehShia.default-release/security.state
0      ./mozilla/firefox/kkehShia.default-release/storage/permanent/chrome/ldb
/3870112724rsaganotttet-es.files/journals
792     ./mozilla/firefox/kkehShia.default-release/storage/permanent/chrome/ldb
/3870112724rsaganotttet-es.files
0      ./mozilla/firefox/kkehShia.default-release/storage/permanent/chrome/ldb
/356128840pddhlie.files
0      ./mozilla/firefox/kkehShia.default-release/storage/permanent/chrome/ldb
/1451318868ntouromlalnodyry--eprc.files
0      ./mozilla/firefox/kkehShia.default-release/storage/permanent/chrome/ldb
/1657114595Amcateirvt1sty.files
0      ./mozilla/firefox/kkehShia.default-release/storage/permanent/chrome/ldb
```

Команда find

```
[fbnati@fedora ~]$ man find
```

```
fbnati@fedora:~ -- man find
FIND(1)                      General Commands Manual                      FIND(1)

NAME
    find - search for files in a directory hierarchy

SYNOPSIS
    find [-H] [-L] [-P] [-D debugopts] [-Olevel] [starting-point...] [ex-
    pression]

DESCRIPTION
    This manual page documents the GNU version of find. GNU find searches
    the directory tree rooted at each given starting-point by evaluating the
    given expression from left to right, according to the rules of
    precedence (see section OPERATORS), until the outcome is known (the
    left hand side is false for and operations, true for or), at which
    point find moves on to the next file name. If no starting-point is
    specified, . is assumed.

    If you are using find in an environment where security is important
    (for example if you are using it to search directories that are
    writable by other users), you should read the 'Security Considerations'
    chapter of the findutils documentation, which is called Finding Files
    and comes with findutils. That document also includes a lot more de-

    Manual page find(1) line 1 (press h for help or q to quit)
```

```
[fbnati@fedora ~]$ find -type d -depth -print
find: warning: you have specified the global option -depth after the argument -t
ype, but global options are not positional, i.e., -depth affects tests specified
before it as well as those specified after it. Please specify global options b
efore other arguments.
/home/fbnati/.mozilla/extensions/{ec883b7f-c20a-464f-9b0e-13a3a9e97384}
/home/fbnati/.mozilla/extensions
/home/fbnati/.mozilla/plugins
/home/fbnati/.mozilla/firefox/Crash Reports/events
/home/fbnati/.mozilla/firefox/Crash Reports
/home/fbnati/.mozilla/firefox/Pending Pings
/home/fbnati/.mozilla/firefox/fkehShia.default-release/minidumps
/home/fbnati/.mozilla/firefox/fkehShia.default-release/crashes/events
/home/fbnati/.mozilla/firefox/fkehShia.default-release/crashes
/home/fbnati/.mozilla/firefox/fkehShia.default-release/security.state
/home/fbnati/.mozilla/firefox/fkehShia.default-release/storage/permanent/chrome/
ldb/3878112724rsgenotttet-es.files/journals
/home/fbnati/.mozilla/firefox/fkehShia.default-release/storage/permanent/chrome/
ldb/3878112724rsgenotttet-es.files
/home/fbnati/.mozilla/firefox/fkehShia.default-release/storage/permanent/chrome/
ldb/381238489whlie.files
/home/fbnati/.mozilla/firefox/fkehShia.default-release/storage/permanent/chrome/
ldb/1451318868ntouronallnodry--qocr.files
```

1. Какие потоки ввода вывода вы знаете?

- `stdin` — стандартный поток ввода (по умолчанию: клавиатура), файловый дескриптор 0;
- `stdout` — стандартный поток вывода (по умолчанию: консоль), файловый дескриптор 1;
- `stderr` — стандартный поток вывод сообщений об ошибках (по умолчанию: консоль), файловый дескриптор 2.

2. Объясните разницу между операцией `>` и `>>`. `>` - создаётся файл и в него записываются данные; `>>` - файл открывается в режиме добавления.

3. Что такое конвейер?

Конвейер (англ. pipeline) в терминологии операционных систем семейства Unix — некоторое множество процессов, для которых выполнено следующее перенаправление ввода-вывода: то, что выводит на поток стандартного вывода предыдущий процесс, попадает в поток стандартного ввода следующего процес-

5. Что такое PID и GID? PID означает идентификатор процесса, Что означает идентификационный номер для текущего процесса в памяти. Идентификатор группы, часто сокращенно GID, представляет собой числовое значение, используемое для представления определенной группы.

6. Что такое задачи и какая команда позволяет ими управлять? Термин задача используется в ядре Linux для обозначения единицы выполнения, которая может совместно использовать различные системные ресурсы с другими задачами в системе. Команда управления задачами `jobs`.

7. Найдите информацию об утилитах `top` и `htop`. Каковы их функции?

- `Top` : Программа позволяет интерактивно просматривать список запущенных процессов Linux.
- `Htop`: Это ещё более мощная утилита для просмотра запущенных процессов в Linux. Пользоваться ею намного удобнее. Здесь поддерживаются не только горячие клавиши, но и управление мышью. Она выводит всё в цвете,

Результаты

В ходе выполнения лабораторной работы ознакомились с инструментами поиска файлов и фильтрации текстовых данных. Приобретение практических навыков: по управлению процессами (и заданиями), по проверке использования диска и обслуживанию файловых систем.