

Table of contents

\\USER

<table border="1"><tr><td>Recherche_FM</td></tr></table>	Recherche_FM
Recherche_FM	

<table border="1"><tr><td><table border="1"><tr><td>C2P</td></tr></table></td></tr></table>	<table border="1"><tr><td>C2P</td></tr></table>	C2P
<table border="1"><tr><td>C2P</td></tr></table>	C2P	
C2P		

<table border="1"><tr><td><table border="1"><tr><td>QA_B1map</td></tr></table></td></tr></table>	<table border="1"><tr><td>QA_B1map</td></tr></table>	QA_B1map
<table border="1"><tr><td>QA_B1map</td></tr></table>	QA_B1map	
QA_B1map		

<table border="1"><tr><td><table border="1"><tr><td><table border="1"><tr><td>1-ScatteringMatrix</td></tr><tr><td>2-AutoFOV_position_for_QA_B1map</td></tr><tr><td>3-QA_B1map</td></tr></table></td></tr></table></td></tr></table>	<table border="1"><tr><td><table border="1"><tr><td>1-ScatteringMatrix</td></tr><tr><td>2-AutoFOV_position_for_QA_B1map</td></tr><tr><td>3-QA_B1map</td></tr></table></td></tr></table>	<table border="1"><tr><td>1-ScatteringMatrix</td></tr><tr><td>2-AutoFOV_position_for_QA_B1map</td></tr><tr><td>3-QA_B1map</td></tr></table>	1-ScatteringMatrix	2-AutoFOV_position_for_QA_B1map	3-QA_B1map
<table border="1"><tr><td><table border="1"><tr><td>1-ScatteringMatrix</td></tr><tr><td>2-AutoFOV_position_for_QA_B1map</td></tr><tr><td>3-QA_B1map</td></tr></table></td></tr></table>	<table border="1"><tr><td>1-ScatteringMatrix</td></tr><tr><td>2-AutoFOV_position_for_QA_B1map</td></tr><tr><td>3-QA_B1map</td></tr></table>	1-ScatteringMatrix	2-AutoFOV_position_for_QA_B1map	3-QA_B1map	
<table border="1"><tr><td>1-ScatteringMatrix</td></tr><tr><td>2-AutoFOV_position_for_QA_B1map</td></tr><tr><td>3-QA_B1map</td></tr></table>	1-ScatteringMatrix	2-AutoFOV_position_for_QA_B1map	3-QA_B1map		
1-ScatteringMatrix					
2-AutoFOV_position_for_QA_B1map					
3-QA_B1map					

\\USER\Recherche_FM\C2P\QA_B1map\1-ScatteringMatrix

TA: 0.2 s PM: REF Rel. SNR: 1.00 : ns_smatrix

Properties

Prio recon	Off
Load images to viewer	On
Inline movie	Off
Auto store images	On
Load images to stamp segments	Off
Load images to graphic segments	Off
Auto open inline display	Off
Auto close inline display	Off
Start measurement without further preparation	On
Wait for user to start	Off
Start measurements	Single measurement

Routine

Filter	None
Coil elements	AC

Contrast**Resolution - Common**

Prescan Normalize	Off
-------------------	-----

Geometry - AutoAlign

Initial Position	Isocenter
L	0 mm
P	0 mm
H	0 mm
Initial Rotation	0.00 deg
Initial Orientation	Transversal

System - Miscellaneous

Positioning mode	REF
Table position	H
Table position	0 mm
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	F >> H
Save uncombined	Off
Coil Select Mode	Default

System - Adjustments

B0 Shim mode	Tune up
B1 Shim mode	TrueForm
Confirm freq. adjustment	Off
Assume Dominant Fat	Off
Assume Silicone	Off
Adjustment Tolerance	Auto

System - Adjust Volume

Position	Isocenter
Orientation	Transversal
Rotation	0.00 deg
A >> P	263 mm
R >> L	350 mm
F >> H	350 mm
Reset	Off

System - pTx Volumes

B1 Shim mode	TrueForm
--------------	----------

System - Tx/Rx

Frequency 1H	499.422825 MHz
Correction factor	1
Gain	Low
Img. Scale Cor.	1.000
Reset	Off
? Ref. amplitude 1H	0.000 V

Sequence - Common

Acquisition duration	0 ms
----------------------	------

Sequence - Special

No of dummy scans	10
No of scan per TX	1
RF Pulse type	Rect
RF Voltage	50.0
RF Duration	1000
RF TBW	2.0

\\USER\Recherche_FM\C2P\QA_B1map\2-AutoFOV_position_for_QA_B1map

TA: 1.2 s PM: REF Voxel size: 0.5×0.5×5.0 mmRel. SNR: 1.00 : profile

Properties

Prio recon	Off
Load images to viewer	On
Inline movie	Off
Auto store images	On
Load images to stamp segments	Off
Load images to graphic segments	Off
Auto open inline display	On
Auto close inline display	Off
Start measurement without further preparation	On
Wait for user to start	Off
Start measurements	Single measurement

Routine

Slice group	1
Slices	1
Position	Isocenter
Orientation	Transversal
Phase enc. dir.	A >> P
FoV read	300 mm
FoV phase	100.0 %
TR	200 ms
Averages	1
Filter	None
Coil elements	AC

Contrast - Common

TR	200 ms
Flip angle	1 deg

Contrast - Dynamic

Averages	1
Measurements	1

Resolution - Common

FoV read	300 mm
FoV phase	100.0 %
Base resolution	600

Resolution - Filter Image

Image Filter	Off
Distortion Corr.	Off
Prescan Normalize	Off
Normalize	Off
B1 filter	Off

Resolution - Filter Rawdata

Raw filter	Off
Elliptical filter	Off

Geometry - Common

Slice group	1
Slices	1
Position	Isocenter
Orientation	Transversal
Phase enc. dir.	A >> P
FoV read	300 mm
FoV phase	100.0 %
TR	200 ms

Geometry - AutoAlign

Slice group	1
Position	Isocenter
Orientation	Transversal
Phase enc. dir.	A >> P
Initial Position	Isocenter
Phase	0 mm
Read	0 mm
Shift	0 mm
Initial Rotation	0.00 deg
Initial Orientation	Transversal

Geometry - Tim Planning Suite

Set-n-Go Protocol	Off
Table position	H
Table position	0 mm
Inline Composing	Off

System - Miscellaneous

Positioning mode	REF
Table position	H
Table position	0 mm
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	F >> H
Coil Combine Mode	Sum of Squares
Save uncombined	Off
Matrix Optimization	Off
Coil Select Mode	Default

System - Adjustments

B0 Shim mode	Tune up
B1 Shim mode	TrueForm
Confirm freq. adjustment	Off
Assume Dominant Fat	Off
Assume Silicone	Off
Adjustment Tolerance	Auto

System - Adjust Volume

Position	Isocenter
Orientation	Transversal
Rotation	0.00 deg
A >> P	263 mm
R >> L	350 mm
F >> H	350 mm
Reset	Off

System - pTx Volumes

B1 Shim mode	TrueForm
--------------	----------

System - Tx/Rx

Frequency 1H	499.422825 MHz
Correction factor	1
Gain	Low
Img. Scale Cor.	1.000
Reset	Off
? Ref. amplitude 1H	0.000 V

Sequence - Part 1

Introduction	Off
--------------	-----

Sequence - Part 1

Dimension	2D
Contrasts	1
Bandwidth	400 Hz/Px

Sequence - Part 2

Gradient mode	Fast
---------------	------

Sequence - Assistant

Mode	Off
------	-----

\\USER\Recherche_FM\C2P\QA_B1map\3-QA_B1map

TA: 0:30 PM: REF Voxel size: 5.0×5.0×2.5 mmPAT: Off Rel. SNR: 1.00 : tfl

Properties

Prio recon	Off
Load images to viewer	On
Inline movie	Off
Auto store images	On
Load images to stamp segments	Off
Load images to graphic segments	Off
Auto open inline display	Off
Auto close inline display	Off
Start measurement without further preparation	Off
Wait for user to start	Off
Start measurements	Single measurement

Routine

Slice group	1
Slices	5
Dist. factor	100 %
Position	L999.0 A999.0 F999.0 mm
Orientation	Transversal
Phase enc. dir.	R >> L
AutoAlign	---
Phase oversampling	0 %
FoV read	320 mm
FoV phase	62.5 %
Slice thickness	2.5 mm
TR	3000.0 ms
TE	2.04 ms
Averages	1
Concatenations	1
Filter	None
Coil elements	AC

Contrast - Common

TR	3000.0 ms
TE	2.04 ms
Magn. preparation	None
Flip angle	5.0 deg
Fat suppr.	None
Water suppr.	None

Contrast - Dynamic

Averages	1
Averaging mode	Long term
Reconstruction	Magnitude
Measurements	1
Multiple series	Each measurement

Resolution - Common

FoV read	320 mm
FoV phase	62.5 %
Slice thickness	2.5 mm
Base resolution	64
Phase resolution	100 %
Phase partial Fourier	Off
Interpolation	Off

Resolution - iPAT

PAT mode	None
----------	------

Resolution - Filter Image

Image Filter	Off
Distortion Corr.	Off
Prescan Normalize	Off
Normalize	Off
B1 filter	Off

Resolution - Filter Rawdata

Raw filter	Off
Elliptical filter	Off

Geometry - Common

Slice group	1
Slices	5
Dist. factor	100 %
Position	L999.0 A999.0 F999.0 mm
Orientation	Transversal
Phase enc. dir.	R >> L
FoV read	320 mm
FoV phase	62.5 %
Slice thickness	2.5 mm
TR	3000.0 ms
Multi-slice mode	Interleaved
Series	Interleaved
Concatenations	1

Geometry - AutoAlign

Slice group	1
Position	L999.0 A999.0 F999.0 mm
Orientation	Transversal
Phase enc. dir.	R >> L
AutoAlign	---
Initial Position	L999.0 A999.0 F999.0
L	999.0 mm
A	999.0 mm
F	999.0 mm
Initial Rotation	90.00 deg
Initial Orientation	Transversal

Geometry - Navigator**Geometry - Tim Planning Suite**

Set-n-Go Protocol	Off
Table position	H
Table position	0 mm
Inline Composing	Off

System - Miscellaneous

Positioning mode	REF
Table position	H
Table position	0 mm
MSMA	S - C - T
Sagittal	R >> L
Coronal	A >> P
Transversal	F >> H
Coil Combine Mode	Adaptive Combine
Save uncombined	Off
Matrix Optimization	Off
AutoAlign	---

System - Miscellaneous

Coil Select Mode	Default
------------------	---------

System - Adjustments

B0 Shim mode	Standard
B1 Shim mode	TrueForm
Confirm freq. adjustment	Off
Assume Dominant Fat	Off
Assume Silicone	Off
Adjustment Tolerance	Auto

System - Adjust Volume

! Position	Isocenter
! Orientation	Transversal
! Rotation	90.00 deg
! R >> L	200 mm
! A >> P	320 mm
! F >> H	25 mm
Reset	Off

System - pTx Volumes

B1 Shim mode	TrueForm
Excitation	Slice-sel.

System - Tx/Rx

Frequency 1H	499.422825 MHz
Correction factor	1
Gain	High
Img. Scale Cor.	1.000
Reset	Off
? Ref. amplitude 1H	0.000 V

Physio - Signal1

1st Signal/Mode	None
TR	3000.0 ms
Concatenations	1

Physio - Cardiac

Magn. preparation	None
Fat suppr.	None
Dark blood	Off
FoV read	320 mm
FoV phase	62.5 %
Phase resolution	100 %

Physio - PACE

Resp. control	Off
Concatenations	1

Sequence - Part 1

Introduction	Off
Dimension	2D
Reordering	Centric
Asymmetric echo	Off
Flow comp.	No
Multi-slice mode	Interleaved
Echo spacing	3.6 ms
Bandwidth	1000 Hz/Px

Sequence - Part 2

RF pulse type	Low SAR
Gradient mode	Whisper
Excitation	Slice-sel.
RF spoiling	On

Sequence - Part 2

Incr. Gradient spoiling	Off
Turbo factor	40

Sequence - Special

B1 mapping type	Fast relative
Export B1 maps	On
Mosaic recon.	On
Dummy RF pulses	0
Sat. flip angle	90 °
Time BW product	9.0
Fill TR time	On
Perform QA pTx	On
FOV shift for QA pTx	3D shift

Sequence - Assistant

Mode	Off
------	-----