Python Data Types - Set, Dictionary

In this lesson, we learn 2 important data types:

- Set : a sequence of unique items
- Dictionary : set of key:value pairs, aka, Map, Associative Array, Hash Table

Set

- an unordered collection of distinct items
- set collection **delimitor** is curly brackets: {, }

In [2]:
```
color_set = {'Red','Green','Blue'}
```

In [3]:
```
type(color_set)
```

Out[3]:
```
set
```

In [4]:
```
color_set.add('White')
```

In [5]:
```
# cannot add duplicate item
color_set.add('Red')
print(color_set)
```

```
{'Blue', 'White', 'Green', 'Red'}
```

In [6]:
```
len(color_set)
```

Out[6]:
```
4
```

In [7]:
```
# check existence
print('Black' in color_set)
```

```
False
```

In [8]:
```
# check existence
print('Red' in color_set)
```

```
True
```

Distinct items in a list

In [9]:
```
num_list = [3, 5, 3, 13, 7, 9, 13, 13]
num_list
```

Out[9]:
```
[3, 5, 3, 13, 7, 9, 13, 13]
```

In [10]:
```
# convert a list to a set
print(set(num_list))
```

```
{9, 13, 3, 5, 7}
```

Set operations

Venn diagram





In [11]:
```
shapes_1 = {'Circle','Triangle','Pentagon', 'Hexagon'}
print(shapes_1)
```

```
{'Triangle', 'Pentagon', 'Circle', 'Hexagon'}
```

In [12]:
```
type(shapes_1)
```

Out[12]:
```
set
```

In [13]:
```
shapes_2 = {'Circle','Triangle','Diamond', 'Square'}
print(shapes_2)
```

```
{'Diamond', 'Triangle', 'Square', 'Circle'}
```

In [14]:
```
# Intersection -- find the common item between two sets
shapes_1.intersection(shapes_2)
```

Out[14]:
```
{'Circle', 'Triangle'}
```

In [15]:
```
# Union -- find total items among all the sets
shapes_1.union(shapes_2)
```

Out[15]:
```
{'Circle', 'Diamond', 'Hexagon', 'Pentagon', 'Square', 'Triangle'}
```

In [16]:
```
# Difference
shapes_1.difference(shapes_2)
```

Out[16]:
```
{'Hexagon', 'Pentagon'}
```

In [17]:
```
# order matters
shapes_2.difference(shapes_1)
```

Out[17]:
```
{'Diamond', 'Square'}
```

Dictionary (https://docs.python.org/3/library/stdtypes.html?highlight=set#dict) / Map

- Dictionary **delimitor** is curly brackets: {, } ,
  - key/value pair **delimitor** is ":"
- Keys are distinct, that is why it uses same delimitors as set
- The value store information associated with a key
- an unordered collection of key:value pair (unlike regular English dictionary, keys are NOT sorted alphabetically)
- a very efficient/useful data structure
- Three nicknames
  - Map (2-dimentional)
  - Associative Array
  - Hash table

Start with an example

In [8]:
```
favorite_sports = {'Ralph Williams' : 'Football',
    'Michael Tippett' : 'Basketball',
    'Edward Elgar' : 'Baseball',
    'Rebecca Clarke' : 'Football',
    'Ethel Smyth' : 'Badminton',
    'Frank Bridge' : 'Rugby',
    'Ralph Williams' : 'Rugby',
    }
print(favorite_sports)
```

```
{'Ralph Williams': 'Rugby', 'Michael Tippett': 'Basketball', 'Edward Elga
r': 'Baseball', 'Rebecca Clarke': 'Football', 'Ethel Smyth': 'Badminton',
'Frank Bridge': 'Rugby'}
```

In [5]:
```
type(favorite_sports)
```

Out[5]: dict

In [6]:
```
len(favorite_sports)
```

Out[6]: 6

In [7]:
```
print(favorite_sports)
```

```
{'Ralph Williams': 'Football', 'Michael Tippett': 'Basketball', 'Edward Elg
ar': 'Baseball', 'Rebecca Clarke': 'Football', 'Ethel Smyth': 'Badminton',
'Frank Bridge': 'Rugby'}
```



How to create dictionary

In [22]:
```
dict2 = { '工作' : 'work', '学习':'study, learn' , '玩':'play'}
```

In [23]:
```
print(dict2)
```

```
{'学习': 'study, learn', '工作': 'work', '玩': 'play'}
```

In [24]:
```
dict2['学习']
```

Out[24]:
```
'study, learn'
```

In [25]:
```
key = '工作'
print("Meaning of %s is %s" % (key,  dict2[key]))
```

```
Meaning of 工作 is work
```

In [13]:
```
dict3 = dict(name='John', age=10, height=54.5, weight= 70)
dict4 = {'age': 10, 'height': 54.5, 'name': 'John', 'weight': 70}
print(dict4['name'])
```

```
John
```

In [27]:
```
dict3
```

Out[27]:
```
{'age': 10, 'height': 54.5, 'name': 'John', 'weight': 70}
```

In [28]:
```
type(dict3)
```

Out[28]:
```
dict
```

In [29]:
```
len(dict3)
```

Out[29]:
```
4
```

Common operations

get all the keys

In [30]:
```
key_list = dict2.keys()
```

In [31]:
```
print(key_list)
```

```
dict_keys(['学习', '工作', '玩'])
```

get all the values

In [32]:
```
value_list = dict2.values()
```

In [33]:
```
print(value_list)
```

```
dict_values(['study, learn', 'work', 'play'])
```

get all the items

key:value pair is called an item

In [34]:
```
item_list = dict2.items()
```

In [35]:
```
print(item_list)
```

```
dict_items([('学习', 'study, learn'), ('工作', 'work'), ('玩', 'play')])
```

In [36]:
```
# count number of items
print(len(dict2))
```

```
3
```

in - existence check

In [37]:
```
print('玩' in dict2)
```

```
True
```

In [38]:
```
print('游戏' in dict2)
```

```
False
```

add an item

In [17]:
```
dict2 = { '工作' : 'work', '学习':'study, learn' , '玩':'play'}
dict2['工作'] = 'game'
a = dict2['工作']
print(a)
```

```
game
```

In [ ]:
```

```

In [40]:
```
dict2
```

Out[40]:
```
{'学习': 'study, learn', '工作': 'work', '游戏': 'game', '玩': 'play'}
```

In [41]:
```
# count number of items
print(len(dict2))
```

```
4
```

update an item

update an item

In [42]:
```
dict2['游戏'] = 'computer game'.upper()
```

In [43]:
```
dict2
```

Out[43]:
```
{'学习': 'study, learn', '工作': 'work', '游戏': 'COMPUTER GAME', '玩': 'pla
y'}
```

remove an item

In [44]:
```
dict2['work'] = '工作'
```

In [45]:
```
dict2
```

Out[45]:
```
{'work': '工作',
 '学习': 'study, learn',
 '工作': 'work',
 '游戏': 'COMPUTER GAME',
 '玩': 'play'}
```

In [46]:
```
del dict2['work']
```

In [47]:
```
dict2
```

Out[47]:
```
{'学习': 'study, learn', '工作': 'work', '游戏': 'COMPUTER GAME', '玩': 'pla
y'}
```

In [48]:
```
dict2['work'] = '工作'
```

In [49]:
```
dict2
```

Out[49]:
```
{'work': '工作',
 '学习': 'study, learn',
 '工作': 'work',
 '游戏': 'COMPUTER GAME',
 '玩': 'play'}
```

In [50]:
```
dict2.pop('work')
```

Out[50]:
```
'工作'
```

In [51]:
```
dict2
```

Out[51]:
```
{'学习': 'study, learn', '工作': 'work', '游戏': 'COMPUTER GAME', '玩': 'pla
y'}
```

clear a dictionary

In [52]:
```
dict3 = {1: 'one', 2: 'two', 3: 'three'}
```

In [53]:
```
dict3
```

Out[53]:
```
{1: 'one', 2: 'two', 3: 'three'}
```

In [54]:
```
dict3.clear()
```

In [55]:
```
dict3
```

Out[55]:
```
{}
```

In [56]:
```
len(dict3)
```

Out[56]:
```
0
```

reset to empty

In [57]:
```
dict3 = {1: 'one', 2: 'two', 3: 'three'}
```

In [58]:
```
dict3
```

Out[58]:
```
{1: 'one', 2: 'two', 3: 'three'}
```

In [59]:
```
dict3 = {}
```

In [60]:
```
dict3
```

Out[60]:
```
{}
```

merge two dictionaries into one

row-wise



	A	B	C
1		Key	Value
2			
3	Dictionary #1	美国	USA
4	data1	法国	France
5		英国	England
6		德国	Germany
7			
8			
9	Dictionary #2	中国	China
10	data2	印度	India
11		日本	Japan
12			
13		List #1	List #2
14		keys	values

In [21]:
```
# western countries
dict4_a = {'美国':'USA', '英国':'England', '法国':'France', '德国':'Germany'
           #, '俄国' : 'Russia'
          }
```

In [22]:
```
dict4_a
```

Out[22]:
```
{'美国': 'USA', '英国': 'England', '法国': 'France', '德国': 'Germany'}
```

In [23]:
```
# eastern countries
dict4_b = {'中国':'China', '印度':'India', '日本':'Japan'}
```

In [24]:
```
dict4_b
```

Out[24]:
```
{'中国': 'China', '印度': 'India', '日本': 'Japan'}
```

In [25]:
```
dict4 = dict(list(dict4_a.items()) + list(dict4_b.items()))
```

In [66]:
```
dict4
```

Out[66]:
```
{'中国': 'China',
 '印度': 'India',
 '德国': 'Germany',
 '日本': 'Japan',
 '法国': 'France',
 '美国': 'USA',
 '英国': 'England'}
```

zip two lists into a dictionary

column-wise

In [26]:
```
key_list = dict4.keys()
```

In [27]:
```
value_list = dict4.values()
```

In [28]:
```
key_list, value_list
```

Out[28]:
```
(dict_keys(['美国', '英国', '法国', '德国', '中国', '印度', '日本']),
 dict_values(['USA', 'England', 'France', 'Germany', 'China', 'India', 'Jap
an']))
```

In [29]:
```
dict5 = dict(zip(key_list, value_list))
```

In [ ]:
```

```

In [30]:
```
dict5
```

Out[30]:
```
{'美国': 'USA',
 '英国': 'England',
 '法国': 'France',
 '德国': 'Germany',
 '中国': 'China',
 '印度': 'India',
 '日本': 'Japan'}
```

In [31]:
```
# switch key/value
dict6 = dict(zip(value_list, key_list))
```

In [73]:
```
dict6
```

Out[73]:
```
{'China': '中国',
 'England': '英国',
 'France': '法国',
 'Germany': '德国',
 'India': '印度',
 'Japan': '日本',
 'USA': '美国'}
```

Complex dictionary

In [74]:
```
# key is string, value is a list
```

In [75]:
```
dict7 = dict(one=[0], two=[0,1], three=[0,1,2], four=[0,1,2,4])
```

In [76]:
```
dict7
```

Out[76]:
```
{'four': [0, 1, 2, 4], 'one': [0], 'three': [0, 1, 2], 'two': [0, 1]}
```

In [77]:
```
# nested dictionary:  key is number, value is a dictionary
```

In [78]:
```
dict8 = {1: {'name':'John Wang', 'sex':'Male', 'grade':7, 'age':14} ,
         2: {'name':'Jane Li', 'sex':'Female', 'grade':8, 'age':15} ,
         3: {'name':'Kevin Chen', 'sex':'Male', 'grade':6, 'age':12}
        }
```

In [79]:
```
dict8
```

Out[79]:
```
{1: {'age': 14, 'grade': 7, 'name': 'John Wang', 'sex': 'Male'},
 2: {'age': 15, 'grade': 8, 'name': 'Jane Li', 'sex': 'Female'},
 3: {'age': 12, 'grade': 6, 'name': 'Kevin Chen', 'sex': 'Male'}}
```

In [80]:
```
dict8[1]
```

Out[80]:
```
{'age': 14, 'grade': 7, 'name': 'John Wang', 'sex': 'Male'}
```

In [81]:
```
#dict8[5]
```

Iterating a Dictionary with for-loop

In [32]:
```
dict6 = \
{'China': '中国',
 'England': '英国',
 'France': '法国',
 'Germany': '德国',
 'India': '印度',
 'Japan': '日本',
 'USA': '美国'}

for item in dict6:
    print(item)
```

```
China
England
France
Germany
India
Japan
USA
```

In [33]:
```
dict6 = \
{'China': '中国',
 'England': '英国',
 'France': '法国',
 'Germany': '德国',
 'India': '印度',
 'Japan': '日本',
 'USA': '美国'}
for key,value in dict6.items():
    print('key=', key,' \t: ', 'value=',value)
```

```
key= China      :  value= 中国
key= England    :  value= 英国
key= France     :  value= 法国
key= Germany    :  value= 德国
key= India      :  value= 印度
key= Japan      :  value= 日本
key= USA        :  value= 美国
```

In [34]:
```
print(dict6.items())
```

```
dict_items([('China', '中国'), ('England', '英国'), ('France', '法国'), ('Ger
many', '德国'), ('India', '印度'), ('Japan', '日本'), ('USA', '美国')])
```

In [35]:
```
dict6 = \
{'China': '中国',
 'England': '英国',
 'France': '法国',
 'Germany': '德国',
 'India': '印度',
 'Japan': '日本',
 'USA': '美国'}
# how to track loop number - use a counter

# initialize the counter before loop starts
n = 0
for item in dict6:
    n = n + 1  # increment counter by 1
    print('loop counter = %d' % n)
    print('\t\tkey=', item)
```

```
loop counter = 1
                key= China
loop counter = 2
                key= England
loop counter = 3
                key= France
loop counter = 4
                key= Germany
loop counter = 5
                key= India
loop counter = 6
                key= Japan
loop counter = 7
                key= USA
```

In [36]:
```
dict6 = \
{'China': '中国',
 'England': '英国',
 'France': '法国',
 'Germany': '德国',
 'India': '印度',
 'Japan': '日本',
 'USA': '美国'}

# how to loop thru a dictionary

# initialize the counter before loop starts
n = 0
for item in dict6:
    n = n + 1  # increment counter by 1
    print('loop counter = %d' % n)
    print('\t\tKey  =', item)
    print('\t\tValue=', dict6[item])
```

```
loop counter = 1
                Key  = China
                Value= 中国
loop counter = 2
                Key  = England
                Value= 英国
loop counter = 3
                Key  = France
                Value= 法国
loop counter = 4
                Key  = Germany
                Value= 德国
loop counter = 5
                Key  = India
                Value= 印度
loop counter = 6
                Key  = Japan
                Value= 日本
loop counter = 7
                Key  = USA
                Value= 美国
```

In [ ]:
```

```