

Component list

BMS Current Sense Block Diagram

Source Data From:		
Project:		

BMS_Current_Sense.PrjPcb
BMS_Current_Sense.PrjPcb

Variant:

None



Report Date: 10/30/2017 1:29:04 AM 1:29:09 AM Print Date: 30-Oct-17 LibRef #Column Name Error:Manufacturer | mn Name Error:Manufacturolumn Name Error:PartTy Description Footprint Column Name Error:Package Referenc Quantity CAPCER 4.7UF 50V 10% X5R 0805 4.7uF ±20% 50V Ceramic Capacitor X5R CAP. 0805 0805 (2012 Metric) 2 CAPCER 2.2UF 25V 10% X5R 0603 2.2µF ±10% 25V Ceramic Capacitor X5R CAP, 0603 0603 (1608 Metric) 3 CAPCER 1UF 50V 10% X7R 0603 1µF ±10% 50V Ceramic Capacitor X7R CAP. 0603 0603 (1608 Metric) 4 CAPCER 0.1UF 50V 10% X7R 0603 0.10µF ±10% 50V Ceramic Capacitor X7R CAP, 0603 0603 (1608 Metric) 5 CAP CER 0.022UF 50V 10% X7R 0603 0.022µF ±10% 50V Ceramic Capacitor X7R CAP, 0603 0603 (1608 Metric) 6 CAPTANT 1UF 25V 10% 0805 1µF Molded Tantalum Capacitors 25V 0805 CAP, TANTALUM 0805 (2012 Metric) 8 Ohm 10000pF ±5% 50V Ceramic Capacitor U2J CAP, 0603 7 CAPCER 10nF 50V 5% X7R 0603 0603 (1608 Metric) 10uF ±10% 25V Ceramic Capacitor X5R 8 CAPCER 10uF 25V 10% X5R 0805 CAP. 0805 0805 (2012 Metric) 9 CAP CER 20PF 50V ±5% C0G/NP0 0603 20pF ±5% 50V Ceramic Capacitor COG, NP0 CAP, 0603 0603 (1608 Metric) 10 IND 6.8uH 260mA 20% 1210 6.8uH Shielded Wirew ound Inductor 260mA INLFV32T-6R8M-EF/IND 6.8uH 204 mOhm Max 1210 (3225 Metric) 11 LED YELLOW CLEAR 2.1V 0603 Yellow 590nm LED Indication - Discrete 2V LED_0603 0603 (1608 Metric) 12 LED GREEN CLEAR 2V 0603 Green 572nm LED Indication - Discrete 2V LED 0603 0603 (1608 Metric) 13 RES SHUNT 100UOHM 5% 36W 60MM 100 µOhms ±5% 36W Shunt, Battery RES SHUNT 100UOHM 60MM Specialized Resistor Metal Element ±175ppm/°C Shunt Fixture, 60mm Pitch 14 RES 0.0 OHM 1/4W 0603 RES SMD 0.0 OHM JUMPER 1/4W 0603 RES, 0603 15 RES 4.7K OHM 1% 1/10W 0603 4.7k Ohm ±1% 0.1W, 1/10W Chip Resistor RES, 0603 0603 (1608 Metric) Moisture Resistant Thick 16 RES 2K OHM 1% 1/10W 0603 2k Ohm ±1% 0.1W. 1/10W Chip Resistor RES, 0603 0603 (1608 Metric) Moisture Resistant Thick 17 RES 120 OHM 1% 1/10W 0603 RES SMD 120 OHM 1% 1/10W 0603 RES. 0603 RES 1.4k OHM 1% 1/10W 0603 RES SMD 1.4K OHM 1% 1/10W 0603 19 RES 604 OHM 1% 1/10W 0603 RES SMD 604 OHM 1% 1/10W 0603 RES, 0603 20 Test Point Test Point 21 IC DCDC ISOLATED 12V 1W 8-SMD 5-Isolated Module DC DC Converter 1 Output IC, Isolated DCDC LEAD 12V 84mA 10.8V - 13.2V Input 22 IC REG LDO 5V 0.1A SOT23-5 Linear Voltage Regulator IC Positive Fixed SOT95P280X145-5N Output 5V 100mA SOT-23-5 23 IC VREF SERIES 4.096V 5MA SOT23-5 Series Voltage Reference IC ±0.2% 5mA IC OP AMP GP RR 10MHZ SOT-23-5 SOT-23-5 24 IC ADC 24BIT 10-DFN 24 Bit Analog to Digital Converter 1 Input 1 IC ADC LTC2484 10-DFN Sigma-Delta 10-DFN (3x3) 25 IC CURRENT AMPLIFIER INA 240 8-Current Sense Amplifier 1 Circuit 8-TSSOP IC CURRENT AMPLIFIER INA240 TSSOP-8 TSSOP 26 IC OP AMP GEN PURPOSE RR 10MHZ IC OP AMP GP RR 10MHZ SOT-23-5 General Purpose Amplifier 1 Circuit Rail-to-SOT-23-5 Rail SOT-23-5 27 IC ISOSPI COMM INTERFACE IC COMM INTERFACE ISOSPI 16-QFN IC COMM INTERFACE ISOSPI 16-QFN .TC6820IUD 28 IC PULSE XFMR 1CT:1CT 350UH SMD PULSE XFMR 1CT:1CT 350UH SMD IC, PULSE XFMR 1CT:1CT 350UH SMD Approved Notes