


# **HEX INVERTER**



# SN54/74LS04

# HEX INVERTER LOW POWER SCHOTTKY



J SUFFIX CERAMIC CASE 632-08



N SUFFIX PLASTIC CASE 646-06



D SUFFIX SOIC CASE 751A-02

#### **ORDERING INFORMATION**

SN54LSXXJ SN74LSXXN SN74LSXXD Ceramic Plastic SOIC

#### **GUARANTEED OPERATING RANGES**

Symbol	Parameter		Min	Тур	Max	Unit
Vcc	Supply Voltage	54 74	4.5 4.75	5.0 5.0	5.5 5.25	V
TA	Operating Ambient Temperature Range	54 74	-55 0	25 25	125 70	°C
I <sub>ОН</sub>	Output Current — High	54, 74			-0.4	mA
lOL	Output Current — Low	54 74			4.0 8.0	mA

## SN54/74LS04

### DC CHARACTERISTICS OVER OPERATING TEMPERATURE RANGE (unless otherwise specified)

			Limits					
Symbol	Parameter		Min	Тур	Max	Unit	Test Conditions	
VIH	Input HIGH Voltage		2.0			٧	Guaranteed Input HIGH Voltage for All Inputs	
V <sub>IL</sub>	Input LOW Voltage	54			0.7	, .	Guaranteed Input LOW Voltage for All Inputs	
		74			0.8			
VIK	Input Clamp Diode Voltage			-0.65	-1.5	V	$V_{CC} = MIN, I_{IN} = -18 \text{ mA}$	
V	Output HIGH Voltage	54	2.5	3.5		V	$V_{CC}$ = MIN, $I_{OH}$ = MAX, $V_{IN}$ = $V_{IH}$ or $V_{IL}$ per Truth Table	
VOH		74	2.7	3.5		V		
Vol	Output LOW Voltage	54, 74		0.25	0.4	V	I <sub>OL</sub> = 4.0 mA	V <sub>CC</sub> = V <sub>CC</sub> MIN, V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub>
VOL		74		0.35	0.5	V	I <sub>OL</sub> = 8.0 mA	per Truth Table
1	Input HIGH Current				20	μΑ	$V_{CC} = MAX$ , $V_{IN} = 2.7 V$	
lΉ					0.1	mA	$V_{CC} = MAX$ , $V_{IN} = 7.0 V$	
Ι <sub>Ι</sub> L	Input LOW Current				-0.4	mA	V <sub>CC</sub> = MAX, V <sub>IN</sub> = 0.4 V	
los	Short Circuit Current (Note 1)		-20		-100	mA	V <sub>CC</sub> = MAX	
lcc	Power Supply Current Total, Output HIGH Total, Output LOW				2.4	mA	V <sub>CC</sub> = MAX	
					6.6			

Note 1: Not more than one output should be shorted at a time, nor for more than 1 second.

## AC CHARACTERISTICS $(T_A = 25^{\circ}C)$

		Limits		Limits			
Symbol	Parameter	Min	Тур	Max	Unit	Test Conditions	
tPLH	Turn-Off Delay, Input to Output		9.0	15	ns	V <sub>CC</sub> = 5.0 V	
tPHL	Turn-On Delay, Input to Output		10	15	ns	C <sub>L</sub> = 15 pF	