

Minimum Spanning Trees


$$m \geq n - 1$$

Input: A connected undirected graph $G=(V, E)$

Output: A minimum spanning tree of G

$\left\{ \begin{array}{l} n - 1 \text{ edges} \\ \text{no cycles} \end{array} \right.$

23-1x



Two greedy algorithms: Managing a set A that is always a subset of some minimum spanning tree.

23.2 Kruskal's algorithm: smallest weighted first (no cycle)

23-1x

MST-KRUSKAL(G, w)


```

1   $A \leftarrow \emptyset$  /* tree edges */
2  for each vertex  $v \in V[G]$ 
3      do MAKE-SET( $v$ )
4  sort the edges of  $E$  into nondecreasing order by weight  $w$ 
5  for each edge  $(u, v) \in E$ , taken in nondecreasing order by weight
6      do if FIND-SET( $u$ )  $\neq$  FIND-SET( $v$ ) /* no cycle */
7          then  $A \leftarrow A \cup \{(u, v)\}$  (two ends are in different sets)
8          UNION( $u, v$ )
9  return  $A$ 


```

$O(V)$ $O(E \lg E)$ $E \times \alpha(V)$ (2 FIND, 1 Union)


(a)
1st




(b)
2nd






(c)
3rd




(d)
4th



(e)
5th★ (f)
6th(g)
7th

⋮

★ (n)
13th
cost = 37

tree → no cycles, connected

Time complexity:Steps 1~3: $O(V)$ Step 4: $O(E \lg E)$ (sorting) $E \times (\text{set operation})$ Steps 5~8: $O(E\alpha(V)) = O(E \lg E)$
(disjoint-set-forest in 21.3)* α is the inverse Ackermann's function* $\alpha(n) \leq 4$ for all practical cases* $T(n) = O(E \lg E)$ * If all weights are bounded integers, $T(n) = O(E\alpha(V))$ → integer sort**Prim's algorithm:** vertices in A always form a single tree.

23-4a

MST-PRIM(G, w, r) 和 current tree 的最小距離





```

1  for each  $u \in V[G]$ 
2      do  $key[u] \leftarrow \infty$ 
3       $\pi[u] \leftarrow \text{NIL}$  parent
4   $key[r] \leftarrow 0$ 
5   $Q \leftarrow V[G]$  build Q } T 由 0 個 node 開始長
6  while  $Q \neq \emptyset$ 
7      do  $u \leftarrow \text{EXTRACT-MIN}(Q)$  V times
8      for each  $v \in \text{Adj}[u]$ 
9          do if  $v \in Q$  and  $w(u, v) < key[v]$ 
10             then  $\pi[v] \leftarrow u$ 
11              $key[v] \leftarrow w(u, v)$  decrease Key at most 2E times





```

Q: priority queue (vertices)

23-5



23-6



Time complexity:

unsorted

unsorted

(a) Implement priority queue Q as an array

solution to Ex. 23.2-2

Steps 1~5: $O(V)$ (Build Q) $O(V)$ $O(V)$
 Step 7: $O(V^2)$ (V times Extract-Min) $O(1)$
 Steps 8~11: $O(E)$ ($2E$ times Decrease-key)
 Total: $O(V^2 + E) = O(V^2)$ (for dense G)
 $(E \approx V^2) \sim \text{simple}$

(b) Implement priority queue Q as a binary heap

Steps 1~5: $O(V)$ (Build Q) $O(V)$ $O(\lg V)$
 Step 7: $O(V \lg V)$ (V times Extract-Min)
 Steps 8~11: $O(E \lg V)$ ($2E$ times Decrease-Key)
 Total: $O(E \lg V)$ (for sparse G) $O(\lg V)$
 $(E \ll V^2)$

(c) Implement Q as a Fibonacci heap

Steps 1~5: $O(V)$ (Build Q) $O(V)$ $O(\lg V)$
 Step 7: $O(V \lg V)$ (V times Extract-Min)
 Steps 8~11: $O(E)$ ($2E$ times Decrease-Key) $O(1)$
 Total: $O(E + V \lg V)$ (for sparse G)
 $(\text{Note } E \geq V - 1) \quad (E \ll V^2)$



Homework: Ex. 23.2-2, 23.2-4, 23.2-5, Prob. 23-1, 23-3.