

Introduction to Benchmark

Database Systems
DataLab, CS, NTHU
Spring, 2018

Outline

- Benchmark Project
 - Introducing Benchmark Project
 - Starting Up Server for Benchmarking
 - Setting Benchmark Configurations
 - Running Benchmark Client

Outline


- Benchmark Project
 - Introducing Benchmark Project
 - Starting Up Server for Benchmarking
 - Setting Benchmark Configurations
 - Running Benchmark Client

Benchmark Project




- Benchmark project is a special client project for automatically benchmarking
- It contains a testbed loader and a testing process
- It also has a lot of adjustable testing parameters

Two Main Methods



Start a Client



Loading Testbed



```
graph TD; A[loadTestbed()] --> B[Connect to server and execute two stored procedures:]; B --> C[SchemaBuilder]; B --> D[TestbedLoader];
```


loadTestbed()

Connect to server and execute two stored procedures:


SchemaBuilder

TestbedLoader


Starting Benchmark




Server & Client





RTE Life Cycle




Execute Tx




JDBC / SP ?



JDBC / SP ?



JDBC / SP ?



Executing a Transaction

- General steps
 - Generate parameters from TxParamGenerator
- Store Procedure
 - CallStoredProc() to start a stored procedure on the remote server, with the generated parameters
 - Remote server will return a SutResultSet when the procedure is finished
- JDBC
 - call Jdbc.execute() to start a Job on the local, with the generated parameters
 - Job will executing each sql via JDBC connector

How Server Process a StoredProc call ?

- When the server receive a remote procedure call, it will ask StoredProcFactory to generate the appropriate StoredProcedure
- The server will then call the StoredProcedure methods:
 - prepare(Obj...)
 - preparing the parameters
 - execute()
 - executing the transaction
 - this method will return the final result to the client

Outline


- Benchmark Project
 - Introducing Benchmark Project
- Starting Up Server for Benchmarking
- Setting Benchmark Configurations
- Running Benchmark Client

Clone the Project First

- <https://shwu10.cs.nthu.edu.tw/courses-databases-2018-spring/db18-assignment-2>


Starting Up Server (1/2)

- To benchmark a VanillaDB server, you need to start up the server in another entry point




Starting Up Server (2/2)

- You also need to add one more VM argument for benchmarking.
- Don't forget to add the Database Directory Name



You can copy those arguments from [here](#)

Server Messages




The screenshot shows an IDE console window with the following tabs: Markers, Properties, Servers, Data Source Explorer, Snippets, Console, and Call Hierarchy. The console output is as follows:

```
S [Java Application] /Library/Java/JavaVirtualMachines/jdk1.8.0_102.jdk/Contents/Home/bin/java (2018年3月20日 下午8:59:14)
三月 20, 2018 8:59:14 下午 org.vanilladb.bench.server.VanillaDbSpStartUp startup
資訊: initing...
三月 20, 2018 8:59:14 下午 org.vanilladb.core.util.PropertiesLoader getPropertyAsString
警告: can't find property: org.vanilladb.core.storage.file.FileMgr.DB_FILES_DIR, using default value: /Users/zulu
三月 20, 2018 8:59:14 下午 org.vanilladb.core.util.PropertiesLoader getPropertyAsString
警告: can't find property: org.vanilladb.core.storage.file.FileMgr.LOG_FILES_DIR, using default value: /Users/zul
三月 20, 2018 8:59:14 下午 org.vanilladb.core.storage.file.FileMgr <init>
資訊: block size 4096
三月 20, 2018 8:59:15 下午 org.vanilladb.core.server.VanillaDb init
資訊: recovering existing database
三月 20, 2018 8:59:16 下午 org.vanilladb.bench.server.VanillaDbSpStartUp startup
資訊: VanillaBench server ready
```

You should see similar messages
if there is nothing wrong.

Setting Benchmark

- Benchmark project also has a properties file for configurations
- `vanillabench.properties`




```
1
2 #
3 # Basic Parameters
4 #
5
6 # The running time for warming up before benchmarking
7 org.vanilladb.bench.BenchmarkParameters.WARM_UP_INTERVAL=3000
8 # The running time for benchmarking
9 org.vanilladb.bench.BenchmarkParameters.BENCHMARK_INTERVAL=6000
10 # The number of remote terminal executors for benchmarking
11 org.vanilladb.bench.BenchmarkParameters.NUM_RTES=10
12 # The IP of the target database server
13 org.vanilladb.bench.BenchmarkParameters.SERVER_IP=127.0.0.1
14 # 1 = JDBC, 2 = Stored Procedures
15 org.vanilladb.bench.BenchmarkParameters.CONNECTION_MODE=2
16 # The path to the generated reports
17 org.vanilladb.bench.StatisticMgr.OUTPUT_DIR=
18 # Whether the RTEs display the results of each transaction
19 org.vanilladb.bench.rte.TransactionExecutor.DISPLAY_RESULT=false
20 # The number of items in the testing data set
21 org.vanilladb.bench.as2.As2Constants.NUM_ITEMS=100000
```

Important Parameters

- CONNECTION_MODE
 - It means whether it should use JDBC or stored procedures


Running Client

- To run clients, create a run configuration for it



Arguments

- We also need to set some arguments
- Program Arguments
 - [Action]
 - 1 : Load Test-Bed
 - 2 : Lunch Benchmark
- VM Arguments
 - Use the same as the server



You can copy those arguments from here,
then click 'Apply' and 'Run'

Notes

- Before running testing, please **load testbed** first
- For now, loading testbed only works when you use stored procedures as interface
- Check if the output directory path that show in properties file exists
 - If not, create one or change the path

Run VanillaDB in Command Line

- Export client and server in .jar format
- Copy three property files into the folder where you export .jar file
- Type in the command as follow:

```
java { VM Arguments } -jar { server/client }.jar { Program Arguments }
```

Q&A

- If you got any problem, you can check here first
- <https://shwu10.cs.nthu.edu.tw/courses-databases-2018-spring/FAQ>
- If your problem was very unique, just send a email let us know