Heterogeneous Computing & GPU Introduction

National Tsing Hua University

2020, Fall Semester

Outline

- Heterogeneous Computing
- GPU

Trend of Parallel Computers



Heterogeneous Computing

- Heterogeneous computing is an integrated system that consists of different types of (programmable) computing units.
  - DSP (digital signal processor)
  - FPGA (field-programmable gate array)
  - ASIC (application-specific integrated circuit)
  - GPU (graphics processing unit)
  - Co-processor (Intel Xeon Phi)
- A system can be a cell phone or a supercomputer

Shift of Computing Paradigm



GPU/Xeon Phi in Top 500 list (rank world's fastest Supercomputer)

- Jaguar was upgraded with GPU and renamed to Titan
  - Increase computation power by a factor of **10** !!!
- 62 systems have accelerator(GPU) or co-processor (Phi)
- http://www.top500.org/lists/

2014 Rank	Name	Country	Manuf-acture	Accelerator	Cores	Rmax (TFlops/s)
1	**Tianhe-2**	China	NUDT	Xeon Phi	3,120K	33.8K
2	**Titan**	US	Cray	NVIDIA K20x	560K	17.6K
3	**Sequoia**	US	IBM	N.A	1,572K	17.2K
4	**K computer**	Japan	Fujitsu	N.A	705K	10.5K

2012 Rank	Name	Country	Manuf-acture	Accelerator	Cores	Rmax (TFlops/s)
6	**Jaguar**	US	Cray	N.A	298K	1.9K

GPU Servers

- Same HW architecture as commodity server, but memory copy between CPU and GPU becomes the main bottleneck





Heterogeneous System Architecture (HSA)

- Aim to provide a common system architecture for designing higher-level programming models for all devices
- Unified coherent memory
  - Single virtual memory address space
  - Prevent memory copy



AMD Accelerated Processing Unit (APU)

- A.k.a ***Fusion:*** a series of 64-bit microprocessors from AMD designed to act as a CPU and GPU on a single chip
  - 2011: Llano, Brazos
  - 2012: Trinity, Brazos-2
  - 2013: Kabini, Temash
  - 2014: Kaveri



Outline

- Heterogeneous Computing
- GPU

GPU (Graphic Processing Unit)

- A specialized chip designed for rapidly display and visualization
  - SIMD architecture
- Massively multithreaded manycore chips
  - NVIDIA Tesla products have up to 5120 scalar processors
  - Over 12,000 **concurrent** threads
  - Over 470 GFOLPS sustained performance
- Two major vendors: NVIDIA and ATI (now AMD)



GPGPU (General-Purpose Graphic Processing Unit)



- **Expose** the horse power of GPUs for general purpose computations
  - Exploit **data parallelism** for solving embarrassingly parallel tasks and numeric computations
  - Users across science & engineering disciplines are achieving 100x or better speedups on GPUs
- Programmable
  - Early GPGPU: using the libraries in computer graphics, such as OpenGL or DirectX, to perform the tasks other than the original hardware designed for.
  - Now **CUDA** and openCL provides an extension to C and C++ that enables parallel programming on GPUs

System Architecture



It is crucial to minimize the data transfer and data usage of GPU memory

E.g.: 128GB shared by 16 cores

E.g.: 12 GB shared by 12K threads

Manycore GPU – Block Diagram

- Consist of multiple stream multi-processors (SM)
- Memory hierarchic:
  - global memory ➔ PBSM/shared memory ➔ local register

Slow, but large & shared

Fast, but small & local



Stream Multiprocessor

- Each SM is a vector machine
- Shared register files
  - Store local variables
- Programmable cache (shared memory)
  - Shared with a normal L1 cache.
- **Hardware scheduling** for thread execution and **hardware context switch**





http://hothardware.com/Articles/NVIDIA-GF100-Architecture-and-Feature-Preview/

NVIDIA CUDA-Enabled GPUs Products

Architecture & Compute Capability	 CUDA-Enabled NVIDIA GPUs			HPC (double precision)
Volta Architecture (compute capabilities 7.x)	**Deep learning Inference**	**Visualization (single precision)**		Tesla V Series V100
Pascal Architecture (compute capabilities 6.x)	Tegra X2, Jetson TX2	GeForce 1000 Series GTX 1080	Quadro P Series P6000	Tesla P Series P100
Maxwell Architecture (compute capabilities 5.x)	Tegra X1 Jetson TX2	GeForce 900 Series	Quadro M Series	Tesla M Series
Kepler Architecture (compute capabilities 3.x)	Tegra K1	GeForce 700 Series GeForce 600 Series	Quadro K Series	Tesla K Series
Applications	 Embedded	 Consumer Desktop/Laptop	 Professional Workstation	 Data Center

NVIDIA GPU HW Specification

		Tesla K40	Tesla P100	Tesla V100	GeForce GTX1080
Launch Date		2013 Oct	2016 Jun	2017 Jun	2016 May
Architecture		Kepler	Pascal	Volta	Pascal
CUDA Cores		2888	3584	5120	2560
Core Clock		745MHz	1126MHz	1370MHz	1607MHz
GPU Memory Bandwidth		288GB/s	732GB/s	900GB/s	320GB/s
GPU Memory Size		12GB	16GB	16GB	8GB
Interconnect Bandwidth	PCIe3x16	32GB/s	32GB/s	32GB/s	32GB/s
	NV Link	----	160GB/s	300GB/s	---
Single Precision		4.29 TFLOPS	9.3 TFLOPS	14 TFLOPS	8.8 TFLOPS
Double Precision		1.43 TFLOPS	4.7 TFLOPS	7.0 TFLOPS	0.2 TFLOPS
TDP		235W	250W	250W	180W
Compute Capability		3.5	6.0	7.0	6.1
Launch Price (USD)		$5499	$7374/$9428(NV)	8GPU: 150K	$550

NVIDIA GPU Architecture Roadmap



GPU Compute Capability

- Programming ability of a GPU device

Feature support (unlisted features are supported for all compute capabilities)	Compute capability (version)							
	1.0	1.1	1.2	1.3	2.x	3.0	3.5	5.0
Integer atomic functions operating on 32-bit words in global memory	No	Yes						
atomicExch() operating on 32-bit floating point values in global memory								
Integer atomic functions operating on 32-bit words in shared memory	No	Yes						
atomicExch() operating on 32-bit floating point values in shared memory								
Integer atomic functions operating on 64-bit words in global memory								
Warp vote functions								

Technical specifications	Compute capability (version)							
	1.0	1.1	1.2	1.3	2.x	3.0	3.5	5.0
Maximum dimensionality of grid of thread blocks	2				3			
Maximum x-, y-, or z-dimension of a grid of thread blocks	65535				2^{31}-1			
Maximum dimensionality of thread block	3							
Maximum x- or y-dimension of a block	512				1024			
Maximum z-dimension of a block	64							
Maximum number of threads per block	512				1024			
Warp size	32							

source: http://en.wikipedia.org/wiki/CUDA

CUDA SDK Device Query

- `deviceQuery.cpp`

```
Device 0: "Tesla M2090"
  CUDA Driver Version / Runtime Version          5.0 / 5.0
  CUDA Capability Major/Minor version number:    2.0
  Total amount of global memory:                 5375 MBytes (5636554752 bytes)
  (16) Multiprocessors x ( 32) CUDA Cores/MP:    512 CUDA Cores
  GPU Clock rate:                                1301 MHz (1.30 GHz)
  Memory Clock rate:                             1848 Mhz
  Memory Bus Width:                              384-bit
  L2 Cache Size:                                 786432 bytes
  Max Texture Dimension Size (x,y,z)             1D=(65536), 2D=(65536,65535), 3D
  Max Layered Texture Size (dim) x layers        1D=(16384) x 2048, 2D=(16384,163
  Total amount of constant memory:               65536 bytes
  Total amount of shared memory per block:       49152 bytes
  Total number of registers available per block: 32768
  Warp size:                                     32
  Maximum number of threads per multiprocessor:  1536
  Maximum number of threads per block:           1024
  Maximum sizes of each dimension of a block:    1024 x 1024 x 64
  Maximum sizes of each dimension of a grid:     65535 x 65535 x 65535
```

CUDA Toolkits

- Software Development Kit(SDK) for CUDA Programming
  - The CUDA-C and CUDA-C++ compiler, nvcc
  - Tools: IDE, Debugger, Profilers, Utilities
  - Library: BLAS, CUDA Device Runtime, FFT, …
  - Sample Code
  - Documentation

CUDA SDK Version	Compute Capability	Architecture
6.5	1.X	Tesla
7.5	2.0-5.x	Fermi, Kepler, Maxwell
8.0	2.0-6.x	Fermi, Kepler, Maxwell, Pascal
9.0	3.0-7.x	Kepler, Maxwell, Pascal, Volta

http://docs.nvidia.com/cuda/cuda-toolkit-release-notes/index.html#major-components

Reference

- Cyril Zeller, NVIDIA Developer Technology slides