

# BASE DE DATOS

```
1 • CREATE DATABASE IF NOT EXISTS `bdgestiontesis` /*!40100 DEFAULT CHARACTER SET utf8mb4 COLLATE utf8mb4_0900_ai_ci;
2 • USE `bdgestiontesis`;
3 -- MySQL dump 10.13 Distrib 8.0.42, for Win64 (x86_64)
4 --
5 -- Host: localhost    Database: bdgestiontesis
6 -----
7 -- Server version  8.0.42
8
9 • /*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
10 • /*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
11 • /*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
12 • /*!50503 SET NAMES utf8 */;
13 • /*!40103 SET @OLD_TIME_ZONE=@@TIME_ZONE */;
14 • /*!40103 SET TIME_ZONE='+00:00' */;
15 • /*!40014 SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS, UNIQUE_CHECKS=0 */;
16 • /*!40014 SET @OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS, FOREIGN_KEY_CHECKS=0 */;
17 • /*!40101 SET @OLD_SQL_MODE=@@SQL_MODE, SQL_MODE='NO_AUTO_VALUE_ON_ZERO' */;
18 • /*!40111 SET @OLD_SQL_NOTES=@@SQL_NOTES, SQL_NOTES=0 */;
19
20 --
21 -- Table structure for table `documentos_requisito`
22 --
23
24 • DROP TABLE IF EXISTS `documentos_requisito`;
25 • /*!40101 SET @saved_cs_client      = @@character_set_client */;
26 • /*!50503 SET character_set_client = utf8mb4 */;
```

```
124 --
125
126 • DROP TABLE IF EXISTS `evaluaciones_jurado`;
127 • /*!40101 SET @saved_cs_client      = @@character_set_client */;
128 • /*!50503 SET character_set_client = utf8mb4 */;
129 • CREATE TABLE `evaluaciones_jurado` (
130   `id_evaluacion_jurado` int NOT NULL AUTO_INCREMENT,
131   `id_sustentacion` int NOT NULL,
132   `codigo_jurado` varchar(20) NOT NULL,
133   `item_1` decimal(2,1) NOT NULL DEFAULT '0.0',
134   `item_2` decimal(2,1) NOT NULL DEFAULT '0.0',
135   `item_3` decimal(2,1) NOT NULL DEFAULT '0.0',
136   `item_4` decimal(2,1) NOT NULL DEFAULT '0.0',
137   `item_5` decimal(2,1) NOT NULL DEFAULT '0.0',
138   `item_6` decimal(2,1) NOT NULL DEFAULT '0.0',
139   `item_7` decimal(2,1) NOT NULL DEFAULT '0.0',
140   `item_8` decimal(2,1) NOT NULL DEFAULT '0.0',
141   `item_9` decimal(2,1) NOT NULL DEFAULT '0.0',
142   `item_10` decimal(2,1) NOT NULL DEFAULT '0.0',
143   `item_11` decimal(2,1) NOT NULL DEFAULT '0.0',
144   `item_12` decimal(2,1) NOT NULL DEFAULT '0.0',
145   `item_13` decimal(2,1) NOT NULL DEFAULT '0.0',
146   `item_14` decimal(2,1) NOT NULL DEFAULT '0.0',
147   `item_15` decimal(2,1) NOT NULL DEFAULT '0.0',
148   `item_16` decimal(2,1) NOT NULL DEFAULT '0.0',
149   `item_17` decimal(2,1) NOT NULL DEFAULT '0.0';
```

