

EXTREME NETWORKS

Onboard Mgmt VLAN XIQ-SE workflow

Ludovico Stevens

Technical Marketing Engineering

September 2022

Onboard Mgmt VLAN XIQ-SE workflow



- Workflow to onboard a VOSS/Fabric Engine switch onto a dedicated switch mgmt VLAN/L2VSN
- Mgmt VLAN / I-SID and IP data extracted from CSV file previously placed on XIQ-SE
- Ability to change the switch sysname (SNMP and ISIS) at the same time
- Ability to set the auto-sense ISIS Hello authentication key during the IP mgmt change
- Ability to re-add the device into a different XIQ-SE site after the mgmt VLAN IP change
- Ability to launch a follow up workflow once this workflow has finished
- Requires minimum VOSS 8.5 (for mgmt convert support)

Workflow manual execution



- Workflow can be manually run against 1 or many switches simultaneously

The screenshot displays the 'Devices' tab in the management interface. A table lists various network devices with columns for Status, Name, Site, IP Address, Poll Status, Poll Details, Device Type, Family, and Firmware. A context menu is open over the table, showing options like FlexView, More Views, Configure..., Compass Search..., Rediscover, Clear Alarms..., Upgrade Firmware..., Add to Device Group..., and More Actions. The 'More Actions' submenu is expanded, showing categories like Access Control, Config, Example, Macro, Provisioning, System, and VLAN. The 'VLAN' category is selected, and the 'Onboard Mgmt VLAN' option is highlighted with a red box.

Status	Name	Site	IP Address	Poll Status	Poll Details	Device Type	Family	Firmware
▲	5320-16P-4XE-DC-FabricEngi...	/World/CTC/Reading/Campus/Universal-Hw-Access	20.0.48.14	Available: 1...	Up: 949 Do...	5320-16P-4XE-DC-F...	Universal P...	8.8.0.0
▲	5320-24T-8XE-FabricEngine	/World/CTC/Reading/Campus/Universal-Hw-Access	20.0.48.13	Available: 1...	Up: 949 Do...	5320-24T-8XE-Fabri...	Universal P...	8.8.0.0
▲	5420F-48P-4XL-FabricEngine	/World/CTC/Reading/Campus/Universal-Hw-Access	20.0.48.10	Available: 1...	Up: 949 Do...	5420F-48P-4XL-Fab...	Universal P...	8.8.0.0
▲	5420M-24W-4YE-FabricEngine	/World/CTC/Reading/Campus/Universal-Hw-Access	20.0.48.11	Available: 1...	Up: 949 Do...	5420M-24W-4YE-Fa...	Universal P...	8.8.0.0
●	5520-24W-SwitchEngine	/World/CTC/Reading/Campus/Universal-Hw-Access	10.8.3.10	Available: 1...	Up: 949 Do...	5520-24W-SwitchEn...	Universal P...	32.1.1.6
●	5520-STK	/World/CTC/Reading/Campus/Universal-Hw-Access	20.0.48.12	Available: 1...	Up: 949 Do...	Switch Engine ARM ...	Universal P...	31.7.1.4
▲	5720-24MXW-FabricEngine	/World/CTC/Reading/Campus/Universal-Hw-Access	20.0.48.16	Available: 1...	Up: 949 Do...	5720-24MXW-Fabri...	Universal P...	8.8.0.0
●	CTC-410C-3/45	/World/CTC/Reading/Campus/Universal-Hw-Access	20.0.203.52	Available: 9...	Up: 948 Do...	XIQ AP	XIQ Native	10.5r1
▶	VSP7448-1	/World/CTC/Reading/Campus/Universal-Hw-Access	20.0.20.76	Available: 1...	Up: 949 Do...	VSP-7400-48Y-8C	VSP Series	8.8.0.0
▶	VSP7448-2	/World/CTC/Reading/Campus/Universal-Hw-Access	20.0.20.77	Available: 9...	Up: 948 Do...	VSP-7400-48Y-8C	VSP Series	8.8.0.0

Workflow automatic execution during onboarding



- Workflow can be automatically run after ZTP+ onboarding, under XIQ-SE Site Actions
- In this case script will always run against 1 switch only, the onboarding switch

Devices **Sandbox** Site Summary Endpoint Locations FlexReports

Discover **Actions** VRF/VLAN Topologies Services Port Templates ZTP+ Device Defaults Endpoint Locations Analytics Custom Variables

☒ Automatically Add Devices Collection Mode: Historical

☒ Add Trap Receiver Collection Interval (minutes): 10

☒ Add Syslog Receiver Map Name: /World/CTC/Reading/Sandbox/Sandbox

☒ Add to Archive

☒ Add to Map

Custom Configuration

+ Add Edit - Delete

Enabled	Vendor	Family	Topology	Task
<input checked="" type="checkbox"/>	Extreme	Universal Platform Fabric Engine	Any	Provisioning/Onboard Mgmt VLAN

Update Cancel

Onboard Mgmt VLAN XIQ-SE workflow inputs



- A CSV file is uploaded to XIQ-SE beforehand
- CSV file has device data which can be device specific
- CSV data is looked up either by device initial (dhcp) IP or Serial Number or MAC Address
- CSV data can be referenced as \$<name> in workflow inputs
- Site variables can still also be referenced but as \${name}

The screenshot displays the XIQ-SE workflow editor for the 'Onboard Mgmt VLAN' workflow. The workflow diagram shows a 'Start' node, a 'Move to VLAN mgmt IP' activity, and an 'End' node. The 'Details' panel on the right lists the inputs for the workflow, with red boxes highlighting the 'CSV data file', 'Index into CSV file', and 'Mgmt VLAN IP' fields. Red arrows point from these fields to the corresponding columns in the CSV file shown in the bottom-left window.

CSV data file: /root/mgmtdata.csv

Index into CSV file: Serial Number

Mgmt VLAN and re-add Site Notes:
Provide new mgmt I-SID, IP, Mask and Default Gateway. The VLAN id is optional and can be omitted. Is not used on DVR Leaf and can be auto-allocated otherwise. A system name can be configured for both SNMP and ISIS at the same time, if provided. The Site to re-add is optional, if not provided the device will get re-added to the same Site.

Mgmt VLAN ID: \$<mgmt vlanid>

Mgmt VLAN I-SID: \$<mgmt isid>

Mgmt VLAN IP: \$<mgmt ip>

Mgmt VLAN Mask: \$<mgmt mask>

Mgmt VLAN Default Gateway: \$<mgmt gateway>

System Name to configure on device: \$<sysname>

Auto-sense ISIS Authentication key:

Site to re-add device using mgmt VLAN IP:

CSV File Content (mgmtdata.csv):

	serial number	mgmt vlanid	mgmt isid	mgmt ip	mgmt mask	mgmt gateway	sysname	site name
1	JA092041G-01023	209	2800209	20.0.209.54	255.255.255.0	20.0.209.1	5420-bld1	/World/building1
2	TB062139K-H0210	209	2800209	20.0.209.53	255.255.255.0	20.0.209.1	5320-bld1	/World/building1
3	TB022131K-H0059	209	2800209	20.0.209.52	255.255.255.0	20.0.209.1	5320-bld2	/World/building2
4	JA102040G-00003	209	2800209	20.0.209.55	255.255.255.0	20.0.209.1	5420-bld2	/World/building2

Workflow execution



Dashboard Devices Discovered Firmware Archives Configuration Templates Reports **Onboard Mgmt VLAN (26787)**

Summary

Status	Start Date/Time	Name	Version	Source	# Devices	Started By	End Date/Time	Message	Path
✓	9/7/2022 10:32:26 ...	Onboard Mgmt VLAN	25	Workflow Designer ...	1	Istevens	9/7/2022 10:32:42 ...	Re-added device using mgmt VLAN IP 20.0.2...	/Workflows/Ludovico/Onboard Mgmt VLAN


Graph View Table View



Stop Workflow

Show Output

Show Variables



Devices Grid

Show Output

Show Variables

Status	Device IP	Output Path	Start Date/Time	End Date/Time	Message
SUCCESS	20.0.48.10		9/7/2022 10:3...	9/7/2022 10:3...	Re-added device using mgmt VLAN IP 20.0.209.54 on L2 I-SID 2800209 to XIQ-SE Site '/World/CTC/Reading/Campus/Univer

The following configuration was successfully performed on switch:

```
-> config term
-> mgmt vlan
->   convert i-sid 2800209 ip 20.0.209.54 255.255.255.0 gateway 20.0.209.1 rollback 130
-> config term
-> mgmt convert-commit
-> snmp-server name 5420-bld1
-> router isis
->   sys-name 5420-bld1
-> exit
-> end
-> save config
Deleted IP '20.0.48.10' from XIQ-SE's database
Deleted IP '20.0.48.10' in NAC Engine Group
Added new device IP '20.0.209.54' to XIQ-SE Site '/World/CTC/Reading/Campus/Universal-Hw-
Access' with admin profile 'PoC Profile'
Exit code SUCCESS
```

Close

KS, INC. ALL RIGHTS RESERVED.

