

project_notebook-zh

November 3, 2019

1 123

A*“Google-maps”

```
In [1]: # Run this cell first!
```

```
from helpers import Map, load_map, show_map
from helper import Maps, load_maps, show_maps
from student_code import shortest_path

%load_ext autoreload
%autoreload 2
```

1.0.1 Map

```
In [2]: map_10 = load_map('map-10.pickle')
        show_map(map_10)
```

```
show_maps(map_10)Jupyter.html
1022
MapA *intersectionsroads
Intersections
intersections
10xy
```

```
In [3]: map_10.intersections
```

```
Out[3]: {0: [0.7798606835438107, 0.6922727646627362],
1: [0.7647837074641568, 0.3252670836724646],
2: [0.7155217893995438, 0.20026498027300055],
3: [0.7076566826610747, 0.3278339270610988],
4: [0.8325506249953353, 0.02310946309985762],
5: [0.49016747075266875, 0.5464878695400415],
6: [0.8820353070895344, 0.6791919587749445],
7: [0.46247219371675075, 0.6258061621642713],
8: [0.11622158839385677, 0.11236327488812581],
9: [0.1285377678230034, 0.3285840695698353]}
```

Roads

```
roads[i] roads[i]
```

```
In [4]: # this shows that intersection 0 connects to intersections 7, 6, and 5
        map_10.roads[0]
```

```
Out[4]: [7, 6, 5]
```

```
In [5]: # This shows the full connectivity of the map
        map_10.roads
```

```
Out[5]: [[7, 6, 5],
         [4, 3, 2],
         [4, 3, 1],
         [5, 4, 1, 2],
         [1, 2, 3],
         [7, 0, 3],
         [0],
         [0, 5],
         [9],
         [8]]
```

```
In [6]: # map_40 is a bigger map than map_10
        map_40 = load_map('map-40.pickle')
        show_map(map_40)
```

show_maps(map_40)Jupyter.html

1.0.2

40039

```
show_map
```

- start - ""
- goal - ""
- path -

```
In [7]: # run this code, note the effect of including the optional
        # parameters in the function call.
        show_map(map_40, start=5, goal=34, path=[5,16,37,12,34])
```

1.0.3

```
student_code.pyFile > Open
```

```
show_mappath[5, 16, 37, 12, 34]
```

```
In [8]: %%bash
        > shortest_path(map_40, 5, 34)
        [5, 16, 37, 12, 34]
```

```
bash: line 1: syntax error near unexpected token `('
bash: line 1: `> shortest_path(map_40, 5, 34)'
```

```
In [9]: path = shortest_path(map_40, 5, 34)
        if path == [5, 16, 37, 12, 34]:
            print("great! Your code works for these inputs!")
        else:
            print("something is off, your code produced the following:")
            print(path)
```

```
shortest path called
great! Your code works for these inputs!
```

1.0.4

- 1.
2. A*
- 3.
- 4.

"""

```
In [10]: from test import test
```

```
        test(shortest_path)
```

```
shortest path called
shortest path called
shortest path called
All tests pass! Congratulations!
```

```
In [ ]:
```