

Finance Data Science

Lecture 8: Kernel Methods; Data Normalization

Laurent El Ghaoui

MFE 230P, Summer 2017
MFE Program
Haas School of Business
UC Berkeley

6/28/2017

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References

Motivation

A linear regression problem

Linear (second-order) auto-regressive model for time-series: y_t linear function of y_{t-1}, y_{t-2}

$$y_t = w_1 + w_2 y_{t-1} + w_3 y_{t-2}, \quad t = 3, \dots, T.$$

This writes $y_t = w^T x_t$, with x_t the “feature vectors”

$$x_t := (1, y_{t-1}, y_{t-2}), \quad t = 3, \dots, T.$$

Define $3 \times (T - 2)$ matrix X with t -th column x_t , and $(T - 2) \times 1$ vector $y = (y_3, \dots, y_T)$.

Model fitting via least-squares:

$$\min_w \|X^T w - y\|_2^2$$

Prediction rule : at time $T + 1$, $\hat{y}_{T+1} = w_1 + w_2 y_T + w_3 y_{T-1} = w^T x_{T+1}$.

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Nonlinear regression

Nonlinear auto-regressive model for time-series: y_t *quadratic* function of y_{t-1}, y_{t-2}

$$y_t = w_1 + w_2 y_{t-1} + w_3 y_{t-2} + w_4 y_{t-1}^2 + w_5 y_{t-1} y_{t-2} + w_6 y_{t-2}^2.$$

This writes $y_t = w^T \phi(x_t)$, with $\phi(x_t)$ the augmented feature vectors

$$\phi(x_t) := \left(1, y_{t-1}, y_{t-2}, y_{t-1}^2, y_{t-1} y_{t-2}, y_{t-2}^2 \right).$$

Prediction rule is $\hat{y}_{T+1} = w^T \phi(x_{T+1})$.

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing


Problem statement

Offset

Scaling

Other normalizations

References



Non-linear (e.g., quadratic) decision boundary

$$w_1x_1 + w_2x_2 + w_3x_1^2 + w_4x_1x_2 + w_5x_2^2 + b = 0.$$

Writes $w^T\phi(x) + b = 0$, with $\phi(x) := (x_1, x_2, x_1^2, x_1x_2, x_2^2)$.

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling


Other normalizations

References

Challenges

In principle, it seems can always augment the dimension of the feature space to make the data linearly separable. (See the video at

<http://www.youtube.com/watch?v=3liCbRZPrZA>)



How do we do it in a computationally efficient manner?

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Generic form of regularized learning problem

Many classification and regression problems can be written

$$\min_w L(X^T w, y) + \lambda \|w\|_2^2$$

where

- ▶ $X = [x_1, \dots, x_n]$ is a $p \times n$ matrix of data points.
- ▶ $y \in \mathbf{R}^n$ contains a response vector (or labels).
- ▶ $w \in \mathbf{R}^p$ contains classifier or regression coefficients.
- ▶ L is a “loss” function that depends on the problem considered.
- ▶ $\lambda \geq 0$ is a regularization parameter.

Prediction/classification rule: depends only on $w^T x$, where $x \in \mathbf{R}^p$ is a new data point.

Note: here, we consider l_2 -norm penalty only!

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

- Squared loss: (for linear least-squares regression)

$$L(z, y) = \|z - y\|_2^2 = \sum_{i=1}^n (x_i - y_i)^2.$$

- Hinge loss: (for SVMs)

$$L(z, y) = \sum_{i=1}^n \max(0, 1 - y_i z_i)$$

- Logistic loss: (for logistic regression)

$$L(z, y) = - \sum_{i=1}^n \log(1 + e^{-y_i z_i}).$$

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Key result

For the generic problem:

$$\min_w L(X^T w, y) + \lambda \|w\|_2^2$$

the optimal w lies in the span of the data points (x_1, \dots, x_n) :

$$w = Xv$$

for some vector $v \in \mathbf{R}^n$.

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Proof

A linear algebra result

For any matrix $X \in \mathbf{R}^{p \times n}$: every $w \in \mathbf{R}^p$ can be written as the sum of two *orthogonal* vectors, one in the range of X and the other orthogonal to it:

$$w = Xv + r$$

where $v \in \mathbf{R}^n$, and $X^T r = 0$ (that is, r is in the nullspace $\mathcal{N}(X^T)$).




Figure shows the case $X = A = (a_1, a_2)$.

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Consequence of key result

For the generic problem:

$$\min_w L(X^T w) + \lambda \|w\|_2^2$$

the optimal w can be written as $w = Xv$ for some vector $v \in \mathbf{R}^n$.

Hence training problem depends only on the $n \times n$ (PSD) matrix $K := X^T X$:

$$\min_v L(Kv) + \lambda v^T Kv.$$

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Kernel matrix

The training problem depends only on the “kernel matrix” $K = X^T X$

$$K_{ij} = x_i^T x_j, \quad 1 \leq i, j \leq n.$$

That is, K contains the scalar products between all data point pairs.

The prediction/classification rule depends on the scalar products between new point x and the training data points x_1, \dots, x_n :

$$w^T x = v^T X^T x = v^T k, \quad k := X^T x = (x^T x_1, \dots, x^T x_n).$$

Computational advantage: Once K is formed (this takes $O(n^2 p)$), then the training problem has only n variables. When $p \gg n$, this leads to a dramatic reduction in problem size.

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

How about the nonlinear case?

In the nonlinear case, we simply replace the feature vectors x_i by some “augmented” feature vectors $\phi(x_i)$, with ϕ a non-linear mapping.

Example : in classification with quadratic decision boundary, we use

$$\phi(x) := (1, x_1, x_2, x_1^2, x_1 x_2, x_2^2).$$

This leads to the modified kernel matrix

$$K_{ij} = \phi(x_i)^T \phi(x_j), \quad 1 \leq i, j \leq n.$$

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

The kernel function

The *kernel function* associated with mapping ϕ is

$$k(x, z) = \phi(x)^T \phi(z).$$

It provides information about the metric in the feature space, *e.g.*:

$$\|\phi(x) - \phi(z)\|_2^2 = k(x, x) - 2k(x, z) + k(z, z).$$

The computational effort involved in

- ▶ solving the training problem;
- ▶ making a prediction,

depends only on our ability to quickly evaluate such scalar products.

We can't choose k arbitrarily; it has to satisfy the above for some ϕ .

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Quadratic kernels

Classification with quadratic boundaries involves feature vectors

$$\phi(x) = (1, x_1, x_2, x_1^2, x_1x_2, x_2^2).$$

Fact : given two vectors $x, z \in \mathbf{R}^2$, we have

$$\phi(x)^T \phi(z) = (1 + x^T z)^2.$$

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Polynomial kernels

More generally when $\phi(x)$ is the vector formed with all the products between the components of $x \in \mathbf{R}^n$, up to degree d , then for any two vectors $x, z \in \mathbf{R}^n$,

$$\phi(x)^T \phi(z) = (1 + x^T z)^d.$$

Computational effort grows linearly in n .

This represents a dramatic reduction in speed over the “brute force” approach:

- ▶ Form $\phi(x), \phi(z)$;
- ▶ evaluate $\phi(x)^T \phi(z)$.

Computational effort grows as n^d .

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Other kernels

Gaussian kernel function:

$$k(x, z) = \exp \left(-\frac{\|x - z\|_2^2}{2\sigma^2} \right),$$

where $\sigma > 0$ is a scale parameter. Allows to ignore points that are too far apart.
Corresponds to a non-linear mapping ϕ to infinite-dimensional feature space.

There is a large variety (a zoo?) of other kernels, some adapted to structure of data (text, images, etc).

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Kernels and sparsity

Kernel methods essentially lift the space of features, to pose the original problem in higher-dimensional space.

Sparse methods seek to improve the interpretability of the results, by selecting a few features that are relevant to the prediction problem at hand.

Unfortunately kernels and sparsity don't mix well, since we lose the interpretation of the original features in the "lifting" process.

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

In some cases we are interested in the *interpretability* of the regression parameters:

- ▶ Which few features are responsible for most of the predictive power?
- ▶ Can we find those features in a reliable way?

Sparse methods attempt to trade-off sparsity of the optimal regression or classification coefficients with predictive power.

In such methods, the l_1 -norm plays an important role.

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

A justification from regularized LS

Consider the *cardinality-constrained* regularized LS:

$$\min_w \|X^T w - y\|_2^2 + \lambda \|w\|_2^2 : \mathbf{Card}(w) = k$$

where $\lambda > 0$ is the regularization parameter, $\mathbf{Card}(w)$ denotes cardinality of w (number of nonzero elements in w), and k imposes a bound on it.

Problem above is very difficult to solve. We can approximate it as

$$\min_w \|X^T w - y\|_2^2 + \frac{\lambda}{k} \|w\|_1^2.$$

Proof: Cauchy-Schwartz inequality implies

$$\sqrt{\mathbf{Card}(w)} \cdot \|w\|_2 \geq \|w\|_1.$$

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References


When λ varies, the set of solutions is the same as that of the “LASSO” problem

$$\min_w \|X^T w - y\|_2^2 + \mu \|w\|_1,$$

where $\mu > 0$ spans the positive real line.

- ▶ Not solvable by direct linear algebra methods.
- ▶ Many efficient algorithms have been proposed for this type of convex problem [2].
- ▶ When the number of variables is not too high, *coordinate descent* (solving the problem one variable at a time, all the others being fixed) works well.

Example: image of Microsoft in NYT headlines



- ▶ Data matrix X records occurrences of words in documents.
- ▶ Response ± 1 vector y records presence/absence of term `microsoft`.
- ▶ Solve LASSO to regress occurrence of Microsoft against other word occurrences.
- ▶ Sparsity allows to find just a few words whose occurrence predicts that of the term “Microsoft” in headlines.

Image of `microsoft` in NYT headlines (1981-2007).

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Can LASSO be kernelized?

Answer : NO.

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

This is due to the fact that the solution to the problem

$$\min_w \|X^T w - y\|_2^2 + \mu \|w\|_1,$$

does not depend only on $K := X^T X$, but on X itself. This is in contrast with the Ridge regression problem

$$\min_w \|X^T w - y\|_2^2 + \mu \|w\|_2^2.$$

The main reason is the lack of rotational invariance of the l_1 -norm.

Kernel methods: summary

- ▶ Kernels need to be chosen by the user.
- ▶ Choice not always obvious; Gaussian or polynomial kernels are popular.
- ▶ Control over-fitting via cross validation (wrt say, scale parameter of Gaussian kernel, or degree of polynomial kernel).
- ▶ Kernel methods not well adapted to sparsity / l_1 -norm regularization (seen next).

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Before we start processing data via a supervised learning algorithm, we need to prepare data:

- ▶ Remove missing values;
- ▶ Remove outlier values;
- ▶ Normalize (offset and rescale) data points;
- ▶ Normalize features.

Offset: the LS case

Consider the penalized least-squares problem:

$$\min_w \|X^T w - y\|_2^2 + \rho^2 \|w\|_2^2. \quad (1)$$

The prediction rule for a new data point x is then $\hat{y}(x) = w^T x$.

It is common to center the $n \times m$ data matrix $X = [x_1, \dots, x_m]$, and modify it to $X^c := [x_1 - \hat{x}, \dots, x_m - \hat{x}]$, with

$$\hat{x} = \frac{1}{m} \sum_{i=1}^m x_i$$

the center of the data points.

This is equivalent to solving the problem

$$\min_{w,b} \|X^T w + b\mathbf{1} - y\|_2^2 + \rho^2 \|w\|_2^2.$$

The prediction rule is now $\hat{y}(x) = w^T x + b$. In effect, centering implicitly allows to consider a more general *affine* rule (as opposed to linear, as in problem (1)).

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References

Offset: dealing with other loss functions

When other loss functions are involved, the previous centering method does not have a natural interpretation as an affine rule.

It is thus *always* better to work with affine rules (arguably more general than linear ones):

$$\min_{w,b} \mathcal{L}(X^T w + b\mathbf{1}, y) + p(w)$$

Such an approach provides an implicit “centering”.

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset**
- Scaling
- Other normalizations

References

Scaling features

Sometimes, scaling the features provides better performance. Just as with centering, scaling should be done differently with different loss functions.

- ▶ The standard approach is to center, and then normalize data by variance.
- ▶ One may use robust methods, where mean and standard deviation are replaced with median and mean absolute deviation.

Kernels

Motivations
Kernel trick
Examples
Kernels and sparsity
Summary

Pre-Processing

Problem statement
Offset
Scaling
Other normalizations

References

Scaling features via data uncertainty models

Consider a least-squares problem:

$$\min_w \|X^T w + b\mathbf{1} - y\|_2$$

Assume for example that the data matrix X is only known up to an interval matrix:

$$\mathcal{X} := \left\{ X \in \mathbf{R}^{n \times m} : \forall i, j, |X_{ij} - \hat{X}_{ij}| \leq R_{ij} \right\},$$

with $\hat{X} = [\hat{x}_1, \dots, \hat{x}_m]$ given, and $R := [r_1, \dots, r_m] \geq 0$ a $n \times m$ matrix describing the uncertainty size around the “center” \hat{X} .

The robust version is

$$\min_w \max_{X \in \mathcal{X}} \sum_{i=1}^m (x_i^T w + b - y)^2 = \min_w \max_{X \in \mathcal{X}} \sum_{i=1}^m (\hat{x}_i^T w + b + r_i^T |w| - y)^2$$

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References

Scaling data points

In practice, it may be advisable to scale data points differently.

- ▶ In time-series prediction, we may use exponential smoothing in order to give more importance to recent time-series values than older ones.
- ▶ In imbalanced classification, we may need to scale the negatively labelled data differently from the positively labelled data.

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Other normalizations

- Using higher-order moments [1].

Kernels

Motivations

Kernel trick

Examples

Kernels and sparsity

Summary

Pre-Processing

Problem statement

Offset

Scaling

Other normalizations

References

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References

Kernels

- Motivations
- Kernel trick
- Examples
- Kernels and sparsity
- Summary

Pre-Processing

- Problem statement
- Offset
- Scaling
- Other normalizations

References



Vadim Asnin.

Algorithm for multivariate data standardization up to third moment.
arXiv preprint arXiv:1204.4148, 2012.



T. Hastie, R. Tibshirani, and J.H. Friedman.

The elements of statistical learning.
Springer, 2009.