Advanced Database System Final Project Report

Name: Yufeng Yuan UML ID: 01506240

E-mail address: Yufeng Yuan@student.uml.edu

1. Computing Selection by MapReduce:

a. Question Description

Find cities whose population is larger than 300,000.

b. Data Source

```
City (ID, Name, CountryCode, District, population)
```

c. Solution

The java source code for this question is in <u>SelectionByMapReduce.java</u>.

In map, first we need check if the population of this city is greater than 300,000,

because we don't need to count, so we just build a map function like: < Name, "">,

Where Name is the name of city whose population is larger than 300,000, and "" is just an empty string.

In Reducer function, we just output each key.

d. Result

The result file was showing in directory result1.

2. Computing Projection by MapReduce

a. Question Description

Find all the name of the cities and corresponding district.

b. Data Source

```
City (<u>ID</u>, Name, CountryCode, District, population)
```

c. Solution

The java source code for this question is in <u>ProjectionByMapReduce.java</u>.

In map, because there might be some cities belongs to same distinct, we the district should not be the key, so we create the key/value pair as <Name, District>.

In Reduce Function, we just simply output the key and value.

d. Result

The result file was showing in directory result2

3. Computing Natural Join by MapReduce

a. Question Description

Find all countries whose official language is English.

b. Data Source

```
Country (Code, Name, Continent, Region, SurfaceArea, IndepYear,
Population, LifeExpectancy, GNP, GNPold, LocalName,
GovernmentForm, HeadOfState, Capital, Code2)

CountryLanguage (CountryCode, Language, IsOfficial, Percentage)
```

c. Solution

The java source code for this question is in NaturalJoinByMapReduce.java.

This question we need to use two table, so I created two map function, first one is

MapCountryLanguage, in this class, we need use the data from CountryLanguage.txt,
first we need to check each country has a Language value equals to "English", and
IsOfficial value equals to "T", if both situation is true, this means this country's
official language is English, then emit <ConutryCode, "FindCountryCode">-... Here
the string "FindCountryCode" just means this CountryCode is selected.

The other Map function is MapCountry, in this class, we just simply output all Code
and Name pair, where the Code in file Country.txt is the CountryCode in
CountryLanguage.txt. Thus, in this mapper, we got <Code, Name>.

In reduce, we can find if the key has two values ("FindCountryCode", Name), the
Name value is what we want to output, if there is only one values (Name), that means
this country's official language is not English. So just simply check if how many
values in each key, if it equals to 2, then output the name.

d. Result

The result file was showing in directory result3.

4. Aggregation by MapReduce

a. Question Description

Find how many cities each district has.

b. Data Source

```
City (ID, Name, CountryCode, District, population)
```

c. Solution

The java source code for this question is in <u>AggregationByMapReduce.java</u>. For this question, this was very similar with the official sample WordCount. In this case, the district will be the key, for each city in this district emit *district*, *one*. In reducer, we just add those ones together and then we can calculate the number of cities in each district.

d. Result

The result file was showing in directory result4.

Problem:

There is a problem makes me confused a long time is that the Text encoding problem.

I found that the original file text encoding format is Western (Mac OS Roman), but the output format is utf-8, I have tried many ways to fix that, one way is to decode the output to ISO-Latin-1 or ISO-Latin-15, but the result was just transfer those unknown characters into '?'. The output shows in those result directories are not decode. I hope I can solve this issues in the future.