

WORK PROCEDURE

PRO-MEC-003A

INSTALLING A GEARBOX ON A CUBEX DRILL

GOAL

The purpose of this procedure is to define a safe way for the installation of the gearbox.

APPLICATION

This procedure applies to all employees of MACHINES ROGER INTERNATIONAL.

INTERPRETATION

The staff with authority for the interpretation of this document are the Maintenance Manager and the Operations Manager. Any request for modification, revision or update must be made to one of these persons.

RESPONSIBILITIES

The worker is responsible for using this procedure for each installation of a gearbox. The supervisor must designate a team leader and the team leader will direct the operator to perform this task. The necessary tools and lifting equipment must be inspected before using them. The operator must have the training to operate the lifting equipment.

PROCEDURE

- 1) Check the work place.
- 2) Put the boom at 90 degrees
- 3) Unscrew swivel and saver sub if the condition of the gear box allows it
- 4) Lower the gear box near the slip plates. Leave space to pass the forks underneath or slings or a V-30 chain
- 5) Apply the lockout procedure**
- 6) Unscrew the two hydraulic hoses and the air hoses (swivel and piston spline)
- 7) Unscrew the bolts leaving the first two from the top (one on the left and one on the right)

CHANGER UN «GEAR BOX» SUR UNE FOREUSE I.T.H.

- 8) Press the forks under the gear box or put a slight tension on the slings or the chain
- 9) Unscrew the two remaining bolts
- 10) Remove the gear box
- 11) Approach the new gear box using lifting equipment
- 12) Do reverse procedure
- 13) Finish by tightening the swivel to (800 lbs of torque)
- 14) Make sure the gear box is turning in the right direction.



Karl Béchard
Maintenance Manager



Christian St-Amour
Operations Manager