

WORK PROCEDURE

PRO-MEC-008A

PROCEDURE FOR CHANGING THE TEFLON ON THE FEED EXTENSION

GOAL

The purpose of this procedure is to provide a safe method for changing the teflon feed extension.

APPLICATION

This procedure applies to all employees of MACHINES ROGER INTERNATIONAL.

INTERPRETATION

The staff with authority for the interpretation of this document are the Maintenance Manager and the Operations Manager. Any request for modification, revision or update must be made to one of these persons.

RESPONSIBILITIES

Worker

The worker is responsible for applying this procedure when changing teflon on the feed extension.

REQUIRED MATERIAL

- 15/16 " wrench
- Ratchet and 15/16 " socket
- Wrench $\frac{3}{4}$

UNDERGROUND WORK PLACE PROCEDURE

1. Barricade the accesses of your workplace.
2. Position the boom vertically (90-90), the tables on the floor and in the center of the slide over.
3. Apply boom stabilizing cylinders " Stinger "

PROCEDURE FOR CHANGING THE TEFLON ON THE FEED EXTENSION

4. Drill the length of the hammer and a 1.8 m rod into the rock. Make sure that the gearbox is fully down on the boom tables.

5. Start removing the bolts from the slide system retainer plates. **(see the explosion view in the appendix)**

N.B. only one part at a time and one side at a time.

6. Change the teflons.

7. When reassembling, check the condition of the assembly bolts. Replace if necessary

IN SHOP PROCEDURE

1. The change of teflons in the workshop must be done using the crane.

2. Use a sling with a capacity of 7000 lbs.

3. Lower the gear box at the tables

4. Stabilize the mast with the overhead crane and the sling start to remove the bolts from the retaining plates of the slide system. **(see the explosion view in the appendix)**

N.B. only one part at a time and one side at a time.

5. Change the teflons.

6. When reassembling, check the condition of the adjustment bolts. Replace if necessary

Adds or modifications	Date	By
Translation review	May 2024	S. Tremblay R. Harrower



Karl Béchard
Maintenance Manager



Christian St-Amour
Operations Manager

PROCEDURE FOR CHANGING THE TEFLON ON THE FEED EXTENSION

APPENDIX

