

WORK PROCEDURE

PRO-OP-ITH-008A

PROCEDURE TO FOLLOW WHEN V-30 BIT FAILURE AND LEAVES PARTS IN THE V-30 DOWN HOLE

OBJECTIVE

The objective of this procedure is to define safe working methods to follow when the V-30 bit failure and leaves parts in the V-30 down hole.

APPLICATION

This procedure applies to all employees of MACHINES ROGER INTERNATIONAL.

INTERPRETATION

Personnel with the authority for the interpretation of this document is the operations manager. Any request for amendment, revision or update must be made with one of these persons.

RESPONSIBILITIES

The worker responsible for the drilling must ensure to follow these steps and follow the instructions that come from the engineering department.

METHOD

When V-30 is being drilled, when one of the V-30 bit breaks or tools are dropped, **it is strictly forbidden for anyone, at all times, to go down to the bottom of the raise** to clear or recover metal parts, tools, bits or any other equipment;

We must :

- 1- The operator must remove the drill rods to remove the V-30 from the raise;
- 2- Before removing the cover, the worker must wear a harness and be attached to an anchor or a lifeline;**
- 3- When the V-30 is removed from the raise, the cover must be replaced;

PROCEDURE TO FOLLOW WHEN V-30 BIT FAILURE AND LEAVES PARTS IN THE V-30 DOWN HOLE

- 4- Install the raise scraper, designed for this purpose;
- 5- Remove the cover;
- 6- Lower the scraper to the edge of the raise;
- 7- Replace the cover;
- 8- Lower the scraper to the bottom of the raise;
- 9- Rotate it until the broken pieces of equipment falls into the pilot hole;
- 10- Remove the scraper from the raise, cover the raise securely;
- 11- If the access to the lower level is possible, it is necessary to recover the cutter;
- 12- If not, the supervisor of the mine must be notified that a bit is present at this place;
- 13- Drilling with V-30 can then be continued.

IMPORTANT: Wearing the harness is mandatory and the worker must be attached to an anchor or lifeline during cover handling and when the cover is removed from the raise.



Christian St-Amour
Director of Operations