FRANMARINE UNDERWATER SERVICES PTY LTD

RISK ASSESSMENT

And Risk Register

MV INTEGRITY III | UVI: 414562 | Class 2C Restricted

Marine Order 504 (2024) — Schedule 1 Compliance

Document Number:	FUS-SMS-INT3-02
Revision:	01
Date:	7 July 2026
Author:	Matthew Hilder
Reviewed By:	Belinda Brooks
Approved By:	Kirby Hamilton
Vessel:	MV Integrity III (UVI 414562)

DOCUMENT CONTROL

Revision History

Rev	Date	Author	Description	Approved
01	7 July 2026	M. Hilder	Initial issue	K. Hamilton

Approval

Role	Name	Date
Author	Matthew Hilder	7 July 2026
Reviewed	Belinda Brooks	7 July 2026
Approved	Kirby Hamilton	7 July 2026

Review Frequency

This document shall be reviewed at least every 12 months, or sooner following a significant incident, change of operations, vessel modification, or change in applicable legislation.

Controlled Distribution

This document is a controlled distribution issued from the Franmarine document management system (DMS), which holds the master record, revision history, and approval log. The controlled digital copy is located in the vessel's SharePoint folder. Printed or downloaded copies are uncontrolled; refer to the SMS Document Register for the current revision status.

TABLE OF CONTENTS

1. PURPOSE AND SCOPE

This risk assessment identifies and assesses hazards associated with the operation of MV Integrity III in Port Jackson, Botany Bay, and the NSW coastline within the Class 2C Restricted limits and adjacent inshore waters. Developed in consultation with the master and crew (Schedule 1, Clause 2). This risk assessment shall be given, on request, to the National Regulator or a marine safety inspector (Schedule 1, Clause 2(2)(d)).

2. METHODOLOGY

2.1 Likelihood

Rating	Likelihood	Description
1	Rare	May occur only in exceptional circumstances
2	Unlikely	Could occur but not expected
3	Possible	Could occur at some time
4	Likely	Will probably occur in most circumstances
5	Almost Certain	Expected to occur in most circumstances

2.2 Consequence

Rating	Consequence	Description
1	Insignificant	No injury, negligible damage
2	Minor	First aid, minor damage
3	Moderate	Medical treatment, moderate damage
4	Major	Serious injury, major damage
5	Catastrophic	Death, loss of vessel

2.3 Risk Matrix

L \ C	Minor	Moderate	Major	Catastrophic
Almost Certain	High	High	Extreme	Extreme
Likely	Medium	High	High	Extreme
Possible	Medium	Medium	High	High
Unlikely	Low	Medium	Medium	High
Rare	Low	Low	Medium	Medium

3. KEY DAILY TASKS

Master: pre-departure checks, voyage planning, navigation, watchkeeping, dive supervision, communications, logbook. Crew: equipment preparation, mooring, diving, deployment/recovery, housekeeping. Standby Diver: team support, emergency readiness, comms relay.

4. LIFEJACKET WEAR

Required during: bar crossings; over-side work; near structures; night ops; rough weather; when directed; emergencies; liferaft drills.

5. STABILITY RISKS

Max 6 POB; 532 kg maximum deadweight per the approved stability book. Risks: overloading, uneven weight, free surface, adverse weather, flooding, modifications.

6. CREWING AS RISK CONTROL

(a) Open water: min 2 crew. (b) Diving: min 3 per AS2299.1. (c) Enclosed transit: 1 (master) acceptable.

7. RISK REGISTER

The following table identifies the person responsible for ensuring that the risk controls for each category are implemented and maintained (Schedule 1, Clause 2(3)(c)).

Risk Area	Responsible Person	Scope
Navigation (NAV)	Master	COLREGs compliance, lookout, passage planning, VTS communications
Weather (ENV)	Master	BOM monitoring, go/no-go decision, abort decision per FUS-SMS-INT3-06K
Vessel systems (VES)	Master (operational) / East Coast Operations Superintendent (maintenance)	Pre-departure checks, defect reporting, MaintainX maintenance schedule
Stability (STB)	Master	Loading, weight distribution, compliance with the approved stability booklet (Stability Booklet 19071-903 Rev A (Global Marine Design))
Personnel (PER)	Master	Lifejacket compliance, crew safety, fit-for-duty, POB procedures, D&A policy
Diving (DIV)	Diving Supervisor	Dive plan, team compliance with AS/NZS 2299.1, standby diver readiness, emergency O2
Other operational (SUR)	Master	Vessel positioning near structures, equipment handling, winch operations, fenders
First aid supplies	East Coast Operations Superintendent	Quarterly inspection, replenishment, expiry tracking, GES 2015/01 compliance
Overall SMS and risk management	Designated Person / Owner	Annual review, resourcing, incident investigation, regulatory compliance, shore support

7.1 Navigation

ID	Hazard	Consequence	L	C	Risk	Controls	L	C	Res
NAV-01	Collision	Injury, damage, pollution	2	4	Med	Lookout, COLREGs, GPS, VHF, voyage plan	1	4	Med
NAV-02	Grounding	Hull damage, flooding	2	4	Med	Charts, GPS, local knowledge, sonar	1	4	Med
NAV-03	Bar crossing	Capsize, swamping	2	5	High	Assess, abort if unsafe, lifejackets	1	5	Med

NAV-04	Night ops	Collision, POB	3	4	High	Nav lights, extra lookout, min 2 crew	2	4	Med
NAV-05	Open water	Exposure, delayed rescue	3	4	High	Min 2 crew, EPIRB, comms plan, weather	2	3	Med

7.2 Weather

ID	Hazard	Consequence	L	C	Risk	Controls	L	C	Res
ENV-01	Adverse weather	Capsize, injury	3	4	High	BOM forecast, monitoring, abort criteria	2	3	Med
ENV-02	Lightning	Electrical, fire	1	4	Med	Monitor, return to port	1	4	Low

7.3 Vessel

ID	Hazard	Consequence	L	C	Risk	Controls	L	C	Res
VES-01	Loss of propulsion	Drift, grounding	2	3	Med	Twin independent engines, maintenance, anchor	1	3	Low
VES-02	Loss of steering	Loss of control	1	4	Med	Pre-check, maintenance, diff thrust	1	3	Low
VES-03	Flooding	Sinking	1	5	Med	Hull inspection, bilge pumps, bailing buckets, skin fittings	1	5	Med
VES-04	Fire	Injury, vessel loss	1	5	Med	No smoking, fuel checks, 2x4.5kg ABE extinguishers	1	4	Low
VES-05	Fuel spill	Environmental harm	2	3	Med	Refuelling proc, spill kit, marina spill number	1	3	Low

7.4 Stability

ID	Hazard	Consequence	L	C	Risk	Controls	L	C	Res
STB-01	Overloading	Loss of stability	2	5	High	Max 6 POB; 532 kg max deadweight;	1	5	Med

						approved stability book			
STB-02	Uneven weight	Loss of stability	2	5	High	Symmetric stowage, fuel management	1	4	Low

7.5 Personnel

ID	Hazard	Consequence	L	C	Risk	Controls	L	C	Res
PER-01	Person overboard	Drowning	2	5	High	Lifejackets, non-slip, POB procedure	1	5	Med
PER-02	Slips/trips/falls	Fractures	3	3	Med	Non-slip, housekeeping, footwear	2	2	Low
PER-03	Manual handling	MSK injury	3	2	Med	Two-person lift, technique, aids	2	2	Low
PER-04	Medical emergency	Death	2	4	Med	Risk-based first aid kit (GES 2015/01), O2 kit for diving, qualified person, procedure	1	4	Med
PER-05	Sun/heat	Heat exhaustion	3	2	Med	Sunscreen, clothing, water, shade	2	2	Low

7.6 Diving

ID	Hazard	Consequence	L	C	Risk	Controls	L	C	Res
DIV-01	Diver injury/entrapment	Drowning	2	5	High	AS2299.1, dive plan, 3-person team	1	5	Med
DIV-02	Vessel movement	Prop strike	2	5	High	Engines off by default; live boating only per documented RA (05H §4.1); continuous comms; Alpha flag; lookout	1	5	Med
DIV-03	Diver struck by vessel	Death	2	5	High	Flags, lookout, low-traffic area	1	5	Med
DIV-04	Equipment failure	Diver emergency	1	5	Med	Pre-dive checks, maintenance,	1	4	Low

						redundant air			
DIV-05	Live boating (manoeuvring with diver deployed)	Prop strike, umbilical fouling	2	5	High	Documented live-boating RA; dedicated tender tending each diver's umbilical clear of the propellers; continuous Supervisor–Master comms; defined abort; job specifics in daily SWMS (05H §4.1)	1	5	Med

7.7 Other Risks

ID	Hazard	Consequence	L	C	Risk	Controls	L	C	Res
SUR-01	Near structures	Damage, POB	3	3	Med	Slow speed, fenders, lookout	2	3	Med
SUR-02	Equipment over side	Loss, injury	2	3	Med	Two-person, securing lines, lifejackets	1	3	Low
FAT-01	Crew fatigue	Impaired judgement	3	4	High	Fatigue plan, records, 12hr limit	2	3	Med
DA-01	Drug/ alcohol	Accidents	1	5	Med	D&A policy, zero BAC, assessment	1	4	Low
LJ-01	No lifejacket	Drowning	2	5	High	Wear procedure, bar/over-side/night	1	5	Med

7.8 First Aid Supplies Risk Assessment

The type and quantity of first aid supplies carried on board MV Integrity III have been determined through a documented risk assessment in accordance with Generic Equivalent Solution GES 2015/01 (AMSA 637). This equivalent solution is available to Class 2C vessels operating in C Restricted waters and permits a risk-based determination of first aid supplies in place of the prescriptive Scale F medication schedule.

The risk assessment considered distance and time to medical aid, communication capability, type of operation and hazards, length of voyage, number and profile of persons onboard, first aid training of crew, environmental conditions, and past incident history. The overall first aid risk rating is low to moderate, based on the combination of short time to definitive care, prompt communications, a small trained adult complement, and short day operations.

7.8.1 Items Not Carried and Risk Basis

The following items from the AMSA Scale F first aid kit list (AMSA 1756) are not carried on board. Each is assessed against the operational risk profile:

Scale F Item	Schedule	Decision	Risk Basis and Alternative
Paracetamol 500 mg / Codeine Phosphate 15 mg tablets (or 500 mg / 8 mg variant)	S4	Not carried	Prescription-only combination analgesic. The codeine component requires a prescription, secure custody, and administration controls disproportionate to the vessel's operations. Paracetamol 500 mg and ibuprofen 200 mg are carried for mild to moderate pain. Pain exceeding this level indicates evacuation to definitive care, which is available within a short timeframe for all assessed operations.
Naproxen 250 mg tablets	S4 / S3	Not carried	Second NSAID not required. Ibuprofen 200 mg is carried as the anti-inflammatory of choice and is sufficient for the short operations assessed.
Betamethasone Valerate 0.02% Cream	S4	Not carried	Prescription-only corticosteroid. Hydrocortisone 1% cream is carried and is sufficient for rashes, bites, and minor skin inflammation encountered in the assessed operations.
Diphenoxylate HCl 2.5 mg / Atropine Sulfate 25 mcg tablets	S4	Not carried	Prescription-only anti-diarrhoeal. Loperamide 2 mg is carried and is sufficient for diarrhoea management during short day operations.
Scalpel, disposable (x2)	N/A	Not carried	Clinical instrument with no trained user onboard. Risk of misuse outweighs benefit for the assessed operations. Shears are retained for cutting dressings and clothing.

7.8.2 Non-Scheduled Medications Carried

The following non-scheduled (general-sale, pharmacy, or pharmacist-only) medications are carried at Scale F quantities as alternatives to the prescription items above:

Medication	Purpose
Paracetamol 500 mg tablets (2 × 20 = 40)	Mild pain relief
Ibuprofen 200 mg tablets (24)	Anti-inflammatory, moderate pain relief
Loperamide 2 mg tablets (16)	Diarrhoea
Hydrocortisone 1% cream 30 g (1)	Rashes, bites, minor skin inflammation
Loratadine 10 mg or Cetirizine 10 mg tablets (10)	Non-sedating antihistamine (allergic reactions, stings)
Hyoscine hydrobromide 0.3 mg tablets (10)	Motion sickness
Antacid tablets (50)	Indigestion

7.8.3 All Other Scale F Items

All remaining dressings, bandages, wound-care, eye-care, instrument, resuscitation, thermal-protection, infection-control, and documentation items specified in AMSA 1756 Scale F are carried at the prescribed quantities. The first aid kit is stored in a waterproof container in the bow compartment.

7.8.4 Diving Emergency Provisions

Diving operations require emergency therapeutic oxygen equipment (demand valve and constant-flow), maintained separately under AS/NZS 2299.1:2015. This equipment is not part of the first aid kit determination.

7.8.5 Inspection and Review

The first aid kit is inspected quarterly (or after any use) against the contents list. Expiry dates are checked and items replaced before lapse. The risk assessment is reviewed annually or when operations change materially.

8. ASSEMBLY STATION PRACTICABILITY

Marine Order 504 (2024), Schedule 1, Clause 12(4)(b) requires the risk assessment to state whether it is practicable for the vessel to have an alternative assembly station in the event that the primary assembly station becomes unusable or inaccessible during an emergency.

MV Integrity III is a 7.68 m aluminium hull vessel with an open deck layout. The primary assembly station is the aft deck. Due to the size and layout of the vessel, the provision of a defined alternative assembly station is not practicable. The entire deck area is visible and accessible, and in the event that the aft deck is compromised (for example by fire), all persons shall move to whichever area of the vessel is safest and prepare to abandon vessel if necessary. An inflatable liferaft sufficient for all

persons on board is the designated survival craft. The emergency plan (FUS-SMS-INT3-06) addresses this contingency.

9. CONSULTATION RECORD

Name	Position	Signature	Date