FRANMARINE UNDERWATER SERVICES PTY LTD

MEANS OF ACCESS

Procedure

MV ROHANI | UVI: 457394

Marine Order 504 (2024) — Schedule 1 Compliance

Document Number:	FUS-SMS-ROH-05D
Revision:	01
Date:	7 July 2026
Author:	Matthew Hilder
Reviewed By:	Belinda Brooks
Approved By:	Kirby Hamilton
Vessel:	MV Rohani (UVI 457394)

DOCUMENT CONTROL

Revision History

Rev	Date	Author	Description	Approved
01	7 July 2026	M. Hilder	Initial issue	K. Hamilton

Approval

Role	Name	Date
Author	Matthew Hilder	7 July 2026
Reviewed	Belinda Brooks	7 July 2026
Approved	Kirby Hamilton	7 July 2026

Review Frequency

This document shall be reviewed at least every 12 months, or sooner following a significant incident, change of operations, vessel modification, or change in applicable legislation.

Controlled Distribution

This document is a controlled distribution issued from the Franmarine document management system (DMS), which holds the master record, revision history, and approval log. The controlled digital copy is located in the vessel's SharePoint folder. Printed or downloaded copies are uncontrolled; refer to the SMS Document Register for the current revision status.

TABLE OF CONTENTS

1. PURPOSE AND SCOPE

This procedure establishes safe embarkation, disembarkation, and access procedures for MV Rohani.

1.1 Regulatory Reference

Marine Order 504 (2024), Schedule 1, Clause 11(5).

2. GENERAL REQUIREMENTS

- A safe means of access shall be provided whenever personnel embark or disembark the vessel.
- The means of access shall be appropriate to the freeboard difference between the vessel and the wharf, pontoon, or other structure.
- Non-slip surfaces or grip tape shall be maintained on all boarding areas.
- All personnel shall wear PFDs during embarkation and disembarkation unless the access arrangement provides fall protection equivalent to a fixed gangway with guardrails.

3. ACCESS FROM A WHARF OR PONTOON

- Where the freeboard difference is less than 600 mm, direct step-on / step-off access is acceptable provided the vessel is securely moored and stable.
- Where the freeboard difference exceeds 600 mm, a gangway or access ladder shall be rigged.
- The access point shall be illuminated during hours of darkness.
- Handholds shall be available at the boarding point.

4. ACCESS FROM ANOTHER VESSEL

- Transfer between vessels shall only be conducted when both vessels are stationary and securely rafted or held alongside.
- All personnel shall wear PFDs during vessel-to-vessel transfer.
- Heavy equipment or stores shall not be hand-carried during personnel transfer.

5. ACCESS FOR DIVING OPERATIONS

- A diving ladder or purpose-built platform shall be rigged before divers enter or exit the water.
- The ladder shall extend at least 600 mm below the waterline.
- A tag line shall be available to assist divers during ascent and descent.
- The dive entry and exit point shall be kept clear of obstructions.

6. RECORDS

Access arrangements are noted in the vessel logbook where non-standard arrangements are used.

7. REFERENCES

- FUS-SMS-ROH-05C Mooring and Berthing
- FUS-SMS-ROH-05H Diving Operations
- Marine Order 504 (2024), Schedule 1, Clause 11(5)