FRANMARINE UNDERWATER SERVICES PTY LTD

BUNKERING AND REFUELLING

Procedure

MV ROHANI | UVI: 457394

Marine Order 504 (2024) — Schedule 1 Compliance

Document Number:	FUS-SMS-ROH-05G
Revision:	01
Date:	7 July 2026
Author:	Matthew Hilder
Reviewed By:	Belinda Brooks
Approved By:	Kirby Hamilton
Vessel:	MV Rohani (UVI 457394)

DOCUMENT CONTROL

Revision History

Rev	Date	Author	Description	Approved
01	7 July 2026	M. Hilder	Initial issue	K. Hamilton

Approval

Role	Name	Date
Author	Matthew Hilder	7 July 2026
Reviewed	Belinda Brooks	7 July 2026
Approved	Kirby Hamilton	7 July 2026

Review Frequency

This document shall be reviewed at least every 12 months, or sooner following a significant incident, change of operations, vessel modification, or change in applicable legislation.

Controlled Distribution

This document is a controlled distribution issued from the Franmarine document management system (DMS), which holds the master record, revision history, and approval log. The controlled digital copy is located in the vessel's SharePoint folder. Printed or downloaded copies are uncontrolled; refer to the SMS Document Register for the current revision status.

TABLE OF CONTENTS

1. PURPOSE AND SCOPE

This procedure establishes the safe refuelling procedure for MV Rohani including spill prevention and emergency response.

1.1 Regulatory Reference

Marine Order 504 (2024), Schedule 1, Clause 11(5). Protection of the Environment Operations Act 1997 (NSW).

1.2 Vessel Configuration

MV Rohani is powered by twin Detroit Diesel 6V-92T diesel inboard engines within an enclosed engine room. Fuel is diesel, carried in two 1,149 L tanks (one port, one starboard; 2,298 L total). The vessel is refuelled via the deck fill points located on deck next to the wheelhouse (port and starboard).

2. GENERAL REQUIREMENTS

- Refuelling shall only be conducted at an approved fuel facility or from approved portable fuel containers.
- No smoking within 10 metres of any fuel operations.
- All engines shall be shut down before refuelling commences.
- All electrical equipment that could cause a spark shall be switched off.
- A fire extinguisher shall be readily accessible at the refuelling point.
- Absorbent materials or a spill kit shall be on hand.

3. REFUELLING PROCEDURE

- Ensure the vessel is securely moored and stable.
- Shut down both main engines.
- Identify the correct fuel type: diesel. Confirm the grade and the receiving tank before inserting the nozzle.
- Open the fuel filler cap on the gunwale. Inspect the fill point for debris.
- Insert the nozzle and commence fuelling at a controlled rate. Do not use the nozzle lock-on feature.
- Maintain contact with the nozzle at all times to prevent static discharge.
- Do not overfill. Stop fuelling when the tank is approximately 90% full to allow for thermal expansion.
- Replace the fuel filler cap and wipe any spilled fuel immediately with absorbent pads.

4. PORTABLE FUEL CONTAINERS

- Only approved, labelled, and sealed portable fuel containers shall be carried.
- Portable containers shall be secured to prevent movement.
- Decanting fuel from portable containers shall be done using a funnel or approved transfer pump.
- No decanting while the vessel is underway.

5. SPILL RESPONSE

5.1 Immediate Actions

- If fuel enters the water, immediately contain the spill using absorbent pads or booms from the onboard spill kit.
- Do not use detergent or dispersant on fuel spills in waterways.

5.2 Notification

- If refuelling at a marina, call the marina's spill response number, which is usually displayed at or near the fuel bowser.
- Notify the East Coast Operations Superintendent — 0452 123 732.
- Report the spill to the NSW EPA Environment Line — 131 555.
- If in port waters, advise the relevant port authority (Sydney VTS on VHF Ch 13).
- Report to AMSA if the spill meets the threshold for notification under MARPOL Annex I.

5.3 Clean-Up

- Recover as much spilled product as possible using absorbent materials.
- Used absorbent materials are classified as contaminated waste and shall be disposed of at an approved facility.
- Do not discharge bilge water that may be contaminated with fuel or oil.
- Record the spill in the vessel logbook including estimated quantity, location, and actions taken.

6. SPILL KIT CONTENTS

- Absorbent pads (oil-only type).
- Absorbent boom or socks.
- Disposal bags.
- Nitrile gloves.

7. RECORDS

Fuel quantities bunkered, date, location, and fuel type are recorded in the vessel logbook.

8. REFERENCES

- FUS-SMS-ROH-06J Oil or Fuel Spill Emergency Procedure
- Marine Order 504 (2024), Schedule 1, Clause 11(5)
- MARPOL Annex I (oil pollution prevention)
- Protection of the Environment Operations Act 1997 (NSW)
- Detroit Diesel 6V-92T Owner's Manual (fuel specification)