FRANMARINE UNDERWATER SERVICES PTY LTD

CARGO OPERATIONS

Procedure

MV ROHANI | UVI: 457394 | Class 2C

Marine Order 504 (2024) — Schedule 1 Compliance

Document Number:	FUS-SMS-ROH-05O
Revision:	01
Date:	7 July 2026
Author:	Matthew Hilder
Reviewed By:	Belinda Brooks
Approved By:	Kirby Hamilton
Vessel:	MV Rohani (UVI 457394)

DOCUMENT CONTROL

Revision History

Rev	Date	Author	Description	Approved By
01	7 July 2026	Matthew Hilder	Initial release	

Approval

Role	Name	Date
Author	Matthew Hilder	7 July 2026
Reviewed	Belinda Brooks	7 July 2026
Approved	Kirby Hamilton	7 July 2026

Review Frequency

This document shall be reviewed at least every 12 months, or sooner following a significant incident, change of operations, vessel modification, or change in applicable legislation.

Controlled Distribution
This document is a controlled distribution issued from the Franmarine document management system (DMS), which holds the master record, revision history, and approval log. The controlled digital copy is located in the vessel's SharePoint folder. Printed or downloaded copies are uncontrolled; refer to the SMS Document Register for the current revision status.

1. PURPOSE AND SCOPE

This procedure establishes the requirements for the safe carriage, distribution, securing, and operations involving cargo carried on MV Rohani. It covers deck cargo within the limits of the approved stability book, lifting cargo using the deck crane, and the prohibition on dangerous goods. This procedure is required under Schedule 1, Clause 11(5)(n) of Marine Order 504 (2024).

1.1 Regulatory Reference

Marine Order 504 (2024), Schedule 1, Clause 11(5)(n) — conduct of cargo operations including the carriage of dangerous goods. National Standard for Commercial Vessels Part C, Subsection 6A — Intact Stability Requirements (Chapters 5A, 5C, 8C). Approved Stability Book — Approved stability book ROHANI BARGE Dft. A (Marine Survey and Design Pty Ltd, 2 Oct 2020). Marine Order 503 (Certificates of survey - national law) 2018; Certificate of Survey COS-94585-003 (operational conditions).

1.2 Vessel Particulars

MV Rohani is a 10.80 m aluminium self-propelled crane barge and diving support vessel. Lightship displacement is 14.661 tonnes. Maximum loaded displacement is 51.163 tonnes. The vessel is approved NSCV 2C for transit and NSCV 2D for lifting operations. Lifting operations are restricted to smooth and partially smooth waters only per Certificate of Survey conditions. The vessel is fitted with one Unic UB-V504J deck crane (3.5 tonne safe working load) and twin spud legs for station-keeping during lifting and over-side operations.

2. DANGEROUS GOODS

MV Rohani does not carry dangerous goods as cargo. The carriage of dangerous goods as defined in Section 4 of NSCV Part C is prohibited on this vessel. This prohibition applies to all dangerous goods classes including but not limited to explosives, compressed gases, flammable liquids and solids, oxidising substances, toxic substances, radioactive material, corrosive substances, and miscellaneous dangerous goods.

The above prohibition does not apply to:

(a) Fuel carried in the vessel's fixed tanks for the propulsion of the vessel.

(b) Small quantities of dangerous goods carried for the safe operation or maintenance of the vessel (for example, lubricating oils, paints, cleaning agents, oxygen for medical or diving use, and battery electrolyte). These shall be stowed securely and in accordance with manufacturer's instructions.

(c) Diving gas cylinders carried for occupational diving operations conducted from the vessel under AS/NZS 2299.1:2015 (refer FUS-SMS-ROH-05H). These shall be stowed, secured, and handled in accordance with AS/NZS 2299.1:2015.

If the carriage of dangerous goods as cargo is ever proposed, the operation shall not commence until this procedure and the vessel's Certificate of Operation have been reviewed and (if necessary) varied to permit the operation, and a dangerous goods declaration, segregation plan, and emergency response arrangements have been prepared.

3. DECK CARGO LIMITS

All deck cargo carried on MV Rohani shall be within the limits of the approved stability book. The total deck cargo and its distribution shall not exceed the limits in the table below.

3.1 Maximum Deck Cargo by Operational Area

Operational Area	Maximum Total Deck Cargo	Distribution Reference
NSCV 2C (transit, sheltered coastal)	10 tonnes	Stability Book Conditions 2 & 3 (MID zone)
NSCV 2D (lifting operations, smooth/partially smooth waters)	30 tonnes	Stability Book Conditions 4 & 5 (FWD/MID/AFT)

3.2 Deck Cargo Zones

Deck cargo is distributed across three nominal zones aligned longitudinally with the approved stability book load cases:

(a) Forward (FWD) zone — centred approximately 3.0 m forward of midships.

(b) Midships (MID) zone — centred at midships (LCG 0.0 m).

(c) Aft (AFT) zone — centred approximately 3.0 m aft of midships.

For 2D operations (30 t total) the load shall be distributed evenly across all three zones (approximately 10 t in each of FWD, MID, AFT) unless an alternative distribution is specifically supported by the stability book.

For 2C transit (10 t total) the load shall be concentrated in the MID zone with the deck crane in the transit (stowed) position.

3.3 Vertical Centre of Gravity

The approved stability calculations assume a vertical centre of gravity (VCG) of deck cargo of 2.500 m above the baseline. Deck cargo with a higher VCG (for example, stacked or tall items) shall not be carried without a separate stability assessment by a competent person and, where required by the National Regulator, endorsement of that assessment by the relevant Survey Authority. The master shall use the freeboard, trim, and any heel observed at the berth to confirm the load is within the approved envelope before departure.

3.4 Free Surface and Liquid Cargo

Liquid cargo is not normally carried on MV Rohani. The fresh water ballast tanks (port and starboard) shall be pressed full at all times as permanent ballast as set out in the stability book. The diesel fuel tanks shall be managed so that the working condition lies between the approved arrival (10%) and departure (98%) cases.

4. LIFTING CARGO

All lifting operations conducted from MV Rohani shall be performed in accordance with FUS-SMS-ROH-05I Crane Operations and within the limits of the approved stability book.

4.1 Crane Lifting Limits

The maximum lifting loads are specified in Table 1 of the approved stability book (Section 2.3) and shall not be exceeded. The crane operator and master shall consult Table 1 before each lift to confirm the working radius and boom configuration are within limits. The load chart shall be displayed at the crane control station.

4.2 Rotational Lifting Zones

The approved stability book (Figure 5) defines three crane rotational zones in which different load and deck cargo combinations are permitted. The following limits apply:

Zone	Rotation From CL	Maximum Crane Load	Maximum Deck Cargo
Forward	±30°	100% of crane load chart	30 tonnes
Starboard 90° (reduced)	Up to 90° to starboard	50% of crane load chart	30 tonnes
Starboard 90° (light deck)	Up to 90° to starboard	50% of crane load chart	15 tonnes

The 50% load chart values are tabulated in Table 2 of the stability book. Lifting outside the forward ±30° zone shall be done in accordance with the reduced load conditions above.

4.3 Heel Angle Limit

NSCV Chapter 8C and the approved stability book require that the angle of heel resulting from any lifting operation shall not exceed 5 degrees. The master shall monitor the vessel's heel during all lifts. If the heel approaches 5 degrees the lift shall be stopped, the load lowered (or returned to deck), and the lift re-assessed before proceeding.

4.4 Weather and Sea State

Lifting operations are restricted to smooth and partially smooth waters only, as a condition of the Certificate of Survey. The master shall confirm the prevailing sea state meets this limit before

commencing any lift. Lifting shall be suspended if the sea state deteriorates beyond smooth or partially smooth waters.

4.5 Spud Legs Deployed

Lifting operations should normally be conducted with the spud legs deployed to hold the vessel station and minimise dynamic effects on stability. Where deployment of spud legs is not practicable (for example, water depth exceeds spud leg length, or the seabed is unsuitable), the vessel shall be securely moored before lifting and the master shall account for any additional heeling or motion in the lift plan. Refer to FUS-SMS-ROH-05L Spud Leg Operations.

5. CARGO SECURING

All deck cargo shall be secured against the worst combination of motion, heel, and weather expected on the voyage. The following requirements apply:

(a) Cargo shall be stowed within the marked or known load zones (FWD, MID, AFT) and shall not obstruct safe access to the helm, engine room hatch, fire-fighting equipment, life-saving equipment, mooring lines, or means of access.

(b) Cargo shall be secured using lashings, ratchet straps, chain binders, or other rated securing devices appropriate to the weight and form of the cargo. Securing devices shall be rated to AS/NZS 4380 (Cargo restraint systems) or equivalent.

(c) Securing points used shall be designated deck eyes, padeyes, bollards, or D-rings rated for the load. Improvised securing points shall not be used.

(d) The master shall visually inspect all cargo securing before departure and periodically during the voyage. Loose, shifting, or damaged securings shall be rectified before continuing.

(e) For loose granular materials, tools, or small items, a deck box or covered storage shall be used. Loose items shall not be left unsecured on deck while the vessel is underway.

(f) Where lifting equipment, dive equipment, or crane attachments are stowed on deck for transit, they shall be secured in accordance with their respective procedures (FUS-SMS-ROH-05I Crane Operations, FUS-SMS-ROH-05H Diving Operations).

6. PRE-DEPARTURE CARGO CHECKS

Before departure on any voyage carrying deck cargo, the master shall confirm the following:

(a) Total deck cargo weight is within the limit for the operational area (10 t for 2C transit; 30 t for 2D lifting operations).

(b) Cargo distribution across the FWD / MID / AFT zones is consistent with the approved stability book load case for the planned operation.

(c) Vertical centre of gravity of the cargo is within the assumed envelope (2.500 m above the baseline). Tall or stacked items have been assessed.

(d) All cargo is properly secured in accordance with Section 5.

(e) The vessel’s freeboard, trim, and any observed heel at the berth are consistent with the planned load condition.

(f) The approved stability book is onboard and accessible.

(g) For lifting voyages, the deck crane is stowed in the transit position (boom retracted and lowered) and the spud legs are pinned in the raised position before departure.

7. UNUSUAL OR ABNORMAL LOADS

Any proposed load that lies outside the conditions presented in Section 3 of the approved stability book shall not be carried until the load has been analysed by a competent person to verify

compliance with applicable stability criteria. Where required by the National Regulator, the analysis shall be endorsed by the relevant Survey Authority before the load is carried. The master shall not commence the operation until the analysis has been completed and accepted.

8. RECORDS

Cargo carried on each voyage shall be recorded in the vessel logbook (refer FUS-SMS-ROH-08). The record shall include the total weight, general description, distribution across deck zones, and (for lifting operations) any lifts conducted including the load weight, working radius, and boom configuration. These records support compliance with Schedule 1, Clause 15 and assist with investigation of any marine incident.

9. REFERENCES

FUS-SMS-ROH-02 Risk Assessment

FUS-SMS-ROH-05A Pre-Departure Checks

FUS-SMS-ROH-05H Diving and ROV Operations

FUS-SMS-ROH-05I Crane Operations

FUS-SMS-ROH-05L Spud Leg Operations

FUS-SMS-ROH-08 Documentation and Logs

Approved Stability Book — Approved stability book ROHANI BARGE Dft. A (Marine Survey and Design Pty Ltd, 2 Oct 2020)

Certificate of Survey COS-94585-003 (Conditions)

Marine Order 504 (2024), Schedule 1, Clause 11(5)(n)

NSCV Part C, Subsection 6A — Intact Stability Requirements

NSCV Part C, Section 4 — Dangerous Goods (definition)

AS/NZS 4380 — Cargo restraint systems