FRANMARINE UNDERWATER SERVICES PTY LTD

ADVERSE WEATHER

Emergency Procedure

MV ROHANI | UVI: 457394

Marine Order 504 (2024) — Schedule 1 Compliance

Document Number:	FUS-SMS-ROH-06K
Revision:	01
Date:	7 July 2026
Author:	Matthew Hilder
Reviewed By:	Belinda Brooks
Approved By:	Kirby Hamilton
Vessel:	MV Rohani (UVI 457394)

DOCUMENT CONTROL

Revision History

Rev	Date	Author	Description	Approved
01	7 July 2026	M. Hilder	Initial issue	K. Hamilton

Approval

Role	Name	Date
Author	Matthew Hilder	7 July 2026
Reviewed	Belinda Brooks	7 July 2026
Approved	Kirby Hamilton	7 July 2026

Review Frequency

This document shall be reviewed at least every 12 months, or sooner following a significant incident, change of operations, vessel modification, or change in applicable legislation.

Controlled Distribution

This document is a controlled distribution issued from the Franmarine document management system (DMS), which holds the master record, revision history, and approval log. The controlled digital copy is located in the vessel's SharePoint folder. Printed or downloaded copies are uncontrolled; refer to the SMS Document Register for the current revision status.

TABLE OF CONTENTS

1. PURPOSE

This procedure establishes the actions to be taken when MV Rohani encounters or is forecast to encounter adverse weather conditions.

1.1 Regulatory Reference

Marine Order 504 (2024), Schedule 1, Clause 12.

2. OPERATIONAL WEATHER LIMITS

MV Rohani is a 10.80 m open/semi-enclosed aluminium diving support vessel. The following operational weather parameters and limits apply to all operations from this vessel.

Parameter	Limit
Wind (sustained)	Do not depart if forecast ≥25 knots. Return to port if sustained ≥25 knots underway.
Gusts	Plan for 40% above forecast (forecast average winds × 1.4 = expected gust ceiling). Cease operations if gusts ≥35 knots.
Wave height	Do not depart if forecast significant wave height ≥2.5 m. Return to port if ≥2.5 m underway.
Swell	Consider combined sea state — steep short-period swell may require a lower threshold than the wave height limit alone.
Visibility	Do not operate if visibility <500 m. Reduce speed per COLREGs Rule 6 below 1 nm visibility.
BOM Strong Wind Warning	Proceed with caution. Master to reassess risk before departure. Consider not departing.
BOM Gale Warning	Do not depart under any circumstances. Return to port if already underway.
BOM Storm Warning	Vessel to be secured in port. No operations.

2.1 General Notes

- Squalls — avoid all squall conditions. Gusts can exceed 40–50 knots with minimal warning.
- Thunderstorms — cease all water-based operations. Remain clear of lightning exposure.
- Tropical cyclones — no vessel should be at sea within several hundred nautical miles of a tropical cyclone.
- Wave height planning rule — always plan for waves up to twice the forecast height. Individual rogue waves can significantly exceed the significant wave height figure.
- Gust planning rule — forecast average winds × 1.4 = expected gust ceiling. Use this figure when assessing whether to depart or continue operations.
- Master's authority — the master may cease operations at any time below these thresholds based on observed conditions, vessel behaviour, or crew safety.

3. WEATHER MONITORING

- Check the Bureau of Meteorology (BOM) marine forecast before departure and at regular intervals during operations.
- Monitor VHF Ch 16 for weather warnings.
- Use onboard instruments and visual observation to monitor changing conditions.

4. ACTIONS IN DETERIORATING WEATHER

- Reduce speed to suit conditions.
- Ensure all crew are wearing PFDs.
- Secure all loose equipment and close all hatches.
- If conditions exceed the operational limits, suspend operations and proceed to the nearest safe port or shelter.
- If unable to reach port safely, head into the wind and sea at minimum steerage way and ride out the conditions.
- Deploy the anchor in a sheltered position if conditions deteriorate further.
- Issue a PAN PAN on VHF Ch 16 if assistance is required.

5. FOG AND RESTRICTED VISIBILITY

- Reduce speed to a safe speed adapted to the conditions.
- Sound fog signals (one prolonged blast at intervals of not more than 2 minutes for a power-driven vessel making way).
- Post an additional lookout.
- Use radar and chart plotter.
- If conditions are too poor to navigate safely, anchor and wait for conditions to improve.

6. POST-INCIDENT

- Record weather-related decisions and actions in the vessel logbook.
- Report any damage or incidents to the East Coast Operations Superintendent.

7. REFERENCES

- FUS-SMS-ROH-06 Emergency Plan
- FUS-SMS-ROH-05F Navigation and Watchkeeping
- Bureau of Meteorology — www.bom.gov.au
- Marine Order 504 (2024), Schedule 1, Clause 12