FRANMARINE UNDERWATER SERVICES PTY LTD

FIRE EMERGENCY

Emergency Procedure

MV SEAGULL | UVI: 425689

Marine Order 504 (2024) — Schedule 1 Compliance

Document Number:	FUS-SMS-SGL-06A
Revision:	01
Date:	7 July 2026
Author:	Matthew Hilder
Reviewed By:	Belinda Brooks
Approved By:	Kirby Hamilton
Vessel:	MV Seagull (UVI 425689)

DOCUMENT CONTROL

Revision History

Rev	Date	Author	Description	Approved
01	7 July 2026	M. Hilder	Initial issue	K. Hamilton

Approval

Role	Name	Date
Author	Matthew Hilder	7 July 2026
Reviewed	Belinda Brooks	7 July 2026
Approved	Kirby Hamilton	7 July 2026

Review Frequency

This document shall be reviewed at least every 12 months, or sooner following a significant incident, change of operations, vessel modification, or change in applicable legislation.

Controlled Distribution

This document is a controlled distribution issued from the Franmarine document management system (DMS), which holds the master record, revision history, and approval log. The controlled digital copy is located in the vessel's SharePoint folder. Printed or downloaded copies are uncontrolled; refer to the SMS Document Register for the current revision status.

TABLE OF CONTENTS

1. PURPOSE

This procedure establishes the actions to be taken in the event of fire on board MV Seagull.

1.1 Regulatory Reference

Marine Order 504 (2024), Schedule 1, Clause 12.

1.2 Vessel Configuration

MV Seagull is an aluminium hull vessel powered by a single Yamaha F150XD outboard engine. There is no enclosed engine room. The primary fire risk areas are the helm station and console (electrical), the fuel tank and fuel lines running to the gunwale filler cap, and any portable fuel containers on deck.

2. IMMEDIATE ACTIONS

- Raise the alarm — shout “FIRE FIRE FIRE” and state the location.
- If safe to do so, isolate the fuel source. Close the fuel line shut-off valve (if fitted). Switch battery isolators to OFF.
- If safe to do so, fight the fire using the nearest extinguisher.
- If the fire cannot be controlled within 60 seconds, or involves the fuel tank or fuel lines, proceed to Section 3.

3. MASTER'S ACTIONS

- Direct all crew to muster.
- Assess whether the fire can be fought or the vessel must be abandoned.
- If underway, shut down outboards unless propulsion is needed to reach safety or to manoeuvre the fire downwind of crew.
- Head count — account for all persons on board.
- Issue a PAN PAN or MAYDAY on VHF Ch 16. Advise the relevant port authority (refer FUS-SMS-SGL-05J for VHF channels).
- Direct crew to don lifejackets.
- If contained, monitor for re-ignition.
- If uncontrolled, prepare to abandon vessel.

4. FIREFIGHTING EQUIPMENT

MV Seagull carries the following firefighting equipment:

- 2 x 4.5 kg ABE-rated dry chemical powder fire extinguishers — both located under the central helm console.
- Fire blanket.

4.1 Operating the Extinguisher

- P — Pull the pin.
- A — Aim at the base of the fire.
- S — Squeeze the handle.
- S — Sweep from side to side.

4.2 Electrical Fires

- Switch both battery isolators to OFF before applying the extinguisher.
- Use the ABE extinguisher (safe for electrical fires). Do not use water.

4.3 Fuel Fires

- Do not attempt to extinguish a fuel fire that has reached the fuel tank. Prepare to abandon vessel.
- For small spilled-fuel fires, use the ABE extinguisher or fire blanket.
- Move portable fuel containers away from the fire if safe to do so.

5. POST-INCIDENT

- Do not restart the engine or switch on isolators until the cause is established and area confirmed safe.
- Report to the East Coast Operations Superintendent immediately.
- Complete an incident report and record in the vessel logbook.
- Replace used extinguishers before vessel returns to service.
- Report to AMSA if applicable.

6. REFERENCES

- FUS-SMS-SGL-06 Emergency Plan
- FUS-SMS-SGL-12 Review and Verification (Hazardous Occurrences and Non-Conformances)
- NSCV C4 (Fire Protection)
- Marine Order 504 (2024), Schedule 1, Clause 12