

[Skip to content](#)

# NlaStripFCurves(bpy\_struct)

base class — `bpy_struct`

**class** `bpy.types.NlaStripFCurves(bpy_struct)`

Collection of NLA strip F-Curves

**find**(`data_path`, \*, `index=0`)

Find an F-Curve. Note that this function performs a linear scan of all F-Curves in the NLA strip.

**PARAMETERS:**

- **data\_path** (*string, (never None)*) – Data Path, F-Curve data path
- **index** (*int in [0, inf], (optional)*) – Index, Array index

**RETURNS:**

The found F-Curve, or None if it doesn't exist

**RETURN TYPE:**

`FCurve`

**classmethod** `bl_rna_get_subclass(id, default=None)`

**PARAMETERS:**

**id** (*str*) – The RNA type identifier.

**RETURNS:**

The RNA type or default when not found.

**RETURN TYPE:**

`bpy.types.Struct` subclass

**classmethod** `bl_rna_get_subclass_py(id, default=None)`

**PARAMETERS:**

**id** (*str*) – The RNA type identifier.

**RETURNS:**

The class or default when not found.

**RETURN TYPE:**

type

## Inherited Properties

- `bpy_struct.id_data`

## Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.id_properties_clear`
- `bpy_struct.id_properties_ensure`
- `bpy_struct.id_properties_ui`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.pop`

- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_overrideable_library`
- `bpy_struct.is_property_readonly`
- `bpy_struct.is_property_set`
- `bpy_struct.property_overrideable_library_set`
- `bpy_struct.property_unset`
- `bpy_struct.type_recast`
- `bpy_struct.values`

## References

- `NlaStrip.fcurves`

[Previous](#)  
[NlaStrip\(bpy\\_struct\)](#)  
[Report issue on this page](#)

Copyright © Blender Authors  
Made with [Furo](#)

[NlaStrip\(bpy\\_struct\)](#)  
[NlaStrips\(bpy\\_struct\)](#)