Skip to content

LineStyleThicknessModifiers(bpy_struct)

```
base class — bpy_struct
```

class bpy.types.LineStyleThicknessModifiers(bpy struct)

Thickness modifiers for changing line thickness

new(name, type)

Add a thickness modifier to line style

PARAMETERS:

- name (string, (never None)) New name for the thickness modifier (not unique)
- type (enum in Linestyle Thickness Modifier Type Items) Thickness modifier type to add

RETURNS:

Newly added thickness modifier

RETURN TYPE:

LineStyleThicknessModifier

remove(modifier)

Remove a thickness modifier from line style

PARAMETERS:

modifier(LineStyleThicknessModifier, (never None)) - Thickness modifier to remove

classmethod bl_rna_get_subclass(id, default=None)

PARAMETERS:

id(str) – The RNA type identifier.

RETURNS:

The RNA type or default when not found.

RETURN TYPE:

bpy.types.Struct subclass

classmethod bl_rna_get_subclass_py(id, default=None)

PARAMETERS:

id(str) – The RNA type identifier.

RETURNS:

The class or default when not found.

RETURN TYPE:

type

Inherited Properties

• bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.driver_add

- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.driver_remove
- bpy struct.get
- bpy_struct.id_properties_clear
- bpy_struct.id_properties_ensure
- bpy struct.id properties ui
- bpy struct.is property hidden
- bpy_struct.is_property_overridable_library bpy_struct.property_unset
- bpy struct.is property readonly
- bpy_struct.is_property_set

- bpy_struct.keyframe_insert
- bpy struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy struct.pop
- bpy_struct.property_overridable_library_set
- bpy struct.type recast
- bpy struct.values

References

• FreestyleLineStyle.thickness_modifiers

Previous LineStyleThicknessModifier Tangent(LineStyleThicknessModifier) Report issue on this page

Copyright © Blender Authors Made with Furo

Linesets(bpy stru