ASSETBROWSER_UL_metadata_tags(UIList)

```
base classes — bpy_struct, UIList
class bpy.types.ASSETBROWSER UL metadata tags(UIList)
    draw item( context, layout, data, item, icon, active data, active propname, index)
    classmethod bl rna get subclass(id, default=None)
        PARAMETERS:
             id (str) – The RNA type identifier.
        RETURNS:
             The RNA type or default when not found.
        RETURN TYPE:
             bpy.types.Struct subclass
    classmethod bl_rna_get_subclass_py(id, default=None)
        PARAMETERS:
             id (str) – The RNA type identifier.
        RETURNS:
             The class or default when not found.
        RETURN TYPE:
             type
```

Inherited Properties

bpy_struct.id_data
UIList.bl_idname
UIList.list_id
UIList.layout_type
UIList.use_filter_sort_alpha
UIList.use_filter_sort_reverse
UIList.use_filter_sort_lock
UIList.bitflag_filter_item

Inherited Functions

• bpy_struct.items

- bpy_struct.as_pointer
 bpy_struct.driver_add
 bpy_struct.driver_remove
 bpy_struct.get
 bpy_struct.id_properties_clear
 bpy_struct.id_properties_ensure
 bpy_struct.id_properties_ui
 bpy_struct.is_property_hidden
 bpy_struct.is_property_overridable_library
 bpy_struct.is_property_readonly
 bpy_struct.is_property_set
- bpy_struct.pop
 bpy_struct.property_overridable_library_set
 bpy_struct.property_unset
 bpy_struct.type_recast
 bpy_struct.values
 UIList.draw_item
 UIList.filter_items

• bpy struct.path resolve

• UIList.append

• UIList.prepend

• UIList.is extended

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- UIList.remove
- UIList.bl_rna_get_subclass
- UIList.bl_rna_get_subclass_py

Previous AOVs(bpy_struct)

Report issue on this page

Copyright © Blender Authors Made with Furo No Action(I